

## **APPENDIX D: TABLES FOR EMISSION REDUCTION AND COST-EFFECTIVENESS CALCULATIONS**

This appendix presents tables summarizing the data needed to calculate the emission reductions and cost-effectiveness of potential projects. Included are data such as engine emission factors, load factors, and other conversion factors used in the calculations discussed in Appendix C: Cost-Effectiveness Calculation Methodology.

	<u>Table Number</u>
Heavy-Duty On-Road Projects	D-1 to D-6
Off-Road Diesel and Non-Mobile Agricultural (Ag) Projects	D-7 to D-9
Large Spark-Ignition (LSI) Projects	D-10 to D13
Locomotive Projects	D-14a to D-14b
Marine Projects	D-15a to D-20
All Engines - Fuel Consumption	D-21
Reference Tables	D-22 to D-25

## HEAVY DUTY ON-ROAD PROJECTS

**Table D-1: Heavy-Duty Vehicles (14,001-33,000 pounds (lbs.) GVWR)  
Emission Factors (g/mile)<sup>(a)</sup> (EF) and Deterioration Rates (g/mile-10k miles) (DR)**

Engine Model Year	NO <sub>x</sub> <sup>(b)</sup>		ROG <sup>(b),(c)</sup>		PM <sup>(b),(i)</sup>	
	EF <sup>(d)</sup>	DR <sup>(e)</sup>	EF <sup>(d)</sup>	DR <sup>(e)</sup>	EF <sup>(d)</sup>	DR <sup>(e)</sup>
Pre-1987	14.52	0.031	0.89	0.051	0.713	0.0283
1987-90	14.31	0.041	0.70	0.060	0.774	0.0252
1991-93	10.70	0.054	0.37	0.031	0.425	0.0193
1994-97	10.51	0.063	0.27	0.036	0.241	0.0129
1998-02	10.33	0.072	0.28	0.036	0.266	0.0116
2003-06	6.84	0.071	0.23	0.021	0.175	0.0067
2007-09	3.99	0.090	0.18	0.007	0.014	0.0008
2007+ <sup>(f)</sup> (0.21-0.50 g/bhp-hr NO <sub>x</sub> FEL)	1.27	0.079	0.06	0.002	0.002	0.0001
2010-12 (0.20 g/bhp-hr NO <sub>x</sub> std)	1.03	0.079	0.06	0.002	0.002	0.0001
2013+ <sup>(g)</sup> (0.20 g/bhp-hr NO <sub>x</sub> std)	1.03	0.045	0.06	0.001	0.002	0.0001
2016+ <sup>(h)</sup> (0.10 g/bhp-hr NO <sub>x</sub> std)	0.52	0.023	0.06	0.001	0.002	0.0001
2016+ <sup>(h)</sup> (0.05 g/bhp-hr NO <sub>x</sub> std)	0.26	0.011	0.06	0.001	0.002	0.0001
2016+ <sup>(h)</sup> (0.02 g/bhp-hr NO <sub>x</sub> std)	0.10	0.005	0.06	0.001	0.002	0.0001

- (a) EMFAC 2014 Zero-Mile Based Emission Factors. Factors are based on diesel engines. Same factors used for alternative fuel engines due to limited alternative fuel data in EMFAC.
- (b) Emission factors incorporate the ultra low-sulfur diesel fuel correction factors listed in Table D-22. NO<sub>x</sub> - Oxides of nitrogen, ROG - Reactive Organic Gases, PM - Particulate Matter.
- (c) EMFAC provides HC emission factors which are converted into ROG.  $ROG = HC * 1.26639$ .
- (d) Emission Factors are based on zero-mile rates contained in EMFAC 2014.
- (e) Deterioration Rate per 10,000 miles.
- (f) All model year 2007 and newer engines with Family Emission Limits (FEL) from 0.21 g/bhp-hr to 0.50 g/bhp-hr NO<sub>x</sub> must use different emission factors from those listed for model years 2010 and newer engines certified to 0.20 g/bhp-hr NO<sub>x</sub> standards. FEL emission factors are based on EMFAC factors for model year 2010-2012 engines that include weighted averaging of 0.5, 0.35, and 0.20 g/bhp-hr NO<sub>x</sub> standards based on sales.
- (h) Deterioration rates for 2013+ engines incorporate use of on-board diagnostic system.
- (i) Factors for 2016+ engines are reduced values of 2013 factors by 50 percent, 75 percent, and 90 percent to correspond with 0.10 g/bhp-hr NO<sub>x</sub>, 0.05 g/bhp-hr NO<sub>x</sub>, and 0.02 g/bhp-hr NO<sub>x</sub> optional low NO<sub>x</sub> standards.
- (k) <sup>(i)</sup> Factors for 2006 or older engines are for unfiltered trucks.

**Table D-2: Heavy-Duty Vehicles (Over 33,000 pounds (lbs.) GVWR)  
Emission Factors (g/mile)<sup>(a)</sup> (EF) and Deterioration Rates (g/mile-10k miles) (DR)**

Engine Model Year	NO <sub>x</sub> <sup>(b)</sup>		ROG <sup>(b),(c)</sup>		PM <sup>(b),(i)</sup>	
	EF <sup>(d)</sup>	DR <sup>(e)</sup>	EF <sup>(d)</sup>	DR <sup>(e)</sup>	EF <sup>(d)</sup>	DR <sup>(e)</sup>
Pre-1987	21.37	0.018	1.38	0.031	1.260	0.0200
1987-90	21.07	0.024	1.08	0.037	1.369	0.0178
1991-93	18.24	0.037	0.78	0.027	0.574	0.0104
1994-97	17.92	0.043	0.58	0.031	0.377	0.0080
1998-02	17.61	0.049	0.60	0.031	0.415	0.0073
2003-06	11.66	0.049	0.49	0.018	0.267	0.0041
2007-09	6.80	0.077	0.39	0.007	0.022	0.0006
2007+ <sup>(f)</sup> (0.21-0.50 g/bhp-hr NO <sub>x</sub> FEL)	2.17	0.068	0.13	0.002	0.004	0.0001
2010-12 (0.2 g/bhp-hr NO <sub>x</sub> std)	1.76	0.068	0.13	0.002	0.004	0.0001
2013+ <sup>(g)</sup> (0.2 g/bhp-hr NO <sub>x</sub> std)	1.76	0.039	0.13	0.001	0.004	0.0001
2016+ <sup>(h)</sup> (0.10 g/bhp-hr NO <sub>x</sub> std)	0.88	0.019	0.13	0.001	0.004	0.0001
2016+ <sup>(h)</sup> (0.05 g/bhp-hr NO <sub>x</sub> std)	0.44	0.010	0.13	0.001	0.004	0.0001
2016+ <sup>(h)</sup> (0.02 g/bhp-hr NO <sub>x</sub> std)	0.18	0.004	0.13	0.001	0.004	0.0001

- (a) EMFAC 2014 Zero-Mile Based Emission Factors. Factors are based on diesel engines. Same factors used for alternative fuel engines due to limited alternative fuel data in EMFAC.
- (b) Emission factors incorporate the ultra-low-sulfur diesel fuel correction factors listed in Table D-22.
- (c) EMFAC provides HC emission factors which are converted into ROG.  $ROG = HC * 1.26639$ .
- (d) Emission Factors are based on zero-mile rates contained in EMFAC 2014.
- (e) Deterioration Rate is per 10,000 miles.
- (f) All model year 2007 and newer engines with Family Emission Limits (FEL) from 0.21 g/bhp-hr to 0.50 g/bhp-hr NO<sub>x</sub> must use different emission factors from those listed for model years 2010 and newer engines certified to 0.20 g/bhp-hr NO<sub>x</sub> standards. FEL emission factors are based on EMFAC factors for model year 2010-2012 engines that include weighted averaging of 0.5, 0.35, and 0.20 g/bhp-hr NO<sub>x</sub> standards based on sales.
- (h) Deterioration rates for 2013+ engines incorporate use of on-board diagnostic system.
- (i) Factors for 2016+ engines are reduced values of 2013 factors by 50 percent, 75 percent, and 90 percent to correspond with 0.10 g/bhp-hr NO<sub>x</sub>, 0.05 g/bhp-hr NO<sub>x</sub>, and 0.02 g/bhp-hr NO<sub>x</sub> optional low NO<sub>x</sub> standards, respectively.
- (k) Factors for 2006 or older engines are for unfiltered trucks.

**Table D-3: Diesel Urban Buses  
Emission Factors (g/mile)<sup>(a)</sup>**

<b>Engine Model Year</b>	<b>NO<sub>x</sub><sup>(b)</sup></b>	<b>ROG<sup>(b),(c)</sup></b>	<b>PM<sup>(b),(e)</sup></b>
Pre-1987	42.97	1.88	0.929
1987-1990	37.39	1.87	0.878
1991-1993	23.72	1.84	0.835
1994-1995	27.71	1.81	1.015
1996-1998	36.46	1.81	1.217
1999-2002	18.97	1.81	0.417
2003	13.02	0.77	0.084
2004-2006	3.56	0.08	0.084
2007+ (0.20 g/bhp-hr NO <sub>x</sub> std)	1.90	0.03	0.011
2016+ <sup>(d)</sup> (0.10 g/bhp-hr NO <sub>x</sub> std)	0.95	0.03	0.011
2016+ <sup>(d)</sup> (0.05 g/bhp-hr NO <sub>x</sub> std)	0.47	0.03	0.011
2016+ <sup>(d)</sup> (0.02 g/bhp-hr NO <sub>x</sub> std)	0.19	0.03	0.011

- (a) EMFAC 2014 Zero-Mile Based Emission Factors.
- (b) Emission factors incorporate the ultra-low-sulfur diesel fuel correction factors listed in Table D-22.
- (c) EMFAC provides HC emission factors which are converted into ROG.  $ROG = HC * 1.26639$ .
- (d) Factors for 2016+ engines are reduced values of 2007 factors by 50 percent, 75 percent, and 90 percent to correspond with 0.10 g/bhp-hr NO<sub>x</sub>, 0.05 g/bhp-hr NO<sub>x</sub>, and 0.02 g/bhp-hr NO<sub>x</sub> optional low NO<sub>x</sub> standards, respectively.
- (e) Factors for 2006 or older engines are for unfiltered trucks.

**Table D-4: Alternative Fuel Urban Buses  
Emission Factors (g/mile)<sup>(a)</sup>**

<b>Engine Model Year</b>	<b>NOx</b>	<b>ROG<sup>(b)</sup></b>	<b>PM<sup>(d)</sup></b>
Pre-2003	21.60	2.68	0.043
2003-06	15.40	3.87	0.023
2007+ (0.20 g/bhp-hr NOx std)	0.65	0.04	0.001
2016+ <sup>(c)</sup> (0.10 g/bhp-hr NOx std)	0.33	0.04	0.001
2016+ <sup>(c)</sup> (0.05 g/bhp-hr NOx std)	0.16	0.04	0.001
2016+ <sup>(c)</sup> (0.02 g/bhp-hr NOx std)	0.07	0.04	0.001

- (a) EMFAC 2014 Zero-Mile Based Emission Factors.
- (b) EMFAC provides HC emission factors which are converted into ROG.
- (c)  $ROG \text{ (pre-2007 engines)} = HC * 0.16137$ .
- (d)  $ROG \text{ (2007+ engines)} = HC * 0.013972$ .
- (e) Factors for 2016+ engines are reduced values of 2007 factors by 50 percent, 75 percent, and 90 percent to correspond with 0.10 g/bhp-hr NOx, 0.05 g/bhp-hr NOx, and 0.02 g/bhp-hr NOx optional low NOx standards, respectively.
- (f) Factors for 2006 or older engines are for unfiltered trucks.

**Table D-5: Diesel Refuse Trucks  
Emission Factors (g/mile)<sup>(a)</sup>**

<b>Engine Model Year</b>	<b>NO<sub>x</sub><sup>(b)</sup></b>	<b>ROG<sup>(b),(c)</sup></b>	<b>PM<sup>(b),(g)</sup></b>
pre-1994	34.69	0.01	0.346
1994-97	31.53	0.01	0.137
1998-02	31.25	0.01	0.144
2003-06	21.39	0.01	0.086
2007-09	11.25	0.14	0.008
2007+ <sup>(d)</sup> (0.21-0.50 g/bhp-hr NO <sub>x</sub> FEL)	1.23	0.26	0.008
2010+ <sup>(e)</sup> (0.20 g/bhp-hr NO <sub>x</sub> std)	1.09	0.04	0.008
2016+ <sup>(f)</sup> (0.10 g/bhp-hr NO <sub>x</sub> )	0.54	0.04	0.008
2016+ <sup>(f)</sup> (0.05 g/bhp-hr NO <sub>x</sub> )	0.27	0.04	0.008
2016+ <sup>(f)</sup> (0.02 g/bhp-hr NO <sub>x</sub> )	0.11	0.04	0.008

Note: These emission factors are not applicable to transfer trucks. Transfer trucks must use the emission factors from Table D-1 or D-2. Per EMFAC 2014, solid waste collection vehicles are considered to be well-maintained and have negligible deterioration which is why only zero-mile emission factors are to be used in calculations for solid waste collection vehicle projects.

- (a) EMFAC 2014 Zero-Mile Based Emission Factors.
- (b) Emission factors incorporate the ultra-low-sulfur diesel fuel correction factors listed in Table D-22.
- (c) EMFAC provides HC emission factors which are converted into ROG.
- (d)  $ROG = HC * 1.26639$ .
- (e) All model year 2007 and newer engines with Family Emission Limits (FEL) from 0.21 g/bhp-hr to 0.50 g/bhp-hr NO<sub>x</sub> must use different emission factors from those listed for model years 2010 and newer engines certified to 0.20 g/bhp-hr NO<sub>x</sub> standards. FEL emission factors are based on EMFAC factors for model year 2010-2012 engines that include weighted averaging of 0.5, 0.35, and 0.20 g/bhp-hr NO<sub>x</sub> standards based on sales.
- (f) These 2010+ emission factors are based only on engines certified to the 0.20 g/bhp-hr NO<sub>x</sub> standard.
- (g) Factors for 2016+ engines are reduced values of 2013 factors by 50 percent, 75 percent, and 90 percent to correspond with 0.10 g/bhp-hr NO<sub>x</sub>, 0.05 g/bhp-hr NO<sub>x</sub>, and 0.02 g/bhp-hr NO<sub>x</sub> optional low NO<sub>x</sub> standards, respectively.
- (h) Factors for 2006 or older engines are for unfiltered trucks.

**Table D-6: Alternative Fuel Refuse Trucks  
Emission Factors (g/mile)<sup>(a)</sup>**

<b>Engine Model Year</b>	<b>NOx</b>	<b>ROG<sup>(b)</sup></b>	<b>PM<sup>(d)</sup></b>
Pre-2007	53.20	9.86	0.091
2007-09	18.80	3.68	0.004
2010+ (0.20 g/bhp-hr NOx std)	0.88	0.14	0.004
2016+ <sup>(c)</sup> (0.10 g/bhp-hr NOx)	0.44	0.14	0.004
2016+ <sup>(c)</sup> (0.05 g/bhp-hr NOx)	0.22	0.14	0.004
2016+ <sup>(c)</sup> (0.02 g/bhp-hr NOx)	0.09	0.14	0.004

Note: These emission factors are not applicable to transfer trucks. Transfer trucks must use the emission factors from Table D-1 or D-2. Per EMFAC 2014, solid waste collection vehicles are considered to be well-maintained and have negligible deterioration which is why only zero-mile emission factors are to be used in calculations for solid waste collection vehicle projects.

- (a) EMFAC 2014 Zero-Mile Based Emission Factors.
- (b) EMFAC provides HC emission factors which are converted into ROG.
- (c)  $ROG(\text{pre-2007 engines}) = HC * 0.16137$ .
- (d)  $ROG(\text{2007+ engines}) = HC * 0.013972$ .
- (e) Factors for 2016+ engines are reduced values of 2010 factors by 50 percent, 75 percent, and 90 percent to correspond with 0.10 g/bhp-hr NOx, 0.05 g/bhp-hr NOx, and 0.02 g/bhp-hr NOx optional low NOx standards, respectively.
- (f) Factors for 2006 or older engines are for unfiltered trucks.

OFF-ROAD PROJECTS AND NON-MOBILE AGRICULTURAL PROJECTS

**Table D-7: Off-Road Diesel Engines Default Load Factors**

Category	Equipment Type	Load Factor
Airport Ground Support	Aircraft Tug	0.54
	Air Conditioner	0.75
	Air Start Unit	0.90
	Baggage Tug	0.37
	Belt Loader	0.34
	Bobtail	0.37
	Cargo Loader	0.34
	Cargo Tractor	0.36
	Forklift	0.20
	Ground Power Unit	0.75
	Lift	0.34
	Passenger Stand	0.40
	Service Truck	0.20
	Other Ground Support Equipment	0.34
	Agricultural (Mobile, Portable or Stationary)	Agricultural Mowers
Agricultural Tractors		0.70
Balers		0.58
Combines/Choppers		0.70
Chippers/Stump Grinders		0.73
Generator Sets		0.74
Hydro Power Units		0.48
Irrigation Pump		0.65
Shredders		0.40
Sprayers		0.50
Swathers		0.55
Tillers		0.78
Other Agricultural		0.51
Construction	Air Compressors	0.48
	Bore/Drill Rigs	0.50
	Cement & Mortar Mixers	0.56
	Concrete/Industrial Saws	0.73
	Concrete/Trash Pump	0.74
	Cranes	0.29
	Crawler Tractors	0.43
	Crushing/Process Equipment	0.78
	Excavators	0.38
	Graders	0.41

**Table D-7: Off-Road Diesel Engines Default Load Factors (Continued)**

<b>Category</b>	<b>Equipment Type</b>	<b>Load Factor</b>
Construction	Off-Highway Tractors	0.44
	Off-Highway Trucks	0.38
	Pavers	0.42
	Other Paving	0.36
	Pressure Washer	0.30
	Rollers	0.38
	Rough Terrain Forklifts	0.40
	Rubber Tired Dozers	0.40
	Rubber Tired Loaders	0.36
	Scrapers	0.48
	Signal Boards	0.78
	Skid Steer Loaders	0.37
	Surfacing Equipment	0.30
	Tractors/Loaders/Backhoes	0.37
	Trenchers	0.50
	Welders	0.45
	Other Construction Equipment	0.42
Industrial	Aerial Lifts	0.31
	Forklifts	0.20
	Sweepers/Scrubbers	0.46
	Other General Industrial	0.34
	Other Material Handling	0.40
Logging	Fellers/Bunchers	0.71
	Skidders	0.74
Oil Drilling	Drill Rig	0.50
	Lift (Drilling)	0.60
	Swivel	0.60
	Workover Rig (Mobile)	0.50
	Other Workover Equipment	0.60
Cargo Handling	Container Handling Equipment	0.59
	Cranes	0.20
	Excavators	0.55
	Forklifts	0.30
	Other Cargo Handling Equipment	0.51
	Sweeper/Scrubber	0.68
	Tractors/Loaders/Backhoes	0.55
	Yard Trucks	0.39
Other	All	0.43

**Table D-8: Uncontrolled Off-Road Diesel Engines  
Emission Factors (g/bhp-hr) (EF) and Deterioration Rates (g/bhp-hr-hr) (DR)**

Horsepower	Model Year	NO <sub>x</sub>		ROG		PM <sub>10</sub>	
		EF	DR	EF	DR	EF	DR
25-49	Pre-1988	6.51	0.000098	1.68	0.000210	0.547	0.0000424
	1988+	6.42	0.000097	1.64	0.000210	0.547	0.0000424
20-119	Pre-1988	12.09	0.00028	1.31	0.000061	0.605	0.0000440
	1988+	8.14	0.00019	0.90	0.000042	0.497	0.0000361
120+	Pre-1970	13.02	0.00030	1.20	0.000056	0.554	0.0000403
	1970-1979	11.16	0.00026	0.91	0.000042	0.396	0.0000288
	1980-1987	10.23	0.00024	0.80	0.000037	0.396	0.0000288
	1988+	7.60	0.00018	0.62	0.000029	0.274	0.0000199

**Table D-9: Controlled Off-Road Diesel Engines  
Emission Factors (g/bhp-hr) (EF) and Deterioration Rates (g/bhp-hr-hr) (DR)<sup>(a)</sup>**

Horsepower	Tier	NOx		ROG		PM10	
		EF	DR	EF	DR	EF	DR
25-49	1	5.26	0.0000980	1.32	0.000170	0.480	0.0000372
	2	4.63	0.0000930	0.22	0.000050	0.280	0.0000218
	4 (Interim)	4.55	0.0000950	0.09	0.000036	0.128	0.0000096
	4 (Final)	2.75	0.0000570	0.09	0.000036	0.009	0.0000010
50-74	1	6.54	0.0001500	0.90	0.000042	0.552	0.0000402
	2	4.75	0.0000710	0.17	0.000025	0.192	0.0000141
	3 <sup>(b)</sup>	2.74	0.0000360	0.09	0.000023	0.192	0.0000141
	4 (Interim)	2.74	0.0000360	0.09	0.000023	0.112	0.0000080
	4 (Final)	2.74	0.0000360	0.09	0.000023	0.009	0.0000009
75-99	1	6.54	0.0001500	0.90	0.000042	0.552	0.0000402
	2	4.75	0.0000710	0.17	0.000025	0.192	0.0000141
	3	2.74	0.0000360	0.09	0.000023	0.112	0.0000080
	4 (Phase-Out)	2.74	0.0000360	0.09	0.000030	0.009	0.0000009
	4 (Phase-In or Alt. NOx)	2.15	0.0000270	0.08	0.000021	0.009	0.0000009
	4 (Final)	0.26	0.0000035	0.05	0.000015	0.009	0.0000009
100-174	1	6.54	0.0001500	0.62	0.000029	0.304	0.0000221
	2	4.15	0.0000600	0.15	0.000023	0.128	0.0000094
	3	2.32	0.0000300	0.09	0.000030	0.112	0.0000080
	4 (Phase-Out)	2.32	0.0000300	0.09	0.000030	0.009	0.0000004
	4 (Phase-In or Alt. NOx)	2.15	0.0000270	0.08	0.000020	0.009	0.0000004
	4 (Final)	0.26	0.0000040	0.05	0.000011	0.009	0.0000004

**Table D-9: Controlled Off-Road Diesel Engines  
Emission Factors (g/bhp-hr) (EF) and Deterioration Rates (g/bhp-hr-hr) (DR)<sup>(a)</sup>  
(Continued)**

Horsepower	Tier	NOx		ROG		PM10	
		EF	DR	EF	DR	EF	DR
175-299	1	5.93	0.0001400	0.29	0.000013	0.120	0.0000064
	2	4.15	0.0000600	0.11	0.000022	0.088	0.0000046
	3	2.32	0.0000300	0.09	0.000023	0.088	0.0000046
	4 (Phase-Out)	2.32	0.0000300	0.09	0.000023	0.009	0.0000003
	4 (Phase-In or Alt. NOx)	1.29	0.0000170	0.06	0.000017	0.009	0.0000003
	4 (Final)	0.26	0.0000036	0.05	0.000011	0.009	0.0000003
300-750	1	5.93	0.0000990	0.29	0.000010	0.120	0.0000064
	2	3.79	0.0000500	0.09	0.000023	0.088	0.0000044
	3	2.32	0.0000300	0.09	0.000023	0.088	0.0000044
	4 (Phase-Out)	2.32	0.0000300	0.09	0.000023	0.009	0.0000003
	4 (Phase-In or Alt. NOx)	1.29	0.0000170	0.06	0.000017	0.009	0.0000003
	4 (Final)	0.26	0.0000036	0.05	0.000011	0.009	0.0000003
751+	1	5.93	0.0000990	0.29	0.000010	0.120	0.0000064
	2	3.79	0.0000500	0.09	0.000023	0.088	0.0000044
	4 (Interim)	2.24	0.0000280	0.06	0.000017	0.051	0.0000021
	4 (Final)	2.24	0.0000280	0.05	0.000011	0.017	0.0000009

Note: Engines participating in the “Tier 4 Early Introduction Incentive for Engine Manufacturers” program per California Code of Regulations, Title 13, section 2423(b)(6) are eligible for funding provided the engines are certified to the final Tier 4 emission standards. The Air Resources Board (ARB) Executive Order indicates engines certified under this provision. The emission rates for these engines shall be equivalent to the emission factors associated with Tier 3 engines.

Note: For equipment with baseline engines certified under the flexibility provisions per California Code of Regulations, Titles 13, section 2423(d), baseline emission rates shall be determined by using the previous applicable emission standard or Tier for that engine model year and horsepower rating. The ARB Executive Order indicates engines certified under this provision.

(a) Emission factors were converted using the ultra low-sulfur diesel fuel correction factors listed in Table D-23.

(b) Alternate compliance option.

## LARGE SPARK IGNITION ENGINES

**Table D-10: Off-Road LSI Equipment Default Load Factors**

Category	Equipment Type	Load Factor
Agriculture (Mobile, Portable or Stationary)	Agricultural Tractors	0.62
	Balers	0.55
	Combines/Choppers	0.74
	Chipper/Stump Grinder	0.78
	Generator Sets	0.68
	Sprayers	0.50
	Swathers	0.52
	Pumps	0.65
	Other Agricultural Equipment	0.55
	Airport Ground Support	A/C Tug
Baggage Tug		0.55
Belt Loader		0.50
Bobtail		0.55
Cargo Loader		0.50
Forklift		0.30
Ground Power Unit		0.75
Lift		0.50
Passenger Stand		0.59
Other Ground Support Equipment		0.50
Construction	Air Compressors	0.56
	Asphalt Pavers	0.66
	Bore/Drill Rigs	0.79
	Concrete/Industrial Saws	0.78
	Concrete/Trash Pump	0.69
	Cranes	0.47
	Gas Compressor	0.85
	Paving Equipment	0.59
	Pressure Washer	0.85
	Rollers	0.62
	Rough Terrain Forklifts	0.63
	Rubber Tired Loaders	0.54
	Skid Steer Loaders	0.58
Tractors/Loaders/Backhoes	0.48	

**Table D-10: Off-Road LSI Equipment Default Load Factors (Continued)**

<b>Category</b>	<b>Equipment Type</b>	<b>Load Factor</b>
Construction	Trenchers	0.66
	Welders	0.51
	Other Construction	0.48
Industrial	Aerial Lifts	0.46
	Forklifts	0.30
	Sweepers/Scrubbers	0.71
	Other Industrial	0.54

**Table D-11a: Off-Road LSI Engines  
Emission Factors (g/bhp-hr) (EF) and Deterioration Rates (g/bhp-hr-hr) (DR)  
Gasoline**

Horsepower	Model Year	NOx		ROG		PM10	
		EF	DR	EF	DR	EF	DR
25-50	Uncontrolled pre-2004	8.01	0.0000406	3.346	0.000367	0.060	0.000
	Controlled 2001 - 2006	1.33	0.0004710	0.717	0.000171	0.060	0.000
	Controlled 2007 - 2009	0.89	0.0001190	0.478	0.000064	0.060	0.000
	Controlled 2010+	0.27	0.0000250	0.143	0.000014	0.060	0.000
51-120	Uncontrolled pre-2004	11.84	0.0000601	2.341	0.000255	0.060	0.000
	Controlled 2001 - 2006	1.78	0.0002070	0.263	0.000082	0.060	0.000
	Controlled 2007 - 2009	1.17	0.0000660	0.130	0.000075	0.060	0.000
	Controlled 2010+	0.35	0.0000300	0.030	0.000014	0.060	0.000
121+	Uncontrolled pre-2004	12.94	0.0001270	1.433	0.000037	0.060	0.000
	Controlled 2001 - 2006	1.94	0.0002780	0.162	0.000103	0.060	0.000
	Controlled 2007 - 2009	1.17	0.0000660	0.131	0.000075	0.060	0.000
	Controlled 2010+	0.35	0.0000300	0.030	0.000014	0.060	0.000

**Table D-11b: Off-Road LSI Engines  
Emission Factors (g/bhp-hr) (EF) and Deterioration Rates (g/bhp-hr-hr) (DR)  
Alternative Fuels**

Horsepower	Model Year	NOx		ROG		PM10	
		EF	DR	EF	DR	EF	DR
25-50	Uncontrolled pre-2004	13.00	0.0000662	0.124	0.000014	0.060	0.000
	Controlled 2001 - 2006	1.95	0.0002760	0.013	0.000010	0.060	0.000
	Controlled 2007 - 2009	1.30	0.0000011	0.008	0.000015	0.060	0.000
	Controlled 2010+	0.39	0.0000002	0.003	0.000003	0.060	0.000
51-120	Uncontrolled pre-2004	10.53	0.0000533	0.140	0.000015	0.060	0.000
	Controlled 2001 - 2006	1.58	0.0003500	0.014	0.000009	0.060	0.000
	Controlled 2007 - 2009	1.04	0.0000125	0.009	0.000004	0.060	0.000
	Controlled 2010+	0.31	0.0000380	0.003	0.000001	0.060	0.000
121+	Uncontrolled pre-2004	10.51	0.0001040	0.124	0.000003	0.060	0.000
	Controlled 2001 - 2006	1.58	0.0002640	0.013	0.000009	0.060	0.000
	Controlled 2007 - 2009	1.04	0.0000125	0.009	0.000004	0.060	0.000
	Controlled 2010+	0.31	0.0000380	0.003	0.000001	0.060	0.000

**Table D-12:  
Emission Factors for Off-Road LSI Engine Retrofits Verified to Absolute Emission  
Number (g/bhp-hr)**

Manufacturers of LSI retrofit systems may verify to a percentage emission reduction or absolute emissions. If a retrofit system is verified to a percentage reduction, the emission factors will be that verified percentage of the appropriate emissions factors in Table D-11a or D-11b. If a retrofit system is verified to an absolute emission number, when calculating emission reductions use the following table for the emission factors and the deterioration rate for the baseline engine.

<b>Fuel</b>	<b>Verified Value</b>	<b>NO<sub>x</sub></b>	<b>ROG</b>	<b>PM10</b>
Gasoline	3.0	1.78	0.26	0.060
	2.5	1.48	0.22	0.060
	2.0	1.19	0.17	0.060
	1.5	0.89	0.13	0.060
	1.0	0.59	0.09	0.060
	0.6	0.35	0.03	0.060
	0.5	0.29	0.03	0.060
Alt Fuel	3.0	1.58	0.16	0.060
	2.5	1.32	0.13	0.060
	2.0	1.05	0.11	0.060
	1.5	0.79	0.08	0.060
	1.0	0.53	0.05	0.060
	0.6	0.31	0.03	0.060
	0.5	0.26	0.03	0.060

**Table D-13a: Off-Road LSI Engines Certified to Optional Standards  
Emission Factors (g/bhp-hr) (EF) and Deterioration Rates (g/bhp-hr-hr) (DR)  
Gasoline**

Horsepower	Optional Standard	NOx		ROG		PM10	
		EF	DR	EF	DR	EF	DR
25-50	0.4	0.18	0.000017	0.09	0.0000087	0.060	0.000
	0.2	0.09	0.000008	0.05	0.0000043	0.060	0.000
	0.1	0.04	0.000005	0.02	0.0000027	0.060	0.000
51-120	0.4	0.24	0.000021	0.04	0.0000034	0.060	0.000
	0.2	0.12	0.000010	0.02	0.0000017	0.060	0.000
	0.1	0.06	0.000005	0.01	0.0000009	0.060	0.000
121+	0.4	0.26	0.000022	0.02	0.0000017	0.060	0.000
	0.2	0.13	0.000011	0.01	0.0000009	0.060	0.000
	0.1	0.06	0.000005	0.01	0.0000009	0.060	0.000

**Table D-13b: Off-Road LSI Engines Certified to Optional Standards  
Emission Factors (g/bhp-hr) (EF) and Deterioration Rates (g/bhp-hr-hr) (DR)  
Alternative Fuels**

Horsepower	Optional Standard	NOx		ROG		PM10	
		EF	DR	EF	DR	EF	DR
25-50	0.4	0.26	0.000022	0.02	0.0000017	0.060	0.000
	0.2	0.13	0.000011	0.01	0.0000009	0.060	0.000
	0.1	0.07	0.000006	0.00	0.0000000	0.060	0.000
51-120	0.4	0.21	0.000031	0.02	0.0000030	0.060	0.000
	0.2	0.11	0.000015	0.01	0.0000013	0.060	0.000
	0.1	0.05	0.000007	0.01	0.0000013	0.060	0.000
121+	0.4	0.21	0.000034	0.01	0.0000016	0.060	0.000
	0.2	0.11	0.000015	0.01	0.0000013	0.060	0.000
	0.1	0.05	0.000010	0.00	0.0000000	0.060	0.000

## LOCOMOTIVES

**Table D-14a: Locomotive  
Emission Factors (g/bhp-hr)  
Based on 1998 Federal Standards**

<b>Engine Model Year</b>	<b>Type</b>	<b>NO<sub>x</sub><sup>(a)</sup></b>	<b>ROG<sup>(b)</sup></b>	<b>PM<sub>10</sub><sup>(a)</sup></b>
Pre-1973	Line-haul and Passenger	12.22	0.51	0.275
	Switcher	16.36	1.06	0.378
1973-2001 Tier 0	Line-haul and Passenger	8.93	1.05	0.516
	Switcher	13.16	2.21	0.619
2002-2004 Tier 1	Line-haul and Passenger	6.96	0.58	0.387
	Switcher	10.34	1.26	0.464
2005-2011 Tier 2	Line-haul and Passenger	5.17	0.32	0.172
	Switcher	7.61	0.63	0.206

Note: These factors are to be used for the project baseline emissions if the baseline locomotive is certified or required to be certified to the 1998 federal locomotive remanufacture standards, and for the reduced emission locomotive if the project locomotive is remanufactured to these 1998 standards.

Factors are based upon Regulatory Impact Analysis: Final United States Environmental Protection Agency (U.S. EPA) Locomotive Regulation (2008).

- (a) NO<sub>x</sub> and PM<sub>10</sub> emission factors have been adjusted by a factor of 0.94 and 0.86, respectively, to account for use of California ultra-low sulfur diesel fuel.
- (b) ROG = HC \* 1.053

**Table D-14b: Locomotive  
Emission Factors (g/bhp-hr)  
Based on 2008 Federal Standards**

<b>Engine Model Year</b>	<b>Type</b>	<b>NO<sub>x</sub><sup>(a)</sup></b>	<b>ROG<sup>(b)</sup></b>	<b>PM10<sup>(a)</sup></b>
1973-2001 Tier 0+	Line-haul and Passenger	6.96	0.58	0.189
	Switcher	11.09	2.21	0.224
2002-2004 Tier 1+	Line-haul and Passenger	6.96	0.58	0.189
	Switcher	10.34	1.26	0.224
2005-2011 Tier 2+	Line-haul and Passenger	5.17	0.32	0.086
	Switcher	7.61	0.63	0.112
2011-2014 Tier 3	Line-haul and Passenger	5.17	0.32	0.086
	Switcher	4.70	0.63	0.086
2015 Tier 4	Line-haul and Passenger	1.22	0.15	0.026
	Switcher	1.22	0.15	0.026

Note: These factors are to be used for the project baseline emissions if the baseline locomotive is certified or required to be certified to the new (2008) federal locomotive remanufacture standards, and for the reduced emission locomotive if the project locomotive is remanufactured to the new standards or meets Tier 3 standards. Factors are based upon Regulatory Impact Analysis: Final U.S. EPA Locomotive Regulation (2008).

(a) NO<sub>x</sub> and PM10 emission factors have been adjusted by a factor of 0.94 and 0.86, respectively, to account for use of California ultra-low sulfur diesel fuel.

(b) ROG = HC \* 1.053

MARINE VESSELS

**Table D-15a: Uncontrolled Harbor Craft Propulsion Engine Emission Factors (g/bhp-hr)**

Horsepower	Model Year	NOx	ROG	PM10
25-50	All	7.57	1.32	0.520
51-120	pre-1997	14.27	1.04	0.575
	1997+	9.70	0.71	0.524
121-250	pre-1971	15.36	0.95	0.527
	1971-1978	14.27	0.79	0.451
	1979-1983	13.17	0.72	0.376
	1984+	12.07	0.68	0.376
251+	pre-1971	15.36	0.91	0.506
	1971-1978	14.27	0.76	0.431
	1979-1983	13.17	0.68	0.363
	1984-1994	12.07	0.65	0.363
251-750	1995+	8.97	0.49	0.260
751+	1995+	12.07	0.60	0.363

**Table D-15b: Controlled Harbor Craft Propulsion Engine  
Emission Factors (g/bhp-hr)**

<b>Horsepower</b>	<b>Tier</b>	<b>NOx</b>	<b>ROG</b>	<b>PM10</b>
25-50	1	6.93	1.30	0.580
	2	5.04	1.30	0.240
	3	5.04	1.30	0.176
51-120	1	6.93	0.71	0.524
	2	5.04	0.71	0.240
	3	5.04	0.71	0.176
121-175	1	8.97	0.49	0.290
	2	4.84	0.49	0.176
	3	3.60	0.49	0.077
176-750	1	8.97	0.49	0.290
	2	4.84	0.49	0.120
	3	3.87	0.49	0.068
751-1900	1	8.97	0.49	0.290
	2	5.24	0.49	0.160
	3	3.87	0.49	0.068
1901+	1	8.97	0.49	0.290
	2	5.24	0.49	0.160
	3	4.14	0.49	0.085

**Table D-16: Tier 4 Harbor Craft Propulsion Engine  
Emission Standards (g/bhp-hr)  
(Not applicable for engines using FEL or ABT for compliance)**

<b>Model Year</b>	<b>Horsepower</b>	<b>Tier</b>	<b>NOx</b>	<b>ROG</b>	<b>PM10</b>
2016+	805-4960	4	1.34	0.142	0.030

**Table D-17a: Uncontrolled Harbor Craft Auxiliary Engine  
Emission Factors (g/bhp-hr)**

<b>Horsepower</b>	<b>Model Year</b>	<b>NOx</b>	<b>ROG</b>	<b>PM10</b>
25-50	all	6.42	1.58	0.460
51-120	pre-1997	12.09	1.23	0.508
	1997+	8.14	0.85	0.417
121-250	pre-1971	13.02	1.13	0.466
	1971-1978	12.09	0.94	0.399
	1979-1983	11.16	0.86	0.333
	1984-1995	10.23	0.82	0.333
	1996+	7.75	0.59	0.255
251-750	pre-1971	13.02	1.08	0.448
	1971-1978	12.09	0.90	0.381
	1979-1983	11.16	0.81	0.321
	1984-1994	10.23	0.77	0.321
	1995+	7.60	0.58	0.230
751+	pre-1971	13.02	1.08	0.448
	1971-1978	12.09	0.90	0.381
	1979-1986	11.16	0.81	0.321
	1987-1998	10.23	0.72	0.321
	1999+	7.75	0.58	0.255

**Table D-17b: Controlled Harbor Craft Auxiliary Engine  
Emission Factors (g/bhp-hr)**

<b>Horsepower</b>	<b>Tier</b>	<b>NOx</b>	<b>ROG</b>	<b>PM10</b>
25-50	1	6.54	1.54	0.511
	2	5.04	1.54	0.240
	3	5.04	1.54	0.176
51-120	1	6.93	0.85	0.464
	2	5.04	0.85	0.240
	3	5.04	0.85	0.176
121-175	1	6.93	0.58	0.255
	2	4.84	0.58	0.176
	3	3.60	0.58	0.077
176-750	1	6.93	0.58	0.255
	2	4.84	0.58	0.120
	3	3.78	0.58	0.068
751-1900	1	6.93	0.58	0.255
	2	5.24	0.58	0.160
	3	3.87	0.58	0.068
1901+	1	6.93	0.58	0.255
	2	5.24	0.58	0.160
	3	4.14	0.58	0.085

**Table D-18: Harbor Craft Load Factors**

<b>Vessel Type</b>	<b>Propulsion Engine</b>	<b>Auxiliary Engine</b>
Charter Fishing	0.52	0.43
Commercial Fishing	0.27	
Ferry/Excursion	0.42	
Pilot	0.51	
Tow	0.68	
Work	0.45	
Other	0.52	
Barge/Dredge	0.45	0.65
Crew & Supply	0.38	0.32
Tug	0.50	0.31

**Table D-19: Shore Power  
Default Emission Rates (Grams per kilowatt-hour (g/kW-hr))**

<b>Pollutant</b>	<b>Emission Rate</b>
NOx	13.09
ROG	0.49
PM10 (marine gas oil fuel with 0.11- 0.5 % sulfur content)	0.38
PM10 (marine gas oil fuel with <= 0.10 % sulfur content)	0.25

**Table D-20: Shore Power  
Default Power Requirements**

<b>Ship Category</b>	<b>Ship Size / Type Default (Twenty-foot Equivalent Unit (TEU))</b>	<b>Power Requirement (kW)</b>
Container Vessel	<1,000	1,000
	1,000 - 1,999	1,300
	2,000 - 2,999	1,600
	3,000 - 3,999	1,900
	4,000 - 4,999	2,200
	5,000 - 5,999	2,300
	6,000 - 6,999	2,500
	7,000 - 7,999	2,900
	8,000 - 9,999	3,300
	10,000 - 12,000	3,700
Passenger Vessel	No Default Value - Use Actual Power Requirement <sup>(a)</sup>	
Reefer	Break Bulk	1,300
	Fully containerized	3,300

(a) The average power requirement for passenger vessels is 7,400 kW (ARB Oceangoing Vessel Survey, 2005).

## ALL ENGINES

**Table D-21: Fuel Consumption Rate Factors (bhp-hr/gal)**

Category	Horsepower/Application	Fuel Consumption Rate
Non-Mobile Agricultural Engines	ALL	17.5
Locomotive	Line Haul and Passenger (Class I/II)	20.8
	Line Haul and Passenger (Class III)	18.2
	Switcher	15.2
Other	< 750 hp	18.5
	≥ 750 hp	20.8

## REFERENCES

The information in these tables has already been incorporated into the preceding emission factor tables. These tables are included for informational purposes.

**Table D-22: Fuel Correction Factors On-Road Diesel Engines**

Model Year	NO <sub>x</sub>	PM <sub>10</sub>	HC
Pre- 2007	0.93	0.72	0.72
2007+	0.93	0.80	0.72

**Table D-23: Fuel Correction Factors Off-Road Diesel Engines**

<b>Model Year</b>	<b>NOx</b>	<b>PM10</b>	<b>HC</b>
Pre-Tier 1	0.930	0.720	0.720
Tier 1 - Tier 3	0.948	0.800	0.720
Tier 4	0.948	0.852	0.720

**Table D-24:  
Capital Recovery Factor (CRF) for Various  
Project Lives At a 1% Discount Rate**

<b>Project Life</b>	<b>CRF</b>
1	1.010
2	0.508
3	0.340
4	0.256
5	0.206
6	0.173
7	0.149
8	0.131
9	0.117
10	0.106
11	0.096
12	0.089
13	0.082
14	0.077
15	0.072
16	0.068
17	0.064
18	0.061
19	0.058
20	0.055

**Table D-25:**  
**Capital Recovery Factor (CRF) for Various Project Lives At a 2% Discount Rate<sup>(a)(b)</sup>**

Project Life	CRF
1	1.020
2	0.515
3	0.347
4	0.263
5	0.212
6	0.179
7	0.155
8	0.137
9	0.123
10	0.111
11	0.102
12	0.095
13	0.088
14	0.083
15	0.078
16	0.074
17	0.070
18	0.067
19	0.064
20	0.061

- (a) Upon ARB approval of the 2017 Moyer Program Guidelines, the discount rate is one percent. Per statute ARB reviews and may update discount rates annually, using the average rates of return for U.S. Treasury securities and the California Consumer Price Index data available at the time of publication.
- (b) The Discount Rate varies from year to year, and may increase beyond 2 percent. The formula used to calculate the CRF based on the Discount Rate can be found in Appendix C, Formula C-2.