

**CARB LCFS FUEL PATHWAY REPORT
CRIMSON RENEWABLE ENERGY LLC BIODIESEL**

**Crimson Renewable Energy LLC
17731 Millux Rd,
Bakersfield, CA 93311
United States**

EXECUTIVE SUMMARY

The California Air Resources Board approved the original LCFS regulation in April 2009 as a discrete early action measure under the California Global Warming Solutions Act of 2006 (AB 32). In addition, the Board subsequently approved amendments to the LCFS in 2011, 2015, 2018, 2019 and 2024. In 2024 CARB developed new simplified calculators based on GREET 4.0 for determining the CI of transportation fuels. The new calculators are required to be used from January, 1, 2025.

Crimson Renewable Energy LLC has been producing biodiesel for a number of years. The plant has recently been expanded with the addition of a new processing line that uses a different production process. This report accompanies a CARB Application for a provisional Carbon Intensity determination for the corn oil, animal fat, and used cooking oil biodiesel produced by both production lines at the expanded plant.

The emissions calculated for the individual stages are summed to determine the fuel cycle CI. The results for the Crimson Renewable Energy LLC biodiesel pathways are shown in the following table.

Table ES- 1 Lifecycle GHG Emissions – Biodiesel (gCO₂e/MJ)

Feedstock	Corn Oil	Animal Fat	UCO Mexico	UCO Zero Energy	UCO Low Energy	UCO Std Energy
Feedstock Production						
Fuel Production						
Indirect Land Use	0.00	0.00	0.00	0.00	0.00	0.00
Tailpipe Emissions	0.76	0.76	0.76	0.76	0.76	0.76
Biodiesel Total	25.27	30.20	19.70	13.74	13.93	18.47
SAFETY CI	2.53	3.02	5.00	1.37	1.39	1.85
Total w/ Safety CI	27.80	33.22	24.70	15.11	15.32	20.32

TABLE OF CONTENTS

EXECUTIVE SUMMARY	I
TABLE OF CONTENTS	II
1. INTRODUCTION	1
1.1 CRIMSON RENEWABLE ENERGY.....	1
1.2 BIODIESEL PROCESS	3
1.3 MODEL SET-UP	5
2. FEEDSTOCK.....	6
2.1 DISTILLERS’ CORN OIL.....	6
2.2 ANIMAL FAT.....	6
2.3 USED COOKING OIL ZERO ENERGY UCO 1	6
2.4 USED COOKING OIL LOW RENDERING ENERGY– UCO 2.....	7
2.5 USED COOKING OIL STANDARD RENDERING ENERGY – UCO 3	7
2.6 USED COOKING OIL FROM MEXICO – STANDARD ENERGY.....	7
2.7 SUMMARY	7
3. BIODIESEL PRODUCTION.....	8
3.1 MASS INPUTS AND OUTPUTS	8
3.2 ENERGY REQUIREMENTS	8
3.2.1 Natural Gas.....	8
3.2.2 Electricity.....	8
3.3 CHEMICALS	8
3.3.1 Methanol	8
3.3.2 Sodium Methylate	8
3.3.3 Citric Acid.....	9
3.3.4 Sodium Hydroxide.....	9
3.3.5 [REDACTED].....	9
3.3.6 Phosphoric Acid.....	9
3.3.7 Sulphuric Acid.....	9
3.3.8 Chemical Summary.....	9
3.4 CO-PRODUCTS	10
3.4.1 Crude Glycerine.....	10
3.4.2 Distilled Glycerine	10
3.4.3 Distillation Bottoms	10
3.4.4 FCO	10
4. BIODIESEL TRANSPORT.....	11
5. TANKS TO WHEELS.....	12
6. INDIRECT LAND USE CHANGE.....	13
7. SUMMARY.....	14

1. INTRODUCTION

This report accompanies a CARB Application for a Carbon Intensity determination for the corn oil, animal fat and used cooking oil biodiesel produced by the plant.

1.1 CRIMSON RENEWABLE ENERGY

Crimson Renewable Energy LLC is a part of Crimson Renewable Energy Holdings.

Crimson Renewable Energy completed its first biodiesel production facility, located in Bakersfield, California, in 2009. This plant is one of the largest of its kind in California. It was upgraded during 2010 and 2011 to handle a wider variety of raw materials including ultra-low carbon feedstocks such as used cooking oils, waste animal fats, and waste corn oil derived from ethanol production. It has a production capacity of 24 million USG per year. Crimson began biodiesel production at this facility in 2011.

Crimson has invested significant resources in designing and testing its own innovative biodiesel production process. Crimson's biodiesel production process is a closed loop, continuous system that minimizes emissions and waste products, and does not create unpleasant odors or high noise levels. Crimson biodiesel production plants feature the application of new technologies and systems for feedstock pre-treatment, transesterification (the chemical process for making methyl esters), glycerin processing and methanol recovery.

Crimson's biodiesel production facility is designed to process multiple types of feedstock ranging from vegetable oils to algae oil to waste cooking oils and animal fats. The Crimson Bakersfield Biodiesel Production Plant uses primarily waste animal fats, used cooking oils and corn oil from distillers grains to produce an ultra-low carbon biodiesel. Crimson works with a variety of feedstock suppliers but in all instances, they strive to work with suppliers who are committed to sustainable practices. Whenever possible, Crimson endeavors to work with in state suppliers.

In 2021 Crimson completed the construction of an additional processing unit (RepCat) at the facility. This new processing line uses a different process and it can be operated as an integrated facility.

The original facility is shown in the following figure.

Figure 1-1 Crimson Renewable Energy LLC Facility



The RepCat facility is shown in the following figure.

Figure 1-2 **Crimson Renewable Energy LLC RepCat**



1.2 BIODIESEL PROCESS

The original Crimson production process employs both acid esterification and transesterification so that both triglycerides and free fatty acids can be converted into biodiesel. This results in a high biodiesel yield in spite of the high free fatty acid levels of the incoming feedstocks. The plant processes mostly used cooking oil, with some distillers' corn oil, and animal fats processed from time to time.

The original Crimson process is shown in the following figure.

2. FEEDSTOCK

Each feedstock for the plant is entered on a separate sheet in the simplified calculator. For Crimson Renewable Energy the feedstock data is entered on the following sheets.

1. Corn Sorghum Oil
2. Tallow 1
3. UCO 1 – Zero Energy Rendering
4. UCO 2 – Low Energy Rendering
5. UCO 3 – Standard Energy Rendering
6. Others 1 – UCO Mexico

UCO 1 and UCO 2 are low energy user defined pathways. The Tallow and Corn Oil pathways use the CA GREET default values. UCO Mexico uses values calculated from the IEA website.

2.1 DISTILLERS' CORN OIL

Biodiesel is produced from distillers' corn oil. The corn oil is received both by truck, from nearby ethanol plants, and by rail car from ethanol plants that are further away. The moisture content of the corn oil is determined at the plant and the monthly average values are entered into the calculator. The average moisture content of the corn oil is recorded and the monthly average is entered in the calculator.

The monthly receipts by mode of transport are shown in the previously uploaded "Support Files" folder in the file "A - Primary Data sheet for GREET".

2.2 ANIMAL FAT

The biodiesel is also produced from animal fat (Tallow 1). The new process has the ability to handle high FFA feedstocks better than the original process so the quantities of animal fats processed has increased.

The default energy for rendering is assumed for this pathway.

Animal fat is all received by rail and by truck. The rail and truck distances are recorded for each shipment. The average value for each month has been recorded and entered into the calculator for each month. The average moisture content of the tallow is recorded and the monthly average is entered in the calculator. The monthly receipts by mode of transport are shown in the previously uploaded "Support Files" folder in the file "A - Primary Data sheet for GREET".

2.3 USED COOKING OIL ZERO ENERGY UCO 1

The next used cooking oil pathway is for zero energy rendering. Crimson Renewable Energy has a number of suppliers who are in this category. The monthly receipts by mode of transport are shown in the previously uploaded "Support Files" folder in the file "A - Primary Data sheet for GREET". The rendering emissions for this user defined pathway are zero g CO₂eq/MJ.

2.4 USED COOKING OIL LOW RENDERING ENERGY– UCO 2

Biodiesel is produced from used cooking oil that uses the low rendering energy. This material is received by truck. The moisture content of the material is measured at the plant and the monthly average value is used in the calculator. The monthly receipts by mode of transport are shown in the previously uploaded “Support Files” folder in the file “A - Primary Data sheet for GREET”. The rendering emissions for this user defined pathway are [REDACTED] of oil.

2.5 USED COOKING OIL STANDARD RENDERING ENERGY – UCO 3

Biodiesel is produced from used cooking oil that uses the standard rendering energy. This material is received by truck and by rail. The moisture content of the material is measured at the plant and the monthly average value is used in the calculator. The monthly receipts by mode of transport are shown in the previously uploaded “Support Files” folder in the file “A - Primary Data sheet for GREET”.

2.6 USED COOKING OIL FROM MEXICO – STANDARD ENERGY

Biodiesel is produced from used cooking oil from Mexico that use the standard rendering energy. This material is received by truck transloaded to rail. The moisture content of the material is measured at the plant and the monthly average value is used in the calculator. The monthly receipts by mode of transport are shown in the previously uploaded “Support Files” folder in the file “A - Primary Data sheet for GREET”.

Rendering energy, truck and rail transport uses CARB supplied default values.

2.7 SUMMARY

The feedstock emissions for the five pathways are shown in the following table.

Table 2-1 Feedstock Summary

Feedstock	G CO ₂ eq/MJ
Corn Oil	[REDACTED]
Animal Fat	[REDACTED]
Others1, UCO Mexico	[REDACTED]
UCO 1, zero energy	[REDACTED]
UCO 2, low energy	[REDACTED]
UCO 3, standard energy	[REDACTED]

3. BIODIESEL PRODUCTION

The production of biodiesel requires energy and chemical inputs. The calculator has a number of required inputs for biodiesel production. These include data on the co-products. These are discussed below.

3.1 MASS INPUTS AND OUTPUTS

The feedstock processed is automatically calculated by the calculator based on receipts and changes in the inventory levels. The production of biodiesel is determined via a calibrated, temperature-corrected meter for each plant.

All production from the plant is measured by a volume meter and temperature corrected to 60F.

3.2 ENERGY REQUIREMENTS

The plant purchases natural gas and electricity from the local utilities.

3.2.1 Natural Gas

The natural gas purchased is billed in therms (99,976 BTU). 10.0024 therms is one million BTU. The invoice values divided by 10.0024 are entered into the calculator.

3.2.2 Electricity

The electric power is billed in kWh. There are three uses of power, Plant 1, RepCat and power for the nitrogen plant.

3.3 CHEMICALS

The RepCat plant uses different chemicals than a typical biodiesel plant. In order to accommodate this, a separate calculator has been developed to calculate the emissions associated with the chemicals. The emission factors for the chemicals are all taken from the CA GREET 3.0 model and are discussed below.

3.3.1 Methanol

The carbon intensity of pure methanol in the CA GREET 3.0 calculator is 6,221 grams/gallon. This can be determined by zeroing out the methanol input into the CA GREET calculator and determining the change in GHG emissions.

3.3.2 Sodium Methylate

The sodium methylate (sodium methoxide) carbon intensity is taken from the CA GREET 3.0 model. This is an input for the biodiesel production process so the emission factor can be determined by zeroing this value and determining the change in the biodiesel production emissions. The emission factor is 49 g CO₂eq/pound.

Sodium methylate is purchased in a solution of methanol. So the methanol portion of the purchase is separated and added to the methanol purchases before the emissions for methanol and sodium methylate are calculated.

3.3.3 Citric Acid

The citric acid carbon intensity is taken from the CA GREET 3.0 model. The emission factor is found on the Ag Inputs sheet in column EN. The CO₂eq is calculated from the values in rows 57 to 67 using the GPS on the fuel spec sheet. The emission factor is 659 g CO₂eq/pound of citric acid.

3.3.4 Sodium Hydroxide

Historically, Plant-1 had used Sodium Hydroxide. This chemical is no longer used.

3.3.5 [REDACTED]

The emission factor for this chemical is on the catalyst sheet, column BJ in the CA GREET 3.0 model. The GHG emissions have to be calculated, from the CO₂, CH₄, N₂O, VOC and CO. This is [REDACTED] CO₂eq/kg of MgO.

3.3.6 Phosphoric Acid

These emissions are found on the Ag Inputs sheet in column G. The value is 0.89 g CO₂eq/gram of P₂O₅. The reporting of phosphoric acid concentration as P₂O₅ equivalents is an old chemistry tradition. To convert to phosphoric concentration the following steps are taken.

$$1000\text{g P}_2\text{O}_5 \times 1 \text{ mol/ } 142 \text{ g} = 7.04 \text{ mol P}_2\text{O}_5.$$



$$\text{Mass of } 14.08 \text{ mol H}_3\text{PO}_4 * 98 \text{ g mol} = 1380 \text{ g H}_3\text{PO}_4$$

So one gram of P₂O₅ is equivalent to 1.38 g of phosphoric acid and the emission factor is 0.89/1.38= 0.68g CO₂eq/gram of phosphoric acid. The process uses a 75% phosphoric acid concentration so the emission factor should be 0.49 g CO₂eq/gram of 75% phosphoric acid. This is 222 g CO₂eq/pound.

3.3.7 Sulphuric Acid

The sulphuric acid carbon intensity is taken from the CA GREET 3.0 model. The emissions are found on the Ag Inputs sheet, column BH, row 92 to 102. The emission factor is 22 g CO₂eq/pound.

3.3.8 Chemical Summary

The sum of the emissions of all of the chemicals is divided by the energy content of the biodiesel produced to arrive at a g CO₂/MJ value. This value is entered in cell L167 on the BD production sheet. The methanol opening and closing inventories and purchases are not entered in the simplified calculator as they are entered in the chemical calculator.

The chemical consumption values for all of the chemicals are shown in the previously uploaded "Support Files" folder in the file "A - Primary Data sheet for GREET".

The calculated carbon intensity for the chemicals is [REDACTED]. This value is almost the same value that would be produced with just the methanol consumption and the standard emission factor for biodiesel chemicals.

3.4 CO-PRODUCTS

The plant produces three co-products, crude glycerine, refined glycerine and distillation bottoms.

3.4.1 Crude Glycerine

The crude glycerine sales are corrected for the glycerine moisture content and the moisture free volume is entered into the calculator.

3.4.2 Distilled Glycerine

The RepCat plant produces a distilled glycerine product. One sample of this has been tested for energy content. The results were 6,867 BTU (LHV)/pound. A factor of 95% is applied to this value since it is a single sample. This value 6,524 is entered in cell P49 on the BD production sheet. Energy content is tested twice per year. To be conservative, the lowest value from all tests is used.

3.4.3 Distillation Bottoms

The RepCat plant can distill the biodiesel and thus produce distillation bottoms. The single sample produced an energy content of 15,572 BTU/pound (LHV). Ninety five percent of this is 14,793 which is entered in cell M49.

3.4.4 FCO

FCO is no longer sold as a by-product and is instead recycled into production.

4. BIODIESEL TRANSPORT

Crimson distributes their biodiesel by truck from the plant to various facilities in central and southern California. The average transportation distance is [REDACTED]. This produces distribution emissions [REDACTED].

Crimson also distributes a portion of biodiesel by rail with an average transportation distance per biodiesel gallon of [REDACTED]. This produces emissions of [REDACTED].

5. TANKS TO WHEELS

The tank to wheels emissions are the same for all biodiesel fuels. This emission category calculates the methane and nitrous oxide emissions associated with the combustion of biodiesel in the vehicle. The value in CA GREET 3.0 is 0.76 g CO₂eq/MJ.

6. INDIRECT LAND USE CHANGE

Crimson feedstocks do not have indirect land use change emissions associated with them.

7. SUMMARY

The emissions calculated for the individual stages are summed to determine the fuel cycle CI. The results for the Crimson Renewable Energy biodiesel pathways are shown in the following table.

Table 7-1 Lifecycle GHG Emissions – Crimson Renewable Energy Biodiesel

Feedstock	Corn Oil	Animal Fat	UCO Mexico	UCO Zero Energy	UCO Low Energy	UCO Std Energy
Feedstock Production						
Fuel Production						
Indirect Land Use	0.00	0.00	0.00	0.00	0.00	0.00
Tailpipe Emissions	0.76	0.76	0.76	0.76	0.76	0.76
Biodiesel Total	25.27	30.20	19.70	13.74	13.93	18.47
SAFETY CI	2.53	3.02	5.00	1.37	1.39	1.85
Total w/ Safety CI	27.80	33.22	24.70	15.11	15.32	20.32