New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 3

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFUL LI	FE (miles)	FUEL TYPE	
YEAR		LDT: <6000# GVW, 3751-	"LEV II" Low Emission	EXH / ORVR	EVAP	Gasoline	
2014	EFJXJ02.0FPT	5750# LVW	Vehicle (LEV II LEV)	150K	150K		
No.	ECS &	SPECIAL FEATURES	EVAPORATIVE FA			DISPLACEMENT (L)	
1	TWC(2),WR-HO2S,H	O2S, DFI, EGR, TC, CAC, OBD(F)	EFJXR0122	3BW			
*		•	*			2	
*		*	*	*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

BE IT FURTHER RESOLVED:

Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

California Environmental Protection Agency

OD Air Resources Board

BE IT FURTHER RESOLVED:

Vehicles certified under this Executive Order shall not be introduced into commerce before January 2, 2013.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____day of December 2012.

J. Wattence Annette Hebert, Chief Mobile Source Operations Division

California Environmental Protection Agency

OB Air Resources Board

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 3

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG (AVERAGE [g/ml] CH4 R CERT STD NMOG		AF = *	NMOG or NMHC	hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed] con-positive releasing vapor social and the social soc										
JERT				ן טוט ן	mi=mile; K	≂1000 miles; [g/mî]	NOx [g/mi]		HC	HO [mg/i	ni]	r m tg	200 1	Hwy NO	
0.016	0.043	CERT	[g/mi]	[g/mi]	CERT	i STD	CERT	STD				CERT	STD	CERT	STD
0.010		[g/mi]				3.4	0.02	0.05		2 1	5.	*	*	0.004	0.07
. Ca	@ 50K	0.053		0.075	1.4	4.2	0.02	0.07			8.	0.001	0.01	0.007	0.09
	@ UL	0.064	*	0.090	1.7			0.05			0.	•	*	*	*
(2 50°F & 4K	0.099	* ,	0.150	1.7	3.4	0.02								a lavil
CO [g/mi] @ 20°F & 50K		19. S. S. S.			NMHC+NOx [g/mi] (composite)				+NOX US06]	CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
			to the second	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT		CERT	STE 3.5
	2.5		000 miles	*	*	*	•	0.05	0.25	3.4	10.5	0.05	0.27	1.7	-
	2.5		@ * miles		*		*	*	*	*	*	*	<u> </u>	<u> </u>	
Evaporative Family		3-Davs DI				ams/test) @ UL (gran			Running L ams/mile)	@ UL	R	On-Board Refueling Vapor Recovery (grams/gallon) @ UL CERT STD			
		•	CERT	S	TD	CERT	S	TD	CER		STD				0.20
	E IV Dotoool		0.34	0	.65	0.55	Ō	.85	0.00	-	0.05		0.02		<u>0.20</u> *
EFJXR01223BW			*		*	*		*	*		*		*		
*				*	*		*	*		*		*		*	
			·		*	+		*	*		*		*		*
DT9-1	* DT 6001-85 GVWR; MD adjusted LVV	00#GVWR, /5=MDV 10 M:LEV=Iow	001-14000# 001-14000#	GVWR; El ehicle; UL on catalyst;	CS= emiss EV=ultra L SCR-U o	sion control EV; SULE r SCRC/SC	system; V=super :R-N or S Diesel Par	STD= sta ULEV; TV CRC-NF rticulate F	Indard; C NC/OC= 13= selec Filter (act	ERT= ce 3-way/oxi tive cata tive); HO2	rtification dizing c ytic red S/O2S	n; LVW=I atalyst; Al uction-ure =heated/o	oaded ven OSTWC=a a/ammonii xygen sen: sor: EGR	icle weight; dsorbing T\ a; NH3OC= sor; WR-HQ =exhaust qa	NC; ammor)2S or
LVW= VU=wan xidation FS=W ectrcula)FI=dire	n catalyst; C (ide rage/line ation; EGRC ect fuel injec	ar/heated a =EGR coole tion; TC/SC	= continuou ir-fuel ratio : er; AIR/AIRE := turbo/sup	s/penduc i sensor; Ni E=seconda per charger	ry air injec r; CAC=ch	tion (belt d arge air co r: prefix 2=	riven)/(el	ectric driv	(en); PAI	R=pulsed	AIR; S	FI/MFI= s rd diagno	equentia/ r	≃direct ozo	is Hiniecti
LVW=: /U=wai xidation FS=W ecircula FI=dire educing PG=liq	n catalyst; C ide rage/line	ar/heated a =EGR coole tion; TC/SC	= continuidu ir-fuel ratio er; AIR/AIR(>= turbo/sup ap; BCAN= E85="85%" 2(siperiodic i sensor; Ni E=seconda ber charger bleed carb Ethanol (***	ry air injec r; CAC=ch on caniste 15%"gasol	ction (belt d large air co- ar; prefix 2= line) Fuel; EAR: VI	riven)/(ele oler; OBI parallel; (E MOD	ven); PAI B)=full/pa series; DELS II	R=pulsed artial/both CNG/LNG	AIR; S on-boa S= com AATIC	FI/MFI= so rd diagno pressed/lic	equentia/ r stic; DOR quefied na	≃direct ozo	is Hiniect

.