California Environmental Protection Agency		EXECUTIVE ORDER A-003-0489
OB Air Resources Board	DAIMLER AG	New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY			ATEGORY USEFUL LIFE (miles)		STANDARD CATEGORY USEFUL LIFE (MILES)		FUEL TYPE
2014 EMBXV03.5U2B		Passenger Car	"LEV II" Ultra Low Emission	EXH / EVAP		Flexible Fuel : Ethanol (E85)/				
		Vehicle (LEV II ULEV)	120K	150K	Gasoline (Tier 2 Unleaded)					
No.		SPECIAL FEATURES	EVAPORATIVE FA	MILY (EVAF)		DISPLACEMENT (L)				
1	2TWC, 2	HO2S(2), DFI, OBD(F)	EMBXR016	EMBXR0160LNF						
*	*		*		į.	3.5				
*		*	*							

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx, as applicable, Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____775 day of June 2013.

Erik White, Chief

Alobile Source Operations Division

California Environmental Protection Agency

Op Air Resources Board

EXECUTIVE ORDER A-003-0489

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	G FLEET GE [g/ml]	NMOG (CH4 R	⊉ RAF=* AF = *	NMOG or NMHC											
CERT	STD	NMOG NMHC		STD	mi=mile; K	=1000 miles;	F=degrees	Fahrenhe	it; SETP=su	upplementa CHO [mg/i	tederal te	st procedure PM [g/	, <u> </u>	Hwy NO	
0.032	0.035	CERT [g/mi]	CERT [g/mi]	[g/mi]	CERT	[g/ml] STD	CERT	x [g/mi] STD				CERT	STD	CERT	STD
	@ 50K	0.011	*	0.040 (0.075)	0.2 (0.7)	1.7 (1.7)	0.02 (0.01)	0.05			B. B.)	* (*)	* (*)	0.01 (0.01)	0.07 (0.07)
	@UL	0.017 (0.017)	*	0.055 (0.090)	0.3 (0.8)	2.1 (2.1)	0.03 (0.02)	0.07 (0.07			1. 1.)	* (*)	0.01 (0.01)	0.02 (0.02)	0.09 (0.09)
	@ 50°F & 4K	+	*	*	*	•	*	*	*	r	*	*	*	*	•
CO	(g/mi)			NMHC+N (comp		CO [g (comp		NMHC [g/mi]	+NOx [US06]		[g/mi] 506]		C+NOx [SC03]		[g/mi] 203]
	F& 50K			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	1.4 (1.0)	SFTP @ 4	4000 miles	•	*	*	*	(0.05)	(0.14)	(1.7)	(8.0)	(0.02)	(0.20)	(0.2)	(2.7)
STD	10.0 (10.0)	SFTP	@* miles	*	*	*	*	*	*	*	*	· +	*	*	*

Evaporative Family		-Days Diurnal + Hot Soak (grams/test) @ UL		2-Days Diurnal + Hot Soak (grams/test) @ UL		ig Loss iile) @ UL	On-Board Refueling Vapor Recovery (grams/gallon) @ Ul	
Evaporative rainity	CERT	STD	CERT	STD	CERT	STD	CERT	STD
EMBXR0160LNF	0.31	0.50	*	0.65	0.000	0.05	(0.03)	(0.20)
*	*	*	*	*	*	*	*	*
*	*	*	*	*	*	+	*	*
		_	•	*	*	*	*	*

* =not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; LDT1=LDT<6000#GVWR,0-3750#LVW; LDT2=LDT<6000#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4=LDT 6001-8500#GVWR,5751-8500#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501-10000#GVWR; MDV5=MDV 10001-14000#GVWR; ECS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight; ALW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3= selective catalytic reduction-urea/ammonia; NH3OC=ammonia oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF = Diesei Particulate Filter (active); HO2S/O2S=heated/oxygen sensor; WR-HO2S or AFS=Wide range/linear/heated air-fuel ratio sensor; NOXS= NOX sensor; RDQS=reductant quality sensor; NH3S = Ammonia sensor; EGR=exhaust gas recirculation; EGRC=EGR cooler; AIR/AIRE=secondary air injection (belt driven)/(electric driven); PAIR=pulsed AIR; SFI/MFI= sequential/ multiport fuel injection; DFI=direct fue injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)(B)=full/partial/both on-board diagnostic; DOR=direct ozone reducing; HCT=Hydrocarbon Trap; BCAN=bleed carbon canister; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol (*15%"gasoline) Fuel;

2014 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	VEHICLE TYPE	SPECIAL FEATURES	OBD II
MERCEDES-BENZ	C 300 4MATIC	EMBXR0160LNF	1	3.5	PC	*	Full
MERCEDES-BENZ	E 350 4MATIC COUPE	EMBXR0160LNF	1	3.5	PC	•	Full