EXECUTIVE ORDER A-003-0491-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 3

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	EXHAUST EMISSION STANDARD CATEGORY USEFUL LIFE		FUEL TYPE
2014 EMBXV05.5U2A	Passenger Car	LEVII OIGA LOW EITHSSION ORVR -		EVAP	Gasoline (Tier 2 Unleaded	
	· · · · · · · · · · · · · · · · · · ·	Vehicle (LEV II ULEV)	120K 150K			
No.	ECS & SPECIAL FEATURES		EVAPORATIVE FAM	IILY (EVAF)		DISPLACEMENT (L)
1	2TWC, 2HO2S(2), DFI, 2TC, CAC, OBD(F)		EMBXR0155		ν.,	
2	2TWC, 2HO2S(2), DFI, OBD(F)		EMBXR0158LNC			
	*		EMBXR0160	EMBXR0160LNC		
*			EMBXR0170	LNS		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50⁰ Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-003-0491 dated April 11, 2013.

Executed at El Monte, California on this

day of July 2013

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 3

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG I AVERAG		NMOG @ CH4 R) RAF=* AF = *	NMOG or	HCHO=form	aldehyde; P	M=particulate	matter; KA	r=reactivity a	opusiment refi	ueling vapor r	ecovery; g=g	diurnal+ ram; mg=millig	gram
CERT	STD	NMOG CERT	NMHC CERT	STD	mi=mile, K=	:1000 miles; g/mi]	F=degrees F NOx I	anrenneit, 3	L I L∼subbleii	mg/mi]	PM [g/mi]	Hwy NO	x [g/mi]
0.030	0.035	[g/mi]	[g/mi]	[g/mi]	CERT	STD	CERT	STD	CERT	STD	CERT	STD	0.06	\$TD 0.07
	@ 50K	0.021	*	0.040	0.5	1.7	0.03	0.05	0.4	8		0.04	0.06	0.09
	@ UL	0.027	*	0.055	0.7	2.1	0.03	0.07	0.5	11.	<u> </u>	0.01	*	*
Profession Advanced	50°F & 4K	*	*	*	*	*	*	*	*			<u> </u>		

W 30 1 & 4			Ox [g/mi] oosite)	CO [g/mi] osite)		+NOx [US06]	00 [US	g/mi] 06]	NMHC [g/mi]		co [[sc	03]
CO [g/mi] @ 20°F & 50K		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT 0.6	SFTP @ 4000 miles	*	*	*	•	0.04	0.14	0.2	8.0	0.03	0.20	0.4	2.7
STD 10.0	SFTP @ * miles	*	*	*	* _	*	*						

Evaporative Family	3-Days Diurna	3-Days Diurnal + Hot Soak (grams/test) @ UL		2-Days Diurnal + Hot Soak (grams/test) @ UL		g Loss ile) @ UL	On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
				CERT STD		STD	CERT	STD	
		CERT STD	- CERT	0.65	0.000	0.05	0.022	0.20	
EMBXR0155LNS	0.19	0.50				0.05	0.02	0.20	
EMBXR0158LNC	0.45	0.50		0.65	0.000			0.20	
EMBXR0160LNC	0.45	0.50	•	0.65	0.000	0.05	0.07		
EMBXR0170LNS	0.39	0.50	,	0.65	0.000	0.05	0.004	0.20	

*=not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; LDT1=LDT≤6000#GVWR,0-3750#LVW; LDT2=LDT≤6000#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4=LDT 6001-8500#GVWR,5751-8500#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501-LDT3=LDT 6001-8500#GVWR; BCS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight; 10000#GVWR; MDV5=MDV 10001-14000#GVWR; ECS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LDT4=LDT400#GVWR, 5751-850#ALVW; MDV=medium-duty vehicle; MDV4=MDV &5501-550#ALVW; MDV=medium-duty vehicle; MDV4=MDV4-MDV &5501-550#ALVW; MDV=mediu

2014 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	VEHICLE TYPE	SPECIAL FEATURES	OBD II
MERCEDES-BENZ	CL 550 4MATIC	EMBXR0170LNS	1	4.7	PC	нст	Full
MERCEDES-BENZ	CL 63 AMG	EMBXR0170LNS	1	5.5	PC	нст	Full
MERCEDES-BENZ	CLS 550	EMBXR0160LNC	1	4.7	PC	нст	Full
MERCEDES-BENZ	CLS 550 4MATIC	EMBXR0160LNC	1	4.7	PC	нст	Full
MERCEDES-BENZ	CLS 63 AMG	EMBXR0160LNC	1	5.5	PC	нст	Full
MERCEDES-BENZ	CLS 63 AMG 4MATIC	EMBXR0160LNC	1	5.5	PC	нст	Full
MERCEDES-BENZ	CLS 63 AMG S	EMBXR0160LNC	1	5.5	PC	нст	Full
MERCEDES-BENZ	CLS 63 AMG S 4MATIC	EMBXR0160LNC	1	5.5	PC	НСТ	Full
MERCEDES-BENZ	E 550 4MATIC	EMBXR0160LNC	1	4.7	PC	нст	Full
MERCEDES-BENZ MERCEDES-BENZ	E 550 CONVERTIBLE	EMBXR0160LNC	1	4.7	PC	нст	Fuil
MERCEDES-BENZ MERCEDES-BENZ	E 550 COUPE	FMBXR0160LNC	1	4.7	PC	нст	Full
MERCEDES-BENZ	E 63 AMG	EMBXR0160LNC	1	5.5	PC	HCT	Full
	E 63 AMG 4MATIC	EMBXR0160LNC	1	5.5	PC	нст	Full
MERCEDES-BENZ	F 63 AMG 4MATIC (Station Wagon)	EMBXR0160LNC	1	5.5	PC	нст	Full
MERCEDES-BENZ		EMBXR0160LNC	1	5,5	PC	нст	Full
MERCEDES-BENZ	E 63 AMG S	LANDARO 100ENO	'				

California	Environmental P	rotection	Agency
Ø∌ Ai	r Resourc	ces B	oard

DAIMLER AG

EXECUTIVE	OPDED	A 002 0404 4	
	UKUEK	A-101.1-0441-1	1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 3

MERCEDES-BENZ	E 63 AMG S 4MATIC	EMBXR0160LNC	1	5.5	PC	HCT	Full
MERCEDES-BENZ	E 63 AMG S 4MATIC (Station Wagon)	EMBXR0160LNC	1	5.5	PC	НСТ	Ful!
MERCEDES-BENZ	S 63 AMG 4MATIC	EMBXR0170LNS	1	5.5	PC	HCT	Full
MERCEDES-BENZ	SL 550	EMBXR0158LNC	1	4.7	PC	HCT	Full
MERCEDES-BENZ	SL 63 AMG	EMBXR0158LNC	1	5.5	PC	HCT	Full
MERCEDES-BENZ	SLK 55 AMG	EMBXR0155LNS	2	5.5	PC	*	Full

-				
· ·				
: :			·	
1				
r :				
:				
ř				
:				
1				
٠				
	,			
•				