California Environmental Protection Agency		EXECUTIVE ORDER A-007-0333
@ Air Resources Board	VOLKSWAGEN AG	New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 3

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY USEFUL LIFE (n		FE (miles)	FUEL TYPE		
2014	EVWXV01.4HEV	Passenger Car	"LEV II" Super Ultra Low Emission Vehicle (LEV il	EXH / ORVR	EVAP	Gasoline (Tier 2 Unleaded)		
	EVVVXVUI.HILEV	i asseriger Car	SULEV)	150K 150K		plus Battery-Assist		
No.	ECS & SPECIAL FEATURES		EVAPORATIVE FA		DISPLACEMENT (L)			
1	WU-TWC, TWC, HO2S(2	2), DFI, TC, AIR, CAC, OBD(P)	EVWXR011					
*		*	*	-	1.4			
*		*	*	the first				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

#### **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50<sup>°</sup> Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx, as applicable, Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

### BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

## **BE IT FURTHER RESOLVED:**

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

#### BE IT FURTHER RESOLVED:

That the listed vehicle models have been certified as an advanced technology (AT) partial zero emission vehicle (PZEV)-Type D Hybrid Electric Vehicle (HEV) and are granted a baseline PZEV allowance of 0.2 and additional PZEV allowances under 13 CCR Section 1962.1(c).

California	Environmental	Protection	Agency
Ø Ai	r Resou	rces B	oard

VOLKSWAGEN AG

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 3

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of July 2013.

wenco Erik White, Chief Mobile Source Operations Division

California Environmental Protection Agency

**O** Air Resources Board

**VOLKSWAGEN AG** 

EXECUTIVE ORDER A-007-0333

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 3

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

			@ RAF=* NMOG or		HCHO=for	maldehyde; I	PM=particul	ate matter;	RAF=read	tivity adjust	ment fact	CO=carbon	st]=2/3 day	diumal+		
CERT	STD	NMOG	NMHC	NMHC	mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure											
0.028	0.035	CERT	CERT	[g/mi]		[g/mi]		x [g/mi]		CHO [mg/mi]		PM [g/			)x [g/mi]	
0.020		[g/mī]	[g/mi]		CERT	STD	CERT	STE			TD	CERT	STD	CERT	STD	
	@ 50K	+	*	*	*	*	*	*			*	*	*	*	*	
and the second	@ UL	0.007	*	0.010	0.2	1.0	0.005	0.02	-		4.	0.000	0.01	0.01	0.03	
@	50°F & 4K	0.010		0.020	0.4	1.0	0.01	0.02	2 .		8.	*	*	*	*	
CO [g/mi]				NMHC+NC (comp		CO [c (comp		NMHC [g/mi]			[g/mi] 506]		C+NOx [SC03]		[g/mi] 203]	
@ 20°F	& 50K		- ,	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STE	
ERT	3.6	SFTP @ 4	000 miles	*	*		*	0.05	0.14	0.02	8.0	0.002	0.20	0.2	2.7	
STD	10.0	SFTP	@* miles	*	*	*	*	*	*	*	*	*	*	*	*	
Eva	porative Far	mily		urnal + Hol ns/test) @ L		2-Days Diu (gram:	urnal + Ho s/test) @			Running L ams/mile)				Refueling V rams/gallor		
			CERT	S	STD CERT		S	STD		CERT STD		CERT		STD		
EV	WXR0110P	HE	0.21	0.	35	0.12	0.35	.35	5 0.00	02 0.05	0.01		0.20			
	*		*			*		*	*	* *			*		*	
*						+		+		*	*		*			
*		*		* *			*		* *		*		* .			
0000#G U=warm xidation o KFS=Wide ensor; EC equential liagnostic	T 6001-850 /WR; MDV ljusted LVM n-up catalys catalyst; CT e range/line GR=exhaus I/ multiport fi ;; DOR=dire ed/liguefied	5=MDV 100 /; LEV=low t; NAC=NO OX/PTOX= ear/heated at t gas recirc uel injection ect ozone re	01-14000# emission vo continuous ir-fuel ratio ulation; EG n; DFI=direc educing; HC	GVWR; EC ehicle; ULE n catalyst; s /periodic tr sensor; No RC=EGR c ct fuel inject T=Hydroca	S= emissi V=ultra LI SCR-U or ap oxidize DXS= NO ooler; AIR ion; TC/S urbon Trap	ion control EV; SULEY SCRC/SC er; DPF = E x sensor; F VAIRE=sec SC= turbo/s b; BCAN=t	System; S V=super U CR-N or S Diesel Par RDQS=re- condary a super cha	STD= sta JLEV; TV CRC-NH ticulate F ductant q ir injectio rger; CA pon canis	ndard; C VC/OC=3 3= selec ilter (acti uality se n (belt di C=charg ter; prefiz	ERT= cer 8-way/oxio tive cataly ive); HO2 nsor; NH3 tiven)/(ele e air coole c 2=parall	tification lizing ca tic redu S/O2S= S = Am ctric dri er; OBD	n; LVW=loa talyst; ADS totion-urea/ heated/oxy monia sen ven); PAIR (F)/(P)(B)	aded vehic TWC=ad ammonia gen sensi sor; PMS =pulsed A =full/partia	cle weight; lsorbing TV ; NH3OC=; or; WR-HO =particulate AIR; SFI/MI al/both on-b	VC; ammon 2S or e matter =]=	
Jinpicos	canquenea	natural gas	, LI O IIqu	621				-			ATIO	N				
MA	AKE		20 MOI	14 MOD		EVAPO	DRATIVE	EC	S E	NGINE SIZE (L)	VE	HICLE		CIAL	OBD	