🔎 Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

#### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP VEHICLE TYPE			CHAUST EMISSION	FE (miles)	FUEL TYPE		
2014	EFMXV02.0VZP	Passenger Car		VII" Super Ultra Low ission Vehicle (LEV II	EXH / ORVR	EVAP	Plug-in	
2014				SULEV)	150K	150K	Gasoline Electric Hybrid	
No.	ECS & SPECIAL FEATURES			EVAPORATIVE FAI		DISPLACEMENT (L)		
1	TWC(2), AFS, HO2S, SF1, EGR, OBD(P)			EFMXR0190				
*	<b>1</b>			*		2		
*	*			*	19 Ang			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

### **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50<sup>o</sup> Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx, as applicable, Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### **BE IT FURTHER RESOLVED:**

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

## **BE IT FURTHER RESOLVED:**

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply w

### **BE IT FURTHER RESOLVED:**

That the listed vehicle models have been certified as an advanced technology partial zero emission vehicle (AT-PZEV) -Type F Hybrid Electric Vehicle (HEV) and are granted a baseline partial zero emission vehicle (PZEV) allowance of 0.2 and additional PZEV allowance under 13 CCR Section 1962.1(c).

That the vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models has been determined to have four deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiency in the listed test group that is produced and delivered for sale in California.

California Environmental Protection Agency

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1769

### OB Air Resources Board

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 3

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2014 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_day of June 2013.

ik White, Chief Mobile Source Operations Division

California Environmental Protection Agency

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1769 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 3

Partial

BCAN

# OB Air Resources Board

ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

CERT         STD         MMOG         NMMC         CERT         STD         MMOG         CERT         STD         CERT	NMOG FLEET NMOG ( AVERAGE [g/mi] CH4 R		D RAF=*	NMOG or NMHC	CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram													
0.026         0.035         [g/mi]         [g/mi] <th>CERT</th> <th>STD</th> <th colspan="2"></th> <th></th> <th colspan="12">mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure</th>	CERT	STD				mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure												
Image: Solver in the second	0.026	0.035			[g/mi]												STD	
Image: Constraint of the second sec	1.2.1.1	6 50K			*					<u> </u>		*		*	*	*	*	
© 10°F & 44         0.016         0.020         0.2         1.0         0.00         0.02         *         8         *			0.009	*	0.010	0.3	1.0	0.02	0.02	2	*	4.		*	0.01	0.02	0.03	
CO [g/m]         NMHC+NOX [g/m]         CO [g/m]         NMHC+NOX         CO [g/m]         Stop         CERT         STD	6			*			1.0	0.00	0.02	2	*	8.		*	*	*	*	
@ 20*F & 50K         CERT         STD         CERT	CO [g/mi]																	
ERT         1.0         SFTP @ 4000 miles         1         10.0         SFTP @ * miles         1 <th1< th=""> <th1< th=""></th1<></th1<>							CERT	STD	CERT	STD	CEF	रम इ	ат	CERT	STD	CERT	STD	
Int     Int     Int     SPTP @* miles     Int	CERT	1.0	SFTP @ 4	000 miles	*	*	*	*	0.02								2.7	
Subject Sub	STD		SFTP	@* miles	*	*	*	*	*	*	*		*	*	*	*	*	
CERT         STD         CERT         STD         CERT         STD         CERT         STD         CERT         STD           EFMXR0190GCX         0.29         0.35         0.29         0.35         0.000         0.05         0.02         0.20           Image: Stress of the strestres of the stress of the stress of the stres of the	(manual teach) (Re 111											On-Board Refueling Vapor Recovery (grams/gallon) @ UL						
EFMXR0190GCX     0.29     0.33     0.29     0.33     0.50     0.50     0.50       Image: Control of the state o	Etaporativo rainity		CERT	s	TD	CERT	STD		CE	CERT STD		rd						
	EFMXR0190GCX			0.29	0	.35	0.29	0										
Image: State in the image: St	*			*														
=not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; LDT1=LDT≤6000#GVWR.0-3750#LVW; LDT2=LDT<6000#GVWR.3751-5750#ALVW; DT3=LDT 6001-8500#GVWR;3751-5750#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501- DT3=LDT 6001-8500#GVWR;3751-5750#ALVW; LDT4=LDT 6001-8500#GVWR;5751-8500#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501- 0000#GVWR; MDV5=MDV 10001-14000#GVWR; ECS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3= selective catalytic reduction-urea/ammonia; NH3C=ammor oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF = Diesel Particulate Filter (active); HO2S/O2S=heated/oxygen sensor; WR-HO2S or oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF = Diesel Particulate Filter (active); HO2S/O2S=heated/oxygen sensor; WR-HO2S or oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF = Diesel Particulate Filter (active); HO2S/O2S=heated/oxygen sensor; WR-HO2S or oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF = Diesel Particulate Filter (active); HO2S/O2S=heated/oxygen sensor; WR-HO2S or NFS=Wide range/linear/heated air-fuel ratio sensor; NOXS= NOX sensor; RDQS=reductant quality sensor; NH3S = Ammonia sensor; EGR=exhaust gas FFS=Wide range/linear/heated air-fuel ratio sensor; NOXS= NOX sensor; RDQS=reductant quality sensor; NH3S = Ammonia sensor; EGR=exhaust gas or collation; EGRC=ter fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)(B)=ful/partial/both on-board diagnostic; DOR=direct ozone reducing; HCT=Hydrocarbon Trap; BCAN=bleed carbon canister; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; .PG=liquefied petroleum gas; E85="85%" Ethanol ("15%" gasoline) Fuel; .PG=liquefied petroleum	*																	
DT3=LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4=LDT 6001-8500#GVWR; STD= standard; CERT= certification; LVW=loaded vehicle weight;         0000#GVWR; MDV5=MDV 10001-14000#GVWR; ECS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight;         04:We=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC;         04:WW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC;         04:WW=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3= selective catalytic reduction-urea/ammonia; NH3OC=ammor         0xidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF = Diesel Particulate Filter (active); HO2S/O2S=heated/oxygen sensor; WR-HO2S or         NAFS=Wide range/linear/heated air-fuel ratio sensor; NOXS= NOX sensor; RDQS=reductant quality sensor; NH3S = Ammonia sensor; ERE=exhaust gas         0:ecirculation; EGRC=EGR cooler; AIR/AIRE=secondary air injection (belt driven)/(electric driven); PAIR=pulsed AIR; SFI/MFI= sequential/ multiport fuel         0:piection; DFI=direct fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)(B)=full/partial/both on-board diagnostic; DOR#direct         0:piection; BCAN=bleed carbon canister; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas;         .PG=liquefied petroleum gas; E85="85%" Ethanol ("15%" gasoline) Fuel;         2014 MODEL       EVAPORATIVE       ECS       ENGINE       VEHICLE       SPECIAL       OBE         NAKE		*		-		-												
2014 MODEL YEAR: VEHICLE MODELS INFORMATION         MAKE       MODEL       EVAPORATIVE FAMILY       ECS NO.       ENGINE SIZE (L)       VEHICLE TYPE       SPECIAL FEATURES       OBE	LDT3=LE 10000#G ALVW=a WU=warr oxidation AFS=Wic recirculat injection;	DT 6001-850 VWR; <b>MDV</b> djusted LVV n-up catalyst; C1 de range/linu ion; EGRC= DFI=direct ducina; HC1	00#GVWR. 5=MDV 100 V; LEV=low st; NAC=NC FOX/PTOX= ear/heated a EGR coole fuel injectio F=Hydrocard	3751-5750# oot-14000# cemission v x adsorptic continuou: air-fuel ratic r; <b>AIR/AIRE</b> n; T <b>C/SC=</b> hon Trap: B	ALVW; LD GVWR; EC ehicle; ULI en catalyst; s/periodic to sensor; N ==secondat turbo/supe CAN=blee	T4=LDT 6 CS= emiss EV=ultra L SCR-U or rap oxidize OXS= NO y air inject r charger; d carbon o	ion control EV; SULE SCRC/SC er; DPF = [ x sensor; ] tion (belt di CAC=chai anister; pri	System; system; V=super t CR-N or S Diesel Par RDQS=re riven)/(ele	STD= sta JLEV; T\ CRC-NH ticulate f ductant ( ectric driv	MC/OC I3= sele Filter (ad quality s ren); PA	CERT= =3-way/ ective c ctive); H ensor; MR=pul	<ul> <li>certific</li> <li>coxidizir</li> <li>atalytic</li> <li>102S/0</li> <li>NH3S =</li> <li>sed AIF</li> <li>Ill/nartia</li> </ul>	ation; L g catal reduction 2S=he Ammon ; SFI/N	LVW=lo lyst; AD on-urea ated/oxy onia ser MFI= se	aded vehi STWC=ad /ammonia ygen sens sor; EGR quential/ r d diagnos	icle weight; dsorbing TV a; NH3OC= sor; WR-HC t=exhaust g multiport fu tic: DOR=	NC; ammoni: <b>)2S or</b> jas el tirect	
MAKE MODEL EVAPORATIVE ECS SIZE TYPE FEATURES OBE		····						EHICLE		ELS	INFO	RMA <sup>-</sup>	NOI					
ECRD C-MAX PHEV EFMXR0190GCX 1 2 PC BCAN Part	MAKE MODEL								SIZE						OBD			
					FEMXR0190GCX			1	2	2 PC		5	BCAN		Partia			

EFMXR0190GCX

FUSION PHEV

FORD

2

1

PC

