BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0347

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted

| MODEL YEAR | TEST GROUP VEHICLE TYPE | | EVIJATION PARIOCIONI | | | | FUEL TYPE | |
|---------------|-------------------------|-----------------------|------------------------|---------------|----------|---------------------------|-----------|------|
| 2014 | EBMXV01.6N16 | Passenger Car | "LEV II" Ultra Low Emi | EXH / ORVR | EVAP | Gasoline (Tier 2 Unleaded | | |
| 1 | | | Vehicle (LEV II ULEV) | | 150K | | | 150K |
| No. | ECS & SPECIAL FEATURES | | EVAPORAT | IVE FAM | # | DISPLACEMENT (L) | | |
| 1 | WU-TWC,TWC, A | AFS,HO2S, SFI, OBD(F) | EBIV | 1XR0128 | E85 | | | |
| * | * | | * | | | | 1.6 | |
| * | | • | * | | | | | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx, as applicable, Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance]. 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961. I and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

BE IT FURTHER RESOLVED:

Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. Executed at El Monte. California on this

Executed at El Monte, California on this

day of July 2013.

Fire Erik White, Chief

Mobile Source Operations Division

@ Air Resources Board

BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0347

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| NMOG FLEET AVERAGE [g/mi] | | CH4 RAF = * NMOG or | | CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NUX=oxides of introgen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diumal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=mittigram mi=mite; K=1000 mites; F=degrees Fahrenheit; SFTP=supplemental federal test procedure | | | | | | | | | | | |
|------------------------------|-------------------|---------------------|--------------|---|----------------------|-------------|-------------|-------------------------|---------------|----------------|------|---------|--------|----------|--|
| CERT | STD | NMOG CERT | NMHC CERT | STD | mi=mile: K= CO [g | 1000 miles; | F=degrees F | fahrenheit: S [g/mi] | r i P≂suppier | mental federal | PM [| 10 | Hwy NO | x [g/mi] | |
| 0.028 | 0.035 | [g/mi] | [g/mi] | [g/mi] | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD | |
| 100 July 100 100 100 | € EDV | 0.034 | * | 0.040 | 0.1 | 1.7 | 0.02 | 0.05 | * | 8. | * | * | 0.002 | 0.07 | |
| 200 | @ 50K | 0.034 | * | 0.055 | 0.1 | 2.1 | 0.03 | 0.07 | * | 11. | * | 0.01 | 0.004 | 0.09 | |
| | @ UL 50°F & 4K | 0.043 | * | 0.080 | 0.2 | 1.7 | 0.01 | 0.05 | * | 16 | * | * | * | | |
| GENERAL C | 30 1 32 410 | 0.000 | | | | -1 00 | (| NIMILCAN | iO- | CO [a/mil | NMI | -iC+NOx | CO | [g/mi] | |

| 36 25 M (0) 20 1 G | | | VOx [g/mi] posite) | | g/mi] oosite) | | +NOx [US06] | co [| g/mi] :06] | | +NOx [SC03] | [SC] | |
|---------------------------|----------------|-------|-----------------------|------|------------------|------|----------------|------|---------------|------|----------------|------|-----|
| CO [g/mi] @ 20°F & 50K | | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD |
| CERT 0.6 | SFTP @ 4000 mi | les * | * | * | * | 0.06 | 0.14 | 4.5 | 8.0 | 0.02 | 0.20 | 0.8 | 2.7 |
| CERT 0.6 STD 10.0 | | les * | * | * | * | * | * | * | * | * | * | * | * |

| C . Familia | 3-Days Diurnal + Hot Soak (grams/test) @ UL. | | 2-Days Diurn (grams/te | al + Hot Soak est) @ UL | Runnin (grams/m | | On-Board Refueling Vapor Recovery (grams/gallon) @ UL | | |
|--------------------|---|------|---------------------------|----------------------------|--------------------|------|--|--------------|--|
| Evaporative Family | CERT | STD | CERT | STD | CERT | STD | CERT | STD | |
| ED14VD0400E0E | 0.38 | 0.50 | * | 0.65 | 0.02 | 0.05 | 0.04 | 0.20 | |
| EBMXR0128E85 | V.30 | * | * | * | * * | * | * | * | |
| | | + | * | * | * | * | * | * | |
| | | * | * | * | * | * | * | * | |
| | | | <u> </u> | | | | | er casout VA | |

* =not applicable; UL=useful tife; PC=passenger car: LDT=light-duty truck; LDT1=LDT<6000#GVWR,0-3750#LVW; LDT2=LDT<6000#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4=LDT 6001-8500#GVWR,5751-8500#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501-1000#GVWR; MDV5=MDV 10001-14000#GVWR; ECS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight; 10000#GVWR; MDV5=MDV 10001-14000#GVWR; ECS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=subra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=subra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=subra LeV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=subra LeV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=subra LeV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LeV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; ALVW=adjusted LeV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; AD

2014 MODEL YEAR: VEHICLE MODELS INFORMATION

| MAKE | MODEL | EVAPORATIVE FAMILY | ECS NO. | ENGINE SIZE (L) | VEHICLE TYPE | SPECIAL FEATURES | OBD II |
|------|--------------------|--------------------|------------|-----------------------|-----------------|---------------------|--------|
| MINI | COOPER CLUBMAN | EBMXR0128E85 | 1 | 1.6 | PC | * | Full |
| MINI | COOPER CLUBVAN | EBMXR0128E85 | 1 | 1.6 | PC | * | Full |
| MINI | COOPER CONVERTIBLE | EBMXR0128E85 | 1 | 1.6 | PC | • | Full |
| MINI | COOPER COUNTRYMAN | EBMXR0128E85 | 1 | 1.6 | PC | * | Full |
| MINI | COOPER COUPE | EBMXR0128E85 | 1 | 1.6 | PC | * | Full |
| MiNI | COOPER PACEMAN | EBMXR0128E85 | 1 | 1.6 | PC | * | Full |
| MINI | COOPER ROADSTER | EBMXR0128E85 | 1 | 1.6 | PC | * | Full |