EXECUTIVE ORDER A-016-0412

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFUL LIFE (miles)		FUEL TYPE	
2014	ETKXV02.5NC1	Passenger Car	"LEV II" Super Ultra Low Emission Vehicle (LEV II	EXH / EVAP		Gasoline	
		-	SULEV)	150K	150K		
No.	ECS & SPECIAL FEATURES			EVAPORATIVE FAMILY (EVAF)			
1	WU-TWC,TV	C,AFS,HO2S,DFI,OBD(F)	ETKXR012	ETKXR0125GAX			
*		*	*				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

BE IT FURTHER RESOLVED:

That the listed vehicle models are granted a baseline partial zero emission vehicle (PZEV) allowance of 0.2 under 13 CCR Section 1962.1(c).

BE IT FURTHER RESOLVED:

Vehicles certified under this Executive Order shall not be introduced into commerce before January 2, 2013.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this $16^{\frac{3}{2}}$ day of November 2012.

Devener Annette Hebert, Chief Møbile Source Operations Division

OD Air Resources Board

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

CERT	STD	NMOG	NMHC		mi=mile; K	O=formaldenyde, PM=particulae inteller, AAP=fectivity edigeterin tecesin, oak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling nile; K=1000 miles; F≍degrees Fahrenheit; SFTP=supplemental federal test CC for/mil NQx [0/mi] HCHO [mg/mi]					a lest proce	st procedure		Hwy NOx [g/ml]		
0.029	0.035	CERT	CERT [g/ml]	[g/mi]	CO [g/mi]							CERT	PM [g/mi]		STD	
0.025		[g/mi] *	<u>l</u> g/mj		CERT	STD		- 310			*	*	*	CERT	*	
	@ 50K		-	0.010	0.1	1.0	0.02	0.02	, - *		4.	•	0.01	0.01	0.03	
		0.006		0.010	0.3	1.0	0.01	0.0		-	8.	*	*	+	*	
	2) 50°F & 4K	0.012		1							_		MHC+NOx	CO	[g/ml]	
CO [g/mi] @ 20°F & 50K		26 + 105			MHC+NOx [g/mi] (composite)		j/mi] osite)	NMHC+NOx [g/mi] [US06]		CO [g/mi] [U\$06]			[g/ml] [SC03]		[SC03]	
		98-17 2		CERT	STD	CERT	STD	CERT	STD	CEF		TD CE	RT STD	CERT	STD	
ERT	0.1	SFTP @ 4	000 miles	*	*	*	•	0.02	0.14	0.7	7 8	.0 0.1)1 0.20		2.7	
	10.0		@* miles	*	•		*	*	*	*		* 1	*	*	*	
Evaporative Family		(gran CERT	s Diurnal + Hot Soak rams/test) @ UL RT STD		(grams/test) @ UL CERT STD			(grams/mile) @ UL CERT STD			CERT		rams/galion) @ UL STD			
	TKXR0125G	A.Y.	0.19		35	*).35	0.00		0.)5	0.01		0.20	
E	*	~~	*	*		*		*	*		*		*		*	
	*		*					*								
	*	<u> </u>	*	*		*	*		*							
DT3=Li 0000#C LVW=a VU=war TOX/P uality s equenti	pplicable; UL DT 6001-850 SVWR; MDV adjusted LVV m-up catalys TOX= contin ensor; EGR= a/ multiport f ic; DOR= dir sed/liquefied	0#GVWR.(5=MDV 100 v; LEV=low t; NAC=NC uous/period exhaust ga uel injection oct ozona r	3751-5750# 001-14000# v emission v Ox adsorptic dic trap oxid is recirculati n; DFI =direct educing: H	ALVW; LD GVWR; EC ehicle; ULE in catalyst; izer; HO2S ion; EGRC: t fuel inject	I4=LDI 6 S= emissi EV=ultra LI SCR-U/SC /02S=hea EGR coo tion; TC/S arbon Trar	ion control EV; SULE CR-N= seli ited/oxyge ler; AIR/A iC= turbo/s n: BCAN=	I system; V=super ective cat n sensor; IRE=secc super cha bleed car	STD= sta ULEV; T alytic red AFS=(ho ondary ain arger; CA bon canis	andard; C WC/OC=: luction-un eated) air injection C=charge ster; prefi	ERT= 3-way/ ea/am -fuel r (belt (air co x 2=pa	certifica (oxidizin nmonia; atio sen driven)/ ooler; O arallel; (ation; LVW g catalyst; NH3OC=a sor; NOX: electric dr BD (F)/(P)	<pre>#=loaded ve ADSTWC= mmonia ox S= NOx ser iven); PAIR (B)=full/par</pre>	hicle weight adsorbing T idation catal isor; RDQS= =pulsed AIR tial/both on-	WC; /st; reducta ; SFI/MI	
	ood and a construction			14 MOE						IFO	RMAT	ION			1	
MAKE		MO			EVAP	APORATIVE		cs 📑			VEHICLE	/EHICLE SPE		ОВС		

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	VEHICLE TYPE	SPECIAL FEATURES	OBD II	
MAZDA	MAZDA6	ETKXR0125GAX	1	2.5	PC	НСТ	Full	