AUDI AG

EXECUTIVE ORDER A-030-0279

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	TEST GROUP VEHICLE TYPE		MISSION ATEGORY	USEFUL LI	FE (miles)	FUEL TYPE	
2014	EADXV02.03UA	Passenger Car	"LEV II" Ultra Lo		EXH / ORVR	EVAP	- Gasoline (Tier 2 Unleaded)	
			Vehicle (LEV		120K	150K	,	
No.				PORATIVE FAM		DISPLACEMENT (L)		
1	WU-TWC,TWC, WR-HO	2	EADXR0110					
*	*		*				2	
•			*					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50⁰ Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx, as applicable, Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

3 day of June 2013.

Ærik White, Chief

Mobile Source Operations Division

AUDI AG

EXECUTIVE ORDER A-030-0279

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF=* AVERAGE [g/mi] CH4 RAF = *				NMOG or NMOG=non-CH4 organic gas; NMHC=non-CH4 procedation; CU=carbon monoxide HCH0=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 procedation; CU=carbon monoxide HCH0=formaldehyde; PM=particulate malter; RAF=reactivity adjustment factor; 2/3 D [g/lest]=2/3 de hol-soak; RL [g/mi]=running loss, ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=									av diumal+		
CERT	STD	NMOG CERT	NMHC CERT	NMHC STD	ml=mile; K	=1000 miles [g/ml]	F=degrees	Fahrenheit x [g/mi]	t; SFTP≂su	ppiemer	ital federa	test procedur	8	Hwy NO	
0.028	0.035	[g/mi]	[g/mi]	[g/mi]	CERT	STD	CERT	STD	CEF		STD	CERT	STD	CERT	STD
	@ 50K	0.031	*	0.040	0.4	1.7	0.02	0.05	*		8.	*	*	0.01	0.07
	@ UL	0.037	*	0.055	0.4	2.1	0.02	0.07	•		11.	*	0.01	0.01	0.09
. . 0	50°F & 4K	0.030	*	0.080	0.3	1.7	0.02	0.05	*		16.	*	*	*	*
CO I	ı/mil	Village S		NMHC+N(CO [g		NMHC- [g/mi] [[g/mi] US06]		C+NOx [[SC03]		[g/mi] 203]
- CO [5	O EVR	Line of the		,					275	C. C.		CEDT	ETD	CERT	STD

3-Days Diurnal + I Evaporative Family (grams/test) (2-Days Di (gran	urnal + H ns/test) @			Running L ams/mile)				Refueling \ ams/gallor			
STD	10.0	ş SF	「P@ * miles	*	*	*	*	*	*	*	•		*		
CERT	2.1	SFTP @	4000 miles	*	*	*	*	0.03	0.14	0.5	8.0	0.02	0.20	0.6	2.7
@ 20	1°F & 50K			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	GERI	SID

Evaporative Family	3-Days Diurnal + Hot Soak (grams/test) @ UL			al + Hot Soak est) @ UL	Runnin (grams/m	g Loss ille) @ UL	On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
штиротишто т штт.	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
EADXR0110D38	0.33	0.50	0.34	0.65	0.000	0.05	0.01	0.20	
*	*	*	*	*	*	*	*	*	
*	*	*	*	*	*	*	*	*	
	*	*	*	*	*	*	*	*	

2014 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	VEHICLE TYPE	SPECIAL FEATURES	OBD II
AUDI	TT COUPE QUATTRO	EADXR0110D38	1	2	PC	*	Full
AUDI	TT ROADSTER QUATTRO	EADXR0110D38	1	2	PC	*	Full
AUDI	TTS COUPE	EADXR0110D38	1	2	PC	*	Full
AUDI	TTS ROADSTER	EADXR0110D38	1	2	PC	*-	Full