lifornia Environmental Protection Agency		EXECUTIVE ORDER A-040-0085			
OB Air Resources Board	FERRARI S.p.A.	New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2			

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-14-012;

# IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEAR	TEST GROUP VEHICLE TYPE		EXHAUST EMISSION STANDARD CATEGORY USEFUL LIFE (mile:			s) FUEL TYPE		
2014	EFEXV06.3HYB Passenger Car		"LEV II" Low Emission	EXH / EVAP		Gasoline (Tier 2 Unleaded		
2014	EFEXV00.5HTB		Vehicle (LEV II LEV)	120K 150K		plus Battery-Assist		
No.			Long Long Long Long Long Long Long Long	EVAPORATIVE FAMILY (EVAF)				
1			EFEXR017	EFEXR017512C				
*		*	•		: 6.3			
*		•	*	*				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

#### **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50<sup>°</sup> Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx, as applicable, Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

### **BE IT FURTHER RESOLVED:**

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 through 2014 Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2009 through 2016 Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended December 6, 2012 (CA Test Procedures)).

# BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13. California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated CA Test Procedures. The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a smallvolume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

3 day of June 2014

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division California Environmental Protection Agency

**O** Air Resources Board

FERRARI S.p.A.

EXECUTIVE ORDER A-040-0085 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

OFOT			DRAF=*	NMOG or	HCHO=for	mane; NMOG= maldehyde; I	PM=particul	ate matter;	RAF=reac	tivity adjustr	nent facto	r; 2/3 D [g/te:	st]=2/3 day	diumal+	-
CERT	STD	NMOG	NMHC	NMHC STD	hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure										
0.075 0.075	CERT	CERT	[g/mi]	CO [g/mi]		NOx [g/mi]				HO [mg/mi]		mi]	Hwy NO		
0.075		[g/mi]	[g/mī]		CERT	STD	CERT	STD			TD	CERT	STD	CERT	STE
	@ 50K	0.036	*	0.075	1.2	3.4	0.02	0.05			5.	*	*	0.02	0.0
Astrophe -	@ UL	0.043	*	0.090	1.2	4.2	0.02	0.07		1	8.	*	0.01	0.02	0.0
1	0 50°F & 4K	0.021	*	0.150	2.1	3.4	0.05	0.05	; *	3	0.	*	*	*	*
CO [g/mī] @ 20°F & 50K		2 a	-	NMHC+NC (compo			CO [g/mi] NMHC+N (composite) [g/mi] [US					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
		** 1		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	ST
ERT	1.8	SFTP @ 40	000 miles		*	*		0.03	0.14	0.5	8.0	0.03	0.20	1.1	2.7
STD	10.0		@* miles	+	*	*	*	*	*	*	+	*	*	*	*
3-Days Diur Evaporative Family (grams/		urnal + Hot is/test) @ U									d Refueling Vapor grams/gallon) @ UL				
			CERT	ST	D	CERT	S	STD		T STD			CERT		STD
EFEXR017512C 0.3		0.34	0.5	50	0.34 0.65		.65	0.03 0.05		0.05	0.08		0.20		
		*			*		*	*		*		*		*	
		*			*		*	*		*		*		*	
			*			*		*	*	* *		*		*	
DT3=LD	blicable; UL= T 6001-850 VWR; MDV djusted LVW	0#GVWR,37	751-5750#/	ALVW; LDT	4=LDT 60	001-8500#	GVWR,5	751-8500	#ALVW;	MDV=me	dium-d	ity vehicle;	MDV4=N	ADV 8501-	
LVW=ac VU=warm xidation ( FS=Wid ensor; E equential iagnostic	catalyst; CT le range/line GR=exhaus I/ multiport fi c; DOR=dire	t; NAC=NO: OX/PTOX= ar/heated ai t gas recircu uel injection ect ozone re	x adsorption continuous ir-fuel ratio ulation; EGF ; DFI=direc ducing; HC	chicle; ULE catalyst; S /periodic tra sensor; NC RC=EGR co t fuel injecti T=Hydroca	V=ultra LE SCR-U or ap oxidize DXS= NO: Doler; AIR ion; TC/S rbon Trap	EV; SULEV SCRC/SC r; DPF = D x sensor; F /AIRE=sec C= turbo/s b; BCAN=b	/=super L R-N or S liesel Part DQS=rec condary ai super chan leed carb	JLEV; TW CRC-NH ticulate F ductant q ir injection rger; CAC on canist	IC/OC=3 3= select ilter (acti- uality ser n (belt dr C=charge er; prefix	-way/oxid ive cataly ve); HO2S isor; NH3 iven)/(elec air coole 2=paralle	izing ca tic reduction S/O2S=I S = Ami ctric driv r; OBD	talyst; ADS ction-urea/a neated/oxyg monia sens ren); PAIR= (F)/(P)(B)=	TWC=ad ammonia; gen senso sor; PMS= pulsed A full/partia	sorbing TV NH3OC=a or; WR-HO particulate IR; SFI/MF	mmon 2S or matte
LVW=ac VU=warm xidation ( FS=Wid ensor; E0 equential iagnostic ompress	catalyst; CT le range/line GR=exhaus I/ multiport fi	t; NAC=NO: OX/PTOX= ar/heated ai t gas recircu uel injection ect ozone re	x adsorption continuous ir-fuel ratio ulation; EGF ; DFI=direc ducing; HC ; LPG=liqu	hicle; ULE n catalyst; S /periodic tra sensor; NC RC=EGR co t fuel injecti T=Hydroca efied petrol	V=ultra LE SCR-U or ap oxidize DXS= NO: Dooler; AIR ion; TC/S rbon Trap leum gas;	EV; SULEY SCRC/SC r; DPF = D x sensor; F XAIRE=sec SC= turbo/s BCAN=b E85="859 AR: VE	/=super L R-N or S liesel Part RDQS=red condary ai super char leed carb %" Ethance	ULEV; TM CRC-NH. ticulate F ductant q ir injection rger; CAC on canist ol ("15%"(	C/OC=3 3= select ilter (acti- uality ser n (belt dr C=charge er; prefix gasoline) ELS IN	-way/oxid ive cataly ve); HO2S asor; NH3 iven)/(elec a air coole 2=paralle Fuel;	izing ca tic redu S/O2S=I S = Am ctric driv r; OBD el; (2) su ATIOI	alyst; ADS ction-urea/a neated/oxyg nonia sens en); PAIR= (F)/(P)(B)= ffix=series	TWC=ad ammonia; gen senso sor; PMS= pulsed A full/partia	sorbing TV NH3OC=e pr; WR-HO :particulate .IR; SFI/MF I/both on-b NG=	mmon 2S or matte