Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION							
	MANUFACTURER	ENGINE FAI	MILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)					
	IGQING ZONGSHEN GENERAL DWER MACHINE CO., L T D.	ECZHS.420 ECZHS.292 ECZHS.420	2H1 (U-U-082-0119) 2H1 (U-U-082-0120) 2H2 (U-U-082-0115) 2H2 (U-U-082-0116) 5.6792H1 (TBC)	292 420, 357 292 420, 357 679	Gasoline					
S.A. = See TBC = To B	Attachment Be Certified	FOUIPME	NT DESCRIPTION							
MODEL YEAR	MODEL EVAPORATIVE FAMILY FUEL TANK SIZE FOUR MENT APPLICATION									
2014 CMH2 4.2, 23, 26, 47 Compressor, Pump, Stump Beater, Generator Set, Other Industrial Equipment										
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL								
	Canister/Metal	See Attachment								
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u> : Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and C</u> Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes =C,										

(Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable		DE	SIGN BASED				
	OSE PERMEATION ams ROG/m²/day)		ANK PERMEATION ams ROG/m²/day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)			
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER		
15	G-05-018, Q-08-005, C-U-05-013	1.5	*	1.4	C-U-07-021, C-U-06-031, Q-11-002, C-U-06-005, C-U-07-016, C-U-07-022, Q-11-023, Q-11-024, Q-13-005		

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this

26th day of September 2013.

hubblit

Erik White, Chief Mobile Source Operations Division

Attachment, 1 of 2

重庆宗申通用动力机械有限公司 CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD. Zongshen Industry Zone, Ba'nan District, Chongqing 400054, China

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

S1.	S2.	1	S3.		S4.	S5.	S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case	Engine or Equipment Model		s Codes approp	(check	Engine Class (I	Fuel System	Fuel Tank	Fuel Tank Internal	Fuel Line Type	Nominal Fuel Line	Fuel Line Inside	Exhaust Family	Fuel Tank Executive		Carbon Canister or Other Venting
(Check One)	mousi	CA Only	49	50 State	or II)	(FI or CARB)	Vol. (Liters)	Surface Area (m ²)		Length ⁽¹⁾ (mm)	Diameter (mm)		Order	Order	Control Executive Order
X	190F_, 183F_, 180F_ FH420_, FH300_, WH4500C, WH5500C, WH6000SC, WH6000SC, WH6000SC, WH6000SC, WH7000EC WH7000EC WH7000EC WH7000EC WH7500EC 21R164 21R165 21R166 41030, 41031 41032 41430 41431 41432 QF4.0_ QF4.5_ QF5.0_ QF5.0_ QF5.0_ QF4000_ QF4500_ QF5000_ QF6000_ QF6000_ QF7000_			X	I	CARB	23 or 26	0.71 or 0.68	multilayer	165 or 520	6.3 or 4.0	ECZHS.4202H1 ECZHS.2922H1 ECZHS.4202H2 ECZHS.2922H2		G-05-018 or Q-08-005 or C-U-05-013	C-U-U7-U22 OF

U-U-082-0121

Attachment, 2 of 2



重庆宗申通用动力机械有限公司 CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD. Zongshen Industry Zone, Ba'nan District, Chongqing 400054, China

190F_ 183F_ 180F_ GH420_ GH360_ GH300_		×	Ħ	CARB	4.2	0.21	multilayer	210	6.3 or 4.0	ECZHS.4202H1 ECZHS.2922H1 ECZHS.4202H2 ECZHS.2922H2	N/A	G-05-018 or Q-08-005 or C-U-05-013	C-U-07-021 or C-U-06-031 or Q-11-002 or C-U-06-005
2V78_ QF10_ QF12_ QF10000_ QF12000_	•	x	II	CARB	23 or 26	0.57 or 0.68	multilayer	1500	4.0	ECZHS.6792H1	N/A	Q-08-005 or C-U-05-013	C-U-07-016 or C-U-07-022 or Q-11-023 or Q-13-005
2V78_ QF10_ QF12_ QF1000_ QF12000_		x	II	CARB	47	0.91	multilayer	1000	4.0	ECZHS.6792H1	N/A	Q-08-005 or C-U-05-013	Q-11-024

(1) The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)

(2) Postfix "_" is the designator(s) for future non-emission related revision change.