EXECUTIVE ORDER U-U-012-0481
New Off-Road Small Spark-Ignition
Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	FNGINE FAMIL		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefier petroleum gas)				
2015	FFJXS	6.4042GB	404	4-stroke, ≥ 225 cc		Gasoline				
DURABILITY HOURS			SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
1000			ЕМ			Compressor, Pump, Pressure Washer, Stump Beater, Generator, Non-Backpack Blower, Leaf Blower/Vacuum and Commercial Turf				
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment								
EGR=exhaust	gas recircu	lation AIR=sec	ondary air injection PAIR=pul	Ised AIR MFI=multi	port fuel inju	=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ection SFI=sequential MFI TBI=throttle body fuel injection ffix)=in series ECM=engine control module				

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549	*	
FAMILY EMISSION LEVEL	8.0	*	*	
CERTIFICATION LEVEL	6.8	386	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of October 2014.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Model Year: 2015

Manufacturer: Fuji Heavy Industries Ltd. Engine Family: FFJXS.4042GB

Issued: August 27, 2014

Revised: E.O. Number:

CARB

ATTACHMENT BY IOH
Small Off-Road Engine Model Summary Form

4-4-012-0481

Page: 9

Units for Table: kW

	47.	48. ,	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case?	Model Desig- nation	Sales Code	Displ. (cc)	Bore/ Stroke	Ignition Timing (BTDC)	Max Power (kW)	Rated Speed (RPM)	Rated Torque (N-m)	Torque Speed (RPM)	Emission Control System
x	EX400Y1	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y2	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y3	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y4	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y5	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y6	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y7	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y8	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX350Y1	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX350Y2	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX350Y3	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX350Y4	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX350Y5	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX350Y6	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX400T1	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400T2	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400T3	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM