EXECUTIVE ORDER U-U-012-0503 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)			
2016	GFJX	S.4042GB	404	4-stroke, ≥ 225 cc		Gasoline			
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
1000		EM			Compressor, Pump, Pressure Washer, Stump Beater, Generator, Non-Backpack Blower, Leaf Blower/Vacuum and Commercial Turf				
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment							

ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549	,*	
FAMILY EMISSION LEVEL	8.0	*	*	
CERTIFICATION LEVEL	6.8	386	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

__ day of 9ctober 2015.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT Pg (of 1

Model Year: 2016

Manufacturer: Fuji Heavy Industries Ltd. Engine Family: GFJXS.4042GB

Issued: September 9, 2015

Page: 9

Revised:

E.O. Number: U-U-0(2-0503

CARB

Small Off-Road Engine Model Summary Form

Units for Table: kW

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case?	Model Desig- nation	Sales Code	Displ. (cc)	Bore/ Stroke	Ignition Timing (BTDC)	Max Power (kW)	Rated Speed (RPM)	Rated Torque (N-m)	Torque Speed (RPM)	Emission Control System
х	EX400YI	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y2	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y3	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y4	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y5	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y6	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y7	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400Y8	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX350Y1	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX350Y2	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX350Y3	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX350Y4	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX350Y5	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX350Y6	50-State	404	89/65	24 deg.	7.4	3600	26.0	2400	EM
	EX400T1	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400T2	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM
	EX400T3	50-State	404	89/65	24 deg.	8.8	3600	27.0	2400	EM