EXECUTIVE ORDER U-U-017-0239

New Off-Road Small Spark-Ignition
Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY GYMXS.0805EH		DISPLACEMENT (cc)	ENGINE CLASS 4-stroke, 50-80 cc inclusive		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefi petroleum gas)		
2016			80			Gasoline		
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
500		EM			Generator			
ENGINE CODES/MODELS (rated power in kilowatt, kW)			See Attachment					

ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	72	536	*	
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	15	336	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 30

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

AMACUMENT PS/of1

RC1 10/19/16
Page: 9

Model Year:

2016

YAMAHA MOTOR CO.,LTD.

Issued: Revised:

9/21/2016

Manufacturer:

Engine Family: GYMXS.0805EH

E.O. Number: u - u - 0.7 - 0.239

Small Off-Road Engine Model Summary Form

Units for Table kW

	47.	48.	4 9.	50.	51.	52 .	53.	54.	55.	56.	
V/orst	Model	Sales	Displ	Bore/	Ignition	Max	Rated Speed	Rated	Torque Speed	Emiss	
Case?	Designation	Code	(CC)	Stroke	Timing	Power	(RPM)	Torque	(RPM)	Control Sys	
	EF20iSX	50-State	80	48.6x43mm	BTDC 23	2.31kw	4500	4.9Nm	4000	EM	
	EF20iSCX	50-State	80	48.6x43mm	BTDC 23	2 31kw	4500	4.9Nm	4000	EM	
	Pro2 0iSX	50-State	80	48.6x43mm	BTDC 23	2.31kw	4500	4.9Nm	4000	EM	
	7DXV-030	50-State	80	48.6x43mm	BTDC 23	2.31kw	4500	4.9Nm	4000	EM	
	Pro2.0iSY	50-State	80	48.6x43mm	BTDC 23	2.31kw	4500	4.9Nm	4000	EM	
Х	EF20iSVX	50-State	80	48.6x43mm	BTDC 23	2.31kw	4500	4.9Nm	4000	EM	
	EF20iSCVX	50-State	80	48.6x43mm	BTDC 23	2.31kw	4500	4.9Nm	4000	EM	
	EF20iSY	50-State	80 .	48.6x43mm	BTDC 23	2.31kw	4500	4.9Nm	4000	EM	
	EF20iSCY	50-State	80	48.6x43mm	BTDC 23	2.31kw	4500	4.9Nm	4000	EM	
	EF20iSMVX	50-State	80	48.6x43mm	BTDC 23	2.31kw	4500	4.9Nm	4000	EM	