ZHEJIANG YAOFENG POWER TECHNOLOGY CO., LTD.

EXECUTIVE ORDER U-U-220-0053 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR ENGINE		NE FAMILY	DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)			
2016	GZYF	S.2241GA	192, 196, 224	4-stroke, >80 d	cc - <225 cc	Gasoline, LPG, and Gasoline-LPG Dual Fue			
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
250		EM			Pump, Pressure Washer, Generator Set, Other OEM Equipment				
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment							

EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	10.0	549	*	
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	8.5	312	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of December 2015.

Comern for 16H

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Model Year: Manufacturer:

Zhejiang Yaofeng Power Technology Co.,

Issued:

R/C 01 03-29-16

Engine Family: GZYPS.2241GA

Revised: E.O. Number: U-U-220-0053

3/17/2016

Small Off-Road Engine Model Summary Form

Units for Table: kW

Attachment page 1 of 1

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case?	Model	Sales	Displ	Bore/	Ignition	Max	Rated Speed	Rated	Torque Speed	
	Designation	Code	(cc)	Stroke	Timing	Power Gasolin	(RPM) e	Torque	(RPM)	Control Sys
	YF168FD-2-L_G	50-State	196	68/54	12BTDC	4.5	4000	. 11N.m	2800	EM
	_		224,192			LPG _{3.5}	3600	11.7N.m	2800	
	YF168FD-2-LPG	50-State	196	68/54	12BTDC	3.5	3600	11.7N.m	2800	EM
X	YF168F-2	50-State	196	68/54	12BTDC	4.5	4000	11N.m	2800	EM
	YF168FD-2	50-State	196	68/54	12BTDC	4.5	4000	11N.m	2800	EM
,	YF170FD	50-State	192	70/50	21BTDC	4.4	4000	12N.m	2500	EM
	YF170FD-L G	50-State	192	70/50	21BTDC	Gasoline 4.4	4000	12 N .m	2500	EM
	11 17 07 2 2_0					LPG _{3.95}	4000	10.5N.m	2500	
	YF172F	50-State	224	72/55	12BTDC	5.1	4000	12.6 N .m	2800	EM
	YF172FD	50-State	224	72/55	12BTDC	5.1	4000	12.6 N .m	2800	EM
	YF172FD-LPG	50-State	224	72/55	12BTDC	4	4000	12.6N.m	2800	EM
	YF172FD-L_G	50-State	224	72/55	12BTDC	Gasoline 5.1	4000	12.6N.m	2800	EM
	,, ,, <u>,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, </u>					LPG 4	4000	12.6 N .m	2800	
	YF172IV	50-State	224	72/55	12BTDC	5.1	4000	12.6N.m	2800	EM ;