

## **ECHO INCORPORATED**

EXECUTIVE ORDER U-U-010-1090
New Off-Road Small Spark-Ignition
Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGI	NE FAMILY	DISPLACEMENT ENGINE C		CLASS	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2019	KEHX	(S.0214KN	21	2-stroke, < 50 cc		Gasoline		
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
300			TWC		Hedge Trimmer			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						
EGR=exhaus	t gas recirc	ulation AIR=sec	ondary air injection PAIR=p	oulsed`AIR MFi≃mu	Iti port fuel injec	warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ction SFI=sequential MFI TBI=throttle body fuel injection fix)=in series ECM=engine control module		

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission

Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	50	536	2.0	
FAMILY EMISSION LEVEL	48	536	1.0	
CERTIFICATION LEVEL	32	280	0.6	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

**BE IT FURTHER RESOLVED:** That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

\_ day of December 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

RCI 7/12/19

ATTACUMENT PS/OFI

Page: 9

Model Year:

2019

Manufacturer: ECHO Incorporated

Engine Family: KEHXS.0214KN

Revised:

11/6/1998

5/23/2019

E.O. Number: U - U - 010 - 1070

## **Small Off-Road Engine Model Summary Form**

Units for Table: kw

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
Х	HT235	50-State	21.2	32.2/26	29.5±2@7500	0.57	7500	0.72 N-m	7500	EM/TWC
	HT232	50-State	21.2	32.2/26	29.5±2@7500	0.57	7500	0.72 N-m	7500	EM/TWC
	DH232	50-State	21.2	32.2/26	29.5±2@7500	0.57	7500	0.72 N-m	7500	EM/TWC
	DH235	50-State	21.2	32.2/26	29.5±2@7500	0.57	7500	0.72 N-m	7500	EM/TWC
	HC-2210	50-State	21.2	32.2/26	29.5±2@7500	0.57	7500	0.72 N-m	7500	EM/TWC
	HC-2810	50-State	21.2	32.2/26	29.5±2@7500	0.57	7500	0.72 N-m	7500	EM/TWC
	HCS-2810	50-State	21.2	32.2/26	29.5±2@7500	0.57	7500	0.72 N-m	7500	EM/TWC
	HCS-3810	50-State	21.2	32.2/26	29.5±2@7500	0.57	7500	0.72 N-m	7500	EM/TWC
	90 MA S									
						=				