

ECHO INCORPORATED

EXECUTIVE ORDER U-U-010-1106

New Off-Road Small Spark-Ignition
Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

| MODEL YEAR | ENGII | NE FAMILY | DISPLACEMENT (cc) | ENGINE CLASS | | FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas) | | | |
|--|--------------|---|-----------------------------|--------------|--|--|--|--|--|
| 2019 | KEHX | (S.0254KO | 25 | 2-9 | stroke, < 50 cc | Gasoline | | | |
| DURABILITY HOURS | | SPECIAL FEATURES & EMISSION CONTROL SYSTEMS | | | TYPICAL EQUIPMENT APPLICATION | | | | |
| 300 | | TWC | | | Line Trimmer, Hedge Trimmer, Edger, Brushcutter, Other OEM Product | | | | |
| ENGINE CODES/MODELS (rated power in kilowatt, kW) | | See Attachment | | | | | | | |
| EGR=exhaus | t gas recirc | ulation AIR=seco | ondary air injection PAIR=p | oulsed AIR | MFI=multi port fuel inject | warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ction SFI=sequential MFI TBI=throttle body fuel injection ix)=in series ECM=engine control module | | | |

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

| *=not applicable | HC+NOx (g/kW-hr) | CO (g/kW-hr) | PM (g/kW-hr) | |
|-----------------------|------------------|--------------|--------------|--|
| STANDARD | 50 | 536 | 2.0 | |
| FAMILY EMISSION LEVEL | 50 | 536 | 1.0 | |
| CERTIFICATION LEVEL | 42 | 254 | 0.8 | |

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

__day of October 2018.

Annette Hebert, Chief

missions Compliance, Automotive Regulations and Science Division

RC1 7/12/19

ATTACUMENT B (of 1

Model Year:

2019

Manufacturer: ECHO Incorporated

Engine Family: KEHXS.0254KO

Revised:

10/15/2004

5/23/2019

E.O. Number: u-u-010-1106

Small Off-Road Engine Model Summary Form

Units for Table: kw

| Worst Case? | 47. Model Designation | 48. Sales Code | 49. Displ (cc) | 50. Bore/ Stroke | 51. Ignition Timing | 52. Max Power | 53. Rated Speed (RPM) | 54. Rated Torque | 55. Torque Speed (RPM) | 56. Emiss Control Sys |
|----------------|-----------------------------|----------------------|----------------------|------------------------|---------------------------|---------------------|-----------------------------|------------------------|------------------------------|-----------------------------|
| Х | SRM-2620 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | SRM-2620S or 2620ST | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | SRM-2620T or 2620U | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | PE-2620 or 2620S | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | PPF-2620 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | PPT-2620 or 2620H | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | PAS-2620 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | HCA-2620 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | SHC-2620 or 2620S | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | BRD-2620 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | T262 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | T262X | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | AH or AHS262 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | BD262 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | C262 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | LE262 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | M262 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | PS262 | 50-State | 25.4 | 34/28 | 24.0±3@8500 | 0.99 | 8500 | 1.11 N-m | 8500 | EM/TWC |
| | | | | | | | | | | |
| | | | | | | | | | | |

Page: 9