

KOHLER COMPANY

EXECUTIVE ORDER U-U-005-0595 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)				
2019	ккнх	S.1731GC	149, 173	4-stroke, >80 cc - <225 cc		Gasoline				
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION					
250			EM			Walk-Behind Lawnmower, Pressure Washer and Generator				
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment								
EGR=exhaus	t gas recirc	ulation AIR=sec	ondary air injection PAIR=	pulsed AIR MFI=mu	Iti port fuel injec	rarm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S tion SFI=sequential MFI TBI=throttle body fuel injection x)=in series ECM=engine control module				

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	10.0	549	•	
FAMILY EMISSION LEVEL	13.2	549	*	
CERTIFICATION LEVEL	11.2	373	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _____ day of July 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Model Year:

Engine Family:

2019

Manufacturer:

Kohler Co.

KKHXS.1731GC

Issued:

Revised:

Carryover 6/11/2018

E.O. Number: u-u-005-0595

hler Co. HXS.1731GC By lof (E.O. Number: Small Off-Road Engine Model Summary Form

Units for Table: kW

47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque		56. Emiss Control Sys
HD775	50-State	173	70 x 45 mm	20° BTDC	3.50 kW	3600	10.8 N-m	2800	EM
HD675	50-State	149	65 x 45 mm	20° BTDC	2.80 kW	3600	9.0 N-m	2600	EM
HD650	50-State	149	65 x 45 mm	20° BTDC	2.69 kW	3600	8.8 N-m	2600	EM
			da a						
		The state of the s							
	• •				Au a 1 a 1 a 1 a 1 a 1 a 1 a 1 a 1 a 1 a				
			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1						
			-						
- 1 1			11 da 1						
p ma									
	The state of the s								
					***************************************	A 11 mm 11 mm 1111 mm 1			
	Model Designation HD775 HD675	Model Sales Designation Code HD775 50-State HD675 50-State	Model DesignationSales CodeDispl (cc)HD77550-State173HD67550-State149	Model Designation Sales Code Displemental (cc) Bore/ Stroke HD775 50-State 173 70 x 45 mm HD675 50-State 149 65 x 45 mm HD650 50-State 149 65 x 45 mm	Model Designation Code Code Code Code Code Code Code Code	Model Designation Sales Code Displ (cc) Bore/ Stroke Ignition Timing Max Power HD775 50-State 173 70 x 45 mm 20° BTDC 3.50 kW HD675 50-State 149 65 x 45 mm 20° BTDC 2.80 kW HD650 50-State 149 65 x 45 mm 20° BTDC 2.69 kW	Model Designation Sales Code Displ (cc) Bore/ Stroke Ignition Timing Max Power Rated Speed (RPM) HD775 50-State 173 70 x 45 mm 20° BTDC 3.50 kW 3600 HD675 50-State 149 65 x 45 mm 20° BTDC 2.80 kW 3600 HD650 50-State 149 65 x 45 mm 20° BTDC 2.69 kW 3600	Model Designation Sales Code Displ (cc) Bore/ Stroke Ignition Timing Max Power Rated Speed (RPM) Rated Torque HD775 50-State 173 70 x 45 mm 20° BTDC 3.50 kW 3600 10.8 N-m HD675 50-State 149 65 x 45 mm 20° BTDC 2.80 kW 3600 9.0 N-m HD650 50-State 149 65 x 45 mm 20° BTDC 2.69 kW 3600 8.8 N-m	Model Designation Sales Code Displ (cc) Bore/ Stroke Ignition Timing Max Power Rated Speed (RPM) Torque (RPM) HD775 50-State 173 70 x 45 mm 20° BTDC 3.50 kW 3600 10.8 N-m 2800 HD675 50-State 149 65 x 45 mm 20° BTDC 2.80 kW 3600 9.0 N-m 2600 HD650 50-State 149 65 x 45 mm 20° BTDC 2.69 kW 3600 8.8 N-m 2600