Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2019	ккнх	(S.7472PF	747	4-stroke, ≥	225 cc	Gasoline		
DURABILITY		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
1000		O2S, ECM, MPI			Riding Mower, Tractor, Compressor, Stump Beater, Commercial Turf and Generator			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						
ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module								

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549	*	
FAMILY EMISSION LEVEL	8.5	549	*	
CERTIFICATION LEVEL	7.2	222	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _____ day of September 2018.

M

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

Model Year: 2019 Manufacturer: Kohler Co. Engine Family: KKHXS.7472PF

ATTACIMENT BIOFI

Issued:

Revised: 7/25/2018

E.O. Number: U-U-005-0615

Small Off-Road Engine Model Summary Form

Units for Table: kW

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
	ECH749	50-State	747	83/69 mm	7-30°	18.6 kW	3600	47.6 N-m	2800	EM, O2S, ECM, MPI
and the second s	ECH740	50-State	747 -	83/69 mm	7-30°	18.5 kW	3600	51.6 N-m	2600	EM, O2S, ECM, MPI
	ECH730	50-State	747	83/69 mm	7-30°	16.9 kW	3600	49.1 N-m	2600	EM, O2S, ECM, MPI
4 din its research a di Ti	ECV730	50-State	747	83/69 mm	7-30°	17.5 kW	3600	51.6 N-m	2200	EM, O2S, ECM, MPI
	ECV740	50-State	747	83/69 mm	7-30°	18.4 kW	3600	51.5 N-m	2400	EM, O2S, ECM, MPI
x	ECV749	50-State	747	83/69 mm	7-30°	19.0 kW	3600	50.7 N-m	2800	EM, O2S, ECM, MPI
and another states and				and encounter.		10 mm	And	ang Longa N	a man managa ang ang ang ang ang ang ang ang an	
wordd drau'r "wrae y aned drawyd """"""""""""""""""""""""""""""""""""			4 THE STREAM		1	•	*		and and a	
		· · · ·	avera de la construcción de la const							1
		,	a politica de la construcción de la constru	· · · · · · · · · · · · · · · · · · ·					And the second se	
			Second in						4	
		2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	and the second se							
							A construction of the second s			
							e			
						аналанан аналан анал 2				
			water and waters						a na	
					The second s	a de la constante de la consta			and the second s	
	•					A constant of the second	The second			
	9 9 9					1			A Martin Martin Contractor	a na ang a la contra ang
- 99	4									
. 19				and an advertise of			A sector of 1 and		Manual	444 444 444 444 444 444 444 444 444 44