Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)			
2019	KEHX	(S.0364KC	36	2-stroke, < 50 cc		Gasoline			
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
300			TWC			Chainsaw			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment							
ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module									

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	50	536	2.0	
FAMILY EMISSION LEVEL	50	536	1.0	
CERTIFICATION LEVEL	38	280	0.7	

**BE IT FURTHER RESOLVED:** That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

**BE IT FURTHER RESOLVED:** That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_day of December 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

AMACHMERT 13 1-11

Model Year:2019Manufacturer:ECHO IncorporatedEngine Family:KEHXS.0364KC

 Issued:
 10/15/2004

 Revised:
 11/20/2018

 E.O. Number:
 LL-LL-C (C - 1134)

## Small Off-Road Engine Model Summary Form

Units for Table: kw

47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque		56. Emiss Control Sys
CS-361P	50-State	35.8	39/30	34±3@10000	1.47	10000	1.40	10000	EM/TWC
						++			
					· · · · ·				
				·					
				┠────┤					
						++			
					·	+			
	Model Designation CS-361P	Model Sales Designation Code CS-361P 50-State	Model DesignationSales CodeDispl (cc)CS-361P50-State35.8Image: State35.8Image: StateImage: Stat	Model DesignationSales CodeDispl (cc)Bore/ StrokeCS-361P50-State35.839/30Image: Sole of the sector of th	Model DesignationSales CodeDispl (cc)Bore/ StrokeIgnition TimingCS-361P50-State35.839/3034±3@10000Image: Sole of the second	Model DesignationSales CodeDispl (cc)Bore/ StrokeIgnition TimingMax PowerCS-361P50-State35.839/3034±3@100001.47Image: Sole of the strong	Model DesignationSales CodeDispl (cc)Bore/ StrokeIgnition TimingMax PowerRated Speed (RPM)CS-361P50-State35.839/3034±3@100001.4710000Image: CodeImage: C	Model DesignationSales CodeDispl (cc)Bore/ StrokeIgnition TimingMax PowerRated Speed (RPM)Rated TorqueCS-361P50-State35.839/3034±3@100001.47100001.40Image: CS-361P50-State35.839/3034±3@100001.47100001.40Image: CS-361P50-State35.839/3034±3@100001.47100001.40Image: CS-361P50-State35.839/3034±3@100001.47100001.40Image: CS-361P50-State35.839/3034±3@100001.47100001.40Image: CS-361P50-State35.839/3034±3@100001.47100001.40Image: CS-361P50-State35.839/3034±3@100001.47100001.40Image: CS-361PImage: CS-361P <tr< td=""><td>Model DesignationSales CodeDispl (cc)Bore/ StrokeIgnition TimingMax PowerRated Speed (RPM)Rated Torque Speed (RPM)CS-361P50-State35.839/3034±3@100001.47100001.4010000Image: CodeImage: Code</td></tr<>	Model DesignationSales CodeDispl (cc)Bore/ StrokeIgnition TimingMax PowerRated Speed (RPM)Rated Torque Speed (RPM)CS-361P50-State35.839/3034±3@100001.47100001.4010000Image: CodeImage: Code

Page: 9