

## CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD.

EXECUTIVE ORDER U-U-082-0335 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGII	NE FAMILY	DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)			
2019	KCZH	IS.5472V1	547	4-stroke, ≥	225 cc	Gasoline			
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
250			EM			Riding Mower, Tractor, Compressor, Pump, Pressure Washer, Stump Beater, Non-Backpack Blower, Tiller, Commercial Turf			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment							
EGR=exhaus	t gas recirc	ulation AIR=seco	ondary air injection PAIR=p	ulsed AIR MFI=mu	Iti port fuel injec	warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S tion SFI=sequential MFI TBI=throttle body fuel injection x)=in series ECM=engine control module			

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549		
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	6.2	442	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

**BE IT FURTHER RESOLVED:** That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Model Year:

Manufacturer:

2019

Chongqing Zongshen General Power

Issued:

Revised:

Engine Family: KCZHS.5472V1

E.O. Number: u-u-082-0335

3/11/2019

**Small Off-Road Engine Model Summary Form** 

PC1:5-9-2019

Units for Table: kw

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case?	Model Designation	Sales Code	Displ (cc)	Bore/ Stroke	Ignition Timing	Max Power	Rated Speed (RPM)	Rated Torque	Torque Speed (RPM)	Emiss Control Sys
X	4X90HU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	8X90KU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	8X90ZU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	8X90YU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	AX90HU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	4X90XU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	4X90KU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	4X90ZU_	50-State	547	90/86	26	11.5	3600	34	2750	ЕМ
	4X90MU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	8X90HU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	8X90XU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	8X90MU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	AX90XU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	AX90KU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	AX90ZU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	AX90MU_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	4X90HW_	50-State	547	90/86	26	11.5	3600	34	2750	EM
	8X90KW_	50-State	547	90/86	26	11.5	3600	34	2750	EM
:	8X90ZW_	50-State	547	90/86	26	11.5	3600	34	2750	EM
				É						