

SUZHOU HONBASE MACHINERY MANUFACTURE CO., LTD.

EXECUTIVE ORDER U-U-156-0069

New Off-Road Small Spark-Ignition
Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGI	NE FAMILY	DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)			
2019	KSHE	3S.0294HB	25, 29	2-stroke,	< 50 cc	Gasoline			
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
50		TWC			Snowblower, Line Trimmer, Hedge Trimmer, Leaf Blower/Vacuum, Brushcutter				
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment							
EGR=exhaus	gas recirc	ulation AIR=seco	ondary air injection PAIR=p	oulsed AIR MFI=mu	ti port fuel inject	varm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S tion SFI=sequential MFI TBI=throttle body fuel injection x)=in series ECM=engine control module			

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	50	536	2.0	
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	31	208	0.6	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _____ day of December 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT PAGE

1 OF I

EO # U-U- 156-CD69 Page: 9

Model Year:

2019

Suzhou Honbase Machinery Manufacture

Issued: Revised:

11/1/2018

Manufacturer: Engine Family: KSHBS.0294HB

E.O. Number:

Small Off-Road Engine Model Summary Form

Units for Table: kW

	47 .	48.	49.	50.	51.	52.	53 .	54.	55.	56.
Worst Case?	Model Designation	Sales Code	Displ (cc)	Bore/ Stroke	Ignition Timing	Max Power	Rated Speed (RPM)	Rated Torque	Torque Speed (RPM)	Emiss Control Sys
X	HY33	50-State	25	33.3/28.4mm	BTDC26	0.72kW	7500	1.0N.m	5500	TWC
	HY36	50-State	29	36.4/28.0mm	BTDC26	0.85kW	7500	1.2N.m	5500	TWC
	HY33	50-State	25	33.3/28.4mm	BTDC26	0.72kW	7500	1.0N.m	5500	TWC
	HY36	50-State	29	36.4/28.0mm	BTDC26	0.85kW	7500	1.2 N .m	5500	TWC