Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGIN	INE FAMILY DISPLACEMENT (CC) ENGINE CLASS (CNG/LNG=com petroleum gas)		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)					
2019	KSUM	S.2081GA	196, 208	4-stroke, > 80cc - < 225cc		Gasoline, LPG, Gasoline-LPG dual-fuel			
DURABILITY		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
500			EM		Generator Set				
ENGIN CODES/MC (rated pow kilowatt,	DDELS wer in			S	See Attachm	ent			

EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel in DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)
STANDARD	10.0	549	
FAMILY EMISSION LEVEL	*	*	۰.
CERTIFICATION LEVEL	7.2	357	*

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-U-252-0025 dated December 18, 2018.

Executed at El Monte, California on this ______ day of September 2019.

Allen Lyons, Chief Emissions Certification and Compliance Division

Page: 9

Model Year: Manufacturer:

2019 Attachment, 1 of 1 SUMEC MACHINERY & ELECTRIC CO., Engine Family: KSUMS.2081GA

Issued: Revised:

E.O. Number: 11- 11- 252-0025-1

Small Off-Road Engine Model Summary Form

Units for Table: kW

6/21/2019

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
	SFE210	50-State	208	70/54	20 BTDC	4.6	4000	11.6	2800	EM
	SFE210E	50-State	208	70/54	20 BTDC	4.6	4000	11.6	2800	EM
	SPE200	50-State	196	68/54	20 BTDC	4.5	4000	11.3	2800	EM
	SPE200E	50-State	196	68/54	20 BTDC	4.5	4000	11.3	2800	EM
	SFE210ER	50-State	208	70/54	20 BTDC	4.6	4000	11.6	2800	EM
	SFE210DF	50-State	208	70/54	20 BTDC	4.6	4000	11.6	2800	EM
X	SFE210DFE	50-State	208	70/54	20 BTDC	4.6	4000	11.6	2800	EM
	SFE210L	50-State	208	70/54	20 BTDC	4.6	4000	. 11.6	2800	EM
									1	