

Subpart I - Standards of performance for Hot Mix Asphalt Facilities

Applicability - §60.90

General	<ol style="list-style-type: none">1.) Facilities affected are each hot mix asphalt facility. For the purpose of this subpart, a hot mix asphalt facility is comprised only of any combination of the following: dryers; systems for screening, handling, storing, and weighing hot aggregate; systems for loading, transferring, and storing mineral filler, systems for mixing hot mix asphalt; and the loading, transfer, and storage systems associated with emission control systems.2.) Any facility that commences construction or modification after June 11, 1973, is subject to the requirements of this subpart.
---------	---

Emission Standards - §60.92

Source	All Emissions
General	<ol style="list-style-type: none">1.) Facility shall not emit gases which contain particulate matter in excess of 90 mg/dscm (0.04 gr/dscf).2.) Facility shall not emit gases which exhibit 20 percent opacity, or greater.

Test Methods and Procedures - §60.93

Source	All Emissions
General	<ol style="list-style-type: none">1.) Facility shall use as reference methods and procedures the test methods in Appendix A of this part or other methods and procedures as specified in this section, except as provided in §60.8(b).2.) Facility shall determine compliance with the particulate matter standards in §60.92 using Method 5 to determine the particulate matter concentration. The sampling time and sample volume for each run shall be at least 60 minutes and 0.90 dscm (31.8 dscf).3.) Method 9 and the procedures in §60.11 shall be used to determine opacity.