

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER N-21-141

Relating to CARB Approval to conduct Primary or Secondary Method and Routine Quality Control Testing at a Less Frequent Rate by Composite Wood Product Manufacturers that use Ultra-low-emitting Formaldehyde Resins under section 93120.3, title 17, California Code of Regulations

**Arauco North America – Duraflake Particleboard**

WHEREAS, the California Air Resources Board (CARB) has adopted the “Airborne Toxic Control Measure to Reduce Formaldehyde Emissions from Composite Wood Products” (ATCM; title 17, California Code of Regulations, sections 93120-93120.12), which establishes formaldehyde emission standards for composite wood products;

WHEREAS, section 93120.1(a)(42) of the ATCM defines “ultra-low-emitting formaldehyde” (ULEF) based resins to mean resins formulated such that average formaldehyde emissions are consistently below the Phase 2 emission standards in section 93120.2, for making hardwood plywood (HWPW), particleboard (PB), medium density fiberboard (MDF), or thin medium density fiberboard (tMDF);

WHEREAS, section 93120.3(d) of the ATCM allows manufacturers of HWPW, PB, MDF, and tMDF who use ULEF-based resins to apply for written approval from the Executive Officer for an exemption from the requirements of section 93120.3(b) of the ATCM;

WHEREAS, section 93120.3(d) of the ATCM allows manufacturers of HWPW, PB, MDF, and tMDF who use ULEF-based resins to submit an application for approval to test their products at a less frequent rate than specified in sections 93120.3(b) and 93120.12, Appendix 2 of the ATCM to the Executive Officer, which includes: (A) a statement indicating which product types will be manufactured using ULEF-based resins for sale in California; (B) the chemical formulation of the candidate ULEF-based resin(s), including base resins, scavenger resins, scavenger additives, catalysts, and other additives as used in manufacturing; (C) the name of their CARB-approved third-party certifier (TPC); and (D) data on the emissions performance of the candidate ULEF-based resin(s);

WHEREAS, the data on emissions performance of the candidate ULEF-based resin required in section 93120.3(d) of the ATCM must be obtained by working with a CARB-approved TPC, and must include six months of routine quality control testing data, the correlation of the routine quality control testing data to primary or secondary testing data, and the results of two primary or secondary method tests, as required in Appendix 2 of section 93120.12 of the ATCM;

WHEREAS, section 93120.3(d)(1) of the ATCM requires that 90 percent of the six months of routine quality control testing data and the results of two primary or secondary method tests must be no higher than 0.05 parts per million (ppm), and all routine quality data must be no higher than 0.08 ppm for ULEF manufacturers of PB to gain approval to conduct their emission testing at a less frequent rate than specified in sections 93120.3(b) and 93120.12, Appendix 2;

WHEREAS, section 93120.3(d)(5) of the ATCM provides that the Executive Officer shall approve the application and issue an Executive Order if the evidence submitted by the applicant is sufficient to demonstrate that the applicant has met the requirements specified in sections 93120.3(d)(1) and 93120.3(d)(2) of the ATCM;

WHEREAS, Arauco Flakeboard America Ltd. (Arauco Flakeboard America or the applicant) submitted an application that we received on January 10, 2013;

WHEREAS, the original application from Arauco Flakeboard America specified the range in product manufacturing parameters, applicable post-press product treatments, base resin trade name(s) and base resin manufacturer(s)/supplier(s), and other ingredients added to the base resin by the applicant to manufacture ULEF PB products;

WHEREAS, CARB was provided base resin/adhesive information specifying the base resin polymer type and minimum and maximum values of all major and any minor ingredients in the base resin on a percent weight of solids basis;

WHEREAS, the base resins/adhesive supplier, commercial name, and resin type are set forth in Confidential Attachment A;

WHEREAS, section 93120.3(d) of the ATCM allows ULEF product manufacturers to apply for re-approval by CARB by submitting an updated application;

WHEREAS, Arauco Flakeboard America submitted the original and the updated applications for approval to CARB as follows:

<b>Executive Order #</b>	<b>Received Date</b>	<b>Signed Date</b>	<b>Actions</b>
N-13-141	01/10/2013	01/23/2013	Original
N-15-141	12/25/2014	01/12/2015	Renewal and amendment to change the company name to "Arauco North America, Inc." (Arauco Duraf Flake Particleboard or the applicant)
N-17-141	01/04/2017	05/12/2017	Renewal
N-19-141	03/29/2019	05/20/2019	Renewal

WHEREAS, Arauco Duraf Flake Particleboard submitted an updated application for re-approval to CARB on April 14, 2021;

WHEREAS, the updated application for renewal from Arauco Duraflake Particleboard was deemed complete on April 26, 2021;

WHEREAS, the Executive Officer finds that the completed, updated application demonstrated the ULEF manufacturer's ability to continue to comply with section 93120.3(d); and

WHEREAS, the Executive Officer approved Arauco Duraflake Particleboard's request for re-approval, and it is appropriate that Executive Order N-19-141 be superseded by this Executive Order N-21-141.

NOW, THEREFORE, IT IS ORDERED that Arauco Duraflake Particleboard is hereby approved as a ULEF manufacturer of PB qualified to test their PB less frequently, as specified by the requirements of section 93120.12, Appendix 2, subsections (f) and (g) of the ATCM, provided that the following terms and conditions are met for products sold, supplied, offered for sale, or manufactured for sale in California:

1. Arauco Duraflake Particleboard must use the commercial resins listed and suppliers listed in Section A of Confidential Attachment A of this Executive Order for the manufacture of ULEF PB products.
2. As specified in Section B of Confidential Attachment A, Arauco Duraflake Particleboard is legally responsible for ensuring that the base resin specifications are within the ranges specified in the original application and any subsequent amendments of this Executive Order.
3. The application rate of the base resins used for the manufacture of ULEF composite wood products by Arauco Duraflake Particleboard must be within the ranges specified in Section C of Confidential Attachment A of this Executive Order.
4. Other chemical components of the base resins (such as sizing wax and release wax) used for the manufacture of ULEF PB products by Arauco Duraflake Particleboard must be within the ranges specified in Section D of Confidential Attachment A of this Executive Order.
5. The allowable operating parameters for press temperature and press time for the base resins used to manufacture the ULEF PB products by Arauco Duraflake Particleboard must be within the ranges specified in Section E of Confidential Attachment A of this Executive Order.
6. Only the composite wood products with the product names listed in Section F of Confidential Attachment A of this Executive Order are authorized under this Executive Order.

BE IT FURTHER ORDERED that this Executive Order N-21-141 supersedes Executive Order N-19-141, which was signed on May 20, 2019.

BE IT FURTHER ORDERED that Arauco Duraflake Particleboard may change the resin system supplier listed in Section A of Confidential Attachment A of this Executive Order if the new resin supplier supplies the same resin type listed in Confidential Attachment A of this Executive Order, at least two primary or secondary method tests are performed on random samples selected by their CARB-approved TPC, and the Chief of the Risk Reduction Branch within the Transportation and Toxics Division is notified before Arauco Duraflake Particleboard uses the resin for production.

BE IT FURTHER ORDERED that Arauco Duraflake Particleboard must conduct confirmatory testing for a new resin supplier by demonstrating that the results of two primary or secondary method tests for the new resin system supplier are no higher than 0.05 ppm for the ULEF PB products authorized under this Executive Order.

BE IT FURTHER ORDERED that the Executive Officer may review and, for good cause, modify or revoke this Executive Order as provided in section 93120.3(d)(5) of the ATCM. The Executive Officer shall not modify or revoke this Executive Order without affording the applicant the opportunity for a hearing in accordance with the procedures specified in title 17, California Code of Regulations, section 60055.1 et seq.

BE IT FURTHER ORDERED that this Executive Order shall have a duration of two years from the date this Executive Order is signed; the applicant may apply for re-approval as provided in section 93120.3(d)(5) of the ATCM.

BE IT FURTHER ORDERED that the applicant must maintain records in electronic or hard copy form for two years, for review by CARB upon request, as specified in section 93120.3(g) of the ATCM.

BE IT FURTHER ORDERED that the applicant must notify the Executive Officer in writing within 30 days if there is any change in their product manufacturing parameters or base resin manufacturer(s) or supplier(s) that does not comply with any of the requirements, terms or conditions specified in the ATCM or this Executive Order.

Executed at Sacramento, California on this 27th day of May 2021.



---

Robert Krieger, Chief  
Risk Reduction Branch  
Transportation and Toxics Division