## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER N-21-134A

Relating to CARB Approval to use No-added Formaldehyde Resins by Composite Wood Product Manufacturers under section 93120.3, title 17, California Code of Regulations

## Timber Products Company

Whereas, the California Air Resources Board (CARB) has adopted the "Airborne Toxic Control Measure to Reduce Formaldehyde Emissions from Composite Wood Products" (ATCM; title 17, California Code of Regulations, sections 93120-93120.12), which establishes formaldehyde emission standards for composite wood products;

Whereas, section 93120.1(a)(29) of the ATCM defines "no-added formaldehyde" (NAF) based resins to mean resins formulated with NAF as part of the resin cross-linking structure for making hardwood plywood (HWPW), particleboard (PB), medium density fiberboard (MDF), or thin medium density fiberboard (tMDF) including, but not limited to resins made from soy, polyvinyl acetate, or methylene diisocyanate;

Whereas, section 93120.3(c) of the ATCM allows manufacturers of HWPW, PB, MDF, and tMDF who use NAF-based resins to apply for written approval from the Executive Officer for an exemption from the requirements of section 93120.3(b) of the ATCM;

Whereas, section 93120.3(c) of the ATCM allows manufacturers of HWPW, PB, MDF, and tMDF who use NAF-based resins to submit an application for an exemption from the requirements of section 93120.3(b) of the ATCM to the Executive Officer, which includes: (A) a statement indicating which product types will be manufactured using NAF-based resins for sale in California; (B) the chemical formulation of the candidate NAF-based resins, including base resins, catalysts, and other additives used in manufacturing; (C) the name of their CARB-approved third-party certifier (TPC); and (D) data on emissions performance of the candidate NAF-based resins;

Whereas, the data on emissions performance of the candidate NAF-based resin required in section 93120.3(c) of the ATCM must be obtained by working with a CARB-approved TPC, and must include three months of routine quality control testing data, the correlation of the routine quality control testing data to primary or secondary testing data, and the results of one primary or secondary method test, as required in Appendix 2 of section 93120.12 of the ATCM;

Whereas, section 93120.3(c)(1) of the ATCM requires that 90 percent of the three months of routine quality control testing data and the results of one primary or secondary method test must be shown to be no higher than 0.04 parts per million (ppm), and that all data must be shown to be no higher than 0.05 ppm for HWPW and 0.06 ppm for PB, MDF, and tMDF;

Whereas, section 93120.3(c)(4) of the ATCM provides that the Executive Officer shall approve the application and issue an Executive Order if the evidence submitted by the applicant is sufficient to demonstrate that the applicant has met the requirements specified in section 93120.3(c)(1) of the ATCM;

Whereas, Timber Products Company (Timber Products or the applicant) submitted an original application that we received on October 19, 2012;

Whereas, the original application from Timber Products specified the range in product manufacturing parameters, applicable post-press product treatments, base resin trade name(s) and base resin manufacturer(s)/supplier(s), and other ingredients added to the base resin by the applicant to manufacture NAF PB Industrial Commercial products;

Whereas, CARB was provided base resin/adhesive information specifying the base resin polymer type and minimum and maximum values of all major and any minor ingredients in the base resin on a percent weight of solids basis;

Whereas, the base resins/adhesive supplier, commercial name, and resin type are set forth in Confidential Attachment A;

Whereas, section 93120.3(c) of the ATCM allows NAF product manufacturers to apply for re-approval to CARB by submitting an updated application;

Whereas, Timber Products submitted the original and the updated applications for approval to CARB as follows:

Executive Order #	Received Date	Signed Date	Action
N-12-134	10/19/2012	11/29/2012	Original
N-15-134	11/19/2014	03/13/2015	Renewal
N-17-134	03/07/2017	05/24/2017	Renewal
N-17-134A	08/09/2018	08/20/2018	Amendment: to add an additional resin system
N-19-134	04/17/2019	05/31/2019	Renewal
N-21-134	05/07/2021	06/04/2021	Renewal

Whereas, Timber Products a request for approval to add a new resin system to the current Executive Order N-21-134 on August 17, 2021;

Whereas, the request for approval to add a new resin system from Timber Products was deemed complete on August 24, 2021;

Whereas, the Executive Officer finds that the completed, updated application demonstrated the NAF manufacturer's ability to continue to comply with section 93120.3(c) of the ATCM; and

Whereas, the Executive Officer approved Timber Products' request for adding a new resin system and it is appropriate that Executive Order N-21-134 be superseded by Executive Order N-21-134A.

Now, therefore, it is ordered that Timber Products is hereby approved as a NAF manufacturer of PB exempt from the requirements of section 93120.3(b) and Appendix 2 of section 93120.12 of the ATCM, provided that the following terms and conditions are met for products sold, supplied, offered for sale, or manufactured for sale in California:

- 1. Timber Products must use the commercial resin listed and supplier listed in Section A of Confidential Attachment A of this Executive Order for the manufacture of NAF PB products.
- 2. As specified in Section B of Confidential Attachment A, Timber Products is legally responsible for ensuring that the base resin specifications are within the ranges specified in the original application and any subsequent amendments of this Executive Order.
- 3. The application rate of the base resins used for the manufacture of NAF PB composite wood products by Timber Products must be within the ranges specified in Section C of Confidential Attachment A of this Executive Order.
- 4. Other chemical components of the base resins (such as sizing wax and release wax) used for the manufacture of NAF PB composite wood products by Timber Products must be within the ranges specified in Section D of Confidential Attachment A of this Executive Order.
- 5. The allowable operating parameters for press temperature and press time for the base resins used to manufacture the NAF composite wood products by Timber Products must be within the ranges specified in Section E of Confidential Attachment A of this Executive Order.
- 6. Only the composite wood products with the product names listed in Section F of Confidential Attachment A of this Executive Order are authorized under this Executive Order.

Be it further ordered that Executive Order N-21-134A supersedes Executive Order N-21-134, which was issued on June 4, 2021.

Be it further ordered that Timber Products may change the resin system supplier listed in Section A of Confidential Attachment A if the new resin supplier supplies the same resin constituent listed in Confidential Attachment A, confirmatory emission tests are conducted, and the Chief of the Risk Reduction Branch within the Transportation and Toxics Division is notified in advance of using the new system for production.

Be it further ordered that Timber Products must conduct confirmatory testing for any new resin system by demonstrating that the results of one primary or secondary method test for the new resin system are no higher than 0.04 ppm for the NAF products authorized under this Executive Order.

Be it further ordered that the application for re-approval specified in section 93120.3(c)(4) of the ATCM, as applicable, requires the applicant to submit the results of at least one primary or secondary method tests for the NAF products listed in Confidential Attachment A based on panels or a set of panels randomly selected and tested by a CARB-approved TPC, and the chemical formulation of the NAF-based resins. In addition, at least one primary or secondary method test must be provided for each facility, which operates in accordance with this Executive Order, and the applicant must also include a current list of their resin suppliers.

Be it further ordered that the Executive Officer may review and, for good cause, modify or revoke this Executive Order as provided in section 93120.3(c)(4) of the ATCM. The Executive Officer shall not modify or revoke this Executive Order without affording the applicant the opportunity for a hearing in accordance with the procedures specified in title 17, California Code of Regulations, section 60055.1 et seq.

Be it further ordered that this Executive Order shall have a duration of two years from the date of issuance of Executive Order N-21-134 (i.e., June 4, 2021); the applicant may apply for re-approval as provided in section 93120.3(c)(4) of the ATCM.

Be it further ordered that the applicant must maintain records in electronic or hard copy form for two years, for review by CARB upon request, as specified in section 93120.3(g) of the ATCM.

Be it further ordered that the applicant must notify the Executive Officer in writing within 30 days of any change in their product manufacturing parameters or base resin manufacturer(s) or supplier(s) that constitute a modification outside the scope of their application for reduced testing under or an exemption from the requirements in section 93120.3(b) of the ATCM.

Executed at Sacramento, California on this <u>8th</u> day of <u>October</u> 2021.

Robert Krieger, Chief Risk Reduction Branch Transportation and Toxics Division