

California Environmental Protection Agency
AIR RESOURCES BOARD

**CALIFORNIA EXHAUST EMISSION STANDARDS AND TEST PROCEDURES FOR
~~2003~~ 2005 AND SUBSEQUENT MODEL ZERO-EMISSION VEHICLES, AND 2001 AND
SUBSEQUENT MODEL HYBRID ELECTRIC VEHICLES, IN THE PASSENGER CAR,
LIGHT-DUTY TRUCK AND MEDIUM-DUTY VEHICLE CLASSES**

Adopted: August 5, 1999
Amended: April 12, 2002
Amended: July 30, 2002
Amended: [Insert Date]

Note: The text of the originally proposed amendments is shown in underline to indicate additions and ~~strikeout~~ to indicate deletions, compared to the test procedures as amended July 30, 2002. The proposed modifications to the original proposal are shown in double underline to indicate additions and ~~double strike-out~~ to indicate deletions.

TABLE OF CONTENTS

Section	Page No.
A. Applicability.....	A-1
B. Definitions.....	B-1
C. Zero-Emission Vehicle Standards.....	C-1
1. ZEV Emission Standard.....	C-1
2. Percentage ZEV Requirements.....	C-1
3. Partial ZEV Allowance Vehicles (PZEVs).....	C-7
4. Qualification for ZEV Multipliers and Credits.....	C-14
5. ZEV and Advanced Technology PZEV High Efficiency Multipliers <u>[Reserved]</u>	C-18
6. In-Extended Service Warranty Multiplier for 2002-2004 Model Year ZEVs and PZEVs With ≥ 10 Mile Zero Emission Range.....	C-22
7. Generation and Use of ZEV Credits; Calculation of Penalties.....	C-22
8. <u>Severability</u>	C-26
D. Certification Requirements.....	D-1
1. Durability and Emission Testing Requirements.....	D-1
2. Information Requirements: Application for Certification.....	D-1
<u>3. ZEV Reporting Requirements</u>	D-3
E. Test Procedures.....	E-1
1. Electric Dynamometer.....	E-1
2. Vehicle and Battery Break-In Period.....	E-1
3. All-Electric Range Test.....	E-1
4. Determination of Battery Specific Energy for ZEVs.....	E-3
5. Determination of the Emissions of the Fuel-fired Heater.....	E-3
6. Hybrid Electric Vehicle FTP Emission Test Provisions.....	E-3
7. Hybrid Electric Vehicle Highway Emission Test Provisions.....	E-8
8. Hybrid Electric Vehicle SFTP Emission Test Provisions.....	E-10
9. State-of-Charge Net Change Tolerances.....	E-14

**CALIFORNIA EXHAUST EMISSION STANDARDS AND TEST PROCEDURES FOR
2003 2005 AND SUBSEQUENT MODEL ZERO-EMISSION VEHICLES, AND 2001 AND
SUBSEQUENT MODEL HYBRID ELECTRIC VEHICLES, IN THE PASSENGER CAR,
LIGHT-DUTY TRUCK AND MEDIUM-DUTY VEHICLE CLASSES**

A. Applicability

The emission standards and test procedures in this document are applicable to ~~2003~~ 2005 and subsequent model-year zero-emission passenger cars, light-duty trucks and medium-duty vehicles, and 2001 and subsequent model-year hybrid electric passenger cars, light-duty trucks and medium-duty vehicles. The general procedures and requirements necessary to certify a vehicle for sale in California are contained in the “California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles” (hereinafter “LDV/MDV TPs”), and apply except as amended herein. A manufacturer may elect to certify a 2000 model-year hybrid electric vehicle under these standards and test procedures and the LDV/MDV TPs.

B. Definitions

In addition to the following, these test procedures incorporate by reference the definitions and abbreviations set forth in the Title 40 Code of Federal Regulations § 86.1803-01, the definitions and abbreviations set forth in the LDV/MDV TPs, and the definitions set forth in section 1900, title 13, CCR.

“Advanced technology PZEV” or “AT PZEV” means any PZEV with an allowance greater than 0.2 before application of the PZEV early introduction phase-in multiplier ~~or the high-efficiency multiplier.~~

“All-Electric Range Test” means a test sequence used to determine the range of an electric vehicle or of a hybrid electric vehicle without the use of its auxiliary power unit. The All-Electric Range Test cycle consists of the Highway Fuel Economy Schedule and the Urban Dynamometer Driving Schedule (see section E of these test procedures).

“Auxiliary power unit” means a device that converts consumable fuel energy into mechanical or electrical energy. Some examples of auxiliary power units are internal combustion engines, gas turbines, or fuel cells.

“Battery electric vehicle” or “BEV” means any vehicle that operates solely by use of a battery or battery pack, or that is powered primarily through the use of an electric battery or battery pack but uses a flywheel or capacitor that stores energy produced by the electric motor or through regenerative braking to assist in vehicle operation.

“Battery or Battery pack” means any electrical energy storage device consisting of any number of individual battery modules or cells that is used to propel a battery electric or hybrid electric vehicle. These terms may also generically refer to capacitor and flywheel energy storage devices in the context of hybrid electric vehicles.

“Battery state-of-charge” means the quantity of electrical energy remaining in the battery relative to the maximum rated capacity of the battery expressed in percent.

“Charge-depleting” means that the battery of a hybrid electric vehicle ultimately fully discharges and impairs vehicle operation as the vehicle continuously operates over a given driving cycle when no off-vehicle charging is performed and the consumable fuel is regularly replenished. Hybrid electric vehicles are required to be classified as either charge-sustaining or charge-depleting over each driving cycle (i.e. UDDS, HFEDS, US06, or SC03).

“Charge-sustaining” means that the battery of a hybrid electric vehicle ultimately does not fully discharge and impair vehicle operation as the vehicle continuously operates over a given driving cycle when no off-vehicle charging is performed and the consumable fuel is regularly replenished. Hybrid electric vehicles are required to be classified as either charge-sustaining or charge-depleting over each driving cycle (i.e. UDDS, HFEDS, US06, or SC03).

“Consumable fuel” means any solid, liquid, or gaseous matter that releases energy when consumed by an auxiliary power unit.

“Fuel-fired heater” means a fuel burning device that creates heat for the purpose of warming the passenger compartment of a vehicle but does not contribute to the propulsion of the vehicle.

“Hybrid electric vehicle” or “HEV” means any vehicle that can draw propulsion energy from both of the following on-vehicle sources of stored energy: 1) a consumable fuel and 2) an energy storage device such as a battery, capacitor, or flywheel.

“Neighborhood Electric Vehicle” or “NEV” means a motor vehicle that meets the definition of “low-speed vehicle” either in section 385.5 of the Vehicle Code or in 49 CFR 571.500 (as it existed on July 1, 2000), and is certified to zero-emission vehicle standards.

“HFEDS” means highway fuel economy driving schedule. See 40 CFR §00.109(b).

“Off-vehicle charge capable” means having the capability to charge a battery from an off-vehicle electric energy source that cannot be connected or coupled to the vehicle in any manner while the vehicle is being driven.

“Placed in service” means having been sold or leased to an end-user and not just to a dealer or other distribution chain entity, and having been individually registered for on-road use by the California Department of Motor Vehicles.

“PZEV” means any vehicle that is delivered for sale in California and that qualifies for a partial ZEV allowance of at least 0.2.

“Regenerative braking” means the partial recovery of the energy normally dissipated into friction braking that is returned as electrical current to an energy storage device.

“SC03” means the U.S. EPA SC03 driving schedule representing vehicle operation with air conditioning, as set forth in Appendix I of 40 CFR Part 86.

“SOC Net Change Tolerance” means the state-of-charge net change tolerance that is applied to the SOC Criterion for charge-sustaining hybrid electric vehicles when validating an emission test. See section D.8 of these procedures for tolerance specifications.

“SOC Criterion” means the state-of-charge criterion that is applied to charge-sustaining hybrid electric vehicle to validate an emission test. The SOC Criterion requires that no net change in battery energy occurs over a given test cycle, i.e. the final battery state-of-charge that is recorded at the end of the emission test must be equivalent to the initial battery state-of-charge that is set at the beginning of the emission test. The SOC Net Change Tolerance shall be applied to the SOC Criterion.

“Specialty electric vehicle ZEV” means a ~~version of an existing electric vehicle ZEV~~ that is designed for a commercial or governmental fleet application, and either [i] has the same battery pack zero emissions energy storage device and chassis as the an existing electric vehicle ZEV from which it is modified, or [ii] in the case of a vehicle that is not based on an existing ZEV platform, is optimized for a particular duty cycle, such as urban delivery service, that conflicts with optimization for maximum vehicle range.

“Type 0, I, II, and III ZEV” all have the meanings set forth in section C.4.4(a).

“US06” means the US06 driving schedule for aggressive driving as set forth in Appendix I of 40 CFR Part 86.

“UDDS” means urban dynamometer driving schedule as set forth Appendix I of 40 CFR Part 86.

“Zero-emission vehicle” or **“ZEV”** means any vehicle certified to zero-emission standards.

“Zero-emission VMT” means the vehicle miles traveled with zero exhaust emissions of any criteria pollutant (or precursor pollutant).

C. Zero-Emission Vehicle Standards.

1. ZEV Emission Standard. The Executive Officer shall certify new ~~2003~~ 2005 and subsequent model passenger cars, light-duty trucks and medium-duty vehicles as ZEVs if the vehicles produce zero exhaust emissions of any criteria pollutant (or precursor pollutant) under any and all possible operational modes and conditions. Incorporation of a fuel-fired heater shall not preclude a vehicle from being certified as a ZEV provided: (1) the fuel-fired heater cannot be operated at ambient temperatures above 40°F, (2) the heater is demonstrated to have zero fuel evaporative emissions under any and all possible operational modes and conditions, and (3) the emissions of any pollutant from the fuel-fired heater when operated at an ambient temperature between 68°F and 86°F do not exceed the emission standard for that pollutant for a ULEV under section 1961(a)(1), title 13, CCR.

A vehicle that would meet the emissions standards for a ZEV except that it uses a fuel-fired heater that can be operated at ambient temperatures above 40°F, that cannot be demonstrated to have zero fuel evaporative emissions under any and all possible operation modes and conditions, or that has emissions of any pollutant exceeding the emission standard for that pollutant for a ULEV under section 1961(a)(1), title 13, CCR, shall be certified based on the emission level of the fuel-fired heater.

2. Percentage ZEV Requirements

2.1 General Percentage ZEV Requirement.

(a) *Basic Requirement.* The minimum percentage ZEV requirement for each manufacturer is listed in the table below as the percentage of the PCs and LDT1s, and LDT2s to the extent required by section C.2.2(c), produced by the manufacturer and delivered for sale in California that must be ZEVs, subject to the conditions in section C.2.2.

<i>Model Years</i>	<i>Minimum ZEV Requirement</i>
2003 <u>2005</u> through 2008	10 percent
2009 through 2011	11 percent
2012 through 2014	12 percent
2015 through 2017	14 percent
2018 and subsequent	16 percent

(b) *Calculating the Number of Vehicles to Which the Percentage ZEV Requirement is Applied.* A manufacturer's volume of PCs and LDT1s produced and delivered for sale in California will be averaged for the 1997, 1998, and 1999 model years to determine the California PC and LDT1 production volume for the model year ~~2003 to~~ 2005 ZEV requirements. For subsequent three-year periods following model years ~~2003 to~~ 2005, a manufacturer's California production volume of PCs and LDT1s, and LDT2s as applicable, will be based on a three-year average of the manufacturer's volume of PCs and LDT1s, and LDT2s as applicable, produced and delivered for sale in California in the prior fourth, fifth and sixth years (e.g. 2006 to 2008 model-year ZEV requirements will be based on

California production volumes of PCs and LDT1s, and LDT2s as applicable, for 2000 to 2002 model years). This production averaging is used to determine ZEV requirements only, and has no effect on a manufacturer's size determination. As an alternative to the three year averaging of prior year production described above, a manufacturer may during model year 2005 or the first model year of a subsequent three year period elect to base its ZEV obligation on the number of PCs and LDT1s, and LDT2s to the extent required by section C.2.1(c), produced by the manufacturer and delivered for sale in California that same year. If a manufacturer elects to use this method after model year 2005 it must be used for each year of the three-year period. In applying the ZEV requirement, a PC, LDT1, or LDT2 (beginning in the 2007 model year) that is produced by a small volume manufacturer, but is marketed in California by another manufacturer under the other manufacturer's nameplate, shall be treated as having been produced by the marketing manufacturer.

(c) *Phase-in of ZEV Requirements for LDT2s.* Beginning with the ZEV requirements for the 2007 model year, a manufacturer's LDT2 production shall be included in determining the manufacturer's overall ZEV requirement under section C.2.1(a) in the increasing percentages shown in the table below.

2007	2008	2009	2010	2011	2012+
17%	34%	51%	68%	85%	100%

(d) *Exclusion of ZEVs in ~~d~~Determining a ~~Manufacturer's~~ ~~Sales~~ ~~Volume~~.* In calculating for purposes of section C2.1(b) and (c) the volume of PCs, LDT1s and LDT2s a manufacturer has produced and delivered for sale in California, the manufacturer shall exclude the number of ZEVs produced by the manufacturer, or by a subsidiary in which the manufacturer has a greater than 50% ownership interest, and delivered for sale in California.

2.2 Requirements for Large Volume, ~~Intermediate Volume, Independent Low Volume, and Small Volume~~ Manufacturers.

(a) *Primary Requirements for Large Volume Manufacturers.*

~~(1) *Model Years 2005-2008.*~~ In the ~~2003~~ 2005 through 2008 model years, a large-volume manufacturer must meet at least ~~20%~~ ~~40%~~ 20% of its ZEV requirement with ZEVs or ZEV credits generated by such vehicles, and at least another ~~20%~~ ~~30%~~ 20% with ZEVs, advanced technology PZEVs, or credits generated by such vehicles. The remainder of the large-volume manufacturer's ZEV requirement may be met using PZEVs or credits generated by such vehicles.

~~(2) *Model Years 2009-2011.*~~ ~~In 2009 through 2011 model years, the maximum portion of a large volume manufacturer's 11% percentage ZEV requirement that may be satisfied by 0.2 allowance PZEVs, or credits generated by such vehicles, is limited to 6% of the manufacturer's applicable California PC, LDT1, and LDT2 production volume. The maximum portion of the ZEV requirement that may be satisfied by advanced technology PZEVs, or credits generated by such vehicles, is limited to 3.75% of the manufacturer's applicable California PC, LDT1, and LDT2 production volume. The~~

1.25% of the manufacturer's applicable California PC, LDT1, and LDT2 production volume that remains must be met only with ZEVs or credits generated by ZEVs.

(3) *Model Years 2012 and subsequent.* As the ZEV requirement increases over time (from 10% ~~from 12%~~ 10% in model year 2003 ~~2012~~ 2005 to 16% in model years 2018 and subsequent), the maximum portion of the a large volume manufacturer's percentage ZEV requirement that may be satisfied by ~~0.2 allowance~~ PZEVs that are not advanced technology PZEVs, or credits generated by such vehicles, is limited to 6% of the manufacturer's applicable California PC, LDT1, and LDT2 production volume; advanced technology PZEVs or credits generated by such vehicles may be used to meet up to one-half of the manufacturer's remaining ZEV requirement.

(b) *Alternative Requirements for Large Volume Manufacturers.*

(1) *Minimum Floor for Production of Type III ZEVs.*

(A) *Requirement For the 2005-2008 Model Years.* A large volume manufacturer electing to be subject to the alternative compliance requirements during model years 2005 through 2008 must produce, deliver for sale, and place in service in California enough 2001-2008 model-year Type III ZEVs to generate ZEV credits sufficient to meet a cumulative percentage ZEV requirement of 1.09 percent of the manufacturer's average annual California sales of PCs and LDT1s over the five year period from model years 1997 through 2001, or submit an equivalent number of credits generated by such vehicles. The manufacturer may meet up to one half of this requirement with Type I or Type II ZEVs, provided that 20 Type I ZEVs or 10 Type II ZEVs will equal one Type III ZEV.

(B) *Requirement For the 2009-2011 Model Years.* A large volume manufacturer electing to be subject to the alternative compliance requirements during model years 2009 through 2011 must produce, deliver for sale, and place in service in California enough 2009-2011 model-year Type III ZEVs to generate ZEV credits sufficient to meet the 2009-2011 alternative path percentage, as calculated pursuant to section C.2.2(b)(1)(E), of the manufacturer's section C.2.1(a) percentage ZEV requirement for the 2010 model year, based on the prior year method described in section C.2.1(b), or submit an equivalent number of credits generated by such vehicles. The manufacturer may meet up to one half of this requirement with Type I or Type II ZEVs, provided that 20 Type I ZEVs or 10 Type II ZEVs will equal one Type III ZEV.

(C) *Requirement For the 2012-2014 Model Years.* A large volume manufacturer electing to be subject to the alternative compliance requirements during model years 2012 through 2014 must produce, deliver for sale, and place in service in California enough 2012-2014 model-year Type III ZEVs to generate ZEV credits sufficient to meet the 2012-2014 alternative path percentage, as calculated pursuant to section C.2.2(b)(1)(E), of the manufacturer's section C.2.1(a) percentage ZEV requirement for the 2013 model year, based on the prior year method described in section C.2.1(b), or submit an equivalent number of credits generated by such vehicles. The manufacturer may meet up to one half of this requirement with Type I or Type II ZEVs, provided that 10 Type I ZEVs or 5 Type II ZEVs will equal one Type III ZEV.

(D) Requirement For the 2015-2017 Model Years. A large volume manufacturer electing to be subject to the alternative compliance requirements during model years 2015 through 2017 must produce, deliver for sale, and place in service in California enough 2015-2017 model-year Type III ZEVs to generate ZEV credits sufficient to meet the 2015-2017 alternative path percentage, as calculated in section C.2.2(b)(1)(E), of the manufacturer's section C.2.1(a) percentage ZEV requirement for the 2016 model year, based on the prior year method described in section C.2.1(b), or submit an equivalent number of credits generated by such vehicles. The manufacturer may meet up to one half of this requirement with Type I or Type II ZEVs, provided that 10 Type I ZEVs or 5 Type II ZEVs will equal one Type III ZEV.

(E) A manufacturer's alternative path percentage for a given time period is calculated as the target number of credits for each time period divided by the applicable combined model year ZEV obligation of all large volume manufacturers for that same time period, where:

<u>Time Period</u>	<u>Target Number of Alternative Path Type III ZEVs</u>	<u>Credits per Vehicle</u>	<u>Target Number of Credits</u>	<u>Combined Model Year ZEV Obligation</u>	<u>Alternative Path Percentage</u>
<u>2009 – 2011</u>	<u>2,500</u>	<u>4</u>	<u>10,000</u>	<u>A</u>	<u>10,000/A</u>
<u>2012 – 2014</u>	<u>25,000</u>	<u>3</u>	<u>75,000</u>	<u>B</u>	<u>75,000/B</u>
<u>2015 – 2017</u>	<u>50,000</u>	<u>3</u>	<u>150,000</u>	<u>C</u>	<u>150,000/C</u>

And where:

A = The combined total section C.2.1(a) percentage ZEV requirement, based on the prior year method described in section C.2.1(b), that would apply for all large manufacturers for the 2010 model year,
B = The combined total section C.2.1(a) percentage ZEV requirement, based on the prior year method described in section C.2.1(b), that would apply for all large manufacturers for the 2013 model year, and
C = The combined total section C.2.1(a) percentage ZEV requirement, based on the prior year method described in section C.2.1(b), that would apply for all large manufacturers for the 2016 model year.

(F) Exclusion of Additional Credits for Transportation Systems. Any additional credits for transportation systems generated in accordance with section C.7.5 shall not be counted towards compliance with this section C.2.2(b)(1)(A)-(E).

(G) Carry-over of Excess Credits. Where a manufacturer generates more qualifying ZEV credits than are needed to meet the minimum floor requirement for the production of Type III ZEVs in one of the periods identified in section C.2.2(b)(1)(A)-(C), the qualifying ZEV credits may be used towards meeting the minimum floor requirement for the production of Type III ZEVs in a subsequent period, provided that the value of these carryover credits shall be based on the model year in which the credits are used.

(H) *Failure to Meet Requirement for Production of Type III ZEVs.* A manufacturer that, after electing to be subject to the alternative requirements in section C.2.2(b) for any model year from 2005 through 2017, fails to meet the requirement in section C.2.2(b)(1)(A)-(D) by the end of the specified three or four year period in which the model year falls, shall be treated as subject to the primary requirements in section C.2.1(a) for all model years in the specified three or four year period.

(2) *Compliance With Percentage ZEV Requirements.* In 2005 through 2008 model years, a large volume manufacturer electing to be subject to the alternative compliance requirements in a given model year must meet at least 40 percent of its ZEV requirement for that model year with ZEVs, advanced technology PZEVs, or credits generated from such vehicles. The remainder of the large volume manufacturer's ZEV requirement may be met using PZEVs or credits generated from such vehicles. As the ZEV requirement increases over time from 11% in model year 2009 to 16% in model years 2018 and subsequent, the maximum portion of the large volume manufacturer's percentage ZEV requirement that may be satisfied by PZEVs that are not advanced technology PZEVs, or credits generated by such vehicles, is limited to 6% of the manufacturer's applicable California PC, LDT1, and LDT2 production volume; ZEVs, advanced technology PZEVs, or credits generated by such vehicles may be used to meet the manufacturer's remaining ZEV requirement.

(3) *Sunset of Alternative Requirements After the 2017 Model Year.* The alternative requirements in section C.2.2(b) are not available after the 2017 model year.

(c) *Election of the Primary or Alternative Requirements for Large Volume Manufacturers.* A large volume manufacturer shall be subject to the primary ZEV requirements for the 2005 model year unless it notifies the Executive Officer in writing prior to the start of the 2005 model year that it is electing to be subject to the alternative compliance requirements for that model year. Thereafter, a manufacturer shall be subject to the same compliance option as applied in the previous model year unless it notifies the Executive Officer in writing prior to the start of a new model year that it is electing to switch to the other compliance option for that new model year. However, a large volume manufacturer that has previously elected to be subject to the primary ZEV requirements for one or more of the model years in the three or four year periods identified in section C.2.2(b)(1)(A)-(D) may prior to the end of the three or four year period elect to become subject to the alternative compliance requirements for the full three or four year period upon a demonstration that it has complied with all of the applicable requirements for that period in section C.2.2(b)(1)(A)-(D).

(d) *Use of Credits from Model Year 2003-2004 PZEVs.* A large volume manufacturer may produce, and deliver for sale in California, model year 2003 or 2004 PZEVs that generate credits exceeding the number of credits equal to 6 percent of the average annual volume of 1997, 1998 and 1999 PCs and LDT1s produced and delivered for sale in California by the manufacturer. In that event, the manufacturer may use those excess credits as AT PZEV credits in the 2005 and 2006 model years.

~~(b) *Intermediate Volume Manufacturers*~~

2.3 Requirements for Intermediate Volume Manufacturers. In ~~2003~~ 2005 and subsequent model years, an intermediate volume manufacturer may meet its ZEV requirement with up to 100 percent partial ZEV allowance vehicles or credits generated by such vehicles.

(e) ~~*Small Volume Manufacturers and Independent Low Volume Manufacturers.*~~

2.4 Requirements for Small Volume Manufacturers and Independent Low Volume Manufacturers. A small volume manufacturer or an independent low volume manufacturer is not required to meet the percentage ZEV requirements. However, a small volume manufacturer or an independent low volume manufacturer may earn and market credits for the ZEVs or PZEVs it produces and delivers for sale in California.

2-32.5 Counting ZEVs and PZEVs in Fleet Average NMOG Calculations. For purposes of calculating a manufacturer's fleet average NMOG value and NMOG credits under sections 1961(b) and (c), title 13, CCR, a vehicle certified as a ZEV is counted as one ZEV, and a PZEV is counted as one SULEV certified to the 150,000 mile standards, regardless of any ZEV or PZEV multipliers.

2-42.6 Implementation Prior to 2003 2005 Model Year. Prior to the ~~2003~~ 2005 model year, a manufacturer that voluntarily produces vehicles meeting the ZEV emission standards applicable to ~~2003~~ 2005 and subsequent model year vehicles may certify the vehicles to those standards and requirements for purposes of calculating fleet average NMOG exhaust emission values and NMOG credits under sections 1961(b) and (c), title 13, CCR, and for calculating ZEV credits as set forth in section C.7.

2-52.7 Changes in Small Volume, Independent Low Volume, and Intermediate Volume Manufacturer Status.

(a) *Increases in California Production Volume.* In ~~the~~ 2003 and subsequent model years, if a small volume manufacturer's average California production volume exceeds 4,500 units of new PCs, LDTs, and MDVs based on the average number of vehicles produced and delivered for sale for the three previous consecutive model years, or if an independent low volume manufacturer's average California production volume exceeds 10,000 units of new PCs, LDTs, and MDVs based on the average number of vehicles produced and delivered for sale for the three previous consecutive model years, or if an intermediate volume manufacturer's average California production volume exceeds 60,000 units of new PCs, LDTs, and MDVs based on the average number of vehicles produced and delivered for sale for the three previous consecutive model years, the manufacturer shall no longer be treated as a small volume, independent low volume, or intermediate volume manufacturer, as applicable, and shall comply with the ZEV requirements for independent low volume, intermediate volume or large volume manufacturers, as applicable, beginning with the sixth model year after the last of the three consecutive model years. The lead time shall be four rather than six years where a manufacturer ceases to be a small or intermediate volume manufacturer in the 2003 or subsequent years due to the aggregation requirements in majority ownership situations, except that if the majority ownership in the

manufacturer was acquired prior to the 2001 model year, the manufacturer must comply with the stepped-up ZEV requirements starting in the 2010 model year.

(b) *Decreases in California Production Volume.* If a manufacturer's average California production volume falls below 4,500, 10,000 or 60,000 units of new PCs, LDTs, and MDVs, as applicable, based on the average number of vehicles produced and delivered for sale for the three previous consecutive model years, the manufacturer shall be treated as a small volume, independent low volume, or intermediate volume manufacturer, as applicable, and shall be subject to the requirements for a small volume, independent low volume, or intermediate volume manufacturer beginning with the next model year. In determining small volume manufacturer status, vehicles produced by one manufacturer and marketed in California by another manufacturer under the other manufacturer's nameplate shall be treated as part of the California production volume of the sales of the marketing manufacturer.

(c) *Calculating California Production Volume in Change of Ownership Situations.* Where a manufacturer experiences a change in ownership in a particular model year, the change will affect application of the aggregation requirements on the manufacturer starting with the next model year. The manufacturer's small or intermediate volume manufacturer status for the next model year shall be based on the average California production volume in the three previous consecutive model years of those manufacturers whose production volumes must be aggregated for that next model year. For example, where a change of ownership during the 2004 model year results in a requirement that the production volume of Manufacturer A be aggregated with the production volume of Manufacturer B, Manufacturer A's status for the 2005 model year will be based on the production volumes of Manufacturers A and B in the 2002-2004 model years. Where the production volume of Manufacturer A must be aggregated with the production volumes of Manufacturers B and C for the 2004 model year, and during that model year a change in ownership eliminates the requirement that Manufacturer B's production volume be aggregated with Manufacturer A's, Manufacturer A's status for the 2005 model year will be based on the production volumes of Manufacturers A and C in the 2002-2004 model years. In either case, the lead time provisions in section 2.5(a) and (b) will apply.

3. Partial ZEV Allowance Vehicles (PZEVs).

3.1 Introduction. This section C.3 sets forth the criteria for identifying vehicles delivered for sale in California as PZEVs. A PZEV is a vehicle that cannot be certified as a ZEV but qualifies for a PZEV allowance of at least 0.2.

3.2 Baseline PZEV Allowance. In order for a vehicle to be eligible to receive a PZEV allowance, the manufacturer must demonstrate compliance with all of the following requirements. A qualifying vehicle will receive a baseline PZEV allowance of 0.2.

(a) *SULEV Standards.* Certify the vehicle to the 150,000-mile SULEV exhaust emission standards for PCs and LDTs in section 1961(a)(1), title 13, CCR (for model years 2003 through 2006, existing SULEV intermediate compliance standards shall apply to all PZEVs). Bi-fuel, fuel-flexible and

dual-fuel vehicles must certify to the applicable 150,000-mile SULEV exhaust emission standards when operating on both fuels;

(b) *Evaporative Emissions.* Certify the vehicle to the evaporative emission standards in section 1976(b)(1)(E), title 13, CCR (“zero” evaporative emissions standards);

(c) *OBD.* Certify that the vehicle will meet the applicable on-board diagnostic requirements in section 1968.1, title 13, CCR for 150,000 miles; and

(d) *Extended Warranty.* Extend the performance and defects warranty period set forth in sections 2037(b)(2) and 2038(b)(2) to 15 years or 150,000 miles, whichever occurs first, ~~For HEVs that are advanced technology PZEVs, the traction battery must be included as a warranty item. except that the time period is to be 10 years for a zero emission energy storage device used for traction power (such as a battery, an ultracapacitor, or a hydraulic, pneumatic and hydrogen other electric storage device) other than the device’s on-board diagnostic elements.~~

3.3 Zero-Emission VMT PZEV Allowance.

(a) *Calculation of Zero Emission VMT Allowance.* A vehicle that meets the requirements of section C.3.2 and has zero-emission vehicle miles traveled (“VMT”) capability will generate an additional zero emission VMT PZEV allowance, calculated as follows:

Urban All-Electric Range	Zero-emission VMT Allowance
< 10 miles	0.0
10 miles to 120 <u>90</u> miles	(10 33.8 + [0.5 x Urban AER])/35
> 120 <u>90</u> miles	2.0 <u>2.25</u>

The urban all-electric range shall be determined in accordance with section E.3.(2)(a) of these test procedures.

(b) *Alternative Procedures.* As an alternative to determining the zero-emission VMT allowance in accordance with the preceding section C.3.3(a), a manufacturer may submit for Executive Officer approval an alternative procedure for determining the zero-emission VMT potential of the vehicle as a percent of total VMT, along with an engineering evaluation that adequately substantiates the zero-emission VMT determination. For example, an alternative procedure may provide that a vehicle with zero-emissions of one regulated pollutant (e.g. NOx) and not another (e.g. NMOG) will qualify for a zero-emission VMT allowance of ~~one-half that of a vehicle with zero emissions of all regulated pollutants~~ 1.5.

(c) *Additional Allowances for Qualifying HEVs.* The Executive Officer shall approve an additional 0.1 zero-emission VMT partial ZEV allowance for an HEV with an all-electric range if the manufacturer demonstrates to the reasonable satisfaction of the Executive Officer that the HEV is equipped with software and/or other strategies that would promote maximum use of off-vehicle charging, and that the strategies employed are reasonably reliable and tamper-proof.

3.4 PZEV Allowance for Advanced ZEV Componentry. A vehicle that meets the requirements of section C.3.2 ~~but does not qualify for any zero-emission VMT partial PZEV allowance under section C.3.3~~ may qualify for an advanced componentry PZEV allowance as provided in this section 3.4.

(a) *Use of High Pressure Gaseous Fuel or Hydrogen Storage System.* A vehicle equipped with a high pressure gaseous fuel storage system capable of refueling at 3600 pounds per square inch or more and operating exclusively on this gaseous fuel shall qualify for an advanced componentry PZEV allowance of ~~0.1~~ 0.2. A vehicle ~~equipped~~ equipped ~~with~~ capable of operating exclusively ~~by~~ on hydrogen stored in a high pressure system capable of refueling at 3600 pounds per square inch or more, or stored in nongaseous form, shall ~~also~~ instead qualify for an advanced componentry PZEV allowance of ~~0.1~~ 0.2 ~~0.3~~.

(b) ~~*Other Advanced ZEV Componentry*~~ *Use of a Qualifying HEV Electric Drive System.*

~~(1) *Qualification for Allowance.* A vehicle shall qualify for an additional advanced componentry allowance of 0.4 in the 2003 through 2011 model years, and 0.35 in the 2012 and subsequent model years, if the manufacturer demonstrates to the reasonable satisfaction of the Executive Officer that the vehicle is equipped with advanced ZEV componentry such as an advanced battery integral to the operation of the vehicle power train or an electric power train and qualifies under one of the two methods listed below. The allowance earned by a vehicle shall be calculated according to one of the following methods, as elected by the manufacturer:~~

~~(A) The maximum system power output available from the electrical storage device divided by the sum of the electrical storage device and the SAE net power of the heat engine is greater than 13%; or~~

~~(B) The maximum system power output available from the electrical storage device divided by the sum of the electrical storage device and the SAE net power of the heat engine is greater than 8% and the maximum power rating of the zero-emission drive system is at least 10 kilowatts.~~

(1) *Classification of HEVs.* HEVs qualifying for additional allowances or allowances that may be used in the AT PZEV category are classified in one of five types of HEVs based on the criteria in the following table.

<u>Characteristics</u>	<u>Type A</u>	<u>Type B</u>	<u>Type C</u>	<u>Type D</u>	<u>Type E</u>
<u>Electric Drive System Peak Power Output</u>	<u>≥ 4 kW</u>	<u>≥ 4 kW</u> <u>< 10 kW</u>	<u>≥ 10 kW</u>	<u>≥ 10 kW</u>	<u>≥ 50 kW</u>
<u>Traction Drive System Voltage</u>	<u>≤ 60 Volts</u>	<u>≥ 60 Volts</u>	<u>≤ 60 Volts</u>	<u>≥ 60 Volts</u>	<u>≥ 60 volts</u>
<u>Traction Drive Boost</u>	<u>Yes</u>	<u>Yes</u>	<u>Yes</u>	<u>Yes</u>	<u>Yes</u>
<u>Regenerative Braking</u>	<u>Yes</u>	<u>Yes</u>	<u>Yes</u>	<u>Yes</u>	<u>Yes</u>
<u>Idle Start/Stop</u>	<u>Yes</u>	<u>Yes</u>	<u>Yes</u>	<u>Yes</u>	<u>Yes</u>

(2) Type A HEVs. A 2008 or earlier model-year PZEV that the manufacturer demonstrates to the reasonable satisfaction of the Executive Officer meets all of the criteria for a Type A HEV does not receive an additional allowance for meeting those criteria but generates credits that may be used in the AT PZEV category through the 2008 model year.

(3) Type B HEVs. A 2008 or earlier model-year PZEV that the manufacturer demonstrates to the reasonable satisfaction of the Executive Officer meets all of the criteria for a Type B HEV qualifies for an additional advanced componentry allowance of 0.2.

(4) Type C HEVs. A PZEV that the manufacturer demonstrates to the reasonable satisfaction of the Executive Officer meets all of the criteria for a Type C HEV qualifies for an additional advanced componentry allowance of 0.2 in the 2003 through 2011 model years, 0.15 in the 2012 through 2014 model years, and 0.1 in the 2015 and subsequent model years.

(5) Type D HEVs. A PZEV that the manufacturer demonstrates to the reasonable satisfaction of the Executive Officer meets all of the criteria for a Type D HEV qualifies for an additional advanced componentry allowance of 0.4 in the 2003 through 2011 model years, 0.35 in the 2012 through 2014 model years, and 0.25 in the 2015 and subsequent model years.

(6) Type E HEVs. A PZEV that the manufacturer demonstrates to the reasonable satisfaction of the Executive Officer meets all of the criteria for a Type E HEV qualifies for an additional advanced componentry allowance of 0.5 in the 2003 through 2011 model years, 0.45 in the 2012 through 2014 model years, and 0.35 in the 2015 and subsequent model years.

~~(7) Severability. In the event that one of the two methods in all or part of section C.3.4(b)(1)-(6) is found invalid, the remainder of these standards and test procedures, including the remainder of section C.3.4(b)(1), remains in full force and effect. In the event that both of the two~~

~~methods in section 3.4(b)(1) are found invalid, the remainder of these standards and test procedures, without section 3.4(b)(1) remains in full force and effect.~~

(1) *CO₂ Reduction Method.*

(A) *General.* ~~A vehicle whose operation results in reduced CO₂ emissions as compared to the average vehicle in its class may qualify for an additional advanced componentry allowance in accordance with this section C3.4(b)(1). The vehicle's class is determined in accordance with section C.5.3.~~

(B) *Equation for Determining Additional Allowance.* ~~The following equation is used to calculate the additional allowance, provided that in order to earn any additional allowance, the CO₂ Savings must be at least 39,000:~~

$$\text{Advanced Componentry Allowance} = \text{CO}_2\text{-Savings} \div 250,000$$

Where: ~~CO₂-Savings = (Class Average CO₂ Production) - (Vehicle CO₂ Production) Vehicle~~

$$\text{CO}_2\text{-Production} = (150,000 \div \text{CMPEG}) \times 19.564$$

~~CMPEG is determined in accordance with section C.5.2~~

~~Class Average CO₂ Production for the 2000-2007 model years is determined using the following table:~~

Vehicle Class	Class Average CO₂ Production, 2000-2007 MY
Subcompact PC	95,902
Compact PC	96,533
Midsize PC	108,689
Large PC	114,633
Small Truck	117,384
Medium Truck	137,131
Large Truck	161,242

~~Class Average CO₂ Production for the 2008-2014 model years is determined in accordance with the following equation:~~

~~Class Average CO₂ Production = (150,000 / Baseline Fuel Economy for model years 2008-2014) × 19.564~~

~~Where: Baseline Fuel Economy for model years 2008-2014 means Baseline Fuel Economy for either the 2008-2011 or 2012-2014 model years, as applicable, as determined in accordance with section C.5.5.~~

~~(C) *Alternative Method for Determining CO₂ Savings of a Vehicle That Is Not Gasoline Fueled.* For purposes of the equation in section C.3.4(b)(1)(B), the Executive Officer shall approve an alternative method for determining CO₂ savings of a vehicle that is not gasoline fueled, if the manufacturer submits the alternative method with an engineering evaluation that demonstrates to the reasonable satisfaction of the Executive Officer that the alternative method fairly represents the CO₂ impacts of the vehicle.~~

~~(2) *Alternative Efficiency Method.* A manufacturer may elect to have a vehicle's additional advanced componentry allowance determined according to the Efficiency Method, in which case the allowance shall be determined in accordance with the following equation:~~

~~Advanced Componentry Allowance = ((CMPEG / (1.3 * Baseline Fuel Economy)) - 1) * 0.5~~

~~Where: CMPEG is determined in accordance with section C.5.2.
Baseline Fuel Economy is determined in accordance with section C.5.4.~~

~~A vehicle earning an Efficiency Method advanced componentry allowance of less than zero pursuant to this subsection will be treated as having an Efficiency Method advanced componentry allowance of zero.~~

~~(3) *Alternative Percent Peak Power Method For the 2000-2007 Model Years.* For the 2000-2007 model years only, a manufacturer may elect to have a vehicle's additional advanced componentry allowance determined using the Percent Peak Power method, in which case the allowance shall be determined in accordance with the following equation:~~

~~Advanced Componentry Allowance = Percentage of "maximum available power" from the electric storage device~~

~~Where: Percentage of "maximum available power" means the maximum system power output available from the electrical storage device divided by the sum of the electrical storage device and the SAE net power of the heat engine. Percentage of "maximum available power" means the maximum system power output available from the electrical storage device divided by the sum of the maximum system power output available from the electrical storage device and the SAE net power of the heat engine. To determine the maximum system power output from the electrical storage device, the complete pack~~

will be subjected to a 10 second, constant power discharge at the maximum 10 second power specified by the OEM. End of pulse voltage must meet or exceed OEM specified minimum voltage. If end of pulse voltage is less than the OEM specified minimum voltage, the test must be repeated at a lower power level until the minimum voltage requirement is satisfied. All tests shall be performed at 25 degrees Celsius.

In order to earn any score using the Percent Peak Power method a vehicle must be able to recover kinetic energy through regenerative braking and provide at least 13 percent of “maximum available power” from the electrical storage device.

3.5 PZEV Allowance for Low Fuel-Cycle Emissions. A vehicle that uses fuel(s) with very low fuel-cycle emissions shall receive a PZEV allowance not to exceed ~~0.2~~ 0.3 (0.15 in the case of an HEV that uses for propulsion any fuel that does not have very low fuel-cycle emissions). In order to receive the fuel-cycle PZEV allowance, a manufacturer must demonstrate to the Executive Officer, using peer-reviewed studies or other relevant information, that NMOG emissions associated with the fuel(s) used by the vehicle (on a grams/mile basis) are lower than or equal to 0.01 grams/mile. Fuel-cycle emissions must be calculated based on near-term production methods and infrastructure assumptions, and the uncertainty in the results must be quantified. The fuel-cycle PZEV allowance is calculated according to the following formula:

$$\text{PZEV Fuel Cycle Allowance} = \del{0.2} \u{0.3} \times [(\text{percent of VMT using fuel(s) meeting the requirements of the preceding paragraph}) / 100]$$

A manufacturer’s demonstration to the Executive Officer that a vehicle qualifies for a fuel-cycle PZEV allowance shall include test results and/or empirical data supporting the estimate of the relative proportion of VMT while operating on fuel(s) with very low fuel-cycle emissions.

3.6 Combined ZEV Allowance.

~~(a) **Calculation of Combined PZEV Allowance for a Vehicle**~~ Calculation of Combined PZEV Allowance for a Vehicle. The combined PZEV allowance for a qualifying vehicle in a particular model year is the sum of the PZEV allowances listed in this section C.3.6, multiplied by any PZEV introduction phase-in multiplier or ~~PZEV high efficiency multiplier~~ listed in section C.3.7 ~~(if a 2002 through 2005 model year PZEV qualifies for both multipliers listed in section C.3.7, the product of the two multipliers is used as the PZEV multiplier)~~, subject to the cap in section C.3.6(b) ~~for 2002 and subsequent model year vehicles.~~

~~(a)~~ (1) *Baseline PZEV Allowance.* The baseline PZEV allowance of 0.2 for vehicles meeting the criteria in section C.3.2;

~~(b)~~ (2) *Zero Emission VMT PZEV Allowance.* The zero-emission VMT PZEV allowance, if any, determined in accordance with section C.3.3.;

(e) (3) *Advanced ZEV Componentry PZEV Allowance.* The advanced ZEV componentry PZEV allowance, if any, determined in accordance with section C.3.4; and

(d) (4) *Fuel-cycle Emissions PZEV Allowance.* The fuel-cycle emissions PZEV allowance, if any, determined in accordance with section C.3.5.

(b) *Caps on the Value of an AT PZEV Allowance.*

(1) *Cap for 2012 and Subsequent Model-Year Vehicles.* The maximum value of AT PZEV allowances a 2012 and subsequent model-year vehicle may earn, including the baseline PZEV allowance, is 3.0.

(2) *Cap Based on the Credit Value of a Type III ZEV.* In no case may the combined AT PZEV allowance for a qualifying vehicle in a particular model year, including the baseline PZEV allowance, exceed the ZEV credits for a Type III ZEV placed in service in the same model year.

3.7 PZEV Multipliers

(a) *PZEV Introduction Phase-In Multiplier.* Each 2000 through 2005 model-year PZEV that is produced and delivered for sale in California, other than a PZEV qualifying for a phase-in multiplier under section C.3.7(b), qualifies for a PZEV introduction phase-in multiplier as follows:

	MY 2000-2003	MY 2004	MY 2005
Multiplier	4.0	2.0	1.33

(b) ~~*AT PZEV High Efficiency Multiplier.*~~ ~~An AT PZEV qualifies for a high efficiency multiplier in accordance with section C.5 starting with the 2002 model year.~~

(e) (b) *Introduction Phase-In Multiplier for PZEVs with > 10 Mile That Earn a Zero Emission Range VMT Allowance.* Each 2000 through 2011 model year PZEV ~~with > 10 miles that earns a zero emission range VMT allowance under section 1962(e)(3)C.3.3~~ and is produced and delivered for sale in California qualifies for a phase-in multiplier as follows:

	MY 2000-2007-2008	MY 2008-2009-2011	<u>MY 2010-2011</u>
Multiplier	2.0 <u>6.0</u>	1.5 <u>3.0</u>	1.25

4. Qualification for ZEV Multipliers and Credits.

4.1 1999-2000 Model-Year ZEV Multiplier Calculation for Extended Electric Range Vehicles. Each ZEV that is produced and delivered for sale in California in the 1999-2000 model years and that has an extended electric range shall qualify for a ZEV multiplier as follows:

All-electric range	MY 1999-2000
100-175	6-10

ZEV multipliers under the above schedule will be determined by linear interpolation between the values shown in the above schedule. Range shall be determined in accordance with section E.3.(2)(a) of these test procedures. ZEVs that have a refueling time of less than 10 minutes and a range of 100 miles or more shall be counted as having unlimited all-electric range, and shall consequently earn the maximum allowable ZEV multiplier for a specific model year. ZEVs that have a range of 80 to 99 miles shall qualify for ZEV multipliers in the 1999-2000 model years in accordance with the following equation:

$$\text{ZEV multiplier} = (6) \times (\text{AER equivalent to a 10 minute recharge}/100) \times 0.5.$$

As an option to the above mechanism, the manufacturer of a 1999 model-year ZEV may elect to have its multiplier based on the regulatory requirements pertaining to multipliers based on range or specific energy in section 1960.1(g)(2) and (h)(2), title 13, CCR, that were applicable to 1999 model-year ZEVs immediately before this section 1962 became operative on November 27, 1999 as a result of the ‘LEV II’ rulemaking.

4.2 ZEV Multipliers for 2001-2002 and Subsequent Model Years.

(a) *ZEV Phase-In Multiplier.* Each 2001 ~~to 2005~~ and 2002 model-year ZEV that is placed in service in California by ~~April 15~~ September 30, 2003 qualifies for a ZEV phase-in multiplier as follows: of 4.0. A 2001 ~~to~~ or 2002 model-year ZEV that is placed in service in California after ~~April 15~~ September 30, 2003 earns credits in accordance with section 4.4 instead of section 4.2.

	MY 2001-2002	MY 2003-2005
<i>Multiplier</i>	4.0	1.25

(b) ~~—~~ *ZEV Discount Multiplier for NEVs.* Each 2004 and subsequent model year NEV that is produced and delivered for sale in California is subject to a ZEV discount multiplier for NEVs as follows:

	MY 2004 – MY 2005	MYs 2006 and Subsequent
Discount Multiplier	0.5	0.15

(e) (b) *ZEV Extended Electric Range Multiplier.*

(1) *Basic Multiplier Schedule.* Each 2001 and ~~subsequent~~ 2002 model-year ZEV that is placed in service in California and that has an extended urban electric range qualifies for a ZEV extended electric range multiplier as follows:

Urban All-Electric Range	Multiplier
< 50 miles	1
≥ 50 miles to < 275 miles	(Urban AER-25)/25
≥ 275 miles	10

A NEV is not eligible to earn a ZEV extended electric range multiplier. In determining ZEV range multipliers, specialty ~~electric vehicles~~ ZEVs may, upon Executive Officer approval, be tested at the parameters used to determine the ZEV multipliers for the existing ~~electric vehicle~~ ZEV.

(2) *Fast refueling.*

(A) *Full Fueling in 10 Minutes or Less.* A ~~2008 and earlier~~ model-year ZEV with the demonstrated capability to accept fuel or electric charge until achieving at least 95% SOC or rated fuel capacity in 10 minutes or less when starting from all operationally allowable SOC or fuel states is counted as having unlimited zero emission range and qualifies for the maximum allowable ZEV extended electric range multiplier.

(B) *At Least 60-Mile Range in Less Than 10 Minutes.* A ~~2008 and earlier~~ 2001-2002 model year ZEV with the demonstrated capacity to accept fuel or electric charge equivalent to at least 60 miles of UDDS range when starting from 20% SOC in less than 10 minutes is counted as having 60 additional miles (up to a 275 mile maximum) of UDDS range in the range multiplier determination in section C.4.2(c)(1).

(3) *Multiplier Phase Down.* ~~Starting with the 2005 model year, the ZEV extended electric range multiplier is phased down to 0.15 of its value in accordance with section C.5.6.~~

4.4 (c) ~~Combined ZEV Multiplier.~~ *Combined Multiplier.* ~~Starting with~~ During the 2001-2002 model years, the combined ZEV multiplier for each ZEV in a specific model year is the product of:

1. (1) The ZEV phase-in multiplier if any as set forth in section C.4.2(a), times
2. ~~(2)~~ (2) In the case of a NEV, the ZEV discount multiplier for NEVs if any as set forth in section C.4.2(b), times
3. ~~(3)~~ (2) The extended electric range multiplier if any as set forth in section C.4.2(e)(b), times
4. The high efficiency multiplier if any as set forth in section C.5.

4.5 4.3 Effect of ZEV Multipliers in the 1996-2002 Model Years. In calculating the number of ZEVs ~~and~~ produced and delivered for sale in California by a manufacturer in a the 1996-2002 model years and the ZEV credits from such vehicles, the number of ZEVs ~~and~~ qualifying for a particular ZEV multiplier shall be multiplied by the combined ZEV multiplier.

4.4 ZEV Credits for 2003 and Subsequent Model Years.

(a) ZEV Tiers for Credit Calculations. Starting in the 2003 model year, ZEV credits from a particular ZEV are based on the assignment of a given ZEV into one of the following five ZEV tiers:

<u>ZEV Tier</u>	<u>Common Description</u>	<u>UDDS ZEV Range</u>	<u>Fast Refueling Capability</u>
<u>NEV</u>	<u>NEV</u>	<u>No minimum</u>	<u>N/A</u>
<u>Type 0</u>	<u>Utility EV</u>	<u><50 miles</u>	<u>N/A</u>
<u>Type I</u>	<u>City EV</u>	<u>>= 50, <100 miles</u>	<u>N/A</u>
<u>Type II</u>	<u>Full Function EV</u>	<u>>= 100 miles</u>	<u>N/A</u>
<u>Type III</u>	<u>Fuel Cell EV</u>	<u>>= 100 miles</u>	<u>Must be capable of replacing 95% maximum rated energy capacity in <= 10 minutes</u>

A specialty ZEV that has the same zero emission energy storage device and chassis as an existing ZEV from which it was modified may, upon Executive Officer approval, be categorized on the basis of the that existing ZEV from which it is modified. A specialty vehicle that is optimized for a particular duty cycle that conflicts with optimization for maximum vehicle range may be promoted to the next higher ZEV tier upon a determination by the Executive Officer that the specialty vehicle has ZEV componentry equivalent to that utilized by ZEVs in the next tier and would meet the requirements for the next tier if optimized for maximum range.

(b) ZEV Credits for 2003 and ~~Subsequent~~ ~~Model~~ ~~Year~~ ZEVs. A 2003 and subsequent model-year ZEV, other than a NEV, earns 1 ZEV credit when it is produced and delivered for sale in California. A 2003 and subsequent model-year ZEV earns additional credits based on the

earliest model year in which the ZEV is placed in service (not earlier than the ZEV's model year). The following table identifies the credits that a ZEV in each of the five ZEV tiers will earn, including the credit not contingent on placement in service, if it is placed in service in the specified model year or by ~~March 31~~ June 30 after the end of the specified model year.

<u>Tier</u>	<u>Model Year in Which ZEV is Placed in Service</u>									
	<u>2003</u>	<u>2004</u>	<u>2005</u>	<u>2006</u>	<u>2007</u>	<u>2008</u>	<u>2009</u>	<u>2010</u>	<u>2011</u>	<u>2012+</u>
<u>NEV</u>	<u>1.25</u>	<u>0.625</u>	<u>0.625</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>
<u>Type 0 (Utility)</u>	<u>1.5</u>	<u>1.5</u>	<u>1.5</u>	<u>1.5</u>	<u>1.5</u>	<u>1.5</u>	<u>1</u>	<u>1</u>	<u>1</u>	<u>1</u>
<u>Type 1 (City)</u>	<u>8</u>	<u>8</u>	<u>8</u>	<u>7</u>	<u>7</u>	<u>7</u>	<u>2</u>	<u>2</u>	<u>2</u>	<u>2</u>
<u>Type II</u>	<u>12</u>	<u>12</u>	<u>12</u>	<u>10</u>	<u>10</u>	<u>10</u>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>
<u>Type III</u>	<u>40</u>	<u>40</u>	<u>40</u>	15 <u>40</u>	15 <u>40</u>	15 <u>40</u>	<u>4</u>	<u>4</u>	<u>4</u>	<u>3</u>

(c) Multiplier for Certain Type I and Type II ZEVs. A 2003 through 2011 model-year Type I and Type II ZEV shall qualify for a multiplier of 1.25 if it is either sold to a motorist or is leased for three or more years to a motorist who is given the option to purchase or re-lease the vehicle at the end of the first lease term.

(d) Counting a Type III ZEV Placed in a Section 177 State. Through the 2011 model year, a Type III ZEV that is certified to the California ZEV standards and is placed in service in a state that is administering the California ZEV requirements pursuant to section 177 of the federal Clean Air Act (42 U.S.C. § 7507) applicable for the ZEV's model year may be counted towards compliance with the California percentage ZEV requirements in section C.2, including the requirements in section C.2.2(b), as if it were delivered for sale and placed in service in California. Similarly, a 2011 and earlier model-year Type III ZEV that is certified to the California ZEV standards and is placed in service in California may be counted towards the percentage ZEV requirements of any state that is administering the California ZEV requirements pursuant to section 177 of the federal Clean Air Act, including requirements based on section C.2.2(b).

5. [Reserved] ZEV and Advanced Technology PZEV High Efficiency Multipliers

5.1 Eligibility. Beginning with the 2005 model year for ZEVs and the 2002 model year for advanced technology PZEVs, both ZEVs and PZEVs are eligible for a high efficiency multiplier. A NEV is not eligible to earn an efficiency multiplier. A vehicle earning an efficiency multiplier value of less than 1.00 pursuant to section C.5.3 will be treated as having an efficiency multiplier of 1.

5.2 Calculation of CMPEG Rating. For all vehicle types, a CMPEG (California miles per equivalent gallon) rating is determined as follows:

(a) For gasoline-fueled vehicles and HEVs with < 10 mile zero emission range, CMPEG = Combined Fuel Economy determined in accordance with 40 CFR Part 600 = $1 / [.55 / (\text{EPA city mpg, unadjusted}) + .45 / (\text{EPA highway mpg, unadjusted})]$.

(b) For BEVs and off-vehicle charge capable HEVs with = 10 mile with mile zero emission range, CMPEG = $[33,705 \text{ AC whr/gal} / (.55 (\text{AC whr/mile UDDS}) + .45 (\text{AC whr/mile HFEDS}))]$ where AC whr/mile values are determined in accordance with section E.3., "Determination of All-Electric Range Urban," and "Determination of All Electric Range Highway." Qualifying hybrid electric vehicle CMPEG determination shall be based solely on electric mode operating efficiency for vehicles that are able to maintain test cycle speed and time tolerances for the entire zero emission range test.

(c) *Alternative Fuel Vehicles.*

(1) For vehicles operating on an alternative fuel other than hydrogen, including CNG or alcohol, CMPEG = Combined Fuel Economy as determined in accordance with 40 CFR Part 600. Alternate fuel vehicle CMPEG shall not be compensated with the federal (1/0.15) "fuel content" factor used in determining average fuel economy.

(2) For vehicles operating on hydrogen, CMPEG shall be determined by converting the combined fuel economy value measured on the basis of miles per kg of hydrogen (MPkg) into CMPEG as follows:

$$\text{Hydrogen MPkg} \times (1.0 \text{ kg H}_2/\text{gallon gasoline}) = \text{CMPEG}$$

(d) For flexible fuel or dual fuel vehicles, CMPEG is the lowest of the federal combined fuel economy values determined for any fuel or fuel mixture on which the vehicle is certified to operate.

5.3 Vehicle classes.

(a) *List of vehicle classes.* Efficiency multipliers will be determined based on assignment of a vehicle to one of the following vehicle classes; interior volume is determined in accordance with SAE Recommended Practice J1100 and U.S. EPA Fuel economy regulations, 40 CFR 600.315-82.

Vehicle Class	Class Description
City Vehicle (effective beginning in 2008 model year)	2-passenger electric vehicle with length < 3 meters
Subcompact PC	Interior volume up to 99 ft ³ , and not a City Vehicle
Compact PC	Interior volume 100-109 ft ³
Midsize PC	Interior volume 110-119 ft ³
Large PC	Interior volume over 120 ft ³
Small Truck	LDT 1
Medium Truck	LDT 2
Large Truck	LDT 3 & 4

(b) ~~Assignment of derivative or converted vehicles.~~ A derivative station wagon shall be placed in the same class as the sedan on which it is based. A minivan shall be placed in the appropriate truck category based on adjusted or adjusted loaded vehicle weight. A derivative or conversion ZEV that shares a production platform with one or more gasoline engine versions shall be placed in the same class as the smallest or lightest gasoline version of the same platform for that model year.

5.4 High efficiency multipliers for the 2002-2007 model years. For model years 2002-2007, the efficiency multiplier for each vehicle class is determined according to the following equation:

$$\text{High Efficiency Multiplier} = \text{CMPEG} / (1.5 * \text{Baseline Fuel Economy})$$

Where: _____ Baseline Fuel Economy is determined in accordance with the following table:

Vehicle Class	Baseline Fuel Economy MY 2002-2007
Subcompact PC	30.6
Compact PC	30.4
Midsize PC	27.0
Large PC	25.6
Small Truck	25.0
Medium Truck	21.4
Large Truck	18.2

5.5 High efficiency multipliers for the 2008 and subsequent model years. For the 2008 and subsequent model years, the efficiency multiplier for each vehicle class is determined in accordance with the following equations:

For ZEVs and PZEVs with > 10 mile Zero Emission Range: Efficiency multiplier = $CMPEG / (2.0 * \text{Baseline Fuel Economy})$

For all other AT PZEVs: Efficiency multiplier = $CMPEG / (1.5 * \text{Baseline Fuel Economy})$

Where: ~~Baseline Fuel Economy~~ for model years 2008-2011 is the model year 2004 unadjusted combined federal sales weighted fuel economy for the vehicle class as determined by U.S. EPA. For a City Vehicle, the baseline fuel economy is 45.9.

~~Baseline Fuel Economy~~ for Model Years 2012-2014 is the model year 2008 unadjusted combined federal sales weighted fuel economy for the vehicle class as determined by U.S. EPA. For a City Vehicle, the baseline fuel economy is 45.9.

~~Baseline Fuel Economy~~ for model years 2015 and beyond shall be determined using the same methodology.

5.6 Phasing in the High Efficiency Multiplier for ZEVs.

(a) ~~Range and Efficiency Phasing Standards.~~ For ZEVs, the high efficiency multiplier is phased in, and the extended electric range multiplier is phased down to 0.15 of its initial value, using the phasing factors in the following schedule:

Range and Efficiency Phasing Factors for Each Model Year

	2004	2005	2006	2007	2008	2009	2010	2011	2012+
Range	1.000	0.825	0.600	0.450	0.300	0.250	0.200	0.200	0.150
Efficiency	0.000	0.100	0.350	0.550	0.600	0.700	0.800	0.800	0.825

(B) *Application of the Range and Efficiency Phasing Factors.* The range and efficiency phasing factors are applied as follows:

$$\text{Phased range multiplier} = ((\text{range multiplier} - 1) \times \text{range phasing factor}) + 1$$

$$\text{Phased efficiency multiplier} = ((\text{efficiency multiplier} - 1) \times \text{efficiency phasing factor}) + 1$$

6. ~~In-Extended Service Warranty Multiplier for 2001-2004 Model-Year ZEVs and PZEVs With ³ 10 Mile Zero Emission Range.~~ Except in the case of a NEV, an additional ZEV or PZEV multiplier will be earned for the by a 2001 through 2011 2004 model-years by a ZEV, or a PZEV with ≥ 10 mile zero emission range whose zero-emission energy storage or conversion system is under an original warranty from the vehicle manufacturer beyond three years of service and for each full year it is registered for operation on public roads in California beyond its first three years of service, through the 2011 calendar year. For the 2001 through 2007 model years, a The manufacturer will receive 0.1 0.2 times the ZEV credit that would be earned by the vehicle if it were leased or sold new in that year, including multipliers, on a year-by-year basis beginning in the fourth year after the vehicle is initially placed in service. For the 2008 through 2011 model years, a manufacturer will receive 0.05 times the ZEV credit earned by the vehicle if it were leased or sold new in that year, including multipliers, on a year-by-year basis beginning in the fourth year. The warranty extended service multiplier is reported and earned in the year following each continuous year of service. ZEVs, other than NEVs, re-leased prior to January 25, 2001 for a period beyond three years of service will earn an additional ZEV multiplier of 0.1 times the ZEV credit earned by the vehicle if it were leased or sold new in that year, including multipliers, for each additional year that they are in service and registered for operation on public roads in California. Such vehicles are not required to have the zero-emission energy storage or conversion system under an original warranty from the vehicle manufacturer.

7. Generation and Use of ZEV Credits; Calculation of Penalties

7.1 Introduction. A manufacturer that produces and delivers for sale in California ZEVs or PZEVs in a given model year exceeding the manufacturer’s ZEV requirement set forth in section C.2 shall earn ZEV credits in accordance with this section C.7.

7.2 ZEV Credit Calculations.

(a) ~~Credits from ZEVs.~~ Credits from ZEVs. The amount of g/mi ZEV credits earned by a manufacturer in a given model year from ZEVs shall be expressed in units of g/mi NMOG, and shall

15-Day Notice version, released 7/29/03 (Final mailout by 8/8/03)

Supplemental comment deadline: 8/25/03

Hearing Dates: 3/27-28/03 and 4/24/03

be equal to the number of credits from ZEVs produced and delivered for sale in California that the manufacturer applies towards meeting the ZEV requirements for the model year subtracted from the number of ZEVs produced and delivered for sale in California by the manufacturer in the model year and then multiplied by the NMOG fleet average requirement for PCs and LDT1s for that model year.

(b) **Credits from PZEVs.** *Credits from PZEVs.* The amount of g/mi ZEV credits from PZEVs earned by a manufacturer in a given model year shall be expressed in units of g/mi NMOG, and shall be equal to the total number of PZEV allowances from PZEVs produced and delivered for sale in California that the manufacturer applies towards meeting its ZEV requirement for the model year subtracted from the total number of PZEV allowances from PZEVs produced and delivered for sale in California by the manufacturer in the model year and then multiplied by the NMOG fleet average requirement for PCs and LDT1s for that model year.

(c) *Separate Credit Accounts.* The number of credits from a manufacturer's [i] ZEVs and [ii] advanced technology PZEVs, and [iii] all other PZEVs shall each be maintained separately.

7.3 ZEV Credits for MDVs and LDTs ~~Other than LDT1s.~~ ZEVs and PZEVs classified as MDVs or as LDTs other than LDT1s may be counted toward the ZEV requirement for PCs and LDT1s, and included in the calculation of ZEV credits as specified in this section C.4 if the manufacturer so designates.

7.4 ZEV Credits for Advanced Technology Demonstration Programs. A vehicle, other than a NEV, that is placed in a California advanced technology demonstration program may earn ZEV credits even if it is not "delivered for sale." To earn such credits, the manufacturer must demonstrate to the reasonable satisfaction of the Executive Officer that the vehicles will be regularly used in applications appropriate to evaluate issues related to safety, infrastructure, fuel specifications or public education, and that for more than 50 percent of the first year of placement the vehicle will be situated in California. Such a vehicle is eligible to receive the same allowances and credits that it would have earned if placed in service. To determine vehicle credit, the model-year designation for a demonstration vehicle shall be consistent with the model-year designation for conventional vehicles placed in the same timeframe.

7.5 ZEV Credits for Transportation Systems.

(a) *General.* In model years 2001 through ~~2007~~ 2011, a ZEV, advanced technology PZEV or PZEV placed as part of a transportation system may earn additional ZEV credits, which may be used in the same manner as other credits earned by vehicles of that category, except as provided in section C.7.5(c) below. A NEV is not eligible to earn credit for transportation systems. To earn such credits, the manufacturer must demonstrate to the reasonable satisfaction of the Executive Officer that the vehicle will be used as a part of a project that uses an innovative transportation system as described in section 7.5(b) below.

(b) *Credits Earned.* In order to earn additional credit under this section (g)(5), a project must at a minimum demonstrate [i] shared use of ZEVs, AT PZEVs or PZEVs, and [ii] the application of “intelligent” new technologies such as reservation management, card systems, depot management, location management, charge billing and real-time wireless information systems. If, in addition to factors [i] and [ii] above, a project also features linkage to transit, the project may receive further additional credit. For ZEVs only, not including NEVs, a project that features linkage to transit, such as dedicated parking and charging facilities at transit stations, but does not demonstrate shared use or the application of intelligent new technologies, may also receive additional credit for linkage to transit. The maximum credit awarded per vehicle shall be determined by the Executive Officer, based upon an application submitted by the manufacturer and, if appropriate, the project manager. The maximum credit awarded shall not exceed the following:

Type of Vehicle	Shared Use, Intelligence	Linkage to Transit
PZEV	2	1
Advanced Technology PZEV	4	2
ZEV	6	3

(c) *Cap on Use of Credits.*

(1) *ZEVs.* Credits earned or allocated by ZEVs pursuant to this section C.7.5, not including all credits earned by the vehicle itself, may be used to satisfy up to one-tenth of a manufacturer’s ZEV obligation in any given model year.

(2) *AT PZEVs.* Credits earned or allocated by AT PZEVs pursuant to this section C.7.5, not including all credits earned by the vehicle itself, may be used to satisfy up to one-twentieth of a manufacturer’s ZEV obligation in any given model year, but may only be used in the same manner as other credits earned by vehicles of that category.

(3) *PZEVs.* Credits earned or allocated by PZEVs pursuant to this section C.7.5, not including all credits earned by the vehicle itself, may be used to satisfy up to one-fiftieth of the manufacturer’s ZEV obligation in any given model year, but may only be used in the same manner as other credits earned by vehicles of that category.

(d) *Allocation of Credits.* Credits shall be assigned by the Executive Officer to the project manager or, in the absence of a separate project manager, to the vehicle manufacturers upon demonstration that a vehicle has been placed in a project. Credits shall be allocated to vehicle manufacturers by the Executive Officer in accordance with a recommendation submitted in writing by the project manager and signed by all manufacturers participating in the project, and need not be allocated in direct proportion to the number of vehicles placed.

7.6 Submittal of ZEV Credits. A manufacturer may meet the ZEV requirements in any given model year by submitting to the Executive Officer a commensurate amount of g/mi ZEV credits

consistent with section C.2. These credits may be earned previously by the manufacturer or acquired from another manufacturer party, except that beginning with the 2006 model year credits earned from NEVs offered for sale or placed in service in model years 2001 through 2005 cannot be used to satisfy more than the following portion of any program category (ZEV, AT PZEV, PZEV) a manufacturer's percentage ZEV obligation that may not only be satisfied with credits from AT PZEVs or PZEVs ZEVs and, starting with the 2009 model year, the manufacturer's percentage ZEV obligation that may be satisfied by credits from AT PZEVs but not PZEVs:

<u>ZEV Category</u>		<u>AT PZEV Category</u>	
<u>2006</u>	<u>2007 and beyond</u>	<u>2009</u>	<u>2010 and beyond</u>
<u>75%</u>	<u>50%</u>	<u>75%</u>	<u>50%</u>

This limitation applies to credits earned in model years 2001 through 2005 by the same manufacturer or earned in model years 2001 through 2005 by another manufacturer and acquired. The amount of ZEV credits required to be submitted shall be calculated according to the criteria set forth in this section C. 7.

7.7 Requirement to Make Up a ZEV Deficit.

(a) *General.* A manufacturer that produces and delivers for sale in California fewer ZEVs than required in a given model year shall make up the deficit by the end of the next model year by submitting to the Executive Officer a commensurate amount of g/mi ZEV credits, except that credits generated from PZEVs may be used to offset deficits for two model years. The amount of ZEV credits required to be submitted shall be calculated by [i] adding the number of ZEVs produced and delivered for sale in California by the manufacturer for the model year to the number of ZEV allowances from partial ZEV allowance vehicles produced and delivered for sale in California by the manufacturer for the model year (for a large volume manufacturer, not to exceed that permitted under section C.2.1), [ii] subtracting that total from the number of ZEVs required to be produced and delivered for sale in California by the manufacturer for the model year, and [iii] multiplying the resulting value by the fleet average requirements for PCs and LDT1s for the model year in which the deficit is incurred.

(b) *Additional Time to Make Up ZEV Deficits for the 2003-2004 Model Years.*

(1) *Model Year 2003 ZEV Deficits.* ~~A manufacturer that produces, and delivers for sale in California, model year 2003 or earlier PZEVs that generate at least twice as many credits as are necessary to take full advantage of the manufacturer's 60% PZEV option for the 2003 model year has through the 2007 model year to fully exercise its option to meet an additional 20% of its ZEV requirement for the 2003 model year with credits from advanced technology PZEVs.~~

(2) *Model Year 2004 ZEV Deficits.* ~~A manufacturer that qualifies under section C.7.7(b)(1), and produces, and delivers for sale in California, model year 2004 or earlier PZEVs that generate at least twice as many credits as are necessary to take full advantage of the manufacturer's 60% PZEV option for the 2003 and 2004 model years, has through the 2008 model~~

~~year to fully exercise its option to meet an additional 20% of its ZEV requirement for the 2004 model year with credits from advanced technology PZEVs.~~

7.8 Penalty for Failure to Meet ZEV Requirements. Any manufacturer that fails to produce and deliver for sale in California the required number of ZEVs or submit an appropriate amount of g/mi ZEV credits and does not make up ZEV deficits within the specified time period shall be subject to the Health and Safety Code section 43211 civil penalty applicable to a manufacturer that sells a new motor vehicle that does not meet the applicable emission standards adopted by the state board. The cause of action shall be deemed to accrue when the ZEV deficits are not balanced by the end of the specified time period. For the purposes of Health and Safety Code section 43211, the number of vehicles not meeting the state board's standards shall be calculated according to the following equation, provided that the percentage of a large volume manufacturer's ZEV requirement for a given model year that may be satisfied with partial ZEV allowance vehicles or ZEV credits from such vehicles may not exceed the percentages permitted under section C.2.1:

$$\frac{(\text{No. of ZEVs required to be produced and delivered for sale in California for the model year}) - (\text{No. of ZEVs produced and delivered for sale in California for the model year}) - (\text{No. of ZEV allowances from partial ZEV allowance vehicles produced and delivered for sale in California for the model year}) - [(\text{Amount of ZEV credits submitted for the model year}) / (\text{the fleet average requirement for PCs and LDT1s for the model-year})]}{(\text{the fleet average requirement for PCs and LDT1s for the model-year})}$$

8. Severability. Each provision of these standards and test procedures is severable, and in the event that any provision of these standards and test procedures is held to be invalid, the remainder of the standards and test procedures remains in full force and effect.

D. Certification Requirements

1. Durability and Emission Testing Requirements. All ZEVs are exempt from all mileage and service accumulation, durability-data vehicle, and emission-data vehicle testing requirements.

2. Information Requirements: Application for Certification. Except as noted below, the Part I (40 CFR § 86.1843-01(c)) certification application shall include the following:

- 2.1 Identification and description of the vehicle(s) covered by the application.
- 2.2 Identification of the vehicle weight category to which the vehicle is certifying: PC, LDT 0-3750 lbs. LVW, LDT 3751-5750 lbs. LVW, LDT 3751 lbs. LVW - 8500 lbs. GVW, or MDV (state test weight range), and the curb weight and gross vehicle weight rating of the vehicle.
- 2.3 Identification and description of the propulsion system for the vehicle.
- 2.4 Identification and description of the climate control system used on the vehicle.
- 2.5 Projected number of vehicles produced and delivered for sale in California, and projected California sales.
- 2.6 Identification of the energy usage in kilowatt-hours per mile from:
 - (a) the battery output (DC energy) (to be submitted with the Part II certification application (40 CFR § 86.1843-01(d));
 - (b) the point when electricity is introduced from the electrical outlet (AC energy); and
 - (c) the operating range in miles of the vehicle when tested in accordance with the All-Electric Range Test set forth in section E, below.
- 2.7 For those ZEVs and HEVs that use fuel-fired heaters, the manufacturer shall provide:
 - (a) a description of the control system logic of the fuel-fired heater, including an evaluation of the conditions under which the fuel-fired heater can be operated and an evaluation of the possible operational modes and conditions under which evaporative emissions can exist;
 - (b) the exhaust emissions value per mile produced by the auxiliary fuel-fired heater operated between 68°F and 86°F; and
 - (c) the test plan which describes the procedure used to determine the mass emissions of the fuel-fired heater.
- 2.8 All information necessary for proper and safe operation of the vehicle, including information on the safe handling of the battery system, emergency procedures to follow in the event of

battery leakage or other malfunctions that may affect the safety of the vehicle operator or laboratory personnel.

2.9 Method for determining battery state-of-charge, battery charging capacity and recharging procedures, and any other relevant information as determined by the Executive Officer.

2.10 Battery specific energy data and calculations as specified in section E.4 of these procedures including the weight of the battery system and the three hour discharge rate (C/3) energy capacity.

2.11 Vehicle and battery break-in period as specified in section E.2 of these test procedures.

2.12 Labeling shall conform with the requirements specified in section 1965, title 13, CCR and the California Motor Vehicle Emission Control and Smog Index Label Specifications.

2.13 For a ZEV, extended range HEV or PZEV that qualifies to receive one or more multipliers under sections C.3 - C.7, the manufacturer shall provide all information relevant to the vehicle's qualification for, and the estimated value of, the multiplier(s). The Executive Officer may request additional information needed to appropriately characterize the vehicle. Based on the submitted information and other relevant data, the Executive Officer shall assign to the vehicle the highest multiplier(s) for which the manufacturer has demonstrated the vehicle qualifies at that time.

2.14 Where a manufacturer plans to require any scheduled maintenance for a PZEV before 150,000 miles, the manufacturer must submit information demonstrating the need for each scheduled maintenance item before 150,000 miles, including actual in-use data, engineering evaluation of the durability of the part, or other relevant information. The manufacturer may require such maintenance for a PZEV only upon the Executive Officer's determination, prior to certification, the manufacturer has demonstrated the need for the scheduled maintenance; this determination may not unreasonably be denied.

3. ZEV Reporting Requirements. In order to verify the status of each manufacturer's compliance with the ZEV requirements for a given calendar year, each manufacturer shall submit a report to the Executive Officer at least annually, by May 1 of the calendar year following the close of the model year, that identifies the necessary delivery and placement data of all vehicles generating ZEV credits or allowances, and all transfers and acquisitions of ZEV credits. The manufacturer may update the report by September 1 to cover activities occurring between April 1 and June 30.

E. Test Procedures

The “as adopted or amended dates” of the 40 CFR Part 86 regulations referenced by this document are the dates identified in the “California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles” incorporated by reference in section 1961(d), title 13, CCR.

1. Electric Dynamometer. All ZEVs must be tested using a 48-inch single roll electric dynamometer meeting the requirements of 40 CFR Subpart B, § 86.108-00(b)(2).

2. Vehicle and Battery Break-In Period. A manufacturer shall use good engineering judgment in determining the proper stabilized emissions mileage test point and report same according to the requirements of section D.2.11 above.

3. All-Electric Range Test. All 2001 and subsequent ZEVs and only off-vehicle charge capable hybrid electric vehicles shall be subject to the All-Electric Range Test specified below for the purpose of determining the energy efficiency and operating range of a ZEV or of an off-vehicle charge capable hybrid electric vehicle operating without the use of its auxiliary power unit. For hybrid electric vehicles, the manufacturer may elect to conduct the All-Electric Range Test prior to vehicle preconditioning in the exhaust and evaporative emission test sequence specified in the “California Evaporative Emission Standards and Test Procedures for 2001 and Subsequent Model Motor Vehicles” as incorporated by reference in section 1976, Title 13, CCR.

3.1 Cold soak. The vehicle shall be stored at an ambient temperature not less than 68°F (20°C) and not more than 86°F (30°C) for 12 to 36 hours. During this time, the vehicle’s battery shall be charged to a full state-of-charge.

3.2 Driving schedule.

3.2.1 Determination of All-Electric Range-Urban.

(a) At the end of the cold soak period, the vehicle shall be placed, either driven or pushed, onto a dynamometer and operated through successive Urban Dynamometer Driving Schedules (UDDS), 40 CFR, Part 86, Appendix I, which is incorporated herein by reference. A 10-minute soak shall follow each UDDS cycle.

(b) For vehicles with a maximum speed greater than or equal to the maximum speed on the UDDS cycle, this test sequence shall be repeated until the vehicle is no longer able to maintain either the speed or time tolerances in 40 CFR § 86.115-00 (b)(1) and (2), or the manufacturer determines that the test should be terminated for safety reasons, e.g. excessively high battery temperature, abnormally low battery voltage, etc. For off-vehicle charge capable hybrid electric vehicles, this determination shall be performed without the use of the auxiliary power unit.

(c) For vehicles with a maximum speed less than the maximum speed on the UDDS cycle, the vehicle shall be operated at maximum available power (or full throttle) when the vehicle cannot achieve the speed trace within the speed and time tolerances specified in 40 CFR § 86.115-00(b)(1) and (2). The test shall be terminated when the vehicle speed when operated at maximum available power (or full throttle) falls below 95 percent of the maximum speed initially achieved on the UDDS cycle or when the battery state-of-charge is depleted to the lowest level allowed by the manufacturer, or the manufacturer determines that the test should be terminated for safety reasons, e.g. excessively high battery temperature, abnormally low battery voltage, etc., whichever occurs first. For off-vehicle charge capable hybrid electric vehicles, this determination shall be performed without the use of the auxiliary power unit.

3.2.2 Determination of All-Electric Range-Highway.

(a) At the end of the cold soak period, the vehicle shall be placed, either driven or pushed, onto a dynamometer and operated through two successive Highway Fuel Economy Driving Schedules (HFEDS), 40 CFR, Part 600, Appendix I, which is incorporated herein by reference. There shall be a 15 second zero speed with key on and brake depressed between two cycles and a 10-minute soak following the two HFEDS cycles.

(b) For vehicles with a maximum speed greater than or equal to the maximum speed on the HFEDS cycle, this test sequence shall be repeated until the vehicle is no longer able to maintain either the speed or time tolerances in 40 CFR § 86.115-00 (b)(1) and (2), or the manufacturer determines that the test should be terminated for safety reasons, e.g. excessively high battery temperature, abnormally low battery voltage, etc. For off-vehicle charge capable hybrid electric vehicles, this determination is optional and shall be performed without the use of the auxiliary power unit.

(c) For vehicles with a maximum speed less than the maximum speed on the HFEDS cycle, the vehicle shall be operated at maximum available power (or full throttle) when the vehicle cannot achieve the speed trace within the speed and time tolerances specified in 40 CFR § 86.115-00(b)(1) and (2). The test shall be terminated when the vehicle speed when operated at maximum available power (or full throttle) falls below 95 percent of the maximum speed initially achieved on the HFEDS cycle or when the battery state-of-charge is depleted to the lowest level allowed by the manufacturer, or the manufacturer determines that the test should be terminated for safety reasons, e.g. excessively high battery temperature, abnormally low battery voltage, etc., whichever occurs first. For off-vehicle charge capable hybrid electric vehicles, this determination shall be performed without the use of the auxiliary power unit.

(d) NEVs are exempt from the all-electric range highway test.

3.2.3 Recording requirements. Once the vehicle is no longer able to maintain the speed and time requirements specified in (2) above, or once the auxiliary power unit turns on, in the case of an off-vehicle charge capable hybrid electric vehicle, the vehicle shall be brought to an immediate stop and the following data recorded:

- (a) mileage accumulated during the All-Electric Range Test;
- (b) Net DC energy from the battery that was expended during the All-Electric Range Test (may be reported as the total DC battery energy output and the total DC battery energy input during the All-Electric Range Test);
- (c) AC energy required to fully charge the battery after the All-Electric Range Test from the point where electricity is introduced from the electric outlet to the battery charger; and
- (d) DC energy required to fully charge the battery after the All-Electric Range Test from the point where electricity is introduced from the battery charger to the battery.

Battery charging shall begin within 1 hour after terminating the All-Electric Range Test.

3.2.4 Regenerative braking. Regenerative braking systems may be utilized during the range test. The braking level, if adjustable, shall be set according to the manufacturer's specifications prior to the commencement of the test. The driving schedule speed and time tolerances specified in (2) shall not be exceeded due to the operation of the regenerative braking system.

4. Determination of Battery Specific Energy for ZEVs

Determine the specific energy of batteries used to power a ZEV in accordance with the U.S. Advanced Battery Consortium's Electric Vehicle Battery Procedure Manual (January 1996), Procedure No. 2, "Constant Current Discharge Test Series," using the C/3 rate. The weight calculation must reflect a completely functional battery system as defined in the Appendix of the Manual, including pack(s), required support ancillaries (e.g., thermal management), and electronic controller.

5. Determination of the Emissions of the Fuel-fired Heater

The exhaust emissions result of the fuel-fired heater shall be determined by operating at a maximum heating capacity with a cold start between 68°F and 86°F for a period of 20 minutes and dividing the grams of emissions by 20. The resulting grams per minute shall be multiplied by 3.0 minutes per mile for a grams per mile value.

6. Hybrid Electric Vehicle FTP Emission Test Provisions

Alternative procedures may be used if shown to yield equivalent results and if approved in advance by the Executive Officer of the Air Resources Board.

6.1 Vehicle Preconditioning

To be conducted pursuant to the "California Evaporative Emission Standards and Test Procedures for 2001 and Subsequent Model Motor Vehicles" as incorporated by reference herein with the following supplemental requirements:

6.1.1 Battery state-of-charge shall be set prior to initial fuel drain and fill before vehicle preconditioning.

6.1.2 For hybrid electric vehicles that do not allow manual activation of the auxiliary power unit, battery state-of-charge shall be set at a level that causes the hybrid electric vehicle to operate the auxiliary power unit for the maximum possible cumulative amount of time during the preconditioning drive.

6.1.3 For hybrid electric vehicles that allow manual activation of the auxiliary power unit, battery state-of-charge shall be set at a level that satisfies one of the following conditions:

- (i) If the hybrid electric vehicle is charge-sustaining over the UDDS, battery state-of-charge shall be set at the lowest level allowed by the manufacturer.
- (ii) If the hybrid electric vehicle is charge-depleting over the UDDS, battery state-of-charge shall be set at the level recommended by the manufacturer for activating the auxiliary power unit when operating in urban driving conditions.

6.1.4 After setting battery state-of-charge, the hybrid electric vehicle shall be pushed or towed to a work area for fuel drain and fill according to sections D.1.1. and D.1.2. of the “California Evaporative Emission Standards and Test Procedures for 2001 and Subsequent Model Motor Vehicles” as incorporated by reference herein.

6.1.5 Following fuel drain and fill, the vehicle shall be pushed or towed into position on a dynamometer and preconditioned. If the auxiliary power unit is capable of being manually activated, the auxiliary power unit shall be manually activated at the beginning of and operated throughout the preconditioning drive.

6.1.6 Within five minutes of completing preconditioning drive, battery state-of-charge shall be set at a level that satisfies one of the following conditions:

- (i) If the hybrid electric vehicle does not allow manual activation of the auxiliary power unit and is charge-sustaining over the UDDS, then set battery state-of-charge to a level such that the SOC Criterion (see section B., Definitions, of these procedures) would be satisfied for the dynamometer procedure (section 6.2 of these procedures). If off-vehicle charging is required to increase battery state-of-charge for proper setting, off-vehicle charging shall occur during 12 to 36 hour soak period.
- (ii) If the hybrid electric vehicle does not allow manual activation of the auxiliary power unit and is charge-depleting over the UDDS, then no battery state-of-charge adjustment is permissible.

(iii) If the hybrid electric vehicle does allow manual activation of the auxiliary power unit, then set battery state-of-charge to manufacturer recommended level for activating the auxiliary power unit when the hybrid electric vehicle is operating in urban driving conditions.

6.2 Dynamometer Procedure

To be conducted pursuant to 40 CFR § 86.135-00 with the following revisions:

6.2.1 Amend subparagraph (a): Overview. The dynamometer run consists of two tests, a “cold” start test, after a minimum 12-hour and a maximum 36-hour soak pursuant to the provisions of the “California Evaporative Emission Standards and Test Procedures for 2001 and Subsequent Model Motor Vehicles” as incorporated by reference herein, and a “hot” start test following the “cold” start test by 10 minutes. Vehicle startup (with all accessories turned off), operation over the UDDS and vehicle shutdown make a complete cold start test. Vehicle startup and operation over the UDDS and vehicle shutdown make a complete hot start test. The exhaust emissions are diluted with ambient air in the dilution tunnel as shown in Figure B94-5 and Figure B94-6. A dilution tunnel is not required for testing vehicles waived from the requirement to measure particulates. Four particulate samples are collected on filters for weighing; the first sample plus backup is collected during the cold start test (including shutdown); the second sample plus backup is collected during the hot start test (including shutdown). Continuous proportional samples of gaseous emissions are collected for analysis during each test. For hybrid electric vehicles with gasoline-fueled, natural gas-fueled and liquefied petroleum gas-fueled Otto-cycle auxiliary power units, the composite samples collected in bags are analyzed for THC, CO, CO₂, CH₄ and NO_x. For hybrid electric vehicles with petroleum-fueled diesel-cycle auxiliary power units (optional for natural gas-fueled, liquefied petroleum gas-fueled and methanol-fueled diesel-cycle vehicles), THC is sampled and analyzed continuously pursuant to the provisions of § 86.110. Parallel samples of the dilution air are similarly analyzed for THC, CO, CO₂, CH₄ and NO_x. For hybrid electric vehicles with natural gas-fueled, liquefied petroleum gas-fueled and methanol-fueled auxiliary power units, bag samples are collected and analyzed for THC (if not sampled continuously), CO, CO₂, CH₄ and NO_x. For hybrid electric vehicles with methanol-fueled auxiliary power units, methanol and formaldehyde samples are taken for both exhaust emissions and dilution air (a single dilution air formaldehyde sample, covering the total test period may be collected). Parallel bag samples of dilution air are analyzed for THC, CO, CO₂, CH₄ and NO_x.

6.2.2 Delete subparagraph (d).

6.2.3 Amend subparagraph (h): The driving distance, as measured by counting the number of dynamometer roll or shaft revolutions, shall be determined for the cold start test and hot start test. The revolutions shall be measured on the same roll or shaft used for measuring the vehicle’s speed.

6.3 Dynamometer Test Run, Gaseous and Particulate Emissions

To be conducted pursuant to 40 CFR § 86.137-96 with the following revisions:

6.3.1 Amend subparagraph (a): General. The dynamometer run consists of two tests, a cold start test, after a minimum 12-hour and a maximum 36-hour soak pursuant to the provisions of the “California Evaporative Emission Standards and Test Procedures for 2001 and Subsequent Model Motor Vehicles” as incorporated by reference herein, and a hot start test following the cold start test by 10 minutes. The vehicle shall be stored prior to the emission test in such a manner that precipitation (e.g., rain or dew) does not occur on the vehicle. The complete dynamometer test consists of a cold start drive of 7.5 miles (12.1 km) and a hot start drive of 7.5 miles (12.1 km). The vehicle is allowed to stand on the dynamometer during the 10 minute time period between the cold and hot start tests.

6.3.2 Amend subparagraph (b)(9): Start the gas flow measuring device, position the sample selector valves to direct the sample flow into the exhaust sample bag, the methanol exhaust sample, the formaldehyde exhaust sample, the dilution air sample bag, the methanol dilution air sample and the formaldehyde dilution air sample (turn on the petroleum-fueled diesel-cycle THC analyzer system integrator, mark the recorder chart, start particulate sample pump No. 1, and record both gas meter or flow measurement instrument readings, if applicable), and turn the key on. If the auxiliary power unit is capable of being manually activated, the auxiliary power unit shall be activated at the beginning of and operated throughout the UDSS.

6.3.2 Delete subparagraph (13).

6.3.3 Amend subparagraph (14): Turn the vehicle off 2 seconds after the end of the last deceleration (at 1,369 seconds).

6.3.4 Amend subparagraph (15): Five seconds after the vehicle is shutdown, simultaneously turn off gas flow measuring device No. 1 and if applicable, turn off the hydrocarbon integrator No. 1, mark the hydrocarbon recorder chart, turn off the No. 1 particulate sample pump and close the valves isolating particulate filter No. 1, and position the sample selector valves to the “standby” position. Record the measured roll or shaft revolutions (both gas meter or flow measurement instrumentation readings), and reset the counter. As soon as possible, transfer the exhaust and dilution air samples to the analytical system and process the samples pursuant to § 86.140, obtaining a stabilized reading of the exhaust bag sample on all analyzers within 20 minutes of the end of the sample collection phase of the test. Obtain methanol and formaldehyde sample analyses, if applicable, within 24 hours of the end of the sample period. (If it is not possible to perform analysis on the methanol and formaldehyde samples within 24 hours, the samples should be stored in a dark cold (4°C to 10°C) environment until analysis. The samples should be analyzed within fourteen days.) If applicable,

carefully remove both pairs of particulate sample filters from their respective holders, and place each in a separate petri dish, and cover.

6.3.3 Amend subparagraph (18): Repeat the steps in paragraphs (b)(2) through (b)(17) of this section for the hot start test. The step in paragraph (b)(9) of this section shall begin between 9 and 11 minutes after the end of the sample period for the cold start test.

6.3.4 Delete subparagraph (19).

6.3.5 Delete subparagraph (20).

6.3.6 Amend subparagraph (21): As soon as possible, and in no case longer than one hour after the end of the hot start phase of the test, transfer the four particulate filters to the weighing chamber for post-test conditioning, if applicable. For hybrid electric vehicles that do not allow manual activation of the auxiliary power unit and are charge-sustaining over the UDDS, a valid test shall satisfy the SOC Criterion (see Definitions, section B of these procedures).

6.3.7 Amend subparagraph (24): Vehicles to be tested for evaporative emissions will proceed pursuant to the "California Evaporative Emission Standards and Test Procedures for 2001 and Subsequent Model Motor Vehicles" as incorporated by reference herein.

6.4 Calculations - Exhaust Emissions

To be conducted pursuant to 40 CFR § 86.144-94 with the following revisions:

6.4.1 Amend subparagraph (a): For light-duty vehicles and light duty trucks:

$$Y_{wm} = 0.43 * \frac{Y_c}{D_c} + 0.57 * \frac{Y_h}{D_h}$$

Where:

(1) Y_{wm} = Weighted mass emissions of each pollutant, i.e., THC, CO, THCE, NMHC, NMHCE, CH₄, NO_x, or CO₂, in grams per vehicle mile.

(2) Y_c = Mass emissions as calculated from the cold start test, in grams per test.

(3) Y_h = Mass emissions as calculated from the hot start test, in grams per test.

(4) D_c = The measured driving distance from the cold start test, in miles.

(5) D_h = The measured driving distance from the hot start test, in miles.

6.5 Calculations - Particulate Emissions

To be conducted pursuant to 40 CFR § 86.145-82 with the following revisions:

6.5.1 Amend subparagraph (a): The final reported test results for the mass particulate (M_p) in grams/mile shall be computed as follows:

$$M_p = 0.43 * \frac{M_{pc}}{D_c} + 0.57 * \frac{M_{ph}}{D_h}$$

Where:

- (1) M_{pc} = Mass of particulate determined from the cold start test, in grams per vehicle mile. (See § 86.110-94 for determination.)
- (2) M_{ph} = Mass of particulate determined from the hot start test, in grams per vehicle mile. (See § 86.110-94 for determination.)
- (3) D_c = The measured driving distance from the cold start test, in miles.
- (4) D_h = The measured driving distance from the hot start test, in miles.

7. Hybrid Electric Vehicle Highway Emission Test Provisions

To be conducted pursuant to 40 CFR § 600.111-93 with the following revisions:

7.1 Amend subparagraph (b)(2): The highway fuel economy test is designated to simulate non-metropolitan driving with an average speed of 48.6 mph and a maximum speed of 60 mph. The cycle is 10.2 miles long with 0.2 stop per mile and consists of warmed-up vehicle operation on a chassis dynamometer through a specified driving cycle. A proportional part of the diluted exhaust emission is collected continuously for subsequent analysis of THC, CO, CO₂, and NO_x using a constant volume (variable dilution) sampler. Diesel dilute exhaust is continuously analyzed for hydrocarbons using a heated sample line and analyzer. Methanol and formaldehyde samples are collected and individually analyzed for methanol-fueled vehicles.

7.2 Amend subparagraph (f)(3): Only one exhaust sample and one background sample are collected and analyzed for THC (except diesel hydrocarbons which are analyzed continuously), CO, CO₂, and NO_x. Methanol and formaldehyde samples (exhaust and dilution air) are collected and analyzed for methanol-fueled vehicles.

7.3 Add subparagraph (f)(5): Battery state-of-charge shall be set prior to performing the HFEDS preconditioning cycle. For hybrid electric vehicles that do not allow manual activation of the auxiliary power unit, battery state-of-charge shall be set at a level that causes the hybrid electric vehicle to operate the auxiliary power unit for the maximum possible cumulative amount of time during the HFEDS preconditioning cycle. For hybrid electric vehicles that allow manual activation of the auxiliary power unit, battery state-of-charge shall be set at a level that satisfies one of the following conditions:

(i) If the hybrid electric vehicle is charge-sustaining over the HFEDS, battery state-of-charge shall be set at the lowest level allowed by the manufacturer.

(ii) If the hybrid electric vehicle is charge-depleting over the HFEDs, battery state-of-charge shall be set at the level recommended by the manufacturer for activating the auxiliary power unit when operating in highway driving conditions.

7.4 Amend subparagraph (h)(5): Operate the vehicle over one HFEDS preconditioning cycle according to the dynamometer driving schedule specified in ?600.109(b). If the auxiliary power unit is capable of being manually activated, the auxiliary power unit shall be manually activated at the beginning of and operated throughout the HFEDS preconditioning cycle.

7.5 Amend subparagraph (h)(6): When the vehicle reaches zero speed at the end of the HFEDS preconditioning cycle, the driver has 17 seconds to prepare for the HFEDS emission measurement cycle of the test. Reset and enable the roll revolution counter. During the idle period, one of the following conditions shall apply:

(i) For hybrid electric vehicles that do not allow the auxiliary power unit to be manually activated and are charge-sustaining over the HFEDS, the vehicle shall be momentarily turned off for 5 seconds and turned back on during the idle period. The battery state-of-charge shall be recorded after the hybrid electric vehicle has fully turned on.

(ii) For hybrid electric vehicles that do not allow the auxiliary power unit to be manually activated and are charge-depleting over the HFEDS, the vehicle shall remain turned on during the idle period.

(iii) For hybrid electric vehicles that allow the auxiliary power unit to be manually activated, the vehicle shall remain turned on with the auxiliary power unit operating during the idle period.

7.6 Add subparagraph (h)(9): At the conclusion of the HFEDS emission test, one of the following conditions shall apply:

(i) For hybrid electric vehicles that do not allow the auxiliary power unit to be manually activated and are charge-sustaining over the HFEDS, record the battery state-of-charge to determine if the SOC Criterion (see Definitions, section B of these procedures) is satisfied. If the SOC Criterion is not satisfied, then repeat dynamometer test run from subparagraph (h)(6). A total of three highway emission tests shall be allowed to satisfy the SOC Criterion. Manufacturers may elect to repeat dynamometer test run from subparagraph (h)(6) if battery energy level increased significantly relative to the initial battery state-of-charge set at the beginning of the HFEDS emission test.

(ii) For hybrid electric vehicles that do not allow the auxiliary power unit to be manually activated and are charge-depleting over the HFEDS, the emission test is completed.

(iii) For hybrid electric vehicles that allow the auxiliary power unit to be manually activated, the emission test is completed.

8. Hybrid Electric Vehicle SFTP Emission Test Provisions

8.1 US06 Vehicle Preconditioning

To be conducted pursuant to 40 CFR § 86.132-00 with the following revisions:

8.1.1 Amend subparagraph (n): Aggressive Driving Test (US06) Preconditioning. (1) If the US06 test follows the exhaust emission FTP or evaporative testing, the refueling step may be deleted and the vehicle may be preconditioned using the fuel remaining in the tank (see paragraph (c)(2)(ii) of this section). The test vehicle may be pushed or driven onto the test dynamometer provided that battery state-of-charge has not been set; otherwise, if battery state-of-charge is set prior to securing vehicle on dynamometer, vehicle shall be pushed or towed into position on dynamometer. Battery state-of-charge shall be set prior to performing the US06 preconditioning cycle. For hybrid electric vehicles that do not allow manual activation of the auxiliary power unit, battery state-of-charge shall be set at a level that causes the hybrid electric vehicle to operate the auxiliary power unit for the maximum possible cumulative amount of time during the US06 preconditioning drive. For hybrid electric vehicles that allow manual activation of the auxiliary power unit, battery state-of-charge shall be set at a level that satisfies one of the following conditions:

(i) If the hybrid electric vehicle is charge-sustaining over the US06, battery state-of-charge shall be set at the lowest level allowed by the manufacturer. The auxiliary power unit shall be manually activated at the beginning of and operated throughout the US06 preconditioning cycle.

(ii) If the hybrid electric vehicle is charge-depleting over the US06, battery state-of-charge shall be set at the level recommended by the manufacturer for activating the auxiliary power unit when operating in highway driving conditions. The auxiliary power unit shall be manually activated at the beginning of and operated throughout the US06 preconditioning cycle.

8.1.2 Delete subparagraphs (n)(1)(i) and (n)(1)(ii).

8.2 US06 Emission Test

To be conducted pursuant to 40 CFR § 86.159-00 with the following revisions:

8.2.1 Amend subparagraph (a): Overview. The dynamometer operation consists of a single, 600 second test on the US06 driving schedule, as described in appendix I, paragraph (g), of this part. The hybrid electric vehicle is preconditioned in accordance with § 86.132-00, to bring it to a warmed-up stabilized condition. This preconditioning is followed by a 1 to 2 minute idle period that proceeds directly into the US06 driving schedule during which continuous proportional samples of gaseous emissions are collected for analysis. If engine stalling should occur during testing, follow the provisions of § 86.136-90 (engine starting and restarting). For hybrid electric vehicles with gasoline-fueled Otto-cycle auxiliary power units, the composite samples collected in bags are analyzed for THC, CO, CO₂, CH₄ and NO_x. For hybrid electric vehicles with petroleum-fueled diesel-cycle auxiliary power units, THC is sampled and analyzed continuously according to the provisions of § 86.110. Parallel bag samples of dilution air are analyzed for THC, CO, CO₂, CH₄ and NO_x.

8.2.2 Amend subparagraph (b)(2): Position (vehicle shall be pushed or towed if battery state-of-charge is set prior to securing to dynamometer otherwise vehicle may be driven as well) the test vehicle on the dynamometer and restrain.

8.2.3 Amend subparagraph (d): Practice runs over the prescribed driving schedule may be performed at test point, provided that battery state-of-charge setting is conducted after practice and an emission sample is not taken, for the purpose of finding the appropriate throttle action to maintain the proper speed-time relationship, or to permit sampling system adjustment.

8.2.4 Amend subparagraph (f)(2)(i): Immediately after completion of the US06 preconditioning cycle, idle the vehicle. The idle period is not to be less than one minute or not greater than two minutes. During the idle period, one of the following conditions shall apply:

(i) For hybrid electric vehicles that do not allow the auxiliary power unit to be manually activated and are charge-sustaining over the US06, the vehicle shall be momentarily turned off for 5 seconds and turned back on during the idle period. The battery state-of-charge shall be recorded after the hybrid electric vehicle has fully turned on.

(ii) For hybrid electric vehicles that do not allow the auxiliary power unit to be manually activated and are charge-depleting over the US06, the vehicle shall remain turned on during the idle period.

(iii) For hybrid electric vehicles that allow the auxiliary power unit to be manually activated, the vehicle shall remain turned on with the auxiliary power unit operating during the idle period.

8.2.5 Amend subparagraph (f)(2)(ix): At the conclusion of the US06 emission test, one of the following conditions shall apply:

(i) For hybrid electric vehicles that do not allow manual activation of the auxiliary power unit and are charge-sustaining over the US06, record the battery state-of-charge to determine if the SOC Criterion (see Definitions, section B of these procedures) is satisfied. If the SOC Criterion is not satisfied, then repeat dynamometer test run from subparagraph (f)(2)(i). A total of three US06 emission tests shall be allowed to satisfy the SOC Criterion. Manufacturers may elect to repeat dynamometer test run from subparagraph (f)(2)(i) if battery energy level increased significantly relative to the initial battery state-of-charge set at the beginning of US06 emission test.

(ii) For hybrid electric vehicles that do not allow the auxiliary power unit to be manually activated and are charge-depleting over the US06, turn off vehicle 2 seconds after the end of the last deceleration.

(iii) For hybrid electric vehicles that allow the auxiliary power unit to be manually activated, turn off vehicle 2 seconds after the end of the last deceleration.

8.3 SC03 Vehicle Preconditioning

To be conducted pursuant to 40 CFR § 86.132-00 with the following revisions:

8.3.1 Amend subparagraph (o): Air Conditioning Test (SC03) Preconditioning. (1) If the SC03 test follows the exhaust emission FTP or evaporative testing, the refueling step may be deleted and the vehicle may be preconditioned using the fuel remaining in the tank (see paragraph (c)(2)(ii) of this section). The test vehicle may be pushed or driven onto the test dynamometer provided that battery state-of-charge has not been set; otherwise, if battery state-of-charge is set prior to securing vehicle on dynamometer, vehicle shall be pushed or towed into position on dynamometer. Battery state-of-charge shall be set prior to performing the SC03 preconditioning cycle. For hybrid electric vehicles that do not allow manual activation of the auxiliary power unit, battery state-of-charge shall be set at a level that causes the hybrid electric vehicle to operate the auxiliary power unit for the maximum possible cumulative amount of time during the SC03 preconditioning drive. For hybrid electric vehicles that allow manual activation of the auxiliary power unit, battery state-of-charge shall be set at a level that satisfies one of the following conditions:

(i) If the hybrid electric vehicle is charge-sustaining over the SC03, battery state-of-charge shall be set at the lowest level allowed by the manufacturer. The auxiliary power unit shall be manually activated at the beginning of and operated throughout the SC03 preconditioning cycle.

(ii) If the hybrid electric vehicle is charge-depleting over the SC03, battery state-of-charge shall be set at the level recommended by the manufacturer for activating the auxiliary power unit when operating in highway driving conditions. The auxiliary power unit shall be manually activated at the beginning of and operated throughout the SC03 preconditioning cycle.

8.3.2 Delete subparagraphs (o)(1)(i) and (o)(1)(ii).

8.4 SC03 Emission Test

To be conducted pursuant to 40 CFR § 86.160-00 with the following revisions:

8.4.1 Amend subparagraph (a): Overview. The dynamometer operation consists of a single, 594 second test on the SC03 driving schedule, as described in appendix I, paragraph (h), of this part. The hybrid electric vehicle is preconditioned in accordance with § 86.132-00 of this subpart, to bring the vehicle to a warmed-up stabilized condition. This preconditioning is followed by a 10 minute vehicle soak (vehicle turned off) that proceeds directly into the SC03 driving schedule, during which continuous proportional samples of gaseous emissions are collected for analysis. The entire test, including the SC03 preconditioning cycle, vehicle soak, and SC03 emission test, is either conducted in an environmental test facility or under test conditions that simulates testing in an environmental test cell (see Sec. 86.162-00 (a) for a discussion of simulation procedure approvals). The environmental test facility must be capable of providing the following nominal ambient test conditions of: 95°F air temperature, 100 grains of water/pound of dry air (approximately 40 percent relative humidity), a solar heat load intensity of 850 W/m², and vehicle cooling air flow proportional to vehicle speed. Section 86.161-00 discusses the minimum facility requirements and corresponding control tolerances for air conditioning ambient test conditions. The vehicle's air conditioner is operated or appropriately simulated for the duration of the test procedure (except for the 10 minute vehicle soak), including the preconditioning. If engine stalling should occur during testing, follow the provisions of § 86.136-90 (engine starting and restarting). For hybrid electric vehicles with gasoline-fueled Otto-cycle auxiliary power units, the composite samples collected in bags are analyzed for THC, CO, CO₂, CH₄ and NO_x. For hybrid electric vehicles with petroleum-fueled diesel-cycle auxiliary power units, THC is sampled and analyzed continuously according to the provisions of § 86.110. Parallel bag samples of dilution air are analyzed for THC, CO, CO₂, CH₄ and NO_x.

8.4.2 Amend subparagraph (b)(2): Position (vehicle shall be pushed or towed if battery state-of-charge is set prior to securing to dynamometer otherwise vehicle may be driven as well) the test vehicle on the dynamometer and restrain.

8.4.3 Amend subparagraph (c)(9): Start vehicle (with air conditioning system also running). If the auxiliary power unit of the hybrid electric vehicle is capable of being manually activated, the auxiliary power unit shall be manually activated at the beginning of and operated

throughout the SC03 emission test. Fifteen seconds after the vehicle starts, begin the initial vehicle acceleration of the driving schedule.

8.4.4 Amend subparagraph (c)(12): Turn the vehicle off 2 seconds after the end of the last deceleration.

8.4.5 Amend subparagraph (d)(7): Start vehicle (with air conditioning system also running). If the auxiliary power unit of the hybrid electric vehicle is capable of being manually activated, the auxiliary power unit shall be manually activated at the beginning of and operated throughout the SC03 emission test. Fifteen seconds after the vehicle starts, begin the initial vehicle acceleration of the driving schedule.

8.4.6 Amend subparagraph (d)(10): At the conclusion of the US06 emission test, one of the following conditions shall apply:

(i) For hybrid electric vehicles that do not allow the auxiliary power unit to be manually activated and are charge-sustaining over the SC03, record the battery state-of-charge to determine if the SOC Criterion (see Definitions, section B of these procedures) is satisfied. If the SOC Criterion is not satisfied, then turn off cooling fan(s), allow vehicle to soak in the ambient conditions of paragraph (c)(5) of this section for 10 minutes, and repeat dynamometer test run from subparagraph (d). A total of three SC03 emission tests shall be attempted to satisfy the SOC Criterion. Manufacturers may elect to repeat dynamometer test run from subparagraph (d) following a 10 minute soak in the ambient conditions of paragraph (c)(5) of this section if battery energy level increased significantly relative to the initial battery state-of-charge set at the beginning of SC03 emission test.

(ii) For hybrid electric vehicles that do not allow the auxiliary power unit to be manually activated and are charge-depleting over the SC03, turn off vehicle 2 seconds after the end of the last deceleration.

(iii) For hybrid electric vehicles that allow the auxiliary power unit to be manually activated, turn off vehicle 2 seconds after the end of the last deceleration.

9. State-of-Charge Net Change Tolerances

9.1 For hybrid electric vehicles that use a battery as an energy storage device, the following state-of-charge net change tolerance shall apply:

$$(\text{Amp-hr}_{\text{final}})_{\text{max}} = (\text{Amp-hr}_{\text{initial}}) + 0.01 * \frac{(\text{NHV}_{\text{fuel}} * m_{\text{fuel}})}{(\text{V}_{\text{system}} * K_1)}$$

$$(\text{Amp-hr}_{\text{final}})_{\text{min}} = (\text{Amp-hr}_{\text{initial}}) - 0.01 * \frac{(\text{NHV}_{\text{fuel}} * m_{\text{fuel}})}{(\text{V}_{\text{system}} * K_1)}$$

Where:

(Amp-hr_{final})_{max} = Maximum allowed Amp-hr stored in battery at the end of the test
 (Amp-hr_{final})_{min} = Minimum allowed Amp-hr stored in battery at the end of the test
 (Amp-hr_{initial}) = Battery Amp-hr stored at the beginning of the test

NHV_{fuel} = Net heating value of consumable fuel, in Joules/kg

m_{fuel} = Total mass of fuel consumed during test, in kg

K₁ = Conversion factor, 3600 seconds/hour

V_{system} = Battery DC bus voltage (open circuit)

9.2 For hybrid electric vehicles that use a capacitor as an energy storage device, the following state-of-charge net change tolerance shall apply:

$$(\text{V}_{\text{final}})_{\text{max}} = \frac{\sqrt{(\text{V}_{\text{initial}})^2 + 0.01 * \frac{(2 * \text{NHV}_{\text{fuel}} * m_{\text{fuel}})}{\text{C}}}}{\text{V}}$$

$$(\text{V}_{\text{final}})_{\text{min}} = \frac{\sqrt{(\text{V}_{\text{initial}})^2 - 0.01 * \frac{(2 * \text{NHV}_{\text{fuel}} * m_{\text{fuel}})}{\text{C}}}}{\text{V}}$$

Where:

(V_{final})_{max} = The stored capacitor voltage allowed at the end of the test

(V_{final})_{min} = The stored capacitor voltage allowed at the end of the test

(V_{initial})² = The square of the capacitor voltage stored at the beginning of the test

NHV_{fuel} = Net heating value of consumable fuel, in Joules/kg

m_{fuel} = Total mass of fuel consumed during test, in kg

C = Rated capacitance of the capacitor, in Farads

9.3 For hybrid electric vehicles that use an electro-mechanical flywheel as an energy storage device, the following state-of-charge net change tolerance shall apply:

$$(\text{rpm}_{\text{final}})_{\text{max}} = \frac{\sqrt{(\text{rpm}_{\text{initial}})^2 + 0.01 * \frac{(2 * \text{NHV}_{\text{fuel}} * m_{\text{fuel}})}{(1 * K_3)}}}{V}$$

$$(\text{rpm}_{\text{final}})_{\text{min}} = \frac{\sqrt{(\text{rpm}_{\text{initial}})^2 - 0.01 * \frac{(2 * \text{NHV}_{\text{fuel}} * m_{\text{fuel}})}{(1 * K_3)}}}{V}$$

Where:

$(\text{rpm}_{\text{final}})_{\text{max}}$	=	The maximum flywheel rotational speed allowed at the end of the test
$(\text{rpm}_{\text{final}})_{\text{min}}$	=	The minimum flywheel rotational speed allowed at the end of the test
$(\text{rpm}_{\text{initial}})^2$	=	The squared flywheel rotational speed at the beginning of the test
NHV_{fuel}	=	Net heating value of consumable fuel, in Joules/kg
m_{fuel}	=	Total mass of fuel consumed during test, in kg
K_3	=	Conversion factor, $4\pi^2/(3600 \text{ sec}^2\text{-rpm}^2)$
I	=	Rated moment of inertia of the flywheel, in kg-m^2