

EQUATION 35

$$CVTS = 0.0042870077 \times DBH^{2.33631} \times HT^{0.74872} \quad (1)$$

$$CV4 = 0.0009684363 \times DBH^{2.39565} \times HT^{0.98878} \quad (2)$$

$$CV8 = 0.0001880044 \times DBH^{1.87346} \times HT^{1.62443} \quad (3)$$

$$CVT = CVTS * RTS \quad (4)$$

$$RTS = 0.9679 - 0.1051 \times 0.5523^{(DBH-1.5)} \quad (4)$$

$$CV4X = CVT \times \left(0.99875 - \frac{43.336}{DBH^3} - \frac{124.717}{DBH^4} + \frac{(0.193437 \times HT)}{DBH^3} + \frac{479.83}{(DBH^3 \times HT)} \right) \quad (5)$$

$$TARIF = \frac{(CV8 \times 0.912733)}{\left((0.983 - 0.983 \times 0.65^{(DBH-8.6)}) \times (BA - 0.087266) \right)} \quad (6)$$

WHERE:

DBH = DBH(CM) CONVERTED TO INCHES (DBH/2.54)

HT = HT (M) CONVERTED TO FEET (HT/0.3048)

BA = BASAL AREA (DBH IN INCHES) BA= .005454154 x DBH²

CVTS = CUBIC FOOT VOLUME, TOTAL STEM, WITH TOP AND STUMP

TARIF = TARIF NUMBER EQUATION

CVT = CUBIC FOOT VOLUME ABOVE STUMP

CV4 = CUBIC FOOT VOLUME, 4-IN TOP

CV8 = CUBIC FOOT VOLUME, SAWLOG (8-IN TOP)

EQUATION 36

$$CVTS = 0.0191453191 \times DBH^{2.40248} \times HT^{0.28060} \quad (1)$$

$$CV4 = 0.0053866353 \times DBH^{2.61268} \times HT^{0.31103} \quad (2)$$

$$CV8 = CV4 \quad (3)$$

$$CVT = CVTS * RTS \quad (4)$$

$$RTS = 0.9679 - 0.1051 \times 0.5523^{(DBH-1.5)} \quad (4)$$

$$CV4X = CVT \times \left(0.99875 - \frac{43.336}{DBH^3} - \frac{124.717}{DBH^4} + \frac{(0.193437 \times HT)}{DBH^3} + \frac{479.83}{(DBH^3 \times HT)} \right) \quad (5)$$

$$TARIF = \frac{(CV8 \times 0.912733)}{\left((0.983 - 0.983 \times 0.65^{(DBH-8.6)}) \times (BA - 0.087266) \right)} \quad (6)$$

WHERE:

DBH = DBH(CM) CONVERTED TO INCHES (DBH/2.54)

HT = HT (M) CONVERTED TO FEET (HT/0.3048)

BA = BASAL AREA (DBH IN INCHES) BA = .005454154 x DBH²

CVTS = CUBIC FOOT VOLUME, TOTAL STEM, WITH TOP AND STUMP

TARIF = TARIF NUMBER EQUATION

CVT = CUBIC FOOT VOLUME ABOVE STUMP

CV4 = CUBIC FOOT VOLUME, 4-IN TOP

CV8 = CUBIC FOOT VOLUME, SAWLOG (8-IN TOP)

EQUATION 37

$$CVTS = 0.0101786350 \times DBH^{2.22462} \times HT^{0.57561} \quad (1)$$

$$CV4 = 0.0034214162 \times DBH^{2.35347} \times HT^{0.69586} \quad (2)$$

$$CV8 = 0.0004236332 \times DBH^{2.10316} \times HT^{1.08584} \times FC^{0.40017} \quad (3)$$

$$CVT = CVTS * RTS \quad (4)$$

$$RTS = 0.9679 - 0.1051 \times 0.5523^{(DBH-1.5)} \quad (4)$$

$$CV4X = CVT \times \left(0.99875 - \frac{43.336}{DBH^3} - \frac{124.717}{DBH^4} + \frac{(0.193437 \times HT)}{DBH^3} + \frac{479.83}{(DBH^3 \times HT)} \right) \quad (5)$$

$$TARIF = \frac{(CV8 \times 0.912733)}{\left((0.983 - 0.983 \times 0.65^{(DBH-8.6)}) \times (BA - 0.087266) \right)} \quad (6)$$

WHERE:

DBH= DBH(CM) CONVERTED TO INCHES (DBH/2.54)

HT = HT (M) CONVERTED TO FEET (HT/0.3048)

BA = BASAL AREA (DBH IN INCHES) BA= .005454154 x DBH²

FC= HARDWOOD FORM CLASS

CVTS= CUBIC FOOT VOLUME, TOP AND STUMP

TARIF= TARIF NUMBER EQUATION

CVT = CUBIC FOOT VOLUME ABOVE STUMP

CV4 = CUBIC FOOT VOLUME, 4-IN TOP

CV8 = CUBIC FOOT VOLUME, SAWLOG (8-IN TOP)

EQUATION 38

$$CVTS = 0.0070538108 \times DBH^{1.97437} \times HT^{0.85034} \quad (1)$$

$$CV4 = 0.0036795695 \times DBH^{2.12635} \times HT^{0.83339} \quad (2)$$

$$CV8 = 0.0012478663 \times DBH^{2.68099} \times HT^{0.42441} \times FC^{0.28385} \quad (3)$$

$$CVT = CVTS * RTS \quad (4)$$

$$RTS = 0.9679 - 0.1051 \times 0.5523^{(DBH-1.5)} \quad (4)$$

$$CV4X = CVT \times \left(0.99875 - \frac{43.336}{DBH^3} - \frac{124.717}{DBH^4} + \frac{(0.193437 \times HT)}{DBH^3} + \frac{479.83}{(DBH^3 \times HT)} \right) \quad (5)$$

$$TARIF = \frac{(CV8 \times 0.912733)}{\left((0.983 - 0.983 \times 0.65^{(DBH-8.6)}) \times (BA - 0.087266) \right)} \quad (6)$$

WHERE:

DBH= DBH(CM) CONVERTED TO INCHES (DBH/2.54)

HT = HT (M) CONVERTED TO FEET (HT/0.3048)

BA = BASAL AREA (DBH IN INCHES) BA= .005454154 x DBH²

FC=HARDWOOD FORM CLASS

CVTS = CUBIC FOOT VOLUME, TOP AND STUMP

TARIF = TARIF NUMBER EQUATION

CVT = CUBIC FOOT VOLUME ABOVE STUMP

CV4 = CUBIC FOOT VOLUME, 4-IN TOP

CV8 = CUBIC FOOT VOLUME, SAWLOG (8-IN TOP)

EQUATION 39

$$CVTS = 0.0125103008 \times DBH^{2.33089} \times HT^{0.46100} \quad (1)$$

$$CV4 = 0.0042324071 \times DBH^{2.53987} \times HT^{0.50591} \quad (2)$$

$$CV8 = 0.0036912408 \times DBH^{1.79732} \times HT^{0.83884} \times FC^{0.15958} \quad (3)$$

$$CVT = CVTS * RTS \quad (4)$$

$$RTS = 0.9679 - 0.1051 \times 0.5523^{(DBH-1.5)} \quad (4)$$

$$CV4X = CVT \times \left(0.99875 - \frac{43.336}{DBH^3} - \frac{124.717}{DBH^4} + \frac{(0.193437 \times HT)}{DBH^3} + \frac{479.83}{(DBH^3 \times HT)} \right) \quad (5)$$

$$TARIF = \frac{(CV8 \times 0.912733)}{\left((0.983 - 0.983 \times 0.65^{(DBH-8.6)}) \times (BA - 0.087266) \right)} \quad (6)$$

WHERE:

DBH= DBH(CM) CONVERTED TO INCHES (DBH/2.54)

HT = HT (M) CONVERTED TO FEET (HT/0.3048)

BA = BASAL AREA (DBH IN INCHES) BA= .005454154 x DBH²

FC=HARDWOOD FORM CLASS

CVTS = CUBIC FOOT VOLUME, TOP AND STUMP

TARIF = TARIF NUMBER EQUATION

CVT = CUBIC FOOT VOLUME ABOVE STUMP

CV4 = CUBIC FOOT VOLUME, 4-IN TOP

CV8 = CUBIC FOOT VOLUME, SAWLOG (8-IN TOP)

HARDWOOD BOARDFOOT VOLUME RATIOS and EQUATIONS

$$\text{CUBUS} = \text{CV4} - \text{CV8} \quad (1)$$

$$\text{RC6} = 0.993 - 0.993 \times 0.62^{(\text{DBH}-6.0)} \quad (2)$$

 IF Hardwood Equation Number is 25 to 31 THEN set

CV4X = CVT

TARIFX = TARIF (note that TARIF was calculated in the cubic volume equation)

Otherwise, for all other hardwood equation numbers, calculate CV4X and TARIFX as follows:

$$\text{CV4X} = \text{CVT} \times 0.99875 - \frac{43.336}{\text{DBH}^3} - \frac{124.717}{\text{DBH}^4} + \frac{0.193437 \times \text{HT}}{\text{DBH}^3} + \frac{479.83}{\text{DBH}^3 \times \text{HT}}$$

$$\text{TARIFX} = \frac{\text{CV8} \times 0.912733}{0.983 - 0.983 \times 0.65^{\text{DBH}-8.6} \times \text{BA} - 0.087266}$$

If TARIF or TARIFX are <0 then set them to .01

$$\text{CV6} = \text{RC6} \times \text{CV4X} \quad (3)$$

$$\text{B4} = \frac{\text{TARIFX}}{0.912733}$$

$$\text{RS616L} = 0.174439 + 0.117594 \times \log(\text{DBH}) \times \log(\text{B4}) - \frac{8.210585}{\text{DBH}^2} + 0.236693 \times \log(\text{B4}) - 0.00001345 \times (\text{B4})^2 - 0.00001937 \times \text{DBH}^2 \quad (4)$$

$$\text{RS616} = 10.0^{\text{RS616L}} \quad (5)$$

$$\text{SV616} = \text{RS616} \times \text{CV6}$$

$$\text{RI6} = -2.904154 + 3.466328 \times \log(\text{DBH} \times \text{TARIFX}) - 0.02765985 \times \text{DBH} - 0.00008205 \times \text{TARIFX}^2 + \frac{11.29598}{\text{DBH}^2} \quad (6)$$

$$\text{XINT6} = \text{RI6} \times \text{CV6} \quad (7)$$

$$\text{RS816} = 0.990 - 0.58 \times (0.484^{\text{DBH}-9.5}) \quad (8)$$

$$\text{SV816} = \text{RS816} \times \text{SV616} \quad (9)$$

Calculated on hardwood species only:

$$\text{R/8} = 0.990 - 0.55 \times (0.485^{\text{DBH}-9.5}) \quad (10)$$

$$\text{XINT8} = \text{XINT6} \times \text{R/8} \quad (11)$$

WHERE:

B4 = BINGO FACTOR

CUBUS = CUBIC FOOT VOLUME, UPPER-STEM PORTION

RC6 = RATIO TO CONVERT CUBIC 4-INCH TOP TO CUBIC 6-INCH TOP

CV6 = CUBIC FOOT VOLUME, 6-INCH TOP (SAWLOG)

RS616 = RATIO TO CONVERT CUBIC 6-INCH TOP TO SCRIB 6-INCH TOP IN 16-FT LOGS

SV616 = SCRIBNER VOLUME--6-INCH TOP (IN 16-FT LOGS)

RS816 = RATIO TO CONVERT CUBIC 6-INCH TOP TO SCRIB 8-INCH TOP IN 16-FT LOGS

SV816 = SCRIBNER VOLUME--8-INCH TOP (IN 16-FT LOGS)

XINT6 = INTERNATIONAL ¼ INCH VOLUME--6-INCH TOP (IN 16-FT LOGS)

R/8 = RATIO TO CONVERT INTERNATIONAL ¼ INCH 6-INCH TOP TO INTERNATIONAL ¼ INCH 8-INCH TOP

XINT8 = INTERNATIONAL ¼ INCH VOLUME--8-INCH TOP (IN 8-FT LOGS)