



MEMORANDUM

To: Harold Holmes
From: Chris Lindhjem and Dave Souten, ENVIRON
cc: Mark Stehly, BNSF
Date: October 3, 2006
Subject: Richmond Facility TAC Emissions Inventory

The attachment to this memorandum documents the data used in estimating toxic air contaminant (TAC) emissions resulting from facility operations and other activities in and around the Richmond facility. As noted in the attachment, this is being submitted as a revision to the earlier preliminary document, responding to ARB request that new on-road and off-road emissions models be used. Emissions inventories for all other BNSF rail yards in the 2006 schedule will be completed in mid-October including the revisions requested by ARB at the end of August.

Activity factors are taken from both ARB documentation and other sources, including site specific survey or other information.

RICHMOND RAILYARD TAC EMISSIONS INVENTORY

Submitted by: ENVIRON International Corporation

Contact: dsouten@environcorp.com; clindhjem@environcorp.com


This draft submittal of the emissions inventory of Toxic Air Contaminants (TAC) for the Richmond, California BNSF Rail Yard is being submitted as a compliment to the Commerce Mechanical inventory submitted on July 24, 2006. These are both being submitted early in the overall BNSF data submittal process for emissions and dispersion modeling under the CARB-Rail MOU for the reduction of toxic (mainly diesel) emissions from rail operations at rail yards throughout California. Information from these two yards, as well as others under the jurisdiction of BSNF will be submitted in 2006 and 2007. The emissions information provides input to the dispersion modeling results also due to be submitted to CARB. These two, Richmond and Commerce Mechanical, are being submitted early to assure that ARB is in agreement with the technical assumptions, data, methods, and results format to be used for all BNSF facilities.

The data describe activities grouped by like emission source and by spatial activity. The emission sources include locomotives, cargo handling equipment, on-road vehicles, off-road equipment, and stationary sources. Emissions factors for diesel PM and organic gases (which are then speciated into other relevant toxic air contaminants) for each source are included, and emissions estimates provided.

Overview of the Richmond Yard

BNSF has been reconsidering the use of the Richmond yard, and according to BNSF, the use of this site during 2005 was less than in previous years. In previous years, the site had handled cargo from the Port of Oakland, but since the opening of the Oakland near dock facility in 2002, less traffic has moved through Richmond. The Richmond yard in 2005 continued intermodal operations, although limited, with trains arriving and originating from the yard.

The site runs generally northeast and southwest with no through traffic immediately adjacent to the yard. There is a yard to the north of the site, but BNSF has no control over it and no traffic moves between the Richmond site and those operations to the north. Nearly all engines at the Richmond yard arrive from and leave toward the northeast. A small line runs south of the Richmond yard for only about one mile. Since only a small number of cars move into the Richmond yard from the southern direction we do not consider a through track in this assessment.



Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

H:\BNSF\MOU Sites\Richmond\richmond_ActivityEmissions_Memo_100306_final.doc

Locomotive Facility Operations

The operations at the Richmond facility include engine-on locomotive activity within the service facility (headings A – C), switching engines (D), and train arrival and departures within the yard (E). There are no adjacent operating tracks with freight (F) or commuter (G) traffic. Under each heading is a description of the operations. A map demonstrating where the emissions occur for operations within the yard is attached as Appendix A1.

Because different locomotive and engine models have different emissions characteristics, it is important to characterize the types and models of the locomotives that arrive and are serviced in the Richmond facility. ENVIRON estimated the locomotive fleet fractions for different locomotive types and models using data provided by BNSF. The operation descriptions below each include a uniquely applicable fleet characterization.

A. Basic Locomotive Service

According to BNSF records, 9,630 locomotives were serviced at Richmond in 2005. The only types of service carried out at the Richmond facility are sand, fuel, and lubricant service (SFS), and M66 and M92 inspections. Load testing is not performed.

Number Served: 9,630 over one year.

Operations

- (1) Movement into yard at about 5 mph in Notch 1 (single locomotive) or Notch 2 (with 4 locomotives) – 100% on Notch 1 is assumed in the study.
- (2) Idle time while refueling is estimated to be 1 hour.
- (3) In-Consist (4 locomotives on average) is estimated to be 30 minutes at Idle.
- (4) [Lead engine load testing – Not performed at Richmond.]
- (5) Movement out of yard at about 5 mph in Notch 2 (4-locomotive consist).

Idle shutdown sometimes occurs after 30 minutes and two 30-minute idle periods are typical during service. BNSF indicated that this operation occurs throughout a 24-hour period. The activities (duration and modes of operations) for the Basic Services are summarized in Table 1.

Table 1. Activities for the Basic Services (A) in the Richmond facility.

Activities	Est. Speed (mph)	Est. Distance (mile)	Est. Time (hour)	Operation Mode
A1: Movement into Yard	5	0.17	0.03	Notch 1
A2: Idling while Refueling	0	0	1.0	Idle
A3: In-consist	0	0	0.5	Idle
A4: Lead Engine Load Test	0	0	0	-
A5: Movement out of Yard	5	0.17	0.03	Notch 2



Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

Since Basic Services are performed on all locomotives passing through the facility, ENVIRON assumed the fleet characteristics for this activity group are equivalent to average fleet characteristics of the locomotive arrivals to the yard. Data provided by BNSF detailed the fleet of locomotives passing the Richmond facility between May 1, 2005 and April 30, 2006. ENVIRON classified the annual locomotive counts by unique engine model description for all BNSF owned and operated engines. Seven percent of BNSF engine model types could not be identified because some engines originally owned by other railroads (such as CSX or Norfolk Southern) were leased by BNSF. This fraction of unidentified engines was reallocated proportionally across the rest of the fleet. The final fleet characterization is shown in Table 2. Engine surrogates were assigned for use with emission factor data.

Table 2. Fleet characterization for locomotive mainline activity past the Richmond facility, as well as for Basic Services (A) in the Richmond facility.

Locomotive Model	Certification Tier	HP	Fleet Fraction	Engine Surrogate
C44-9W	0	4400	35.4%	Dash-9
C44-9W	1	4400	17.2%	Dash-9
SD40-2	Precontrolled	3000	7.2%	GP-4x
C44-9W	Precontrolled	4400	7.1%	Dash-9
GP30	Precontrolled	2500	6.3%	GP-3x
ES44DC	2	4400	6.2%	ES44/Dash-9
C40-8W	0	4135	4.6%	Dash-8
GP39-2	Precontrolled	2300	3.7%	GP-3x
GP35	Precontrolled	2500	3.3%	GP-3x
B40-8W	Precontrolled	4000	1.2%	Dash-8 Tier 0
B40-8	Precontrolled	4000	1.2%	Dash-8 Tier 0
GP60M	0	3800	1.1%	GP-60
B40-8W	0	4000	0.9%	Dash-8
SD40-2	0	3000	0.8%	GP-4x Precontrolled
GP60	0	3800	0.5%	GP-60
GP38-2	Precontrolled	2000	0.5%	GP-3x
SD39	Precontrolled	2300	0.3%	GP-3x
GP39E	Precontrolled	2300	0.3%	GP-3x
GP60B	0	3800	0.2%	GP-60
SD60M	Precontrolled	3800	0.2%	GP-60
SD60	Precontrolled	3800	0.2%	GP-60
GP60	Precontrolled	3800	0.2%	GP-60
SD50	Precontrolled	3482	0.1%	GP-50
B23-7	Precontrolled	2250	0.1%	Dash-7
GP9	Precontrolled	1750	0.1%	Switchers
GP25	Precontrolled	2500	0.1%	GP-3x
SD45-2	Precontrolled	3272	0.1%	GP-4x
SW1500	Precontrolled	1500	0.1%	Switchers
GP40M	Precontrolled	3000	0.1%	GP-4x
SD45-2T	Precontrolled	3400	0.07%	GP-4x
GP38	Precontrolled	2000	0.06%	GP-3x
SD40	Precontrolled	3000	0.05%	GP-4x



Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

Locomotive Model	Certification Tier	HP	Fleet Fraction	Engine Surrogate
SD75M	0	4300	0.05%	SD-7x
GP15-1	Precontrolled	1500	0.05%	Switchers
SD40-2T	Precontrolled	3000	0.05%	GP-4x
SD45	Precontrolled	3450	0.05%	GP-4x
SD40-2B	Precontrolled	3000	0.04%	GP-4x
AC4400CW	1	4400	0.03%	Dash-9
GP39M	Precontrolled	2300	0.03%	GP-3x
SD70MAC	Precontrolled	4000	0.03%	SD-7x
GP40E	Precontrolled	3000	0.02%	GP-4x
SD45-2B	Precontrolled	3600	0.02%	GP-4x
SD60M	0	3800	0.02%	GP-60
GP40X	Precontrolled	3600	0.01%	GP-4x
GP50	Precontrolled	3600	0.01%	GP-50
SD60	0	3800	0.01%	GP-60
SD70MAC	0	4000	0.010%	SD-7x
SD40-1	Precontrolled	3000	0.005%	GP-4x

B. Basic Engine Inspection

No such activity occurs within the Richmond facility.

C. Full Engine Service/Inspection

No such activity occurs within the Richmond facility.

D. Switching Engine Movements

Switching engine fleet characteristics in the Richmond area were determined by a roster of engines made available by BNSF in early 2006. The data are shown in Table 3. Most engines are of similar power and type. This fleet was used to describe the switching engine activity assuming equivalent use of all six engines in the fleet.

Table 3. Locomotive switching engine fleet characterization for service to the Richmond facility.

Locomotive Model	Certification Tier	HP	Number of Engines	Engine Surrogate
GP-25	Precontrolled	2500	1	GP-3x
GP-35	Precontrolled	2500	1	GP-3x
GP-9	Precontrolled	1750	1	Switcher
SW1500	Precontrolled	1500	3	Switcher

The time in mode for switching engine activity (Table 4) was determined from event recorder downloads of a sample of three engines operating in this yard. For one of the engines, two days of event recorder data were available. The three engines chosen range from 1,500 – 2,500 hp, and are representative of the switching engines dedicated to the area.

Table 4. Switching engine (~1,500 hp) relative time in mode

Throttle Notch	Time in Mode
DB	0.04%
Idle	87.09%
1	4.31%
2	4.47%
3	2.07%
4	1.00%
5	0.41%
6	0.20%
7	0.08%
8	0.32%

The total switching engine activity consists of two engines operating at all times each day of the year (i.e. 48 hours of switching engine use per day or 17,520 hours per year).

E. Train Arrival and Departures in Classification Yard

The primary locomotive activity was determined to be arriving and departing line-haul engines throughout the yard. The typical activity of line-haul engines in the Richmond yard is to arrive with a train, be cut from the train, move to the refueling area, move the ready area where the engines will be assigned a train and then leave. Because the refueling/maintenance is done at a specific location, that activity was singled out of the overall yard activity of engines.

The number of engines moving through the yard was determined from two data sources; automatic readers located north of the yard and train arrival and departure databases. The automatic readers are deemed more accurate than the train arrival and departure data, however automatic readers can make errors if the train is immobile or moving slowly near readers. Data provided by BNSF showed a total of 10,752 locomotives moving in or out of the Richmond facility between May 1, 2005 and April 30, 2006. By contrast, the train arrival and departure information had included 10,845 arrivals and 10,747 departures of which nearly 821 arrivals and departures occurred within one minute of each other, making clear a level of uncertainty in those estimates. Despite the uncertainty in the number of engines arriving at the site, for this analysis, 10,752 locomotives were estimated to enter the yard.

BNSF provided duty cycle information to characterize the notch settings used by these locomotives. ENVIRON calculated average time in mode for freight movement activity along the mainline from the event recorder data for four representative locomotives, as well as

complete start-up data for three representative locomotives. The average time in mode data are summarized in Table 5.

Table 5. Locomotive time in mode arriving at the Richmond facility.

Throttle Notch	Est. Time (hours)
DB	0.445
Idle	2.333
1	0.196
2	0.091
3	0.020

The fleet characterization for locomotives along the mainline was provided in Table 2, and derived from all engines passing the site on the adjacent mainlines.

F. Freight Movements on Adjacent Mainline

BNSF reads radio tags for most of the traffic along its mainline, cataloging every locomotive that comes in and out through the northeast entrance to the yard. However, the main line is removed and not adjacent to the Richmond yard, so no emissions were estimated. There is no non-BNSF (foreign) activity on those mainlines or within the Richmond yard.

G. Commuter Rail Operations on Adjacent Mainline

No such activity occurs within the Richmond facility.

Locomotive Emission Factors for Diesel Particulate Matter

Emission factors used in this study were based primarily on the emission factors used in the California Air Resources Board (ARB)'s Risk Assessment Study for the Union Pacific Roseville facility, and the Southwest Research Institute (SwRI, 2000) study sponsored by ARB, entitled "Diesel Fuel Effects on Locomotive Exhaust Emissions." Since the publication date of the Roseville report, ARB provided ENVIRON with additional emission factors for criteria pollutants, and made some adjustments to the original Roseville data (ARB, 2006a). ENVIRON also received permission from the engine owners to obtain additional emission factor data from the Exhaust Plume Study performed by SwRI (2005). The PM emission factors relevant to all locomotives in the Richmond facility are summarized in Tables 6a and 6b for several different locomotive model groups and certification tiers. Specific locomotives and engines in each locomotive model group can be inferred from the fleet characterization tables provided above.

Based on conversation with the principal researcher on all the locomotive studies (SwRI, 2006), ENVIRON learned that a default fuel sulfur content of 0.3% was used on all test results and certification data produced with locomotives to date (the emission rates in SwRI, 2000 were those with 0.3% sulfur fuel). The emission rates using this fuel are reflected in Table 6a.

Table 6a. PM emission factors for locomotives used in the study, assuming default fuel sulfur content (0.3%).

Locomotive Model Group	Cert Tier ^a	Emission Factors (g/hr) by Throttle Notch									
		Idle	DB ^b	1	2	3	4	5	6	7	8
Switchers (1)	Precntl	31.0	56.0	23.0	76.0	138.0	159.0	201.0	308.0	345.0	448.0
GP-3x (1)	Precntl	38.0	72.0	31.0	110.0	186.0	212.0	267.0	417.0	463.0	608.0
GP-4x (1)	Precntl	47.9	80.0	35.7	134.3	226.4	258.5	336.0	551.9	638.6	821.3
GP-50 (1)	Precntl	26.0	64.1	51.3	142.5	301.5	311.2	394.0	663.8	725.3	927.8
GP-60 (1)	Precntl	48.6	98.5	48.7	131.7	284.5	299.4	375.3	645.7	743.6	941.6
SD-7x (1)	Precntl	24.0	4.8	41.0	65.7	156.8	243.1	321.1	374.8	475.2	589.2
Dash-7 (1)	Precntl	65.0	180.5	108.2	121.2	359.5	327.7	331.5	299.4	336.7	420.0
Dash-9 (2)	Precntl	32.1	53.9	54.2	108.1	219.9	289.1	370.6	437.7	486.1	705.7
EMD 12-710G3 (3)	Precntl	27.5	54.5	34.0	112.5	208.0	234.5	291.0	423.0	545.0	727.5
GP-60 (4)	0	21.1	25.4	37.6	75.5	239.4	352.2	517.8	724.8	1125.9	1319.8
SD-7x (1)	0	14.8	15.1	36.8	61.1	230.4	379.8	450.8	866.2	1019.1	1105.7
Dash-8 (1)	0	37.0	147.5	86.0	133.1	291.4	293.2	327.7	373.5	469.4	615.2
Dash-9 (5)	0	33.8	50.7	56.1	117.4	229.2	263.8	615.9	573.9	608.0	566.6
Dash-9 (4)	1	16.9	88.4	62.1	140.2	304.0	383.5	423.9	520.2	544.6	778.1
ES44/Dash-9 (4)	2	7.7	42.0	69.3	145.8	304.3	365.0	405.2	418.4	513.5	607.5

(1) Final locomotive emission factors (an update to the Roseville study emission factors Table B-1) received via email from Dan Donohue of ARB, May 9, 2006.

(2) "Diesel Fuel Effects on Locomotive Exhaust Emissions," Southwest Research Institute, October 2000.

(3) EPA, 1997.

(4) Confidential data from SwRI, 2005.

(5) Average of ARB and confidential source.

^a Precntl: Precontrolled

^b DB: Dynamic Braking

Table 6b provides emission factors adjusted for fuel sulfur content of 0.105%. This adjustment was performed according to documented ARB procedures from the OFFROAD Modeling Change Technical Memo (Wong, 2005). All locomotive emissions presented in this document utilized the emission factors from Table 6b.

Table 6b. Emission Factors for locomotives used in the study, adjusted for reduced fuel sulfur content (0.105%).

Locomotive Model Group	Cert Tier ^a	Emission Factors (g/hr) by Throttle Notch									
		Idle	DB ^b	1	2	3	4	5	6	7	8
Switchers (1)	Precntl	31.0	56.0	23.0	76.0	131.8	146.1	181.5	283.2	324.4	420.7
GP-3x (1)	Precntl	38.0	72.0	31.0	110.0	177.7	194.8	241.2	383.4	435.3	570.9
GP-4x (1)	Precntl	47.9	80.0	35.7	134.3	216.2	237.5	303.5	507.4	600.4	771.2
GP-50 (1)	Precntl	26.0	64.1	51.3	142.5	288.0	285.9	355.8	610.4	681.9	871.2
GP-60 (1)	Precntl	48.6	98.5	48.7	131.7	271.7	275.1	338.9	593.7	699.1	884.2
SD-7x (1)	Precntl	24.0	4.8	41.0	65.7	149.8	223.4	290.0	344.6	446.8	553.3
Dash-7 (1)	Precntl	65.0	180.5	108.2	121.2	322.6	302.9	307.7	268.4	275.2	341.2
Dash-9 (2)	Precntl	32.1	53.9	54.2	108.1	197.3	267.3	343.9	392.4	397.3	573.3
EMD 12-710G3 (3)	Precntl	27.5	54.5	34.0	112.5	186.6	216.8	270.1	379.3	445.4	591.0

ENVIRON

Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

Locomotive Model Group	Cert Tier ^a	Emission Factors (g/hr) by Throttle Notch									
		Idle	DB ^b	1	2	3	4	5	6	7	8
GP-60 (4)	0	21.1	25.4	37.6	75.5	228.7	323.6	467.7	666.4	1058.5	1239.3
SD-7x (1)	0	14.8	15.1	36.8	61.1	220.1	349.0	407.1	796.5	958.1	1038.3
Dash-8 (1)	0	37.0	147.5	86.0	133.1	261.5	271.0	304.1	334.9	383.6	499.7
Dash-9 (5)	0	33.8	50.7	56.1	117.4	205.7	243.9	571.5	514.6	496.9	460.3
Dash-9 (4)	1	16.9	88.4	62.1	140.2	272.8	354.5	393.4	466.4	445.1	632.1
ES44/Dash-9 (4)	2	7.7	42.0	69.3	145.8	273.0	337.4	376.0	375.1	419.6	493.5

(1) Final locomotive emission factors (an update to the Roseville study emission factors Table B-1) received via email from Dan Donohue of ARB, May 9, 2006.

(2) "Diesel Fuel Effects on Locomotive Exhaust Emissions," Southwest Research Institute, October 2000.

(3) EPA, 1997.

(4) Confidential data from SwRI, 2005.

(5) Average of ARB and confidential source.

^a Precontl: Precontrolled

^b DB: Dynamic Braking

The sulfur content value of 0.105% used for the adjustment was obtained by averaging data provided by BNSF for diesel fuel dispensed and corresponding sulfur level at all California sites and those near California. For sites outside of California, ENVIRON assumed that half of the fuel dispensed would be used in California, because trains moving in either direction may be fueled there. In reality, it is likely that less than half of the out-of-state fuel dispense will be used in California, because many of those sites are a significant distance from the state border.

Table 7. Fuel sulfur and total annual fueling at various locomotive fueling locations

Location	State	Total Gallons	% Sulfur
Holbrook	AZ	21,935	0.192
Phoenix	AZ	3,542,292	0.034
Flagstaff	AZ	2,019	0.192
Kingman	AZ	334,309	0.034
Vacaville	CA	33,074	0.034
Redding	CA	1,004	0.192
Summit	CA	1,750	0.192
San Diego	CA	530	0.192
Bakersfield	CA	240,976	0.034
Barstow	CA	1,946,092	0.015
Oakland	CA	1,762,993	0.034
Needles	CA	770,667	0.192
Bakersfield	CA	131,075	0.034
Bakersfield	CA	11,070	0.034
Corona	CA	103,982	0.034
Fresno	CA	2,669,884	0.034
Kaiser	CA	460,390	0.034
Kings Park	CA	61,900	0.034
Pittsburg	CA	12,695	0.034
Riverbank	CA	2,070,244	0.034

ENVIRON

Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

H:\BNSF\MOU Sites\Richmond\richmond_ActivityEmissions_Memo_100306_final.doc

Location	State	Total Gallons	% Sulfur
San Bernardino	CA	9,940,295	0.034
San Diego	CA	111,369	0.192
Stockton	CA	1,018,965	0.034
Stuart Mesa	CA	41,509	0.192
Terminal Island	CA	14,816,643	0.192
Victorville	CA	66,042	0.034
Watson	CA	1,152,454	0.192
Bakersfield	CA	11,236	0.192
Winslow	AZ	3,496,072	0.170
Belen	NM	202,462,278	0.192
Barstow	CA	52,439,321	0.015
Commerce	CA	31,573,289	0.015
Richmond	CA	22,255,177	0.034
Klamath Falls	OR	3,070,865	0.381

The fuel sulfur correction methodology described by ARB (2005a) was used to adjust PM emission rates from an average fuel sulfur level of 0.3% to 0.105% using the fuel sulfur – PM relationship equation, $A + B * (\text{fuel sulfur, ppm})$. The emission reductions calculated for GE and EMD engines shown in Table 8 were applied to the base emission rates to calculate the emission rates at the in-use fuel sulfur levels.

Table 8. Fuel sulfur emission reductions by notch and engine type

Notch	B	A	Fuel Sulfur 0.3%	Fuel Sulfur 0.105%	Reduction
			EF (g/hp-hr)	EF (g/hp-hr)	
GE 4-stroke Engine					
8	0.00001308	0.0967	0.13594	0.110434	18.76%
7	0.00001102	0.0845	0.11756	0.096071	18.28%
6	0.00000654	0.1037	0.12332	0.110567	10.34%
5	0.00000548	0.132	0.14844	0.137754	7.20%
4	0.00000663	0.1513	0.17119	0.1582615	7.55%
3	0.00000979	0.1565	0.18587	0.1667795	10.27%
EMD 2-stroke engine					
8	0.0000123	0.3563	0.3932	0.369215	6.10%
7	0.0000096	0.284	0.3128	0.29408	5.98%
6	0.0000134	0.2843	0.3245	0.29837	8.05%
5	0.000015	0.2572	0.3022	0.27295	9.68%
4	0.0000125	0.2629	0.3004	0.276025	8.11%
3	0.0000065	0.2635	0.283	0.270325	4.48%

Locomotive Diesel PM Emission Estimates

A. Basic Service

The annual PM emissions for Basic Service by individual activities are presented in Table 9. Most of the maintenance PM emissions were estimated to originate from the idling activities (A2+A3, 90%) in this facility.

Table 9. Estimated annual PM emissions associated with the Basic Services (A) in the Richmond facility.

Locomotive Model Group	Cert Tier	# of Loco	PM Emissions by Operation Activity (grams)					Annual Total (grams)
			A1	A2	A3	A4	A5	
Switchers	Precntl	25	17	779	390	-	57	1,244
GP-3x	Precntl	1408	1,309	53,495	26,747	-	4,646	86,197
GP-4x	Precntl	817	875	39,167	19,584	-	3,292	62,917
GP-50	Precntl	15	23	390	195	-	64	672
GP-60	Precntl	61	90	2,984	1,492	-	243	4,808
SD-7x	Precntl	3	4	70	35	-	6	114
Dash-7	Precntl	14	44	879	440	-	49	1,412
Dash-9	Precntl	686	1,116	22,028	11,014	-	2,225	36,383
GP-60	0	175	197	3,693	1,846	-	396	6,133
SD-7x	0	6	6	86	43	-	11	146
Dash-8	0	758	1,955	27,993	13,996	-	3,025	46,970
Dash-9	0	3408	5,734	115,304	57,652	-	11,998	190,688
Dash-9	1	1655	3,083	27,966	13,983	-	6,960	51,992
ES44/Dash-9	2	600	1,248	4,623	2,312	-	2,626	10,809
Total		9,630	15,702	299,456	149,728	-	35,598	500,484

B. Basic Engine Inspection

No such activity occurs within the Richmond facility.

C. Full Engine Service/Inspection

No such activity occurs within the Richmond facility.

D. Switch Engine Activity

Estimated annual PM emissions for switching activities at the Richmond facility are presented in Table 10. Forty-eight hours per day of switching activity over 365 days per year were assumed to be divided equally between all six locomotives in the switching fleet.



Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

Table 10. Estimated annual PM emissions associated with movements of cars to car repair yard and in the adjacent classification yard of the Richmond facility.

Locomotive Model Group	Cert Tier	# of Loco	PM Emissions (grams)
Switchers	Precntl	4	449,649
GP-3x	Precntl	2	285,627
Total		6	735,276

E. Train Arrival and Departure

The PM emission estimates for BNSF freight movements during the one-year period are presented in Table 11.

Table 11. Estimated annual PM emissions associated with BNSF freight movements along the mainline adjacent to the Richmond facility.

Locomotive Model Group	Cert Tier	# of Loco	PM Emissions by Throttle Notch (grams)					Annual Total PM Emissions (grams)
			Idle	DB	1	2	3	
Switchers	Precntl	28	2,030	700	126	193	74	3,124
GP-3x	Precntl	1572	139,364	50,376	9,539	15,657	5,605	220,540
GP-4x	Precntl	912	102,038	32,501	6,375	11,094	3,959	155,966
GP-50	Precntl	17	1,015	477	168	216	97	1,973
GP-60	Precntl	69	7,774	3,004	654	818	374	12,623
SD-7x	Precntl	3	182	7	26	19	10	243
Dash-7	Precntl	15	2,290	1,214	320	166	98	4,089
Dash-9	Precntl	766	57,387	18,373	8,130	7,498	3,033	94,422
GP-60	0	195	9,620	2,209	1,438	1,336	897	15,500
SD-7x	0	6	223	44	47	36	29	378
Dash-8	0	846	72,926	55,539	14,246	10,196	4,438	157,347
Dash-9	0	3805	300,388	85,818	41,778	40,436	15,705	484,126
Dash-9	1	1848	72,857	72,704	22,461	23,457	10,115	201,594
ES44/Dash-9	2	670	12,045	12,533	9,095	8,851	3,674	46,197
Total		10,752	780,140	335,499	114,404	119,973	48,106	1,398,122

G. Commuter Rail Operations on Adjacent Mainline

No such activity occurs within the Richmond facility.

Non-Locomotive Facility Operations, Emission Factors and Emission Estimates

The operations at the Richmond facility also include non-locomotive activity within the yard (H through L). Under each heading is a description of the operations.

H. Cargo Handling Equipment Operations

Cargo handling equipment (CHE) is used to handle intermodal freight at the Richmond site and includes yard hostlers, cranes, and container handling equipment.

Activity

Input data was received for BNSF for California sites CHE characteristics. BNSF could only provide the CHE 2005 fuel consumption at the Richmond site at 44,421 gallons diesel for all equipment. While default hours of operation were available and the fuel consumption could have provided an estimate of the actual load factor, ARB (2006c) used the equipment population list and the default input data to estimate emissions using their modeling approach and activity estimates for such equipment. Table 12 shows Richmond site CHE characteristics and activity.

Table 12. Richmond CHE characteristics and activity.

ARB Equipment Type	Model Year	Fuel Type	Rated Horsepower	Activity (hrs/yr)
Cranes	1994	D	225	2569
Cranes	1996	D	225	1555
Container Handling Equipment	1999	D	225	236
Yard Trucks	1997	D	200	1289 ^a
Yard Trucks	1997	D	150	1289 ^a
Yard Trucks	2004	D	150	1289 ^a
Yard Trucks	2004	D	150	1289 ^a
Yard Trucks	2004	D	150	1289 ^a

^a ARB, 2005b default

Emissions

Emissions from CHE were estimated by ARB for the Richmond facility with the CHE emissions shown in Table 13.

Table 13. CHE Emissions Estimates (grams per year).

Fuel Type	ARB Equipment Type	PM (grams)
D	Cranes	102,477
D	Cranes	25,455
D	Container Handling Equipment	4,869
D	Yard Trucks	24,072
D	Yard Trucks	41,438
D	Yard Trucks	17,522
D	Yard Trucks	17,522



Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

Fuel Type	ARB Equipment Type	PM (grams)
D	Yard Trucks	17,522
Total		250,878

I. On-road Container Truck Operations

The Richmond site is characterized by container service where tractor-trailers receive or deliver containers to the container yard. BNSF determined the truck counts at the facility entrance and exit gates. However, these truck counts are conducted in such a manner that only tractor-trailer combination trucks are counted. Therefore, summing the total truck entrances and exits will overestimate the total truck trips by the number of trips where trucks both enter and leave as a tractor-trailer combination. To address this problem, BNSF identified the trucks using tags that were counted as both an entrance and exit as tractor-only or tractor-trailer combinations within a period of time. But because many tractors may make several trips to the facility within a single day, a time limit for matching entrances and exits was used to limit the entrance and exit matches. Shown in Table 14. are the derived truck trip totals using 30 minutes, 1 hour, 1.5 hours, and 2 hours as the period for determining truck matches. Note how the estimated truck trips decrease as the matching period increases. Because the time a truck spends on site at Richmond is nearly an hour on average, return trips cannot reasonably have been within one hour. Thus, one hour was used as the period of matching, but it is acknowledged that some trucks may spend more than an hour on site, and therefore would be counted at both the entrance and exit.

Table 14. Richmond truck counts by matching time period for 4 months.

Truck Trip Description	30 Min	1 Hr	1.5 Hr	2 Hr
Total Trucks Logging In & Out Gates (Trailer-Truck In, Trailer-Truck Out) (Matches)	2,635	3,811	4,017	4,073
Trucks Logging In Without Logging Out (Trailer-Truck In, Bobtail Out)	9,084	7,908	7,702	7,646
Trucks Logging Out Without Logging In (Bobtail In, Trailer-Truck Out)	8,107	6,931	6,725	6,669
Total Truck Trips	19,826	18,650	18,444	18,388
Scaled to 12 months		55,950		

A sample chase truck study was conducted to determine entrance queuing time, average speed and distance on site, time on site (engine on or off noted), and exit queuing time. The results for five trucks chased were used to estimate the average operation characteristics for all trucks at the Richmond site. This information is summarized in Table 15.

Table 15. Average truck operation characteristics at the Richmond site.

Mode	Time (min)	Speed (mph)	Distance (miles)
Entrance	1.26	--	--
Travel on site	10.70	14.58	2.6
Idle on Site	29.45	--	--
Exit Queue	1.7	--	--

ENVIRON estimated the emissions for these container trucks using the Bay Area population age distribution to determine the average HHDDV truck emission rates for 2005 using the draft EMFAC2005 model (2006c). The emission rates were calculated for each age of engine by interpolating between 10 and 15 mph at an average speed of 14.58 mph emission factor.

Table 16. PM Emission rates by truck age for Richmond.

Age	Bay Area Truck Age Distribution	Idle PM EF (g/hr)	10 mph PM EF (g/mile)	14.58 mph PM EF (g/mile)	15 mph PM EF (g/mile)
1	5.47%	1.07	0.53	0.42	0.41
2	5.23%	1.07	0.59	0.47	0.46
3	4.81%	1.07	0.65	0.51	0.50
4	4.49%	1.38	2.12	1.38	1.31
5	4.20%	1.38	2.30	1.50	1.42
6	3.95%	1.38	2.48	1.61	1.53
7	4.33%	1.38	2.64	1.71	1.63
8	4.48%	1.38	2.79	1.81	1.72
9	6.01%	1.99	2.96	1.92	1.83
10	5.27%	1.99	3.10	2.01	1.91
11	6.53%	1.99	3.23	2.10	1.99
12	5.63%	1.99	3.34	2.17	2.07
13	4.23%	2.65	4.82	3.13	2.97
14	3.29%	2.65	4.94	3.21	3.05
15	4.00%	2.65	5.06	3.29	3.13
16	4.92%	3.54	5.63	4.46	4.35
17	4.26%	3.54	5.72	4.53	4.42
18	3.35%	3.54	5.81	4.60	4.49
19	2.65%	4.42	5.94	4.70	4.59
20	2.39%	7.10	6.17	4.89	4.77
21	2.36%	7.10	6.25	4.95	4.83
22	1.80%	7.10	6.32	5.01	4.89
23	0.86%	7.10	6.39	5.06	4.94
24	0.75%	7.10	6.45	5.11	4.99
25	0.79%	7.10	6.51	5.15	5.03
26	0.61%	7.10	6.56	5.19	5.07
27	0.71%	7.10	6.60	5.23	5.10
28	0.47%	7.10	6.65	5.26	5.14
29	0.32%	7.10	6.68	5.29	5.16

Age	Bay Area Truck Age Distribution	Idle PM EF (g/hr)	10 mph PM EF (g/mile)	14.58 mph PM EF (g/mile)	15 mph PM EF (g/mile)
30	0.19%	7.10	6.71	5.32	5.19
31	0.28%	7.10	6.74	5.34	5.21
32	0.29%	7.10	6.76	5.35	5.23
33	0.25%	7.10	6.78	5.37	5.24
34	0.18%	7.10	6.79	5.38	5.25
35	0.14%	7.10	6.81	5.39	5.26
36	0.12%	7.10	6.82	5.40	5.27
37	0.11%	7.10	6.83	5.41	5.28
38	0.08%	7.10	6.84	5.42	5.29
39	0.04%	7.10	6.86	5.43	5.30
40	0.05%	7.10	6.87	5.44	5.31
>40	0.10%	7.10	6.88	5.45	5.32
Average		2.71		2.61	

Combining the emission factor data with the age distribution data, emission values were calculated on a per truck basis and are shown in Table 17. The emissions labeled as On-site refer to trucks that are moving within the site boundary as a mobile source. Idle on site represents the idling done by trucks that are on site but away from the exit gate. Idle – entrance and Idle – exit represent the emissions at the entrance/exit gate queues. Table 17 also provides an approximation of the per site trip emissions by mode from all trucks at the Richmond facility based on the estimated 55,950 truck trips in 2005.

Table 17. PM emissions per truck trip and for 2005 at Richmond.

Mode	Per Truck Trip (g)	Annual (55,950 Truck Trips) (g)
Travel on Site	6.79	380,091
Idle on Site	1.33	74,362
Idle - Entrance	0.06	3,171
Idle - Exit	0.08	4,292
Annual Estimate		461,916

J. On-road Fleet Vehicle Operations

There are 22 fleet vehicles based at the Richmond facility according to records from BNSF. Eighteen of these vehicles are associated with the Mechanical department at the Richmond site, and four with the Intermodal or other administrative department. Parameters including gross vehicle weight rating (GVWR), fuel type and annual mileage are known for each vehicle. The draft EMFAC2005 model (ARB, 2006c) provides an average trip distance for each vehicle type in 2005. With this estimate of miles per trip, total annual mileage for each vehicle can be converted to an estimated number of trips. A conservative assumption that all trips either start or end on site can be combined with an approximate distance of about 3000 feet from the



Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

Mechanical facility parking lot to the gate or about 850 feet from the Intermodal/Administrative facility parking lot to the gate in order to estimate the amount of on-site driving for each vehicle.

Using this procedure, the distance driven on site each year by the 22 fleet vehicles is estimated. Each vehicle's GVWR can be used to assign the appropriate vehicle type and emission factor to calculate the emissions associated with driving on site throughout the year. Table 18 provides a summary of relevant parameters for emissions modeling.

Table 18. On-road fleet vehicle activity at the Richmond facility.

EMFAC Vehicle Type	Fuel	# of Vehicles	Average Annual Mileage	Est. Annual Mileage on Site
LDT2	Gasoline	4	77,768	2,422
LHDT1	Gasoline	10	233,838	115,236
MHDT	Diesel	6	44,433	12,703
HHDT	Diesel	2	21,577	431

Annual PM and TOG emission factors from a draft version of EMFAC2005 and on-site emissions estimates for the fleet vehicles are presented in Table 19. Note that gasoline and diesel vehicle estimates were kept separate, so that gasoline TOG exhaust and evaporative emissions could be speciated into TACs differently. ARB Speciate Profile #2105 will be used for the gasoline TOG exhaust emissions, and Profile #422 will be used for the gasoline TOG evaporative emissions.

Table 19. On-road fleet vehicle emissions at the Richmond facility.

EMFAC Vehicle Type	Fuel	PM EF (g/mi)	PM Emissions (grams)	TOG Exhaust EF (g/mi)	TOG Exhaust Emissions (grams)	TOG Evap EF (g/mi)	TOG Evap Emissions (grams)
LDT2	Gasoline	0.04	1,523	0.44	187,114	0.25	110,426
LHDT1	Gasoline	0.04		0.61		0.39	
MHDT	Diesel	0.354	4,296	0.395	4,063	0	0
HHDT	Diesel	0.366		0.821		0	

K. Other Off-Road Equipment

K1. Transport Refrigeration Unit Operations

Transportation Refrigeration units (TRUs) are used to regulate temperatures during the transport of products with temperature requirements. In BNSF operations, temperatures are regulated by TRUs in shipping containers and in railcars when the material being shipped require such temperature regulation.

TRU emissions were estimated in accordance with the methodology presented by an early version of the OFFROAD model provided by ARB (2006c). TRU yearly activity was estimated using the time onsite by TRU configuration (either railcar or shipping



Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

container) and mode of transport was provided by BNSF. This activity data was used along with ARB default age, horsepower, and load factor input estimates in the OFFROAD model to estimate TRU emissions. All TRUs are assumed to use diesel fuel.

K1a. Boxcars

Richmond site boxcar TRU activity is shown in Table 20. As TRUs are not expected to be operating when a boxcar is not loaded, the TRU activity presented here represents loaded TRU shipping containers only. Richmond boxcar TRU emissions are presented in Table 21.

Table 20. Richmond site Boxcar TRU yearly activity.

Yearly Visits	Total Time Onsite (hours)	Average Time Onsite / Visit (hours)
327	5,886	18

Table 21. Richmond site Boxcar TRU emissions (grams per year).

Mode	TOG	PM
Train Arrival – Train Departure	409,909	83,400

K1b. Containers

Richmond site container TRU activity is shown in Table 22. As TRUs are not expected to be operating when a shipping container is not loaded, the TRU activity presented here represents loaded TRU shipping containers only. Richmond container TRU emissions by mode are presented in Table 23.

Table 22. Richmond site shipping container TRU yearly activity.

Yearly Visits	Total Time Onsite (hours)	Average Time Onsite / Visit (hours)
2,187	21,870	10

Table 23. Richmond site shipping container TRU emissions (grams per year).

Mode	TOG	PM
All Modes	1,523,057	309,879

K2. Track Maintenance Equipment Operations

Track maintenance equipment includes equipment used to service tracks anywhere in California though it may be housed at any given facility. This equipment category includes large and small engines and equipment.

Activity

BNSF California track maintenance equipment can be used on any or all tracks within California to maintain the network. Therefore, the approach used to determine the activity and emissions for a given facility was to estimate emissions from all track maintenance equipment and apportion those emissions by site using the relative track mileage (including all tracks, main line and other tracks) at the site to the California total track mileage.

The Richmond site has 16.5 miles of track within its boundaries compared with the California regional total of 3,779 miles. This represents 0.4% of the total California track mileage that is maintained.

Appendix A2 shows a list of all BNSF track maintenance equipment located in California with horsepower and operational parameters. Based on BNSF staff knowledge of equipment characteristics, it was assumed that all track maintenance equipment was diesel powered except two forklifts (equipment IDs TM1 and TM2) which were assumed to be powered by 4-stroke gasoline engines. Forklifts TM1 and TM2 could not be assumed to be diesel powered because diesel forklifts of 16 to 25 horsepower diesel forklifts were not included in the ARB OFFROAD model.

If rated horsepower was not available, horsepower was assumed to be ARB default (ARB, 2006c) for the most populous horsepower range for the assigned ARB equipment category and type. Load factors were assumed to be ARB OFFROAD model default (ARB, 2006b).

Emissions

Exhaust emissions from track maintenance equipment were estimated using the draft version of the OFFROAD model. (ARB, 2006c) Emissions from track maintenance equipment at the Richmond facility along with California totals are shown in Table 24.

Table 24. Track maintenance equipment emissions estimates (grams per year).

Site	Gasoline			Diesel	
	Evaporative TOG	Exhaust TOG	PM	TOG	PM
Richmond	94	533	15	53,724	19,668
California Totals	21,469	121,981	3,525	12,305,162	4,504,844

K3. Other Off-road Equipment (including Portable Engine) Operations

There are other types of off-road equipment dedicated to the Richmond site including forklifts and other equipment.

Activity

Surveys were returned by equipment operators with relevant equipment characteristics and operational information. Table 25 shows Richmond site portable engine characteristics and activity. When not available, model year was assumed to be equivalent to 2005 minus ARB 2006c useful life.

Table 25. Portable and other offroad engine equipment characteristics and operation.

ARB Equipment Type	Model Year	Fuel Type	Rated Horsepower
Forklifts	2000	D	149 ^a
Forklifts	1998 ^a	LPG	70 ^a
Forklifts	1993 ^a	D	149 ^a
Specialty Vehicles	2002 ^c	G	20 ^b
Specialty Vehicles	2002 ^c	G	20 ^b
Specialty Vehicles	2002 ^c	G	20 ^b
Specialty Vehicles	2002 ^c	G	20 ^b
Specialty Vehicles	2001	G	20
Specialty Vehicles	2001	G	20
Specialty Vehicles	2002	G	20
Specialty Vehicles	2002	G	20
Specialty Vehicles	2002	G	20
Specialty Vehicles	2003	G	20
Specialty Vehicles	2001	G	10
Specialty Vehicles	2002 ^c	G	20 ^b
Specialty Vehicles	2002 ^c	G	20 ^b
Specialty Vehicles	2002 ^c	G	20 ^b
Specialty Vehicles	2002 ^c	G	20 ^b

^a Based on ARB, 2006c

^b Based on characteristics of similar equipment at Richmond site



Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

Emissions

Emissions from portable engine offroad equipment at the Richmond facility are shown in Table 26 using default activity and other input data from the draft OFFROAD model (ARB, 2006c). The diesel TOG from this equipment will be speciated using ARB Speciate Profile #818.

Table 26. Portable engine equipment emissions estimates (grams per year).

Fuel Type	ARB Equipment Type	Evaporative TOG (grams)	Exhaust TOG (grams)	PM (grams)
D	Forklifts	0	114,720	43,204
LPG	Forklifts	0	143,367	2,268
D	Forklifts	0	160,626	60,405
G	Specialty Vehicles	3,934	4,627	130
G	Specialty Vehicles	3,934	4,627	130
G	Specialty Vehicles	3,934	4,627	130
G	Specialty Vehicles	3,626	4,627	130
G	Specialty Vehicles	3,934	4,930	140
G	Specialty Vehicles	3,626	4,930	140
G	Specialty Vehicles	3,626	4,930	140
G	Specialty Vehicles	3,626	4,930	140
G	Specialty Vehicles	3,626	4,930	140
G	Specialty Vehicles	3,626	4,627	130
G	Specialty Vehicles	3,626	2,061	70
G	Specialty Vehicles	3,626	4,627	130
G	Specialty Vehicles	3,626	4,627	130
G	Specialty Vehicles	3,934	4,627	130
G	Specialty Vehicles	3,934	4,627	130
LPG Fuel		0	143,367	2,268
2-Stroke Gasoline Fuel		56,238	2,061	70
4-Stroke Gasoline Fuel			66,295	1,870
Diesel Fuel		---	275,346	103,609

L. Stationary Sources

Air quality permits for the Richmond facility show several types of stationary sources for potential evaluation.

Source types:

- (1) Gasoline storage and dispensing units [1 on site]
- (2) Diesel-fueled internal combustion engines (ICEs) [3 on site]

The gasoline storage and dispensing unit is comprised of a 1000 gallon tank and hose with nozzle. Phase I and II vapor recovery systems are in place. Throughput is limited to 400,000 gallons per year. The total VOC emissions will be determined at a later date.



Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

The relevant parameters for the three diesel ICEs, as well as their estimated annual PM and TOG emissions are presented in Table 27. To estimate emissions from the three diesel ICEs at the Richmond site, ENVIRON utilized the ARB OFFROAD model provided by ARB (2006c). The diesel TOG from these ICEs will be speciated using ARB Speciate Profile #818.

Table 27. Parameters and PM emissions estimates for the diesel-fueled ICEs at the Richmond facility.

Specifications	Brake horsepower (hp)	Maximum Est. Operation Time (hr/yr)	PM Emissions (grams)	TOG Emissions (grams)
Generac SD 300 w/ filter	446	100	8,191	27,584
Generac SD 250 w/ filter	400	100	7,346	24,739
Generac SD 600	846	100	15,538	52,322
Total			31,075	104,644

Total TAC emissions from the Richmond facility

The estimated total annual diesel PM (DPM) emissions associated with the operations in the Richmond facility are summarized in Table 28. As shown in Table 28, about 13% of the DPM emissions were associated with the Basic Services operation, while about 36% was associated with train arrivals and departures and 19% from switching at the facility.

Table 28. Estimated total annual DPM emissions associated with the operations in the Richmond facility.

Facility Operations	DPM Emissions		Percentage
	Grams	Metric Tons	
Basic Services (A)	500,484	0.500	13%
Basic Engine Inspection (B)	-	-	-
Full Engine Service/Inspection (C)	-	-	-
Switching (D)	735,276	0.735	19%
Train Arrival and Departure (E)	1,398,122	1.398	36%
Adjacent Freight Movements (F)	-	-	-
Adjacent Commuter Rail Operations (G)	-	-	-
Cargo Handling Equipment Operations (H)	250,878	0.251	6%
On-Road Container Truck Operations (I)	461,916	0.462	12%
On-Road Fleet Vehicle (J)	4,296	0.004	0%
Transport Refrigeration Units (K)	393,279	0.393	10%
Track Maintenance (K)	19,668	0.020	1%
Other Off-Road (K)	103,609	0.104	3%
Stationary Sources (L)	31,075	0.031	1%
Total	3,898,603	3.90	

The estimated total annual emissions of total organic gases (TOG) (for speciation into the other TACs) associated with gasoline, LPG, or CNG operations in the Richmond facility are summarized in Table 29. Diesel TOG is not included in the tabulation.

Table 29. Estimated total annual TOG emissions associated with gasoline, LPG, or LNG operations in the Richmond facility.

Facility Operations	TOG Emissions		Percentage
	Grams	Metric Tons	
On-Road Fleet Vehicle (J)	297,540	0.298	53%
Track Maintenance (K)	627	0.001	0%
Other Off-Road (K)	267,691	0.268	47%
Total	566,128	0.566	

References

- ARB. 2006a. Email from Dan Donohue of ARB to Chris Lindhjem of ENVIRON, May 9, 2006.
- ARB. 2006b. E-mail communication from Sandee Kidd with Draft OFFROAD Model Emission Factors, ARB. April, 2006.
- ARB. 2006c. Draft OFFROAD, and Draft EMFAC2005 models on disk. August, 2006. Cargo handling equipment emissions provided September 26, 2006.
- ARB. 2005a. OFFROAD Modeling Change Technical Memo, "Changes to the Locomotive Inventory," prepared by Walter Wong, preliminary draft. March 16, 2005. Available online March 31, 2006: http://www.arb.ca.gov/msei/on-road/downloads/docs/Locomotive_Memo.pdf
- ARB. 2005b. "Ports and Intermodal Rail Yards", California Air Resources Board, <http://www.arb.ca.gov/regact/cargo2005/cargo2005.htm>, October, 2005. and "Rulemaking to Consider to Consider the Adoption of a Proposed Regulation for Mobile Cargo Handling Equipment at Ports and Intermodal Rail Yards," December 8, 2005.
- ARB. 2003. Staff Report: Initial Statement Of Reasons For Proposed Rulemaking: Airborne Toxic Control Measure For In-Use Diesel-Fueled Transport Refrigeration Units (TRU) and TRU Generator Sets, and Facilities Where TRUs Operate, California Air Resources Board, <http://www.arb.ca.gov/regact/trude03/trude03.htm>, October 2003.
- ARB. 2000a. "EMFAC Technical Support Document: HC Conversions". California Air Resources Board, http://www.arb.ca.gov/msei/on-road/doctable_test.htm, February, 2000.

- ARB. 2000b. "MSC #99-32: Public Meeting to Consider Approval of California's Emissions Inventory of Off-Road Large Compression-Ignited Engines (≥ 25 hp) Using the New OFFROAD Emissions Model", Staff Report, California Air Resources Board, <http://www.arb.ca.gov/msei/off-road/pubs.htm>, January, 2000.
- ARB. 1998. "MSC #98-27: Public Meeting to Consider Approval of the California Off-Road Large Spark-Ignited Engine Emissions Inventory", Staff Report, California Air Resources Board, <http://www.arb.ca.gov/msei/off-road/pubs.htm>, October, 1998.
- EEA. 1997. "Documentation of Input Factors for the New Off-Road Mobile Source Emissions Inventory Model", Energy and Environmental Analysis, Inc., February, 1997.
- EMFAC. 2003. EMFAC model version: Emfav2002 V2.2 Apr 23 2003. California Air Resources Board.
- EPA. 2005. "Conversion Factors for Hydrocarbon Emission Components", U.S. Environmental Protection Agency, EPA420-R-05-015, December, 2005.
- SwRI. 2006. Personal communication between S. Fritz of SwRI and C. Lindhjem of ENVIRON, May 2006.
- SwRI, 2005, "Exhaust Plume Study," correspondence with Steve Fritz at SwRI, September 2005 and May 2006.
- SwRI, 2000 "Diesel Fuel Effects on Locomotive Exhaust Emissions." Prepared for California Air Resources Board, October 2000.
- Wong, ARB, March 2005, <http://www.arb.ca.gov/ei/areasrc/arbomobilsrctrains.htm>

APPENDIX A1

FACILITY OPERATIONS MAP



Golden Gate Plaza • 101 Rowland Way • Novato, California 94945-5010 USA

Tel: (415) 899-0700 • Fax: (415) 899-0707 • www.environcorp.com

To be included at a later date.

APPENDIX A2

TRACK MAINTENANCE EQUIPMENT

Equipment ID	Equipment Type	ARB Category	ARB Equipment type	Engine Model Year	Engine Horsepower	Dual Engine (Y/N)	Operating Hours Per week	Average Operating Hours Per Year
TM1	FORKLIFT	Industrial	Forklifts	1998	17	N	30	1440
TM2	FORKLIFT	Industrial	Forklifts	1985	17	N	30	1440
TM3	ANCHOR APPLICATOR	Industrial	Other General Industrial	1988	50	N	25	1200
TM4	ANCH REMVR	Industrial	Other General Industrial	1994	90	N	15	720
TM5	ANCHOR BOXER	Industrial	Other General Industrial	1987	76	N	25	1200
TM6	ANCHOR BOXER	Industrial	Other General Industrial	1987	76	N	25	1200
TM7	ANCHOR REMOVER	Industrial	Other General Industrial	1995	50	N	20	960
TM8	ANCHOR APP/REM	Industrial	Other General Industrial	2004	50	N	25	1200
TM9	ANCHOR APP/REM	Industrial	Other General Industrial	2004	50	N	25	1200
TM10	ANCHOR APP/REM	Industrial	Other General Industrial	2004	50	N	25	1200
TM11	AIR COMPRESSOR	Commercial	Air Compressors	1989	35	N	12	576
TM12	AIR COMPRESSOR	Commercial	Air Compressors	1989 ^a	35	N	15	720
TM13	AIR COMPRESSOR	Commercial	Air Compressors	1989 ^a	35	N	10	480
TM14	AIR COMPRESSOR	Commercial	Air Compressors	1989 ^a	35	N	10	480
TM15	ADZ/CRIB-DCF	Industrial	Other General Industrial	2002	90	N	15	720
TM16	DBL BRM	Industrial	Other General Industrial	1983	100	N	0	0
TM17	DBL BRM	Industrial	Other General Industrial	1985	100	N	0	0
TM18	DBL BRM TRLR	Industrial	Other General Industrial	2000	100	N	25	1200
TM19	BALLAST REGULATOR	Industrial	Other General Industrial	1981	64	N	17.29	829.92
TM20	BALLAST REGULATOR	Industrial	Other General Industrial	1991	64	N	0	0
TM21	BALLAST REGULATOR	Industrial	Other General Industrial	1986	64	N	0	0
TM22	BALLAST REGULATOR	Industrial	Other General Industrial	1979	64	N	45	2160
TM23	BALLAST REGULATOR	Industrial	Other General Industrial	1984	175	N	45	2160
TM24	BALLAST REGULATOR	Industrial	Other General Industrial	1983	175	N	0	0
TM25	BALLAST REGULATOR	Industrial	Other General Industrial	1985	175	N	0	0
TM26	BALLAST REGULATOR	Industrial	Other General Industrial	1996	175	N	10.2	489.6
TM27	BALLAST REGULATOR	Industrial	Other General Industrial	1996	175	N	31.33	1503.84
TM28	BALLAST REGULATOR	Industrial	Other General Industrial	1996	175	N	0	0
TM29	BALLAST REGULATOR	Industrial	Other General Industrial	2003	175	N	15	720

Equipment ID	Equipment Type	ARB Category	ARB Equipment type	Engine Model Year	Engine Horsepower	Dual Engine (Y/N)	Operating Hours Per week	Average Operating Hours Per Year
TM30	LOCOMOTIVE CRANE	Construction	Cranes	1979	250	N	0	0
TM31	TRUCK CRANE	Construction	Cranes	1986	175	Y	0	0
TM32	RUBBER TIRED CRANE	Construction	Cranes	1982	175	N	0	0
TM33	RUBBER TIRED CRANE	Construction	Cranes	1999	175	N	0	0
TM34	RUBBER TIRED CRANE	Construction	Cranes	2001	175	N	0	0
TM35	WHL LDR	Construction	Rubber Tired Loaders	1974	300	N	3.06	146.88
TM36	CRN/LDR HR	Construction	Cranes	1974	100	N	0	0
TM37	CRN/LDR HR	Construction	Cranes	1984	100	N	0	0
TM38	CRN/LDR HR	Construction	Cranes	1984	100	N	3.36	161.28
TM39	CRN/LDR HR	Construction	Cranes	1984	100	N	28.8	1382.4
TM40	WHL LDR*GP	Construction	Rubber Tired Loaders	1995	120	N	0	0
TM41	SKID-LDR FBHTAH	Construction	Skid Steer Loaders	2003	74	N	0	0
TM42	CRN/LDR HR	Construction	Cranes	2004	100	N	26.56	1274.88
TM43	BK-HO/LDR	Construction	Tractors/Loaders/Backhoes	1992	75.5	N	2	96
TM44	BK-HO/LDR	Construction	Tractors/Loaders/Backhoes	1992	75.5	N	0	0
TM45	BK-HO/LDR EH	Construction	Tractors/Loaders/Backhoes	1995	69	N	12.37	593.76
TM46	BK-HO/LDR EH	Construction	Tractors/Loaders/Backhoes	1995	69	N	46.38	2226.24
TM47	BK-HO/LDR EF	Construction	Tractors/Loaders/Backhoes	1998	78	N	0	0
TM48	BK-HO/LDR EF	Construction	Tractors/Loaders/Backhoes	1999	78	N	0	0
TM49	BK-HO/LDR EF	Construction	Tractors/Loaders/Backhoes	1999	78	N	12.88	618.24
TM50	BK-HO/LDR EF	Construction	Tractors/Loaders/Backhoes	1999	78	N	7.31	350.88
TM51	BK-HO/LDR EF	Construction	Tractors/Loaders/Backhoes	1999	78	N	8.91	427.68
TM52	BK-HO/LDR EF	Construction	Tractors/Loaders/Backhoes	2000	78	N	0	0
TM53	BK-HO/LDR EF	Construction	Tractors/Loaders/Backhoes	2003	88	N	0	0
TM54	BK-HO/LDR EF	Construction	Tractors/Loaders/Backhoes	2004	88	N	1.65	79.2
TM55	BK-HO/LDR EF	Construction	Tractors/Loaders/Backhoes	2004	88	N	9.93	476.64
TM56	BK-HO/LDR EF	Construction	Tractors/Loaders/Backhoes	2004	88	N	6.13	294.24
TM57	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	119	N	15	720

Equipment ID	Equipment Type	ARB Category	ARB Equipment type	Engine Model Year	Engine Horsepower	Dual Engine (Y/N)	Operating Hours Per week	Average Operating Hours Per Year
TM58	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	85	N	15	720
TM59	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	74	N	15	720
TM60	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	74	N	15	720
TM61	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	74	N	15	720
TM62	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	74	N	15	720
TM63	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	74	N	15	720
TM64	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	74	N	15	720
TM65	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	74	N	15	720
TM66	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	85	N	15	720
TM67	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	99	N	15	720
TM68	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	74	N	15	720
TM69	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	74	N	15	720
TM70	BK-HO/LFR EF	Construction	Tractors/Loaders/Backhoes	1989 ^a	85	N	15	720
TM71	Directional Boring Machine	Construction	Bore/Drill Rigs	2002 ^a	82 ^b	N	15	720
TM72	Manlift	Industrial	Aerial Lifts	1989 ^a	34 ^b	N	15	720
TM73	Trencher	Construction	Trenchers	1998 ^a	39	N	15	720
TM74	Trencher	Construction	Trenchers	1998 ^a	39	N	15	720
TM75	Trencher	Construction	Trenchers	1998 ^a	39	N	15	720
TM76	Trencher Rider	Construction	Trenchers	1998 ^a	79	N	15	720
TM77	RAIL LIFTER	Industrial	Other General Industrial	1997	19	N	20	960
TM78	TIE SPIKER	Industrial	Other General Industrial	1986	19	N	0	0
TM79	TIE SPIKER	Industrial	Other General Industrial	1986	19	N	0	0
TM80	TIE SPIKER	Industrial	Other General Industrial	1991	19	N	3.1	148.8
TM81	TIE SPIKER	Industrial	Other General Industrial	2002	90	N	10	480
TM82	TIE SPIKER	Industrial	Other General Industrial	2002	90	N	10	480
TM83	TIE SPIKER	Industrial	Other General Industrial	2002	90	N	10	480
TM84	SPIKE PULLER	Industrial	Other General Industrial	1984	35	N	10	480
TM85	SPIKE PULLER	Industrial	Other General Industrial	1995	35	N	10	480
TM86	SPIKE PULLER	Industrial	Other General Industrial	1995	35	N	10	480
TM87	SPIKE PULLER	Industrial	Other General Industrial	1986	35	N	0	0

Equipment ID	Equipment Type	ARB Category	ARB Equipment type	Engine Model Year	Engine Horsepower	Dual Engine (Y/N)	Operating Hours Per week	Average Operating Hours Per Year
TM88	DITCHER/SPREADER	Industrial	Other General Industrial	1980	97 ^b	N	15	720
TM89	TIE TAMPER	Industrial	Other General Industrial	1985	175	N	20	960
TM90	TIE TAMPER	Industrial	Other General Industrial	1985	175	N	3.74	179.52
TM91	TIE TAMPER	Industrial	Other General Industrial	1989	250	N	22.4	1075.2
TM92	TIE TAMPER	Industrial	Other General Industrial	1995	250	N	40	1920
TM93	TIE TAMPER	Industrial	Other General Industrial	1996	250	N	40	1920
TM94	TIE TAMPER	Industrial	Other General Industrial	1996	250	N	90	4320
TM95	TIE TAMPER	Industrial	Other General Industrial	1996	250	N	40	1920
TM96	TIE TAMPER	Industrial	Other General Industrial	1997	250	N	0.92	44.16
TM97	TIE TAMPER	Industrial	Other General Industrial	2000	250	N	35	1680
TM98	TIE TAMPER	Industrial	Other General Industrial	2000	300	N	40	1920
TM99	TIE TAMPER	Industrial	Other General Industrial	2001	250	N	31	1488
TM100	TIE TAMPER	Industrial	Other General Industrial	2002	300	N	35	1680
TM101	TIE TAMPER	Industrial	Other General Industrial	2003	250	N	0	0
TM102	TIE TAMPER	Industrial	Other General Industrial	1995	175	N	0	0
TM103	TIE TAMPER	Industrial	Other General Industrial	1987	175	N	0	0
TM104	TIE TAMPER	Industrial	Other General Industrial	1985	150	N	15	720
TM105	TIE CRANE	Construction	Cranes	1982	64	N	15	720
TM106	TIE CRANE	Construction	Cranes	1982	64	N	0	0
TM107	TIE CRANE	Construction	Cranes	1985	64	N	0	0
TM108	TIE CRANE	Construction	Cranes	1986	64	N	0	0
TM109	TIE PLUGGER	Industrial	Other General Industrial	2000	90	N	20	960
TM110	TIE PLUGGER	Industrial	Other General Industrial	2002	90	N	20	960
TM111	TIE PLUGGER	Industrial	Other General Industrial	2003	90	N	20	960
TM112	TIE INSERT/EXTRACT	Industrial	Other General Industrial	1985	175	N	0	0
TM113	TIE INSERT/EXTRACT	Industrial	Other General Industrial	1985	175	N	0	0
TM114	TIE INSERT/EXTRACT	Industrial	Other General Industrial	1987	175	N	41.58	1995.84
TM115	DOZER	Construction	Crawler Tractors	1985	145	N	0	0
TM116	WELDER	Commercial	Welders	1984	64	N	25	1200
TM117	WELDER	Commercial	Welders	1984	64	N	25	1200

Equipment ID	Equipment Type	ARB Category	ARB Equipment type	Engine Model Year	Engine Horsepower	Dual Engine (Y/N)	Operating Hours Per week	Average Operating Hours Per Year
TM118	WELDER	Commercial	Welders	1986	64	N	25	1200
TM119	WELDER	Commercial	Welders	1987	64	N	25	1200
TM120	WELDER	Commercial	Welders	1988	40	N	25	1200
TM121	WELDER	Commercial	Welders	1988	64	N	25	1200
TM122	WELDER	Commercial	Welders	1988	64	N	25	1200
TM123	WELDER	Commercial	Welders	1998	64	N	25	1200
TM124	WELDER	Commercial	Welders	1999	64	N	25	1200
TM125	WELDER	Commercial	Welders	1999	64	N	25	1200
TM126	WELDER	Commercial	Welders	1999	64	N	25	1200
TM127	WELDER	Commercial	Welders	2000	64	N	25	1200
TM128	WELDER	Commercial	Welders	2000	64	N	25	1200
TM129	WELDER	Commercial	Welders	2000	40	N	25	1200
TM130	WELDER	Commercial	Welders	2000	40	N	25	1200
TM131	WELDER	Commercial	Welders	2001	64	N	25	1200
TM132	WELDER	Commercial	Welders	2003	40	N	25	1200
TM133	WELDER	Commercial	Welders	2003	64	N	25	1200
TM134	WELDER	Commercial	Welders	2003	40	N	25	1200
TM135	WELDER	Commercial	Welders	2004	64	N	25	1200
TM136	WELDER	Commercial	Welders	2004	64	N	25	1200
TM137	WELDER	Commercial	Welders	2004	64	N	25	1200
TM138	WELDER	Commercial	Welders	2004	40	N	25	1200
TM139	WELDER	Commercial	Welders	2005	40	N	25	1200
TM140	WELDER	Commercial	Welders	2005	40	N	25	1200
TM141	WELDER	Commercial	Welders	2005	40	N	25	1200
TM142	WELDER	Commercial	Welders	2005	40	N	25	1200
TM143	RAIL HEATER	Industrial	Other General Industrial	1982	90	N	25	1200
TM144	RAIL HEATER	Industrial	Other General Industrial	1995	90	N	25	1200
TM145	SPIKE RECLAIMER	Industrial	Other General Industrial	1992	90	N	25	1200
TM146	TIE PLATE RETRIEVER	Industrial	Other General Industrial	2003	25	N	25	1200
TM147	TRACK STABILIZER	Industrial	Other General Industrial	1989	300	N	9.26	444.48

Equipment ID	Equipment Type	ARB Category	ARB Equipment type	Engine Model Year	Engine Horsepower	Dual Engine (Y/N)	Operating Hours Per week	Average Operating Hours Per Year
TM148	TRACK STABILIZER	Industrial	Other General Industrial	2000	300	N	45	2160
TM149	TRACK STABILIZER	Industrial	Other General Industrial	2001	300	N	45	2160

^a Model year estimated as 2005 minus ARB 2006c default useful life.

^b Horsepower estimated as ARB 2006c default for the most populous horsepower range for the associated equipment type.