

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-12-25

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

NAVISTAR INTERNATIONAL TRANSPORTATION CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and,

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Navistar International Transportation Corporation 1998 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage: Loader, Tractor, Pump, Compressor

Fuel Type: Diesel

<u>Engine Family</u>	<u>Liters (Cubic Inches)</u>	<u>Exhaust Emission Control Systems and Special Features</u>
WNVXL0530ANB	8.7 (530)	Turbocharger Engine Control Module

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

<u>Exhaust Emissions (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
1.0	8.5	6.9	0.4	20	15	50

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

<u>Exhaust Emissions (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
0.1	0.6	6.7	0.1	8	2	20

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

1. Any engine which employs a defeat device shall not be covered by this Executive Order.
2. Within 90 days following the issuance of this Executive Order, the manufacturer must show cause, to the satisfaction of the Executive Officer or his designee, that the strategy for fuel injection timing, including timing during the fuel economy mode, is not a defeat device.

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 28<sup>th</sup> day of July 1998.



R. B. Summerfield, Chief  
Mobile Source Operations Division

# LARGE ENGINE MODEL SUMMARY

Manufacturer: Navistar E. O. # U-R-12-25 Process Code: New Submission

EPA Engine Family: WNVXL0530ANB Manufacturer Family Name: DT-530E

1. Engine Code    2. Engine Model    3. BHP @ RPM (SAE Gross)    4. Fuel Rate: mm/stroke @ peak HP (for diesel only)    5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)    6. Torque @ RPM (SEA Gross)    7. Fuel Rate: mm/stroke @ peak torque    8. Fuel Rate: (lbs/hr) @ peak torque    9. Emission Control Device Per SAE J1930

IA225	IA225	225 @ 2200	118.0	87.0	670 @ 1600	136.2	73.0	ECM, TC, DI
IAB225	IAB225	225 @ 2200	118.0	87.0	670 @ 1600	136.2	73.0	ECM, TC, DI
IA215	IA215	215 @ 2200	108.5	80.0	670 @ 1700	137.8	78.5	ECM, TC, DI
IAB215	IAB215	215 @ 2200	108.5	80.0	700 @ 1500	139.2	70.0	ECM, TC, DI
IA205	IA205	205 @ 2200	105.8	78.0	611 @ 1600	121.2	65.0	ECM, TC, DI
IA190	IA190	190 @ 2200	102.4	75.5	610 @ 1300	125.1	54.5	ECM, TC, DI