	Cummins Inc.	EXECUTIVE ORDER U-R-002-0245-1 New Off-Road Compression-Ignition Engines
--	--------------	--

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2004	4CEXL0505ABC	8.3	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Charge Air Cooler, Powertrain Control Module			Tractor	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
130 ≤ kW < 225	Tier 2	STD	N/A	N/A	6.6	3.5	0.20	20	15	50
		FEL	N/A	N/A	6.4	N/A	0.17	N/A	N/A	N/A
		CERT	--	--	5.5	0.9	0.13	6	1	14

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.


BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby cancels and replaces Executive Order U-R-002-0245 dated November 25, 2003.

Executed at El Monte, California on this 9TH day of September 2004.


Allen Lyons, Chief
Mobile Source Operations Division

Engine Model Summary Form

ATTACHMENT Pg 1 of 1

U-P-002-0245-1

Manufacturer: Cummins Inc.
Engine category: Nonroad Over 50 Hp
EPA Engine Family: 4CEXL0505ABC
Mr Family Name: D413
Process Code: New Submission

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: min/stroke @ peak IIP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak IIP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: min/stroke@peak torque	8. Fuel Rate: (lbs/hr)@peak torque	9. Emission Control Device Per SAE J1930
8152;FR91063	QSC8.3-C	300@2200	139	103.0	1000@1400	189	89.3	PCM,TC,CAC
8152;FR90965	QSC8.3-C	300@2100	148	104.5	1000@1400	189	89.3	PCM,TC,CAC
8152;FR91064	QSC8.3-C	280@2200	131	97.5	1000@1400	189	89.3	PCM,TC,CAC
8152;FR91107	QSC8.3-C	285@2200	131	97.1	935@1400	178	83.9	PCM,TC,CAC
8152;FR91110	QSC8.3-C	280@2200	134	99.2	900@1400	174	81.8	PCM,TC,CAC
8153;FR91065	QSC8.3-C	260@2200	122	90.4	870@1400	169	79.9	PCM,TC,CAC
8153;FR91066	QSC8.3-C	240@2200	113	84.0	800@1400	153	72.1	PCM,TC,CAC
8153;FR91108	QSC8.3-C	245@1800	138	83.8	870@1400	168	79.4	PCM,TC,CAC
8153;FR91067	QSC8.3-C	215@2200	106	78.3	664@1400	133	62.5	PCM,TC,CAC