	<b>YANMAR DIESEL ENGINE CO., LTD.</b>	<b>EXECUTIVE ORDER U-R-028-0296</b> New Off-Road Compression-Ignition Engines
---	---------------------------------------	---

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2006	6YDXL1.50M3N	1.496	Diesel	3000, 5000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection			Crane, Loader, Tractor, Excavator, Dozer, Pump, Compressor	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 2	STD	N/A	N/A	7.5	6.6	0.80	20	15	50
19 ≤ kW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT	--	--	5.8	4.0	0.31	2	3	3

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed at El Monte, California on this 20<sup>th</sup> day of December 2005.

  
Allen Lyons, Chief  
Mobile Source Operations Division

# Engine Model Summary Form

U-R-028-0296  
ATTACHMENT, p1 of 1

Manufacturer: Yanmar Co., Ltd.  
 Engine category: Nonroad CI  
 EPA Engine Family: 6YDXL1.50M3N  
 Mfr Family Name: N/A  
 Process Code: New Submission

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke@peak torque	8. Fuel Rate: (lbs/hr)@peak torque	9. Emission Control Device Per SAE J1930
N/A	3TNV84-VM2	34.6/3000	30.0	14.9	76.0/1200	34.0	6.7	EM
N/A	3TNV84-D	34.3/3000	29.6	14.7	72.8/1200	33.1	6.6	EM
N/A	3TNV84-J	33.1/2900	29.4	14.1	72.8/1200	33.1	6.6	EM
N/A	3TNV84-K	31.9/2800	29.2	13.5	72.8/1200	33.1	6.6	EM
N/A	3TNV84-L	30.7/2700	29.1	13.0	73.6/1200	33.5	6.6	EM
N/A	3TNV84-M	29.6/2600	29.0	12.5	72.5/1200	32.5	6.4	EM
N/A	3TNV84-N	28.4/2500	28.3	11.7	72.2/1300	32.4	7.0	EM
N/A	3TNV84-P	27.2/2400	28.1	11.1	72.8/1300	32.8	7.0	EM
N/A	3TNV84-Q	26.0/2300	27.9	10.6	73.4/1300	33.1	7.1	EM
N/A	3TNV84-S	24.9/2200	27.3	9.9	73.1/1100	32.4	5.9	EM
N/A	3TNV84-W	22.5/2000	26.6	8.8	70.6/1200	30.0	6.0	EM
N/A	3D84E-5K	32.0/2800	29.2	13.5	74.0/1300	32.2	6.9	EM
N/A	3D84E-5L	30.7/2700	29.1	13.0	73.6/1200	33.5	6.6	EM
N/A	3D84E-5M	29.6/2600	28.6	12.3	73.3/1300	33.0	7.1	EM
N/A	3D84E-5N	28.4/2500	28.3	11.7	72.2/1300	32.4	7.0	EM
N/A	3D84E-5P	27.2/2400	28.1	11.1	72.8/1300	32.8	7.0	EM
N/A	3D84E-5Q	26.0/2300	27.9	10.6	73.4/1300	33.1	7.1	EM
N/A	3D84E-5S	24.9/2200	27.3	9.9	73.1/1100	32.4	5.9	EM
N/A	3CD1-D	34.3/3000	29.6	14.7	72.8/1200	33.1	6.6	EM
N/A	3CD1-I	33.1/2900	29.4	14.1	72.8/1200	33.1	6.6	EM
N/A	3CD1-K	31.9/2800	29.2	13.5	72.8/1200	33.1	6.6	EM
N/A	3CD1-L	30.7/2700	29.1	13.0	73.6/1200	33.5	6.6	EM
N/A	3CD1-M	29.6/2600	29.0	12.5	72.5/1200	32.5	6.4	EM
N/A	3CD1-N	28.4/2500	28.3	11.7	72.2/1300	32.4	7.0	EM
N/A	3CD1-P	27.2/2400	28.1	11.1	72.8/1300	32.8	7.0	EM
N/A	3CD1-Q	26.0/2300	27.9	10.6	73.4/1300	33.1	7.1	EM