

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-119-4
Relating to Certification of New Motor Vehicles

SOUTH BAY 4 WHEEL DRIVE

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That South Bay 4 Wheel Drive exhaust emission control systems for 1977 model-year light duty trucks are certified for the engine family described below:

- Engine Family: 20R(TC)
- Engine: 133.6 CID
- Transmission: 4-Speed Manual, or 5-Speed Manual
- Exhaust Emission Control Systems: Oxidation Catalyst, Exhaust Gas Recirculation, Air Injection, Engine Modification.

- Models: Toyota Hilux Pickup Truck-1 - Baja 4-Wheel Drive Conversions
- Toyota Hilux Pickup Truck-2 - Baja 4-Wheel Drive Conversions

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1977 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
20R(TC)	0.3	8	1.8


BE IT FURTHER RESOLVED: That this certification is contingent upon South Bay 4 Wheel Drive affixing a permanent catalyst overheat warning label on the driver's sun-visor of all catalyst-equipped vehicles. This label must be approved by the Executive Officer.

BE IT FURTHER RESOLVED: That this certification is also contingent upon South Bay 4 Wheel Drive listing in the owner's manual the operating cautions associated with a catalyst-equipped vehicle. This listing must be approved by the Executive Officer.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 25 day of February, 1977.



G. C. Hass, Chief
Vehicle Emissions Control Division

Passenger Cars Light-Duty TrucksManufacturer South Bay 4 Wheel Drive Executive Order No. A- 119-4 Page 1 of 1Engine Family 20R(TC) Engine (CID) 133.6 Engine Code _____Emission Control System AI-EGR-EM-OC +10%(A/C) Yes No

Vehicle Models (If Coded see attachment)	Trans	Inertia Weight	Distributor	Fuel System	EGR System	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
			Type	Type		
			Mfgr. Part Number	Mfgr. Part Number	Part No. Service**	
Hilux Pickup Truck Pickup Truck 2 (All with Baja 4-Wheel Drive Conversions)	M/T4 M/T5	3000	Nippondenso 19100- 38020	Aisan Koqyo 21100- 38160	25620- 38100	(1) 8°BTDC@800RPM in neutral; vacuum line remain connected to distributor. (2) Lean Drop idle (See attached sheet) (3) 800 RPM in neutral

Comments ** No Service

Shift speed (1 to 2) 10 mph, (2 to 3) 20 mph, (3 to 4) 30 mph, (4 to 5) 40 mph

Axle ratio: 4.111

Date of Issue: 18 January 1977

AbbreviationsDistributor

C-Centrifugal Advance

V-Vacuum Advance

VR-Vacuum Retard

TI - Transistorized Ignition

EI-Electronic Ignition

Fuel System

EFI, FI

nV-nVenturi Carburetor

VV-Variable Venturi

Exhaust Emission Control System

AI-Air Injection

CAI-Catalyst Air Injection

EFI-Electronic Fuel Injection

EGR-Exhaust Gas Recirculation

EM-Engine Modification

EFE-Early Fuel Evaporation

ESAC-Electronic Spark Advance
Control

FI-Fuel Injection

OC-Oxidation Catalyst

PAI-Pulse Air Injection

RC-Reduction Catalyst

TR-Thermal Reactor

TWC-Three Way Catalyst

λ-Air Fuel Ratio Sensor

*ServiceI-Inspect, repair/replace
as needed

R-Replace

Toyota Lean Idle Drop Method

Attachment to Specialized Automotive Engineering's Supplemental Data Sheet

Engine Family: 20 R(TC)

Page 1 of 1

All adjustment must be made with engine at normal operating temperature.

- (1) Coolant temperature 190°F
- (2) Choke valve fully open

Before adjusting the idle mixture, the basic timing, 8° BTDC @ 800 RPM (manual transmission(M/T) or 8° BTDC @ 850 RPM, (automatic transmission (A/T) and idle speed, 800 RPM (M/T) or 850 RPM (A/T), must be within specifications. All adjustments must be made in neutral with all accessories (wipers, heater, air conditioning, etc.) off.

Adjust the idle mixture screw to obtain the maximum engine speed (engine RPM). Readjust idle speed screw to return engine speed to 870 RPM (M/T) or 920 RPM (A/T). Repeat attempt to increase the engine speed by adjusting idle mixture screw and again readjusting the engine speed back to 870 RPM (M/T) or 920 RPM (A/T). When it is no longer possible to increase engine speed by adjusting the mixture screw, the idle mixture screw must be adjusted until the idle speed at 800 RPM (M/T) or 850 RPM (A/T) is obtained.