

State of California  
Air Resources Board

EXECUTIVE ORDER A-17-32  
Relating to Certification of New Motor Vehicles

AMERICAN MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That American Motors Corporation exhaust emission control systems for 1977 model-year passenger cars are certified for the engine family described below:

Engine Family: I-2C  
Engine: 258 CID  
Transmission: 3-Speed Automatic  
Exhaust Emissions Control Systems: Air Injection, Exhaust Gas Recirculation,  
Oxidation Catalyst

Models: Pacer Sedan  
Pacer Wagon  
Hornet 2-Door Sedan  
Hornet 4-Door Sedan  
Hornet Hatchback  
Hornet Wagon  
Gremlin

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1977 model vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
I-2C	0.30	5.2	1.1


BE IT FURTHER RESOLVED: That this certification is contingent upon American Motors Corporation affixing a permanent catalyst overheat warning label on the driver's sun-visor of all catalyst-equipped vehicles. This label must be approved by the Executive Officer.

BE IT FURTHER RESOLVED: That this certification is also contingent upon American Motors Corporation listing in the owner's manual the operating cautions associated with a catalyst-equipped vehicle. This listing must be approved by the Executive Officer.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 13 day of August, 1976.



G. C. Hass, Chief  
Division of Vehicle Emissions Control

Manufacturer AMERICAN MOTORS CORPORATION Executive Order No. A-17-32 Page 1 of 1  
 Engine Family I-2C Engine (CID) 258 Engine KA2C-3D-2 & Code KA2C-3D-1  
 Emission Control System AI, EGR, OC +10%(A/C) Yes  No

Vehicle Models (If Coded see attachment)	Trans	Inertia Weight	Distributor Type : EI, C, V, TCSA Mfgr. Part Number	Fuel System Type : 1-2V Mfgr. Part Number	EGR System: Backpressure Sensitive Part No. Service*	Tune-Up Specification
Pacer Hornet, Gremlin  (KA2C-3D-2)	AYT3 (3.08) rear axle ratio)	3500	3229719, which is Prestolite IDJ-4002F #106  or  <u>3230401</u>	Carter 8117	Eaton G61353 (EGR Valve- Backpressure Sensor Integral System), which is 3230176.  I-30,000 mi.  or  Eaton G61363, which is 3230181. ----- I-30,000 mi.	(1) 8° + 2° BTDC @ 500 RPM in "drive" with vacuum disconnected  (2) 25 RPM Lean Drop  (3) 700 RPM + 100 RPM in "drive"
Pacer, Hornet, Gremlin  (KA2C-3D-2)				Carter 8117SA =====	Eaton G61351 =====	

Comments: Running Change No. 77-10, 1 November, 1976  
R/C 77-16C, 12 May, 1977, adds RFI suppressing distributor

Date of Issue: August 11, 1976  
12 May, 1977, R/C 77-25C adds engine code KA2C-3D-2

- |                          |                                       |  |
|--------------------------|---------------------------------------|--|
| Abbreviations            | Exhaust Emission Control System       | TCSA-Transmission Controlled Spark Advance |
| Distributor              | AI-Air Injection                      | OC-Oxidation Catalyst                      |
| C-Centrifugal Advance    | CAI-Catalyst Air Injection            | PAI-Pulse Air Injection                    |
| V-Vacuum Advance         | EFI-Electronic Fuel Injection         | RC-Reduction Catalyst                      |
| VR-Vacuum Retard         | EGR-Exhaust Gas Recirculation         | TR-Thermal Reactor                         |
| HEI-High Energy Ignition | EM-Engine Modification                | TWC-Three Way Catalyst                     |
| EI-Electronic Ignition   | EFE-Early Fuel Evaporation            | λ-Air Fuel Ratio Sensor                    |
| Fuel System              | ESAC-Electronic Spark Advance Control | *Service                                   |
| EFI, FI                  | FI-Fuel Injection                     | I-Inspect, repair/replace as needed        |
| nV-nVenturi Carburetor   |                                       |  |
| VV-Variable Venturi      |                                       |  |