State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-30-7 Relating to Certification of New Motor Vehicles

AUDI NSU AUTO UNION AG

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That Audi NSU Auto Union AG exhaust emission control systems for 1977 model-year passenger cars are certified for the engine family described below:

Engine Family: Audi 80 Cl

Engine: 97 CID

Transmission: 3-Speed Automatic and 4-Speed Manual

Exhaust Emissions Control Systems: Engine Modification, Exhaust Gas

Recirculation, Fuel Injection,

Oxidation Catalyst

Models: Audi Fox Sedan

Audi Fox Station Wagon

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1977 model vehicles:

Engine Family	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	
	Grams per Mile	Grams per Mile	Grams per Mile	
Audi 80Cl	0.12	1.0	1.1	

BE IT FURTHER RESOLVED: That this certification is contingent upon Audi NSU Auto Union AG affixing a permanent catalyst overheat warning label on the driver's sun-visor of all catalyst-equipped vehicles. This label must be approved by the Executive Officer.

BE IT FURTHER RESOLVED: That this certification is also contingent upon Audi NSU Auto Union AG listing in the owner's manual the operating cautions associated with a catalyst-equipped vehicle. This listing must be approved by the Executive Officer.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 24 day of September, 1976.

G. C. Hass, Chief

Division of Vehicle Emissions Control

Engine Fami				Engine (CID		CodeYG A/C) YesX	See commer
Vehicle Models (If Coded see attachment)		Inertia Weight	Type : C,V, VR. Mfgr.	Type: FI	Venturi Vac- uum Control- Part No. led	Tune-Up Specificati (1) Basic Timing (2) Idle Mixture (3) Idle Speed	on
Audi Fox Sedan Audi Fox Station Wagon	A/T3 (3.91 axle ratio) M/T4 (4.11 axle ratio)	2,500 (See comments	Bosch 0 231) 176 057, which is VW 049 905 205A	Mixture control Unit 049 133 353.D, consisting of Bosch 0 438 120 008 Air Flow Sensor; Bosch 0 438 100 007 Fuel Distributor; Bosch 0 438 140 011 warm-up Regulator; and 0 280 170 401 Starting Valve		(1) 3° + 1° ATDC at idle speed with vacuum connected (2) 0.3% maximum at tail- pipe (3) 925+75 in neu- tral with head- lamps on high beam (Label No. 849 000 331 Q)	
Comments: Actua Manua Date of Issue:	1 transm	mission s	shift points	: 15 -25 - 4		Je for Ayo.	

V-uum Advance VR-Vacuum Retard HEI-High Energy Ignition EI-Electronic Ignition Fuel System EFI, FI nV-nVenturi Carburetor

CAI-Catalyst Air Injection EFI-Electronic Fuel Injection EGR-Exhaust Gas Recirculation EM-Engine Modification EFE-Early Fuel Evaporation ESAC-Electronic Spark Advance Control Et Funt Injection

PAI-Pulse Air Injection RC-Reduction Catalyst TR-Thermal Reactor TWC-Three Way Catalyst λ-Air Fuel Ratio Sensor *Service I-Inspect, repair/replace