

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-16-207  
Relating to Certification of New Motor Vehicles

MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Mazda Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: TTK1.6VJG2EK Displacement: 1.6 Liters (98 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Warm-Up Three Way Catalytic Converter
- Three Way Catalytic Converter
- Heated Oxygen Sensors (two)
- Exhaust Gas Recirculation
- Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gas</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.125	3.4	0.4	0.015	10.0
100,000	0.156	4.2	0.6	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1996 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are (Values in parentheses are actual certification values before rounding off.):

<u>Miles</u>	<u>Non-Methane Organic Gas</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.068	0.6	0.0 (0.04)	0.001	2.7
100,000	0.073	0.7	0.0 (0.04)	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BBE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 19<sup>th</sup> day of July 1995.



R. B. Summerfield  
Assistant Division Chief  
Mobile Source Division

1996AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Mazda Motor Corporation Engine Family TTK1.6VJG2EK  
 Evap Family TTK1065BYMA1  
 All Eng Codes in Eng Fam: CA X 49S      50S       
 Stds. Type : CA Tier-1      AB965      TLEV X LEV      ULEV      ZEV      US EPA Tier 1       
 Evap Std: 50K  
 Veh. Calss: LDV  
 Fuel Type(s): Gasoline  
 Service Accum: Std AMA  
 NMOG Test Procedure: Std  
 Hybrid: N/A  
 Engine Config : I-4  
 Valves/Cly. 4  
 Engine : Front X Mid.      Rear     

In-Use Exh Std: Full in Use  
 Single Cert Std for Multi-Class Eng Fam: N/A  
 Emission Test Fuel(s): Phase II  
 R/L Test Procedure: N/A  
 APU Cycle: One Spark N/A  
 Displacement 1.6 Liters (97.5) Cu. inches  
 Rated HP 105 @ 6200 RPM  
 Drive: FWD X RWD      4WD-FT      4WD-PT     

Exhaust ECS & Special Feature (incl. CARB, MFI, etc.)  
 (Use abbreviations per SAE J1930 MAY91)

(2) HO2S/TWC/WU-TWC/EGR/SFI

Engine Code (Cert, Std.)	Vehicle Model (if coded see attachment)	Trans. Type A-automatic M-manual	ETW	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalyst Part No.
2B6D2AA6	Mazda MX-3	M5	2750	6.0	Distributor: B6BF	EGR Control Valve: B6BF	Monolith Converter: B6GD(Pre.) B6DE (Main)
2B6D2AAT				6.6 **	ECU: B6GD		
2B6DTAA6		L4		6.0	Distributor: B6BF		
2B6DTAAT				6.6 **	ECU: B6GF		

Revisions:  
1290

Issue date:	April 28, 1995				
Rev. No.					
Date					

\*\* with A/C