

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-86-196
Relating to Certification of New Motor Vehicles

MITSUBISHI MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Mitsubishi Motors Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: TMT3.0V8GFEK Displacement: 3.0 Liters (181.4 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Exhaust Gas Recirculation
- Dual Heated Oxygen Sensors (two)
- Dual Warm Up Three-Way Catalytic Converters
- Three Way Catalytic Converter
- Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (in-use compliance standards in parentheses) for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Hydrocarbons</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> | <u>Carbon Monoxide (20°F)</u> |
|--------------|---------------------------------|------------------------|------------------------|-------------------------------|
| 50,000 | 0.25 (0.32) | 3.4 (5.2) | 0.4 (0.4) | 10.0 (10.0) |
| 100,000 | 0.31 (n/a) | 4.2 (n/a) | 0.6 (n/a) | n/a |

The certification exhaust emission values for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Hydrocarbons</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> | <u>Carbon Monoxide (20°F)</u> |
|--------------|---------------------------------|------------------------|------------------------|-------------------------------|
| 50,000 | 0.14 | 1.7 | 0.1 | 5.2 |
| 100,000 | 0.17 | 2.0 | 0.1 | n/a |

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 20 percent of the manufacturer's projected sales of 1996 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".


BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 30th day of August 1995.



R. B. Summerfield
Assistant Division Chief
Mobile Source Division

**1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM DUTY VEHICLES**

Manufacturer: Mitsubishi Motors Corp Exh Engine Family: TMT3.CVBGFEEK(3.CB-S)
 Evap Engine Family: TMT1054AYMAD(Diamante) & TMT1058BYMAE(Stealth)
 All Engine Codes in Eng Fam: CA__ 49S__ 50S_X__ AB 965__
 Exh Std: CA Tier-1_X__ TLEV__ LEV__ ULEV__ ZEV__ ; US EPA Tier-1_X__
 Evap Std: 50K_X__ Useful Life with R/L__ In-Use Std: Full In-Use__ Alt In-Use_X__
 Veh Class(es): PC_X__ LDT1__ LDT2__ MGVI__ MDV2__ MDV3__ MDV4__ MDV5__
 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, ..., MDV4)
 Fuel Type(s): Dedicated_X__ Flex-Fuel__ Dual-Fuel__ Bi-Fuel__ Gasoline_X__
 Diesel__ CNG__ LNG__ LPG__ M85__ Other (specify)_____
 Emis Test Fuel: IndoX__ Ph2__ CNG__ LPG__ M85__ Other (specify)_____
 Diesel: 13 CCR 2282__ 40CFR 86.113-90__ 40CFR 86.113-94__
 Service Accum: Std AMA__ Mod AMA__ Mfr ADP__ Other (specify) AMA4 (Sec 20.07)
 NMOG Test Proc: N/A_X__ Std__ Equip__ R/L Test Proc: SHED__ Pt Source__
 Hybrid: Type A__ B__ C__ APU Cycle (e.g., Otto, Diesel, Turbine)_____
 Engine Configuration: V6 Displacement: 3.0 Liters / 181.4 Cubic Inches
 Valves per Cylinder: 2 Rated HP: 161@5500RPM(Stealth), 172@5500RPM(Diamante)
 Engine: Front_X__ Mid__ Rear__ Drive: FWD_X__ RWD__ 4WD-FT__ 4WD-PT__
 Exhaust ECS (eg., EGR, MPI, TC, CAC): EGR+2HO2S(2)+2WUTWC+TWC+SEI
 (abbreviations per SAE J1930 SEP91)

| Engine Code (also list CAL/FED/BOTH) | Vehicle Models (if coded see attachment) | Trans. Type *1 | ETW | DPA or RLHP | Ignition (ECM/PCM) Part No. | EGR System Part No. | Catalytic Converter Part No. |
|--|--|----------------------|------|-------------------|--|--------------------------------------|---|
| ABM(BOTH) | Dodge Stealth | M5 | 3500 | 7.0 | Distributor: MD320732 (T5T43071) | EGR Valve: MD199283 (K5T58980) | Front(R): MR127572 |
| BM(BOTH) | | | | 6.4 | | | ECM: MD319637 (E2T61374) |
| ABA(BOTH) | | L4 | 3625 | 6.9 | ECM: MD319634 (E2T61273) | Solenoid: MD161746 (K5T49681) | Rear: MB906265 (K4) |
| BA(BOTH) | | | | 6.3 | | | |
| ABA-J(BOTH) | Mitsubishi Diamante | L4 | 3875 | 7.5 | Distributor: MD320732 (T5T43071) | EGR Valve: MD153340 (K5T56471) | Front(R): MR127572 |
| | | | | | ECM: MD319634 (E2T61273) | Solenoid: MD161746 (K5T49681) | Front(L): MR126693 |
| | | | | | | | Rear: MB925699 (Q2) or XR266347 \$ |

*1: M-Manual transmission
 L-Automatic transmission with lock-up