

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-254-40
Relating to Certification of New Motor Vehicles

HYUNDAI MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Hyundai Motor Company exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: THY1.5VJG1FK Displacement: 1.5 Liters (91.2 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Heated Oxygen Sensors (two)
- Three Way Catalytic Converter
- Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (in-use compliance standards in parentheses) for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.25 (0.32)	3.4 (5.2)	0.4 (0.4)	10.0 (10.0)
100,000	0.31 (n/a)	4.2 (n/a)	0.6 (n/a)	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.16	1.0	0.2	5.9
100,000	0.17	1.1	0.2	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 20 percent of the manufacturer's projected sales of 1996 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".


BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 5 day of July 1995.


R. B. Summerfield
Assistant Division Chief
Mobile Source Division

1996 AIR RESOURCES SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer : HYUNDAI MOTOR CO. Exh Eng Fam : THY1.5VIG1FK Evap Fam : THY1033BYM03
 All Eng Codes in Eng Fam : CA X 49S 50S AB965
 Exh Std : CA Tier-1 X TLEV LEV ULEV ZEV ; US EPA Tier-1
 Evap Std : 50K X Useful life with R/L In-Use Exh Std : Full In Use Alt In Use X
 Veh Class(es) : PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5
 Single Cert Std for Multi-Class Eng Fam : N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
 Fuel Type(s) : Dedicated Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel
 CNG LNG LPG M85 Other (specify)
 Emiss Test Fuel(s) : Indo X PH2 CNG LPG M85 other (specify)
 Diesel : 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-90
 Service Accum : Std AMA Mod AMA X Mfr ADV OTHER (SPECIFY)
 NMOG Test procedure : N/A X Std Equiv R/L Test Proc : SHED Pt Source
 Hybrid : Type A B C , APU Cycle (e.g., Otto, Diesel, Turbine)
 Engine Configuration : I-4 Displacement : 1.5 / Liters 91.2 / Cubic Inches
 Valves Per Cylinder : 4 Rated HP : 98 @ 6000 RPM
 Engine : Front X Mid Rear Drive : FWD X RWD 4WD-FT 4WD-PT
 Exhaust ECS (e.g., MFI EGR., TC, CAC, : HO2S(2) + TWC + SFI +
 (use abbreviations per SAE J1930 SEP91)

Eng. Code (list CA/ 49ST/50ST)	Veh. Models (IF Coded see Attachmt.)	Trans. Type: A-Auto. M-Man.	Equiv. Test Weight	DPA or RLHP	Ign. Sys. (ECM/PCM) part No.	EGR Syst. Part No.	Catalyst Part No.
ACM5-P, /CM5-P, ACM5-S, /CM5-S (C/A)	ACCENT (4DR SEDAN)	M5	2500	SEDAN(4DR) : 6.8 SPORTY(3DR) : 6.6	39110-26010 (9030930013)	N/A	28950-22070 (H1CC18), 28950-22075 (HOCC18),
ACL4-P, /CL4-P, ACL4-S, /CL4-S (CA)	& (3DR SPORTY)	L4	↑	SEDAN(4DR) : 6.5 SPORTY(3DR) : 6.2	↑	N/A	↑

Issued : 7-1-95
Revised :