

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Divisions 25.5 and 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following on-road motor vehicles with a manufacturer's GVWR over 10,000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	VEHICLE FAMILY NAME	VEHICLE TYPE	VEHICLE SERVICE CLASS	SUBCATEGORY (Vehicle Size / Engine Cycle / Duty Cycle)	VEHICLE MAKE & MODELS
2021	MPCR2VOCVC2K	Vocational	Medium HDV	Medium HDV/Diesel/Urban	Peterbilt: Model 520, Model 348, Model 330, Model 367, Model 579, Model 537, Model 220, Model 567, Model 536, Model 389, Model 567, Model 535, Model 548, Model 337, Model 365, Model 220, Model 579 Kenworth: T270, K270, T180, T380, T470, T170, T280, T440, W900, T800, T480, W990, T880, T680, T370, K370

EMISSION CONTROL SYSTEMS

LRRD, LRRS, LRRR, ITR, WR, VSL, TPMS, VSLE

*=not applicable; VSL = Vehicle speed limiter; VSLS = "Soft-top" vehicle speed limiter; VSLE = Expiring vehicle speed limiter; VSLED = Vehicle speed limiter with both "soft-top" and expiration; ITR = Engine shutoff; IRT5 = Engine shutoff after 5 minutes or less of idling; IRTE = Expiring engine shutoff; LRRR = Low rolling resistance tires (all); LRRD = Low rolling resistance tires (drive); LRRS = Low rolling resistance tires (steer); ATS = Aerodynamic side skirt and/or fuel tank fairing; ARF = Aerodynamic roof fairing; ARFR = Adjustable height aerodynamic roof fairing; TGR = Gap reducing tractor fairing (tractor to trailer gap); ADVH = Vehicle includes advanced hybrid technology components; ADVO = Vehicle includes other advanced-technology components (i.e., non-hybrid system); INV = Vehicle includes innovative (off-cycle) technology components; ATI = Automatic tire inflation system; TPMS = Tire pressure monitoring system; WR = Weight Reduction

Shown below are the CO₂ Greenhouse Gas Exhaust Emission Standard (STD) in g/ton-mile and/or the CO₂ Family Emission Limit(s) (FEL) of the listed vehicle family in g/ton-mile as applicable under 17 CCR 95663:

GVWR (pounds)	STD [CO ₂ (in g/ton-mile)]	Highest Projected FEL [CO ₂ (in g/ton-mile)]	Lowest Projected FEL [CO ₂ (in g/ton-mile)]
26,000 < GVWR ≤ 33,000	265	562	171

BE IT FURTHER RESOLVED: The manufacturer has demonstrated certification compliance with the Greenhouse Gas Emission Standards as specified in Title 17 CCR 95663 and the incorporated "California Greenhouse Gas Exhaust Emission Standards and Test Procedures for 2014 and Subsequent Model Heavy-Duty Vehicles" (HDV Test Procedures) adopted October 21, 2014 as last amended June 27, 2019.

BE IT FURTHER RESOLVED: For the listed air conditioning platform(s) in the attachment the manufacturer has demonstrated certification compliance with the AC Leakage Standard specified in 17 CCR 95663(a)(1)(B)7 and Section 1037.115 of the incorporated "California Greenhouse Gas Exhaust Emission Standards and Test Procedures for 2014 and Subsequent Model Heavy-Duty Vehicles" (HDV Test Procedures) adopted October 21, 2014, as last amended June 27, 2019.

BE IT FURTHER RESOLVED: For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: The listed vehicle models on this Executive Order are certified conditionally on the manufacturer providing responses for information in a timely manner, and the California Air Resources Board approving that information, that are compliant with the California Greenhouse Gas Exhaust Emissions and Test Procedures for 2014 and Subsequent Model Heavy-Duty Vehicles (last amended June 27, 2019), as described in the manufacturer's request for Conditional Executive Order dated January 12, 2021.



Failure to provide the above information within 90 days of the effective date of this Executive Order, or failure of the information to be approved by the California Air Resources Board may be cause for the Executive Officer to rescind this conditional certification, in which case all vehicles covered under this conditional certification would be deemed uncertified and subject to a civil penalty of up to \$40,050 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 26th day of January 2021.

Allen Lyons, Chief
Emissions Certification and Compliance Division

A/C PLATFORM SUMMARY TABLE

Vehicle family		Date	EO	
MPCR2VOCVC2K		01/21/21	A-384-0101	
A/C Platform ID	Refrigerant Type	Refrigerant Capacity (g)	STD (HFC (g/year))	Leak Rate (HFC (g/year))
NOIDLE 0000610 SLEEPER_NI	R134a	2353	35.3	17.4
NOIDLE 0000810 SLEEPER_NI	R134a	2353	35.3	17.5
NOIDLE 0000990 SLEEPER_NI	R134a	2353	35.3	17.5
NOIDLE 0005671 SLEEPER_NI	R134a	2353	35.3	22.0
NOIDLE 0005791 SLEEPER_NI	R134a	2353	35.3	22.0
ROOF-MTD-CONDENSER0000800	R134a	1588	23.8	20.7
STANDARD 0000170	R134a	1361	20.4	15.9
STANDARD 0000180	R134a	879	13.2	13.1
STANDARD 0000270	R134a	1361	20.4	15.9
STANDARD 0000280	R134a	879	13.2	13.1
STANDARD 0000301	R134a	953	14.3	13.4
STANDARD 0000370	R134a	1361	20.4	15.9
STANDARD 0000410	R134a	1616	24.2	18.0
STANDARD 0000500	R134a	1588	23.8	16.5
STANDARD 0000610	R134a	1474	22.1	12.0
STANDARD 0000610 SLEEPER	R134a	1758	26.4	13.2
STANDARD 0000800	R134a	1588	23.8	16.4
STANDARD 0000800 SLEEPER	R134a	1899	28.5	22.4
STANDARD 0000810	R134a	1474	22.1	12.1
STANDARD 0000810 SLEEPER	R134a	1758	26.4	13.3
STANDARD 0000900	R134a	1446	21.7	16.8
STANDARD 0000900 SLEEPER	R134a	1814	27.2	22.8
STANDARD 0000990	R134a	1474	22.1	12.1
STANDARD 0000990 SLEEPER	R134a	1758	26.4	13.3
STANDARD 0002201	R134a	953	14.3	13.4
STANDARD 0003251	R134a	1315	19.7	16.3
STANDARD 0003301	R134a	1315	19.7	16.3
STANDARD 0003371	R134a	1315	19.7	16.3
STANDARD 0003481	R134a	1315	19.7	16.3
STANDARD 0003651	R134a	1270	19.1	16.8
STANDARD 0003651 SLEEPER	R134a	1950	29.3	19.3
STANDARD 0003671	R134a	1270	19.1	16.8
STANDARD 0003671 SLEEPER	R134a	1950	29.3	19.3
STANDARD 0003891	R134a	1315	19.7	16.8
STANDARD 0003891 SLEEPER	R134a	1474	22.1	19.3
STANDARD 0005201	R134a	1315	19.7	19.7
STANDARD 0005671	R134a	1474	22.1	12.8
STANDARD 0005671 SLEEPER	R134a	1758	26.4	14.0
STANDARD 0005791	R134a	1474	22.1	12.8
STANDARD 0005791 SLEEPER	R134a	1758	26.4	14.0