

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Divisions 25.5 and 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following on-road motor vehicles with a manufacturer's GVWR over 26,000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	VEHICLE FAMILY NAME	VEHICLE TYPE	SUBCATEGORY	VEHICLE MAKE & MODELS
2021	MDTN2TRACHHC	Tractor	Heavy-Haul Tractor	Freightliner: Cascadia; 113, 125, 116, 126 SD108, SD114, SD122 Western Star; 4700SB, 4700SF, 4900EX, 4900FA, 4900SA, 5700XE, 6900XD

EMISSION CONTROL SYSTEMS

ARF, ATS, LRRR, LRRD, LRRS, WR

*=not applicable; VSL = Vehicle speed limiter; VSLS = "Soft-top" vehicle speed limiter; VSLE = Expiring vehicle speed limiter; VSLE = Vehicle speed limiter with both "soft-top" and expiration; IRT5 = Engine shutoff after 5 minutes or less of idling; IRTE = Expiring engine shutoff; LRRR = Low rolling resistance tires (all); LRRD = Low rolling resistance tires (drive); LRRS = Low rolling resistance tires (steer); ATS = Aerodynamic side skirt and/or fuel tank fairing; ARF = Aerodynamic roof fairing; ARFR = Adjustable height aerodynamic roof fairing; TGR = Gap reducing tractor fairing (tractor to trailer gap); ADVH = Vehicle includes advanced hybrid technology components; ADVO = Vehicle includes other advanced-technology components (i.e., non-hybrid system); INV = Vehicle includes innovative (off-cycle) technology components; ATI = Automatic tire inflation system; TPMS = Tire pressure monitoring system; WR = Weight Reduction

Shown below are the CO₂ Greenhouse Gas Exhaust Emission Standard (STD) in g/ton-mile and/or the Family Emission Limit(s) (FEL) of the listed vehicle family in g/ton-mile as applicable under 17 CCR 95663:

STD [CO ₂ (in g/ton-mile)]	Highest Projected FEL [CO ₂ (in g/ton-mile)]	Lowest Projected FEL [CO ₂ (in g/ton-mile)]
52.4	59.7	48.3

BE IT FURTHER RESOLVED: The listed vehicle family is certified to the CO₂ Emission Standards for Heavy-Haul Tractors as specified in Section 1037.106 or to the Optional CO₂ Emission Standards for Tractors at or above 120,000 pounds GCWR specified in Section 1037.670 of the "California Greenhouse Gas Exhaust Emission Standards and Test Procedures for 2014 and Subsequent Model Heavy-Duty Vehicles" (HDV Test Procedures) adopted October 21, 2014, as last amended June 27, 2019.


BE IT FURTHER RESOLVED: The manufacturer has demonstrated certification compliance with the Greenhouse Gas Emission Standards as specified in Title 17 CCR 95663 and the incorporated "California Greenhouse Gas Exhaust Emission Standards and Test Procedures for 2014 and Subsequent Model Heavy-Duty Vehicles" (HDV Test Procedures) adopted October 21, 2014 as last amended June 27, 2019.

BE IT FURTHER RESOLVED: For the listed air conditioning platform(s) in the attachment the manufacturer has demonstrated certification compliance with the AC Leakage Standard specified in 17 CCR 95663(a)(2)(B)3 and Section 1037.115 of the incorporated "California Greenhouse Gas Exhaust Emission Standards and Test Procedures for 2014 and Subsequent Model Heavy-Duty Vehicles (HDV Test Procedures) adopted October 21, 2014, as last amended June 27, 2019.

BE IT FURTHER RESOLVED: For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), and 13 CCR 2035 et seq. (emission control warranty).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 12th day of January 2021.



Allen Lyons, Chief
 Emissions Certification and Compliance Division

A/C PLATFORM SUMMARY TABLE

Vehicle family	Date	EO
MDTN2TRACHHC	12/30/2020	A-395-0098

A/C Platform ID	Refrigerant Type	Refrigerant Capacity (g)	STD (HFC (g/year))	Leak Rate (HFC (g/year))
P4 116, 126 Day	R-134a	1305	19.6	9.4
P4 116,126 48"60"72"SLP	R-134a	1816	27.2	11.3
P4 116,126 48"60"72" w Park	R-134a	2497	37.5	16.5
P4 114,126 48"60"72"w TriPac	R-134a	2723	40.8	34.4
W4 121 Day with RMC	R-134a	2043	30.6	13.4
M2 Day	R-134a	1305	19.6	10.4
M2 Crew	R-134a	1476	22.1	13.8
24U 132 Day	R-134a	1419	21.3	10.2
24 U 132 slp 70	R-134a	1861	27.9	11.8
24 U 132 slp w NITE	R-134a	2484	37.3	13.3
WST Day Cab	R-134a	1532	23.0	10.5
WST Day Cab with Roof	R-134a	2202	33.0	17.3
WST Sleeper	R-134a	1759	26.4	19.9
WST Sleeper RestStar	R-134a	2198	33.0	21.5