Garph J.

(Page 1 of 2)

# State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER M-1-290 Relating to Certification of New Motorcycles

### KAWASAKI HEAVY INDUSTRIES, LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and,

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Kawasaki Heavy Industries, Ltd. exhaust emission control systems are certified as described below for four-stroke gasoline-powered motorcycles:

Engine Family	Displacement Cubic Centimeters	Class	Exhaust Emission Control Systems & Special Features
YKAXC1.20AAB	1199	Ш	Sequential Multiport Fuel Injection Pulsed Secondary Air Injection Oxidation Catalytic Converter

Vehicle models and transmissions are listed on the attachment. Production motorcycles shall be in all material respects the same as those for which certification is granted.

The following are the exhaust emission standards and exhaust certification emission values for this engine family. The designated hydrocarbons standard shall be listed on the permanent tune-up label:

andards	Hydrocarbons	Carbon	Monoxide
	(Certification)	(Standard)	(Certification)
		Grams per	Grams per
Kilometer	<u>Kilometer</u>	Kilometer	Kilometer
2.2	1.3	12	5
	(Designated) Grams per Kilometer	(Designated) (Ćertification) Grams per Kilometer Kilometer	(Designated) (Ćertification) (Standard) Grams per Kilometer Kilometer Kilometer

BE IT FURTHER RESOLVED: That the above-described certification is subject to the following terms, limitations and conditions:

The above designated hydrocarbons standard shall be the exhaust limit for this engine family during the model year and therefore cannot be redesignated by the manufacturer. It represents the hydrocarbons exhaust emission standard applicable to this engine family that shall be applied when determining compliance of any motorcycle within this engine family pursuant to Section 2101 of Title 13, California Code of Regulations. It will also be used to determine compliance with the above corporate average hydrocarbons standard as required per Section 1958(b), Title 13 of the California Code of Regulations.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That these motorcycles are found exempt from compliance with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this \_\_\_\_\_\_\_/4 day of December 1999.

For R. B. Summerfield, Chief Mobile Source Operations Division

E.O.#: M-1-290 Page: 6

Issued: NOV 0 1 1999 Revised:

Engine Family: YKAXC1.20AAB

## Motorcycle Model Summary Form

65. Model Designation	66. Worst Case	67. Disp. (cc)	68. Bore / Stroke (mm)	69. Basic Ignition Timing (degrees)	70 Power (kW)	71 Rated Speed (RPM)	72 Rated Torque (Nm)	73. Rated Speed (RPM)
ZX1200-A1	Yes	1199	83.0X55.4	10°/1000 rpm	131	9500	136	7500

65. Model Designation	74. EIM (kg)	75. Loaded Vehicle Weight Range (kg)	76 Road Load (nt)	77 Total Vehicle Mass (kg)	78 Full Weight with All Factory Options (kg)	79. Trans. Type	80 N/V
ZX1200-A1	380	376 ~ 385	151.7	243	305	M-6	36.69

€. 0.#: M-1-290 Page: 1

Issued: NOV 0 1 1999

Revised:

Date: 12/10/99

# **Motorcycle Engine Family Information Form**

2.	Certification Cont	ntact Person, address, phone, and		y	
	Jeffrey D. Shetler				104.74
	Kawasaki Motors		2004		
	Tel: 949-770-040	oad, Irvine, CA 92618-	2084 149-460-560	2	
		141.7	+2 +00-300		
3.	Model Year: 200	00	10.	Displacement:	1199cm <sup>3</sup>
4.	Process Code: New (new correction revision r/c f/f etc.)		11.	Number of Cylinde	ers: <u>4</u>
5.	(new, correction, revision, r/c, f/f. etc.)  Engine Family: YKAXC1.20AAB  50s Engine Code:  49s Engine Code:  Calif. Engine Code: ZXT20A-AC1		12.	Cylinder Arrangen	nent: <u>Inline-4</u>
٠.			13.	Cylinder Head Co	onfiguration: <u>DOHC</u>
			14.	Type of Cooling:	Liquid
6.	Emission Control System: <u>SFI+PAIR+OC</u>		<u>C</u> 15.	Combustion Cycle	: 4
7.	Calif. Designated Standard: 2.2 gm/km		16.	16. Method of Aspiration: Natural	
3.	Projected Annual	The second of th	17.	Fuel System: Fue	I Injected
3.		The second of th			
	New Technology	Yes X No	18.	Fuel System: _Fue Number of Catalyti	
	New Technology If yes, cite the cor	Yes X No respondence or reference	18.		
	New Technology	Yes X No respondence or reference	18.		
	New Technology If yes, cite the cor	Yes X No respondence or reference	18.		
).	New Technology If yes, cite the corsubmittal docu	Yes X No respondence or reference ument:	18.	Number of Catalyti	c Converters: 1
Э.	New Technology If yes, cite the corsubmittal documents	Yes X No respondence or reference iment:	18.		
). 19.	New Technology If yes, cite the corresubmittal docu  Adjustable Paramet Parameter(s)	Yes X No respondence or reference ament:  ters:  Adjustable Range	Tamper F	Number of Catalyti  Resistance Method (or NA)  um cap is placed	c Converters: 1
9. Air	New Technology If yes, cite the corsubmittal docu  Adjustable Paramet Parameter(s)  adjust on ttle body	Yes X No respondence or reference ament:  ters:  Adjustable Range (or NA)	Tamper F	Number of Catalyti Resistance Method (or NA)	C Converters: 1  Method Approved
Air	New Technology If yes, cite the corresubmittal docu  Adjustable Paramet Parameter(s)	Yes X No respondence or reference ament:  ters:  Adjustable Range (or NA)	Tamper F	Number of Catalyti  Resistance Method (or NA)  um cap is placed	C Converters: 1  Method Approved
Air hro	New Technology If yes, cite the corsubmittal docu Adjustable Parameter Parameter(s) adjust on ttle body /Fuel Ratio)	Yes X No respondence or reference ment:  Adjustable Range (or NA)  NA	Tamper F	Number of Catalyti  Resistance Method (or NA)  um cap is placed	C Converters: 1  Method Approved
Air hro Air	New Technology If yes, cite the corsubmittal docu Adjustable Parameter Parameter(s) adjust on ttle body /Fuel Ratio)	Yes X No respondence or reference ament:  ters:  Adjustable Range (or NA)	Tamper F an aluming over the ac	Number of Catalyti  Resistance Method (or NA)  um cap is placed	C Converters: 1  Method Approved
Air hro Air	New Technology If yes, cite the corsubmittal documental	Yes X No respondence or reference ment:  Adjustable Range (or NA)  NA  ssion Control Systems:	Tamper F an aluming over the ac	Number of Catalyti  Resistance Method (or NA) um cap is placed djusting screw	Method Approved  Carry over
9. Air hro Air	New Technology If yes, cite the corsubmittal docu  Adjustable Paramet Parameter(s)  adjust on ttle body /Fuel Ratio)  AECDs In the Emisaust System	Yes X No respondence or reference ment:  Adjustable Range (or NA)  NA	Tamper F an aluming over the ac	Number of Catalyti  Resistance Method (or NA) um cap is placed djusting screw	Method Approved  Carry over  Sealed loop
9. Air hro Air	New Technology If yes, cite the corsubmittal docu  Adjustable Paramet Parameter(s)  adjust on ttle body /Fuel Ratio)  AECDs In the Emisaust System	Yes X No respondence or reference ment:  Adjustable Range (or NA)  NA  ssion Control Systems:	Tamper F an aluming over the ac	Number of Catalyti  Resistance Method (or NA) um cap is placed djusting screw	Method Approved  Carry over
Air hro Air	New Technology If yes, cite the corsubmittal docu  Adjustable Paramet Parameter(s)  adjust on ttle body /Fuel Ratio)  AECDs In the Emisaust System	Yes X No respondence or reference ment:  Adjustable Range (or NA)  NA  ssion Control Systems:	Tamper F an aluming over the ac	Number of Catalyti  Resistance Method (or NA) um cap is placed djusting screw	Method Approved  Carry over  Sealed loop
Air hro Air 20.	New Technology If yes, cite the corsubmittal docu  Adjustable Paramet Parameter(s)  adjust on ttle body /Fuel Ratio)  AECDs In the Emisaust System	Yes X No respondence or reference ment:  Adjustable Range (or NA)  NA  ssion Control Systems:	Tamper F an aluming over the ac	Number of Catalyti  Resistance Method (or NA) um cap is placed djusting screw	Method Approved  Carry over  Sealed loop

Reviewed by: La

E-0-#: M-1-290 Page: 4 Issued: NOV 0 1 1899

Revised:

Engine Family: YKAXC1.20AAB

## **Motorcycle Test Information Form**

<ul><li>29.</li><li>30.</li><li>31.</li><li>32.</li><li>33.</li></ul>	Test Information  Vehicle ID: _JE  Service Accumul  Maximum Rated  Displacement:	CAZX9A18YA000004  ation Duration:15000  Power:131 kW @ 95  1199cc  :Indolene: 95 ~ 99 RON	(km) 500_RPM	37. 38. 39.	Road Load:151.7 Inertia Mass:380  N/V:36.69  EVAP. Bench Test I Date:2/23/11  Reference:8  Unscheduled Mainten  If yes, Vehicle Log p	Method Approved 983 4ARB-03 nance: Yes _X	
		n Deterioration Factors:		Emissi	ion Values		
			НС	Emissi	ion Values		
	Exhaust Emissio	n Deterioration Factors:		Emiss			
	Exhaust Emissio	n Deterioration Factors:  System Kilometers	HC	Emissi	CO	Check one:	
	Exhaust Emissio Test Number	Note of the section o	HC 1.24	Emissi	CO 4.5		- X
	Exhaust Emissio  Test Number  1 2	System Kilometers 3512 6012	HC 1.24 1.61	Emissi	CO 4.5 4.0	Regular DF	X
	Exhaust Emissio  Test Number  1  2  3	System Kilometers 3512 6012 6042	HC 1.24 1.61 1.17	Emissi	CO 4.5 4.0 5.9	Regular DF Modified DF	
	Exhaust Emissio  Test Number  1  2  3  4	System Kilometers 3512 6012 6042 12012	HC 1.24 1.61 1.17 1.62	Emissi	CO 4.5 4.0 5.9 6.0	Regular DF	nicle

HC = 1.4071

 $HC = 1.4887 \quad CO = 5.0614$ 

CO = 4.9096

42	r	* *	77	D 1.
43.	EM	ISSIOI	1 lest	Results:

Interpolated Values at 15000 km?

Extrapolated Values at 30000 km:

Official Test Results		Test 1	Test 2	Test 3	Test 4
g/km	СО	4.6			
g/km	CO <sub>2</sub>	149.1			
g/km	HC	1.24			
g/test	Evap.	1.060			

	Deterioration Factors
(X)	1.031
(X)	1.058

0.047

Certification Levels:

g/km	CO	(5)		
g/km	HC C	1.3		THE STATE
g/test	Evap.	1.107		

E.O. #: M-1-290 Page: 5

Issued: NCV 0 1 1833

Revised:

Engine Family: YKAXC1.20AAB

### **Evaporative Emission Information**

- 45. Evaporative Family: YKAXE17.0A02
- 46. Number of Evap. Canisters: 1
- 47. Design Working Capacity: 17.0 g
- 48. Configuration: Sealed loop
- 49. Number of Storage Areas: 1
- 50. Fuel Reservoir Volume: 4.0 liters
- 51. Vent System Configuration: Sealed loop
- 52. Nominal Tank Capacity: 23.2 liters

- 53. Engine Displacement Class: III
- 54. Storage Medium Composition: Activated carbon
- 55. Evap. Canister Medium Volume: 400cm<sup>3</sup>
- 56. Evap. Family Sales: 350
- 57. Engine Code: ZGT20A-AC1
- 58. Evap. Emission Family Code: YKAXE17.0A02
- 59. Evap. Emission Family Group: CVK30-001
- 60. Overall Evap D.F. = 0.047 •Evap certification level = 1.107 g/test

#### Bench DF

- 61. Test Vehicle ID: JKAZG9A19GA000012
- 62. Test Results:

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3500	1.197
2	15000	1.269
3		
4	Deline Control of	
5		
6		
7		
Interpolated Va	dues at15000 km	: = 1.269
Extrapolated V	alues at <u>30000</u> km	: = <u>1.3629</u>
Bench Test D.F.	. = 0.094	

Regular DF:	X
Modified DF:	
If different vehic	cle
specify the vehic	ele ID

#### Vehicle DF

- 63. Test Vehicle ID: JKAZG9A19GA000012
- 64. Test Results.

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3662	1.153
2	4815	1.454
3	4844	1.158
4	10039	1.490
5	10069	1.144
6	15013	1.060
7		
Interpolated Va	alues at 15000 km:	= 1.1715
Extrapolated V	alues at 30000 km:	= 1.0164
Vehicle Test D.	F. = 0.000	