State of California AIR RESOURCES BOARD

EXECUTIVE ORDER M-2-355 Relating to Certification of New Motorcycles

HONDA MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and,

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Honda Motor Co., Ltd. exhaust emission control systems are certified as described below for four-stroke gasoline-powered motorcycles:

	Displacement		Exhaust Emission Control Systems
Engine Family	Cubic Centimeters	Class	& Special Features
YHNXCO.58AAA	583	III	Engine Modification

Vehicle models and transmissions are listed on the attachment. Production motorcycles shall be in all material respects the same as those for which certification is granted.

The following are the exhaust emission standards and exhaust emission certification values for this engine family. The designated hydrocarbons standard shall be listed on the permanent tune-up label:

Hydrocarbon St	tandards	Hydrocarbons	Carbon M	Monoxide
(Corporate Average) Grams per	(Designated) Grams per	(Certification) Grams per	(Standard) Grams per	
Kilometer	Kilometer	Kilometer	Kilometer	
1.0	0.9	0.7	12	9

BE IT FURTHER RESOLVED: That the above-described certification is subject to the following terms, limitations and conditions:

The above designated hydrocarbons standard shall be the exhaust limit for this engine family during the model year and therefore cannot be redesignated by the manufacturer. It represents the hydrocarbons exhaust emission standard applicable to this engine family that shall be applied when determining compliance of any motorcycle within this engine family pursuant to Section 2101 of Title 13, California Code of Regulations. It will also be used to determine compliance with the above corporate average hydrocarbons standard as required per Section 1958(b), Title 13 of the California Code of Regulations.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That these motorcycles are found exempt from compliance with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 16 day of June 1999.

R. B. Summerfield, Chief Mobile Source Operations Division

E.O. #: M-2-355 section: 7 Page:6 Issued: 1999/03/19

Revised:

Engine Family: YHNXC0.58AAA

Motorcycle Model Summary Form

65. Model Designation	66. Worst Case	67. Disp. (cc)	68. Bore / Stroke (mm)	69. Basic Ignition Timing (degrees)	70. Power (kW)	71. Rated Speed (RPM)	72. Rated Torque (Nm)	73. Rated Speed (RPM)
VT600C	Х	583	75.0 / 66.0	4.2(BTDC)	28.3	6500	50	3500
VT600CD		583	75.0 / 66.0	4.2(BTDC)	28.3	6500	50	3500
VT600CD2		583	75.0 / 66.0	4.2(BTDC)	28.3	6500	50	3500

65. Model Designation	74. EIM (kg)	75. Loaded Vehicle Weight Range (kg)	76. Road Load (nt)	Total Vehicle Mass (kg)	78. Full Weight with All Factory Options (kg)	79. Trans. Type	80. N/V
VT600C	320	316 - 325	139.5	325	325	M4	41.6
VT600CD	320	316 - 325	139.5	325	325	M4	41.6
VT600CD2	320	316 - 325	139.5	325	325	M4	41.6

E.O. #: M-2-355 Section: 7 Page:1

Issued: 1999/03/19

Revised:

Motorcycle Engine Family Information Form

Manufacturer: Honda M Certification contact	Person, address, phone, ar	d fax:	
Julie Barkow, Certi American Honda Moto 1919 Torrance Blvd.	fication Assistant, Certifi r Co., Inc. Mail Stop 500-2 , Torrance CA 90501-2746	cation Department	.com
Model Year: 2000		10. Displacement (cc): 58	3
Process Code: New (new, correction, revi	.sed, r/c, f/f, etc.)	11. Number of Cylinder:	2
Engine Family: YHNXC	0.58AAA	12. Cylinder Arrangement:	: 52 Degrees V-2
50s Eng. Code: N 49s Eng. Code: N		13. Cylinder Head Configu	uration: OHV/OHC
Calif. Eng. Code		14. Type of Cooling: Lic	quid Cooled
Emission Control Syst	em: EM	15. Cambustion Cycle: Ot	to
Calif. Designated Sta	ndard(g/km): 0.9	16. Method of Aspiration:	: Natural
	CONFIDENTIAL s ⊠ No		
New Technology: Ye If yes, cite the correct the submittal document. Adjustable Parameter.	s × No espondence or reference :: N/A	18. Number of Catalytic C	Converters: N/A
New Technology: Technology: Yes	s × No espondence or reference :: N/A		
New Technology: Ye If yes, cite the correct the submittal document. Adjustable Parameter.	es No espondence or reference :: N/A s: Adjustable Range (or N/A)	18. Number of Catalytic C	Converters: N/A
New Technology: Ye If yes, cite the corre the submittal document Adjustable Parameter Parameters(s) Carburetor Pilot	s \(\sum No\) espondence or reference :: N/A s: Adjustable Range (or N/A)	18. Number of Catalytic C Tamper Resistance Method (or N/A) Recess "D" shaped head that	Method Approved Approved by EPA on
New Technology: Ye If yes, cite the corre the submittal document Adjustable Parameter Parameters(s) Carburetor Pilot	s No espondence or reference :: N/A s: Adjustable Range (or N/A) Not Limited	18. Number of Catalytic C Tamper Resistance Method (or N/A) Recess "D" shaped head that	Method Approved Approved by EPA on
New Technology: Ye If yes, cite the corre the submittal document Adjustable Parameter Parameters(s) Carburetor Pilot Screw	s No espondence or reference :: N/A s: Adjustable Range (or N/A) Not Limited	18. Number of Catalytic C Tamper Resistance Method (or N/A) Recess "D" shaped head that	Method Approved Approved by EPA on
New Technology: Ye If yes, cite the corre the submittal document Adjustable Parameter Parameters(s) Carburetor Pilot Screw AECDs in the Emission Exhaust System AECDs In System:	s No espondence or reference :: N/A s: Adjustable Range (or N/A) Not Limited	Tamper Resistance Method (or N/A) Recess "D" shaped head that requires a special tool Evaporative System AECDs In System:	Method Approved Approved by EPA on
New Technology: Ye If yes, cite the corre the submittal document Adjustable Parameters Parameters(s) Carburetor Pilot Screw AECDs in the Emission Exhaust System	s No espondence or reference :: N/A s: Adjustable Range (or N/A) Not Limited	Tamper Resistance Method (or N/A) Recess "D" shaped head that requires a special tool Evaporative System	Method Approved Approved by EPA on

Application Processed by: Joseph Jegede Date: 6/10/99 Reviewed by: State Date: 6/10/99

E.O. #: M-2-355 Section: 7 Page:4

Issued: 1999/03/19

Revised:

Engine Family: YHNXCO.58AAA

Motorcycle Test Information Form

27. Are you carrying over test results from a previously certified family? Yes □ No

a) If yes, indicate family name: XHNXCO.58AAA

b) Is the family being certified identical to the family from which the data is being carried over? Yes

28. Model Designation of Test Vehicle: VT600C

29. Test Information Number: X01

30. Vehicle ID: 9900-01

31. Service Accumulation Duration (km): 15013

32. Maximum Rated Power (kW @ RPM): 28.3 @ 6500

33. Displacement (cc): 583

34. Certification Fuel: Indolene

35. Test Data Set: 1

42. Exhaust Emission Deterioration Factor

36. Road Load(nt): 139.5

37. Inertia Mass(kg): 320

38. N/V: 41.6

39. Evap Bench Test Method Approval:

Data: March 9, 1983

Reference: 17.01.01-1(ARB) & 17.01.02-2(ARB) thru 17.01.02-12(ARB) in 1999 Model

Year Application

40. Unscheduled Maintenance: ∑ Yes ☐ No

41. If yes Vehicle Log Provided: See Section 7 page 14

		Emission Va	alues
Test Number	System Kilometers	HC	∞
1	3602	0.57	9.1
2	6385	0.58	9.6
3	6415	0.62	10.0
4	9755	0.59	9.6
5	12954	0.63	9.6
6	12984	0.61	8.8
7	15013	0.62	9.2
Interpolate	d Values at 15,000 km:	HC = 0.6239	$\infty = 9.2564$
Extrapolate	d Values at 30,000 km:	HC = 0.6823	$\infty = 8.8188$

Regular DF	X
Modified DF	
If Different Specify Vehi	

Deterioration

43. Emission Test Results:

Official Test Results		Test 1	Test 2	Test 3	Test 4
g/km	œ	9.2			
g/km	Ω,	77.3			
g/km	нс	0.62			
g/km	Evap.	0.61			

	Factors
(20)	1.000 (0.953)
(X)	1.094
(+)	0.2

44. Certification Levels:

g/km	00	(9)	
g/km	HC	(0.7)	
g/test	Evap.	0.8	

():Calculated Value

E.O.#: M-2-355 Section: 7 Page:5

Issued: 1999/03/19

Revised:

Engine Family: YHNXC0.58AAA

Evaporative Emission Information

45. Evaporative Family: YHNXE0024FZH

46. Number of Evap. Canisters: 1

47. Design Working Capacity(g): 23.5

48. Configuration: Open Bottom

49. Number of storage Areas: 1

50. Fuel Reservoir Volume (cc): 94

51. Vent System Configuration: Internal

52. Nominal Tank Capacity(liter): 11.0

53. Engine Displacement Class: III

54. Storage Medium Composition: Charcoal

55. Evap. Canister Medium Volume(cc): 570 +/- 10

56. Evap. Family Sales: CONFIDENTIAL

57. Engine Code: YCC2

58. Evap. Emission Family Code: 00ZH

59. Evap. Emission Family Group: T

60. Overall Evap D.F.= 0.2

Bench DF

61. Test Vehicle ID: 9900-01

62. Test Results:

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3500	0.21
2	3500	0.21
3	3500	0.22
4	15000	0.40
5	15000	0.28
6	15000	0.26
7		
Interpolated	i Values at 15,000 km	n: = <u>0.313</u>
Extrapolated	i Values at 30,000 km	n: = <u>0.444</u>
Bench Test I	o.f. = 0.13	

Regular DF	X
Modified DF	
If Different Specify Vehi	Vehicle

Vehicle DF

63. Test Vehicle ID: 9900-01

64. Test Results:

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3602	0.20
2	6385	0.69
3	6415	0.43
4	9755	0.70
5	12954	0.73
6	12984	0.44
7	15013	0.61
Interpolated	i Values at 15,000 km	n: = <u>0.673</u>
Extrapolated	i Values at 30,000 km	n: = <u>1.034</u>
Vehicle Test	D.F. = 0.36	