#### State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER M-2-363 Relating to Certification of New Motorcycles

HONDA MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and,

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Honda Motor Co., Ltd. exhaust emission control systems are certified as described below for four-stroke gasoline-powered motorcycles:

Engine Family	Displacement Cubic Centimeters	<u>Class</u>	Exhaust Emission Control Systems & Special Features
YHNXCO.60CBA	599	III	Pulsed Secondary Air Injection

Vehicle models and transmissions are listed on the attachment. Production motorcycles shall be in all material respects the same as those for which certification is granted.

The following are the exhaust emission standards and exhaust emission certification values for this engine family. The designated hydrocarbons standard shall be listed on the permanent tune-up label:

Hydrocarbon S	tandards	Hydrocarbons	Carbon N	Monoxide
(Corporate Average) Grams per Kilometer		(Certification) Grams per Kilometer	(Standard) Grams per Kilometer	Grams per
1.0	1.1	0.9	12	7

BE IT FURTHER RESOLVED: That the above-described certification is subject to the following terms, limitations and conditions:

The above designated hydrocarbons standard shall be the exhaust limit for this engine family during the model year and therefore cannot be redesignated by the manufacturer. It represents the hydrocarbons exhaust emission standard applicable to this engine family that shall be applied when determining compliance of any motorcycle within this engine family pursuant to Section 2101 of Title 13, California Code of Regulations. It will also be used to determine compliance with the above corporate average hydrocarbons standard as required per Section 1958(b), Title 13 of the California Code of Regulations.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That these motorcycles are found exempt from compliance with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 13 day of September 1999.

R. B. Summerfield, Chief Mobile Source Operations Division

E.O.#: M-2-363 Section: 7 Page:6

Issued: 1999/07/08

Revised:

Engine Family: YHNXC0.60CBA

## Motorcycle Model Summary Form

65. Model Designation	66. Worst Case	67. Disp. (cc)	68. Bore / Stroke (mm)	69. Basic Ignition Timing (degrees)	70. Power (kW)	71. Rated Speed (RPM)	72. Rated Torque (Nm)	73. Rated Speed (RPM)
CBR600F4	Х	599	67.0 / 42.5	5 (BTDC)	73.1	12000	61.8	10500

65. Model Designation	74. EIM (kg)	75. Loaded Vehicle Weight Range (kg)	76. Road Load (nt)	77. Total Vehicle Mass (kg)	78. Full Weight with All Factory Options (kg)	79. Trans. Type	80. N/V
CBR600F4	290	286 - 295	133.4	295	295	M6	48.8
	22						
			No. of the				

E. O. #: M-2-363

Section: 7 Page:1 Issued: 1999/07/08

Revised:

### Motorcycle Engine Family Information Form

Manufacturer: Honda M	3002 30.7 222.				
Certification contact	Person, address, phone, a	nd fax:			
American Honda Motor 1919 Torrance Blvd.	fication Assistant, Certif r Co., Inc. Mail Stop 500- , Torrance CA 90501-2746 -3417 Fax: (310)783-3510 E		com		
Model Year: 2000		10. Displacement(cc): 599			
Process Code: New (new, correction, revi	sed, r/c, f/f, etc.)	11. Number of Cylinder: 4			
Engine Family: YHNXC	0.60CBA	12. Cylinder Arrangement: L-4  13. Cylinder Head Configuration: OHV/DOHC			
50s Eng. Code: N					
49s Eng. Code: N/A Calif. Eng. Code: YCF1		14. Type of Cooling: Liquid Cooled			
Emission Control Syste	em: PAIR	15. Cambustion Cycle: Otto			
Calif Daginsted Ct-	ndard(g/km): 1.1	16. Method of Aspiration:	16. Method of Aspiration: Natural		
Calif. Designated Star			I TO COLL CLL		
	CONFIDENTIAL		cors		
Project Annual Sales:  New Technology: Ye  If yes, cite the corre  the submittal document  Adjustable Parameter	CONFIDENTIAL  S No espondence or reference  NA  S:	17. Fuel System: Carburet 18. Number of Catalytic C	cors		
Project Annual Sales:  New Technology:   Ye  If yes, cite the corre  the submittal document	CONFIDENTIAL  as $\boxtimes$ No aspondence or reference  as: N/A	17. Fuel System: Carburet	cors		
Project Annual Sales:  New Technology: Ye  If yes, cite the corre  the submittal document  Adjustable Parameter	CONFIDENTIAL  S No espondence or reference  N/A  Adjustable Range	17. Fuel System: Carburet 18. Number of Catalytic C	cors		
Project Annual Sales:  New Technology:   If yes, cite the correct the submittal document.  Adjustable Parameter.  Parameters(s)  Carburetor Pilot	CONFIDENTIAL  S No Espondence or reference  N/A  S:  Adjustable Range (or N/A)  Not Limited	17. Fuel System: Carburet 18. Number of Catalytic C  Tamper Resistance Method (or N/A)  Recess "D" shaped head that	onverters: N/A  Method Approved  Approved by EPA on		
Project Annual Sales:  New Technology:   If yes, cite the correct the submittal document.  Adjustable Parameter.  Parameters(s)  Carburetor Pilot Screw	CONFIDENTIAL  S No Espondence or reference  N/A  S:  Adjustable Range (or N/A)  Not Limited	17. Fuel System: Carburet 18. Number of Catalytic C  Tamper Resistance Method (or N/A)  Recess "D" shaped head that	onverters: N/A  Method Approved  Approved by EPA on		
Project Annual Sales:  New Technology:  Ye  If yes, cite the corre  the submittal document  Adjustable Parameters  Parameters(s)  Carburetor Pilot  Screw  AECDs in the Emission	CONFIDENTIAL  S No Espondence or reference  N/A  S:  Adjustable Range (or N/A)  Not Limited	17. Fuel System: Carburet  18. Number of Catalytic C  Tamper Resistance Method (or N/A)  Recess "D" shaped head that requires a special tool	onverters: N/A  Method Approved  Approved by EPA on		
Project Annual Sales:  New Technology:  Ye  If yes, cite the corre the submittal document  Adjustable Parameter:  Parameters(s)  Carburetor Pilot Screw  AECDs in the Emission  Exhaust System  AECDs In System:  PAIR Check Valve	CONFIDENTIAL  S No Espondence or reference  :: N/A  s:  Adjustable Range (or N/A)  Not Limited  n Control System:	17. Fuel System: Carburet  18. Number of Catalytic C  Tamper Resistance Method (or N/A)  Recess "D" shaped head that requires a special tool  Evaporative System  AECDs In System: Evap CAV Solenoid Valve	Method Approved  Approved by EPA on 09/03/91		
Project Annual Sales:  New Technology:  Ye  If yes, cite the corre  the submittal document  Adjustable Parameters  Parameters(s)  Carburetor Pilot  Screw  AECDs in the Emissio  Exhaust System  AECDs In System:	CONFIDENTIAL  S No Espondence or reference  N/A  S:  Adjustable Range (or N/A)  Not Limited  n Control System:	17. Fuel System: Carburet  18. Number of Catalytic C  Tamper Resistance Method (or N/A)  Recess "D" shaped head that requires a special tool  Evaporative System  AECDs In System:	Method Approved  Approved by EPA on 09/03/91		

Date: 9/10/99

Date: oglogo

Application Processed by: Joseph Tegede

Reviewed by: 16

E.O. #: M-2-363 Section: 7 Page: 4

Issued: 1999/07/08

Revised:

Engine Family: YHNXCO.60CBA

### Motorcycle Test Information Form

27. Are you carrying over test results from a previously certified family? Xes No

a) If yes, indicate family name: XHNXEO.60CBA

b) Is the family being certified identical to the family from which the data is being carried over? Yes

28. Model Designation of Test Vehicle: CBR600F4

29. Test Information Number: X05

30. Vehicle ID: 99CF-01

31. Service Accumulation Duration(km): 15013

32. Maximum Rated Power (kW @ RPM): 73.1 @ 12000

33. Displacement (cc): 599

34. Certification Fuel: Indolene

35. Test Data Set: 1

42. Exhaust Emission Deterioration Factor

36. Road Load(nt): 133.4

37. Inertia Mass(kg): 290

38. N/V: 48.8

39. Evap Bench Test Method Approval:

Data: March 9, 1983

Reference: 17.01.01-1(ARB) & 17.01.02-2(ARB) thru 17.01.02-12(ARB) in 1999 Model

Year Application

40. Unscheduled Maintenance: Yes No

(X)

(XX) (+)

41. If yes Vehicle Log Provided: N/A

		Emission Va	alues
Test Number	System Kilameters	HC	$\infty$
1	3655	0.93	6.9
2	6456	0.85	6.9
3	6486	0.87	7.0
4	9753	0.90	7.0
5	12949	0.93	7.3
6	12978	0.85	6.8
7	15013	0.89	7.1
Interpolated	Values at 15,000 km:	HC = 0.8861	$\infty = \frac{7.0897}{}$
Extrapolated	Values at 30,000 km:	HC = 0.8792	$\infty = 7.3394$

Regular DF	
Modified DF	
If Different Specify Veh	

43. Emission Test Results:

Official Test Results	7,	Test 1	Test 2	Test 3	Test 4
g/km	$\infty$	7.1		(19)	
g/km	∞ <u>,</u>	117.5			
g/km	HC	0.89			Way.
g/km	Evap.	0.64			

Deterioration Factors 1.035 1.000 (0.992)

44. Certification Levels:

g/km	$\infty$	0	PITHETATELL
g/km	HC	0.9	
g/test	Evap.	0.7	

():Calculated Value

E. O. #: M-2-363 Section: 7 Page:5

Issued: 1999/07/08

Revised:

Engine Family: YHNXCO.60CBA

### Evaporative Emission Information

45. Evaporative Family: YHNXE0025LZK

46. Number of Evap. Canisters: 1

47. Design Working Capacity(g): 25.0

48. Configuration: Open Bottom

49. Number of storage Areas: 1

50. Fuel Reservoir Volume (cc): 360

51. Vent System Configuration: Internal

52. Naminal Tank Capacity(liter): 17.0

53. Engine Displacement Class: III

54. Storage Medium Composition: Charcoal

55. Evap. Canister Medium Volume (cc): 680 +/- 10

56. Evap. Family Sales: CONFIDENTIAL

57. Engine Code: YCF1

58. Evap. Emission Family Code: 00ZK

59. Evap. Emission Family Group: L

60. Overall Evap D.F. = 0.1

#### Bench DF

61. Test Vehicle ID: 95CF-01

62. Test Results:

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3500	0.50
2	3500	0.46
3	3500	0.48
4	15000	0.51
5	15000	0.55
6	15000	0.55
7		
Interpolated	Values at 15,000 km:	= 0.537
Extrapolated	Values at 30,000km:	= 0.611
Bench Test D	.F. = 0.07	
	CONTROL AND ADDRESS OF THE PARTY OF THE PART	

Regular DF	
Modified DF	
If Different Specify Vehi	Vehicle

#### Vehicle DF

63. Test Vehicle ID: 95CF-01

64. Test Results:

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3685	0.47
2	6482	0.55
3	6512	0.53
4	9750	0.61
5	12954	0.65
6	12984	0.59
7	15012	0.64
Interpolated	Values at 15,000km:	= 0.653
Extrapolated	Values at 30,000km:	= 0.864
Vehicle Test	D.F. = 0.21	