Juli

(Page 1 of 2)

### State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER M-3-304 Relating to Certification of New Motorcycles

YAMAHA MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and,

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Yamaha Motor Co., Ltd. exhaust emission control systems are certified as described below for four-stroke gasoline-powered motorcycles:

Displacement		Exhaust Emission Control Systems
bic Centimeters	Class	& Special Features
1294	III	Engine Modification
		Displacement bic Centimeters Class 1294 III

Vehicle models and transmissions are listed on the attachment. Production motorcycles shall be in all material respects the same as those for which certification is granted.

The following are the exhaust emission standards and exhaust emission certification values for this engine family. The designated hydrocarbons standard shall be listed on the permanent tune-up label:

Hydrocarbon St		Hydrocarbons					
(Corporate Average)	(Designated)	(Certification)	(Standard)	(Certification)			
Grams per	Grams per	Grams per	Grams per	Grams per			
Kilometer	Kilometer	Kilometer	Kilometer	Kilometer			
1.4	1.5	1.3	12	6			

BE IT FURTHER RESOLVED: That the above-described certification is subject to the following terms, limitations and conditions:

The above designated hydrocarbons standard shall be the exhaust limit for this engine family during the model year and therefore cannot be redesignated by the manufacturer. It represents the hydrocarbons exhaust emission standard applicable to this engine family that shall be applied when determining compliance of any motorcycle within this engine family pursuant to Section 2101 of Title 13, California Code of Regulations. It will also be used to determine compliance with the above corporate average hydrocarbons standard as required per Section 1958(b), Title 13 of the California Code of Regulations.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That these motorcycles are found exempt from compliance with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this \_\_\_\_\_ day of August 1999.

R. B. Summerfield, Chief

Mobile Source Operations Division

E.O. & M-3-304

Section: 7 Page: 6 Issued: July 20, 1999

Revised:

Engine Family: YYMXC1.29GEB

### Motorcycle Model Summary Form

Model Designation	Worst	Disp. (cc)	Bore / Stroke (mm)	Basic Ignition Timing (degrees)	Power (kW)	Rated Speed (RPM)	Rated Torque (Nm)	Rated Speed (RPM)
XVZ13TF	d. = 1	1294	79.0 / 66.0	5	72.1	6000	120.6	4750
XVZ13TFC	V	1294	79.0 / 66.0	5	72.1	6000	120.6	4750
XVZ13TFL		1294	79.0 / 66.0	5	72.1	6000	120.6	4750
XVZ13TFLC		1294	79.0 / 66.0	5	72.1	6000	120.6	4750

65. Model Designation	74. EIM (kg)	75. Loaded Vehicle Weight Range (kg)	76. Road Load (nt)	77. Total Vehicle Mass (kg)	78. Full Weight with All Factory Options (kg)	79. Trans. Type	80. N/V
XVZ13TF	490		169.4	394	402.90	MT-5	31.0
XVZ13TFC	490		169.4	394	402.90	MT-5	31.0
XVZ13TFL	490		169.4	394	402.90	MT-5	31.0
XVZ13TFLC	490		169.4	394	402.90	MT-5	31.0

E.O.# M-3-304 Section:7 Page:1 Issued:July 20,1999 Revised

## Motorcycle Engine Family Information Form 0.25

Name:	Michael J. Schmitt Division Manager Government Relations Yamaha Motor Corporation	Engineer Engineering on, U.S.A. Motorcycle (	Engineering Administration Division Motorcycle Operations Group Yamaha Motor Co., Ltd.				
Address:	6555 Katella Avenue Cypress, California 90		i, Iwata-shi ef. 438-8501, Japan				
Phone No.:	(714) 761-7710	(0538) 37-4	148				
Fax. No:	(714) 229-7940	(0538) 37-40	095				
49s Engine Calif.Engir Emission Contr Calif.Designat Projected Annu New Technology	Carry-over YYMXC1. 29GEB Code:  Code:  ne Code:  ne Code:  ed Standard: 1.5g/km al Sales:  Yes V No the correspondence or red document:	13. Cylinder He: 14. Type of Coo 15. Combustion ( 16. Method of A: 17. Fuel System 18. Number of Ca	viinders: <u>4</u> rangement: <u>V-4 (70°)</u> ad Configuration: <u>DOHC</u> ling: <u>Water</u> Cycle: <u>4</u> spiration: <u>Natural</u>				
Parameter(s		Tamper Resistance Method (or NA)	Method Approved				
	mission Control Systems:	N/AEvaporative System					

POCESSED BY: Joseph Jegede DIE: 8/10/99 REVIEWED BY: Joseph Jegede DIE: 8/10/99

E.O. # M-3-304 Section: 7 Page: 4 Issued: July 20, 1999 Revised:

Engine Family: YYMXC1.29GEB

### Motorcycle Test Information Form

41. AI	e y	ou ca	arrying	over	rest	result	s irom a	prev	rious	ly cer	lllled	lamı	y?	V	res	1	VO			
a)	If	yes,	indic	ate fa	mily	name:	XYMXC1.	29GE	EB											
b)	Is	the	family	being	cert	tified	identical	lto	the	family	from	which	the	data	is	being	carri	ed over	?	Yes

28. Model Designation of Test Vehicle: XVZ13TFC

29. Test Information Number: 4XY

30. Vehicle ID: JYAVP04Y2XA000003

31. Service Accumulation Duration: 3 months

32. Maximum Rated Power: 72.1 kW @ 6000 RPM

33. Displacement: 1294 cc

34. Certification Fuel: Unleaded Gasoline

35. Test Data Set: 6

36. Road Load: 169.4 NT at 65km/h

37. Inertia Mass: 490 kg

38. N/V: 31.0

39. EVAP. Bench Test Method Approved:

Date: January 12, 1982

Reference:

40. Unscheduled Maintenance: Yes v No

41. If yes, Vehicle Log provided:

42. Exhaust Emission Deterioration Factors:

		Emissi	on Values	
Test Number	System Kilometers	HC	CO	
1	3551	1.05	6.9	
2	6966	1.03	6.4	
3	7002	1.12	6.3	
4	13169	1.15	6.0	
5	13205	1.17	5.8	
6	15190	1.16	5.9	
7				

Extrapolated Values at 30000 km: HC= 1.3361 CO= 4.5428

legular DF	V
lodified DI	3
f differen	nt vehicle
pecify vel	

#### 43. Emission Test Results:

Official Test Results		Test 1	Test 2	Test 3	Test 4
g/km	СО	5.9			
g/km	CO2	116.3			
g/km	HC	1.16			
g/km	Evap.	1.16			

Factors (X) 0.7848 1.1416 (X) (+)0.0017

Deterioration

#### 44. Certification Levels:

g/km	СО	6	
g/km	HC	1.3	
g/km	Evap.	1.2	