State of California AIR RESOURCES BOARD

EXECUTIVE ORDER M-6-75 Relating to Certification of New Motorcycles

BAYERISCHE MOTOREN WERKE AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and,

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Bayerische Motoren Werke AG exhaust emission control systems are certified as described below for four-stroke gasoline-powered motorcycles:

Engine Family	Displacement Cubic Centimeters	Class	Exhaust Emission Control Systems & Special Features
YBMXC01.1R21	1130, 1085, & 848	III	Multiport Fuel Injection Three Way Catalytic Converter Heated Oxygen Sensor

Vehicle models and transmissions are listed on the attachment. Production motorcycles shall be in all material respects the same as those for which certification is granted.

The following are the exhaust emission standards and exhaust emission certification values for this engine family. The designated hydrocarbons standard shall be listed on the permanent tune-up label:

Hydrocarbon Standards		Hydrocarbons	Carbon Monoxide		
(Corporate Average)	(Designated)	(Certification)	(Standard)	(Certification)	
Grams per Kilometer					
1.4	0.7	0.6	12	7	

BE IT FURTHER RESOLVED: That the above-described certification is subject to the following terms, limitations and conditions:

The above designated hydrocarbons standard shall be the exhaust limit for this engine family during the model year and therefore cannot be redesignated by the manufacturer. It represents the hydrocarbons exhaust emission standard applicable to this engine family that shall be applied when determining compliance of any motorcycle within this engine family pursuant to Section 2101 of Title 13, California Code of Regulations. It will also be used to determine compliance with the above corporate average hydrocarbons standard as required per Section 1958(b), Title 13 of the California Code of Regulations.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That these motorcycles are found exempt from compliance with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 14 day of July 1999.

R. B. Summerfield, Chief

Mobile Source Operations Division

Section: 7: Page: 6

Issued:4/16/99 Revised:

Engine Family: YBMXC01.1R21

Motorcycle Model Summary Form

65.	66.	67.	68.	69.	70	71	72	73.
Model	Wors	Disp.	Bore	Basic	Power	Rated	Rated	Rated
Designation	t	(cc)	- 1	Ignition	(kW)	Speed	Torque	Speed
	Case		Stroke (mm)	Timing (degrees)		(RPM)	(Nm)	(RPM)
R1150GS	X	1130	101/70,5	0° static	62	6750	98	5250
R1100RS		1085	99/70,5	0° static	66	7250	95	5500
R1100RT		1085	99/70,5	0° static	66	7250	95	5500
R1100R		1085	99/70,5	0° static	59	6750	97	5250
R1100S		1085	99/70,5	0° static	72	7500	97	5750
R850R		848	87,5/70,5	0° static	52	7000	77	5500

65. Model Designation	74. EIM (kg)	75. Loaded Vehicle Weight Range (kg)	76 Road Load (nt)	77 Total Vehicle Mass (kg)	78 Full Weight with All Factory Options (kg)	79. Trans. Type	80 N/V
R1150GS	330	326-335	141,6	460	256	M-6	31,2
R1100RS	320	316-325	139,5	450	246	M-5	34,7
R1100RT	360	356-365	147,4	490	280	M-5	35,9
R1100R	320	316-325	139,5	450	242	M-5	37.0
R1100S	310	306-315	137,5	450	236	M-6	36,0
R850R	320	316-325	139,5	450	242	M-5	39,5

44. Certification Levels:

g/km

g/km

g/test

(6,939)

(0,583)

1,130

CO

HC

Evap.

Section: 7: Page: 4

Issued:4/16/99 Revised:

Engine Family: YBMXC01.1R21

Motorcycle Test Information Form

27.	Are you carrying a) If yes, indica b) Is the family	te family name:						ver?		
28.	Model Designation	on of Test Vehic	cle: <u>R1150</u>	OGS :	36. Road Load: <u>141.6 N</u>					
29.	Test Information	Number: R21			37. Inertia Mass: 330 kg					
30.	Vehicle ID: V 20	1811			38. N/V: <u>31,18</u>					
31.	1. Service Accumulation Duration: 15010 (km) 2. Maximum Rated Power: 62 kW @ 6750 RPM			m)	39. EVAP. Bench Test Method Approved: Date: 1996					
	2. Maximum Rated Power: 62 kW @ 6750 RPM			PM	Reference: V 201153					
	Displacement: 11				40. Unsched	luled Maintena	ance:	Yes X No		
34.	Certification Fue	l: <u>95 RON</u>			41. If yes, V	ehicle Log pro	ovided: _			
35.	Test Data Set: 1									
42.	Exhaust Emission	Deterioration !	Factors:							
	A CLUBS				nission Valu					
	Test Number	System Kild	ometers	HC	CO		14.0			
	1	3740		0,278	4,106					
	2	10014		0,335	4,437			ck one:	Tv	
	3	10032		0,308	3,802		_	ular DF	X	
	4	15010		0,408	5,317			dified DF	ala	
	5						_	ifferent vehi		
	6						spe	cify vehicle	ш	
	7						4			
	Interpolated V	alues at 15 000	km:	HC = 0.39'	73 CO =	4,9491				
	Extrapolated V	alues at 30 000	0 km:	HC = 0.56	74 CO =	6,4589				
43.	Emission Test Re	sults:	37							
	Official Test Results		Test 1	Test 2	Test 3	Test 4		Deteriora Factor	and the second second	
	g/km	СО	5,317				(X)	1,305		
	g/km	CO ²	164,4							
	g/km	HC	0,408				(X)	1,428		
	g/test	Evap.	0,870				(+)	0,260		

2000 / BMW Motorcycle

Section: 7: Page: 1
Issued: 4/16/99 # A-6-75

Motorcycle Engine Family Information Form

T. MINITEDITAL	ET: BMW			
Mr. Gordon BMW of No Montvale, N Phone No. 2	orth America, Inc.	one, and fax:	0.	56
3. Model Year	: 2000	10. Displacement: 113	сс: 1085 сс; 848 сс	
5. Engine Fam 50s Eng 49s Eng Calif. E 6. Emission Co 7. Calif. Design 8. Projected An 9. New Technol	ction, revision, r/c, f/f, etc.) illy: YBMXC01.1R21 pine Code: X pine Code: ngine Code: nurol System: MFI, TWC, HC nurol Standard: 0.7 g/km HC nurol Sale: total California ogy Yes X No ne correspondence or reference	15. Method of Aspirat 17. Fuel System: FI 18. Number of Catalytic	ent: opposed figuration: OHC ir 4 stroke on: natural	
19. Adjustable Parameter(s	The state of the s	Tamper Resistance Method	Method Approved	
1 11 11 11 (3)	(or NA)	(or NA)		
Ignition timing	N.A.	N.A.		
range during				
Idle speed	1050 = 50 RPM (R1150GS)	N.A.		
Idle speed	(R1150GS) 1000 + 150 RPM (R1100RS/RT/R; R850R)	N.A.		
	(R1150GS) 1000 + 150 RPM	N.A.		
Idle speed Idle speed Idle speed 20. AECDs In the	(R1150GS) 1000 + 150 RPM (R1100RS/RT/R; R850R) 1100 = 50 RPM	N.A.		
Idle speed Idle speed Lidle speed	(R1150GS) 1000 + 150 RPM (R1100RS/RT/R; RESOR) 1100 = 50 RPM (R1100S) Emission Control Systems:	N.A.	Purge valve	

Section: 7: Page: 5

Issued:4/16/99 Revised:

Engine Family: YBMXC01.1R21

Evaporative Emission Information

45. Evaporative Family: YBMXC0040R21

46. Number of Evap. Canisters: 1

47. Design Working Capacity: 40 g

48. Configuration: metal can

49. Number of Storage Areas: 1

50. Fuel Reservoir Volume: 25 1

51. Vent System Configuration: purge

52. Nominal Tank Capacity: 25 l

53. Engine Displacement Class: III

54. Storage Medium Composition: charcoal

Evap. Canister Medium Volume: 725 cm³

56. Evap. Family Sales (California)

57. Engine Code: 50s

58. Evap. Emission Family Code: 50s

59. Evap. Emission Family Group: NA

60. Overall Evap D.F. = 0,260

Bench DF

61. Test Vehicle ID: V 201153

62. Test Results:

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3500	0,377
2	10000	0,323
3	15000	0,473
4		
5		Marie Carrier
6		
7		
Interpolated V	falues at 15000 km : = 0	,433
Extrapolated V	Values at $30000 \text{ km} = 0$,547
Bench Test D.l	F. = 0,114	

Reg	gular DF:	X
Mo	dified DF:	
	erent vehicle	

Vehicle DF

63. Test Vehicle ID: V 201811

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3740	0,56
2	10014	0,76
3	10032	0,63
4	15010	0,87
5		
6		
7		
Interpolated V	alues at 15000 km: = 0	.849

Extrapolated values at 30000 km:

Vehicle Test D.F. = 0,407

Processed by: Runy 6/30/99
Reviewed by: Joseph Teyede 7/7/99