EXECUTIVE ORDER M-004-0364 New On-Road Motorcycles

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the engine and emission control systems produced by the manufacturer are certified as described below for four-stroke gasoline-powered motorcycles. Production vehicles shall be in all material respects the same as those for which certification is granted. The manufacturer shall ensure that character "C" or "3" is not used in the eighth (8<sup>th</sup>) position of the vehicle identification number (VIN) of all vehicles in the engine family listed below. Violation of this VIN provision may result in incorrect registration of the vehicles.

MODEL YEAR	ENGINE FAMILY	EVAPORATIVE FAMILY	ENGINE DISPLACEMENT (cc)	CLASS			
2005	5SKXC.638VA2	5SKXE0018YT7	638	III			
	FEATURES & ONTROL SYSTEMS	VEHIC (equivalent inerti	* = not applicable				
SFI,	PAIR, OC		AN650 (360 kg) AN650A (360 kg)				
ABBREVIATIONS: HO2S=heated O2S TBI=throttle body fo	EGR=exhaust gas recircula	tion AIR=secondary air injection PAII	R=pulsed AIR MFI=multi port fuel injection SF	2S=oxygen sensor l=sequential MFI 2) (suffix)=in series			

The following are the exhaust hydrocarbon plus oxides of nitrogen (HC+NOx) and carbon monoxide (CO) standards, or designated HC+NOx standard as applicable, and certification levels in grams per kilometer (g/km), and evaporative standard and certification level in grams per test (g/test) for this engine/evaporative family. The designated HC+NOx standard, as applicable, shall be listed on the permanent tune-up label.

				EARLY COMP	LIANCE CREDIT MUL	TIPLIER	*	
	HC+NOx	(g/km)		CO	(g/km)	EVAPORATIVE (g/test)		
CORPORATE AVERAGE STANDARD	DESIGNATED STANDARD	(DIRECT) STANDARD	CERTIFICATION LEVEL	STANDARD	CERTIFICATION LEVEL	STANDARD	CERTIFICATION LEVEL	
1.4	1.3	*	1.0	12	2	2.0	0.3	

**BE IT FURTHER RESOLVED:** That certification to the designated HC+NOx standard listed above, as applicable, is subject to the following terms, limitations and conditions:

The designated HC+NOx standard shall be the exhaust emission limit for this engine family and cannot be changed during the model year. It serves as the HC+NOx exhaust standard applicable to this engine family for determining compliance with Title 13, California Code of Regulations, Sections 1958(b) and 2101.

**BE IT FURTHER RESOLVED:** That the listed motorcycles are certified to the aforementioned HC+NOx standard, or designated standard as applicable, prior to the 2008 model year and are hereby granted an early-compliance credit multiplier listed above pursuant to Title 13, California Code of Regulations, Section 1958(g).

**BE IT FURTHER RESOLVED:** That the Executive Officer has been provided all materials required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Sections 2035 et seq.).

**BE IT FURTHER RESOLVED:** That because the listed motorcycles are certified to 0.2 grams per test or more below the applicable evaporative standard, the vehicles are exempt from complying with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Vehicles in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 2674 day of January 2005.

Allen Lyons, Chief Mobile Source Operations Division

## CLASS III MOTORCYCLE 2005 MODEL-YEAR CERTIFICATION REVIEW SHEET

Manufacturer: Engine Family: Evaporative Family: Evaporative Games	2	<u>JRAT</u>	<u>10 N</u>		Engine Information:  638 Displacement (cc)  L2 Engine Config.  4 Valves/Cylinder  4 Strokes/Cycle  liquid Cooling Medium  EFI No. Carburetors							
Rated HP: <u>54.</u> Exhaust ECS & (per SAE J	3 kW: 40.5 & special feat 1930 Sep91)	@ <u>7.0</u> ires:		M CCM / P.		s locati OC	on CA	49S	_Bbls. pe			
1. W 2. W 3. Tu	Page No. In Application Previously Submitted Sec. 7, pp 10~13 Sec. 7 page 14											
Vacuum Hose Diagram 4. Projected Sales 5. Vehicle Description 6. Durability Data Plot					Sec 7, page 16 Sec. 7, page 9 Attached							
7. Ca 8. Ca	chaust/Evaporativ ALIFORNIA Sale rry-Over/Carry- Durability Bench Emission rpe Evaporativ	es < 500 Across M			EXHAU New n/a New	ST	) ''	APORATI 030014 030003 030014	5 <b>ж</b>			
10. EV 11. Fi 12. EF	AP Bench Test Il Pipe / Access A Certificate* orporate Plan	Proc. App S Zone				oate: Ex Suzuki-	29JAN empt MC-05-3					
UNIT: g/km					1) Projected Emissions include DFs							
VEHICLE I.D.	Engine Disp Code	Trans	EIM	RL Force	MPG	нс	NOx	HC+NOx	со	EVAP gm/tst	CO2	Test N
[AN650] JS1CP51A052100005 [AN650] JS1CP51A532100014	- P506 638 [10G1]	CVT	360kg	147.7	39.7	0.31	0.64	0.95	2.2	0.28	135.9	AA6
<b>*</b> JS1VX51L0 <u>H</u> 21 <u>00035</u>   [VS1400GL]	:DFB 1360	)	Emissi	ion Stan	dards:		10	4 1/3	12	182	.0	
		olies with nclude det					1.4 Co 1.052	orporate A	Average <u>1.145</u>	0.03		
	EVAP DF The MY200									!		
. Remarks:	Model name	AN	650A	<u> </u>			•	CP51A CP51	В			
D . T 1 011	*EPA certif	icate nun	nder is i	based on	tne sequ	uential	order of	applicat	ion subn	nission.		
Date Issued: 21dec Application Processed by H:\CERT\MC2005\AN65\k5.	my	D	ate <u> -2 </u>	<u>-05</u> 1	Reviewed	l by	2/4	ale	TT 90-10-1		ZY-0	?'[