Californi	a En	vironm	ental	Protect	ion	Agency
Ø A	ir	Res	ou	rces	B	oard

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

MANUFACTURER ENGINE FAMILY (F.O. NUMBER) ENGINE (CNG/LNG=compressed/li				ESCRIPTION	ENGINE D		
S.A. = See Attachment; TBC = To Be Certified EQUIPMENT DESCRIPTION MODEL YEAR EVAPORATIVE FAMILY FUEL TANK SIZE (liters) EQUIPMENT APPLICATION	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		ENGINE FAMILY (E.O. NUMBER)		MANUFACTURER		
MODEL         EVAPORATIVE FAMILY         FUEL TANK SIZE (liters)         EQUIPMENT APPLICATION		Gasoline	768	HKBXB.7682AA (U-L-016-0099)		KUBOTA CORPORATION	
		PLICATION	QUIPMENT A		FUEL TANK SIZE		MODEL
		(liters)				CC5	
EMISSION CONTROL SYSTEMS (ECS) ENGINE and/or EQUIPMENT MODEL		ODEL		ENGINE and/or I		CONTROL SYSTEMS (ECS)	EMISSION
Canister/Co-extruded ZG227		,	Canister/Co-extruded				

A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u>:- Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and Code</u>:-Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). <u>Note</u>: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standards (Title 13, California Code of Regulations, Section 2433(b)(4)(B), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m<sup>2</sup>/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	DESIGN BASED						
FUEL HOSE PERMEATION (grams ROG/m <sup>2</sup> /day)			ANK PERMEATION ams ROG/m <sup>2</sup> /day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)			
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER		
15	Q-07-018, G-05-018, Q-14-008	1.5	0.4	1.4	C-U-07-022		

**BE IT FURTHER RESOLVED:** That for the listed engines for the aforementioned model-year, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2433(d) (certification and test procedures), 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of May 2017.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division