## TOYOTA INDUSTRIAL EQUIPMENT MFG., INC.

EXECUTIVE ORDER U-L-004-0024 New Off-Road Large Spark-Ignition Engines At & Above 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following new large spark-ignition engines and emission control systems produced by the manufacturer are certified for use in off-road equipment as described below. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY NAME	ENGINE DISPLACEMENT (liters)	FUEL TYPE		
2010	ATIEB02.204Y	2.237	Gasoline, LPG, Gasoline-LPG Dual Fuel, Gasoline-CNG Dual Fuel		
DURABILITY HOURS		IAL FEATURES & CONTROL SYSTEMS	TYPICAL EQUIPMENT USAGE		
Three-Way Catalyt 5000 Heated Oxyger Multiport Fuel		ay Catalytic Converter, ed Oxygen Sensor, port Fuel Injection	Forklift and Tractor		
	NE MODELS er in kilowatt, kW)	S	ee Attachement		

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx) and carbon monoxide (CO) exhaust certification emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2433(b)(1)) and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with 13 CCR Section 2433(b)(3) of "California Exhaust and Evaporative Emission Standards and Test Procedures for New 2007 through 2009 Off-Road Large Spark-ignition Engines (2007- 2009 Test Procedure 1048)" amended March 2, 2007.

(g/kW-hr)	HC+NOx	со
Exhaust Standards	0.8	20.6
Certification Levels	0.4	16.9

The following is the evaporative hydrocarbon emission standard (13 CCR Section 2433(b)(3)) and certification emission level for this engine family in grams per gallon of fuel tank capacity (g/gallon).

Evaporative Certification Method	HC Certification Level (g/gallon)	HC Certification Standard (g/gallon)		
Design Based	N/A	0.2		

BE IT FURTHER RESOLVED: That for the listed engines for the aforementioned model-year, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2433(c) (certification and test procedures), 13 CCR Section 2434 (emission control labels), and 13 CCR Sections 2435 and 2436 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this day of December 2009.

Annette Hebert, Chief Mobile Source Operations Division

## ATTACHMENT

Model Year: _2010	
Manufacturer Name: _TOYOTA INDUSTRIA	L_EQUIPMENT_
Engine Family: ATIEB02.204Y	<u> </u>
OFF ROAD I SI ENGINE SLIDDI EMENTAL I	NEORMATION

Page:					
Issued	:				
Revise	d:				
E.O.#:	31/2	ة مسد إ	204	00	24

## **\$12. MODEL SUMMARY** (Use an asterisk (\*) to identify worst-case engine model used for certification testing.)

S13. Engine Model	S14. Engine Code	S15. Sales Codes (Check ALL appropriate)		S16. Eng. Displ.	S17. Rated Power	S18. Rated Speed	S19. Peak Torque	S20. Peak Torque	
		Calif. Only	49- State	50- State	(Liters)	(kW)	(RPM)	(FT-LB)	Speed (RPM)
4YH(G)	50\$	_		х	2.237	44	2570	121	2570
4Y(G)	50\$			х	2.237	38	2570	118	2100
4YL(G)	508			х	2.237	36	2250	118	2100
4YH(G/LP)	50\$			x	2.237	42(LPG) 42(G)	2570	118(LPG) 119(G)	2200(LPG) 2570(G)
4Y(G/LP)	50\$			x	2.237	38(LPG) 38(G)	2570	118(LPG) 118(G)	2100(LPG) 2100(G)
4YL(G/LP)	50S			х	2.237	36(LPG) 36(G)	2250	118(LPG) 118(G)	2100(LPG) 2100(G)
4YH(LPG)	<b>50S</b>			х	2.237	42	2570	118	2200
4Y(LPG)	50\$			х	2.237	38	2570	118	2100
4YL(LPG)	<b>50S</b>			х	2.237	36	2250	118	2100
4YH(G/CN)	508			x	2.237	37(CNG) 42(G)	2570	108(CNG) 113(G)	1600(CNG) 2570(G)
4Y(G/CN)	50S			x	2.237	37(CNG) 37(G)	2570	108(CNG) 113(G)	· 1600(CNG) 2200(G)
							_		