## California Environmental Protection Agency Air Resources Board

## GLOBAL COMPONENT TECHNOLOGIES CORPORATION

EXECUTIVE ORDER U-L-059-0001 New Off-Road Large Spark-Ignition Engines Above 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2: and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following new large spark-ignition engines and emission control systems produced by the manufacturer are certified for use in off-road equipment as described below. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY NAME	ENGINE DISPLACEMENT (liters)	FUEL TYPE		
2014 ENFXB02.147D		2.1	Dual Fuel, Gasoline or LPG		
DURABILITY HOURS		IAL FEATURES & CONTROL SYSTEMS	TYPICAL EQUIPMENT USAGE		
5000	Body Injection (LPG)	on (Gas and Dual Fuel), Throttle I, Three-Way Catalytic Converter, and Oxygen Sensor	Forklift		
ENGINE MODELS (rated power in kilowatt, kW)		See Attachment			

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx) and carbon monoxide (CO) exhaust certification emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2433(b)(1)) and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with 13 CCR Section 2433(b)(3).

(g/kW-hr)	HC+NOx	со
Exhaust Standards	0.8	20.6
Certification Levels	0.5	3.8

The following is the evaporative hydrocarbon emission standard (13 CCR Section 2433(b)(3)) and certification emission level for this engine family in grams per gallon of fuel tank capacity (g/gallon).

<b>Evaporative Certification Method</b>	HC Certification Level (g/gallon)	HC Certification Standard (g/gallon)		
Design Based	N/A	0.2		

BE IT FURTHER RESOLVED: That for the listed engines for the aforementioned model-year, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2433(c) (certification and test procedures), 13 CCR Section 2434 (emission control labels), and 13 CCR Sections 2435 and 2436 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of

FixErik White, Chief

Mobile Source Operations Division

## ATTACHNEUT B (08)

Model Year: 2014
Manufacturer Name: Global Component Technologies Corporation

Engine Family: <u>ENFXB02.147D</u>
OFF-ROAD LSI ENGINE SUPPLEMENTAL INFORMATION

Page:

Issued: 05/20/2013 . Revised:

E.O.#: U-L-059-0001

S12. MODEL SUMMARY (Use an asterisk (\*) to identify worst-case engine model used for certification testing.)

S13.	S14.	Sa	S15. des Cod check Al	les	S16. Eng.	S17.	S18.	S19.	S20. Peak
Engine Model	Engine Code	appropriate)		Displ. (Liters)	Power (kW)	Speed (RPM)	Torque (Nm)	Torque Speed	
		Calif. Only	49- State	50- State					(RPM)
K21 N-1				٧	2.065	34.3	2700	135.8	1800
K21 N-2				٧	2.065	37.4	2700	145.4	1800
K21 N-3	(Gasoline)			٧	2.065	34.3	2700	135.8	1800
NZ1 14-5	(LPG)			٧	2.065	35.8	270 <b>0</b>	145.3	1800
K21 M-1				٧	2.065	34.1	2700	135.5	1800
K21 M-2				V	2.065	37.3	2700	145.1	1800
K21 M-3	(Gasoline)			٧	2.065	34.1	2700	135.5	1800
RZT W-3	(LPG)			٧	2.065	35.5	2700	145.0	1800
*K21 K-1				V	2.065	35.1	2700	136.4	1800
K21 K-2				V	2.065	38.8	2700	146.2	1800
K21 K-3	(Gasoline)			V	2.065	35.1	2700	136.4	1800
K21 K-3	(LPG)			V	2.065	37.3	2700	145.9	1800
K21 T-1				٧	2.065	32.1	2700	136.0	1800
K21 T-2				V	2.065	37.0	2700	144.9	1800
K21 T-3	(Gasoline)			V	2.065	32.1	2700	136.0	1800
	(LPG)			٧	2.065	34.8	2700	144.1	1800